

# RF EXPOSURE EVALUATION REPORT

**Product Name:** ONEBOT Programming Master  
**Trade Mark:** ONEBOT  
**Model No. / HVIN:** AIQIEDU-C  
**Report Number:** 180912010RFC-5  
**Test Standards:** FCC 47 CFR Part 1 Subpart I  
**FCC ID:** 2ALJ6-AIQIEDU-C  
**Test Result:** PASS  
**Date of Issue:** December 7, 2018

Prepared for:

**Beijing AIQI Technology Co., LTD.**  
Room.D1203, The 11th floor, Block D, No.9 Shangdi 3rd St., Haidian  
District, Beijing,100085, China

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
16/F, Block A, Building 6, Baoneng Science and Technology Park,  
Qingxiang Road No.1, Longhua New District, Shenzhen, China  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Tested by: Eason Zhong  
Eason Zhong  
Project Engineer

Reviewed by: Kevin Liang  
Kevin Liang  
Assistant Manager

Approved by: Billy Li  
Billy Li  
Technical Director

Date: December 7, 2018

## Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China  
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

**Version**

Version No.	Date	Description
V1.0	December 7, 2018	Original



# CONTENTS

- 1. GENERAL INFORMATION ..... 4
  - 1.1 CLIENT INFORMATION ..... 4
  - 1.2 EUT INFORMATION ..... 4
    - 1.2.1 DESCRIPTION OF ACCESSORIES ..... 4
  - 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD ..... 4
  - 1.4 OTHER INFORMATION ..... 5
  - 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS ..... 5
  - 1.6 DEVIATION FROM STANDARDS ..... 5
  - 1.7 ABNORMALITIES FROM STANDARD CONDITIONS ..... 5
  - 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER ..... 5
- 2. EQUIPMENT LIST ..... 5
- 3. MPE EVALUATION ..... 6
  - 3.1 REFERENCE DOCUMENTS FOR EVALUATION ..... 6
  - 3.2 MPE COMPLIANCE REQUIREMENT ..... 6
    - 3.2.1 LIMITS ..... 6
    - 3.2.2 TEST PROCEDURE ..... 7
  - 3.3 MPE CALCULATION METHOD ..... 7
    - 3.3.1 FCC 47 CFR PART 1 SUBPART I ..... 7
  - 3.4 MPE CALCULATION RESULTS ..... 7
    - 3.4.1 FOR WLAN ..... 7
- APPENDIX 1 PHOTOS OF TEST SETUP ..... 8
- APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS ..... 8

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	Beijing AIQI Technology Co., LTD.
<b>Address of Applicant:</b>	Room.D1203, The 11th floor, Block D, No.9 Shangdi 3rd St., Haidian District, Beijing,100085, China
<b>Manufacturer:</b>	Beijing AIQI Technology Co., LTD.
<b>Address of Manufacturer:</b>	Room.D1203, The 11th floor, Block D, No.9 Shangdi 3rd St., Haidian District, Beijing,100085, China

### 1.2 EUT INFORMATION

<b>Product Name:</b>	ONEBOT Programming Master	
<b>Model No.:</b>	AIQIEDU-C	
<b>Trade Mark:</b>	ONEBOT	
<b>DUT Stage:</b>	Production Unit	
<b>EUT Supports Function:</b>	2.4 GHz ISM Band:	Bluetooth V4.2
<b>Software Version:</b>	V1.0	
<b>Hardware Version:</b>	V2.0	
<b>Sample Received Date:</b>	September 20, 2018	
<b>Sample Tested Date:</b>	September 22, 2018 to October 10, 2018	

#### 1.2.1 Description of Accessories

None.

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

<b>Frequency Band:</b>	2400 MHz to 2483.5 MHz
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Bluetooth Version:</b>	Bluetooth V4.2 LE
<b>Type of Modulation:</b>	GFSK
<b>Number of Channels:</b>	40
<b>Channel Separation:</b>	2 MHz
<b>Antenna Type:</b>	Multilayer Chip Antenna
<b>Antenna Gain:</b>	0 dBi
<b>Maximum Peak Power:</b>	-1.87 dBm
<b>Normal Test Voltage:</b>	9 Vdc

### 1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + 2k \text{ MHz}, k = 0, \dots, 39$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

### 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

**FCC 47 CFR Part 1 Subpart I**

All test items have been performed and recorded as per the above standards

### 1.6 DEVIATION FROM STANDARDS

None.

### 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

### 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

### 3. MPE EVALUATION

#### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

#### 3.2 MPE COMPLIANCE REQUIREMENT

##### 3.2.1 Limits

##### 3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

##### Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

##### Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	<b>1</b>	30

**Note:** f = frequency in MHz: \* = Plane-wave equivalent power density.

### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3.3 MPE CALCULATION METHOD

### 3.3.1 FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 3.4 MPE CALCULATION RESULTS

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.4.1 For WLAN

For BT\_LE function, operating at 2402MHz to 2480 MHz for GFSK.

#### 3.4.1.1 Antenna Type:

Chain 0: External Antenna

#### 3.4.1.2 Antenna Gain:

Chain 0: 2402 MHz to 2480 MHz z: 0 dBi

#### 3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(mW)	(mw/cm <sup>2</sup> )	
LE	2402	-2	1	0	-1	0.7943	1	0.0002
	2440	-2	1	0	-1	0.7943	1	0.0002
	2480	-2	1	0	-1	0.7943	1	0.0002

## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

\*\*\* End of Report \*\*\*

---

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---

---