




# RF TEST REPORT



Report No.: 17070412-FCC-R1

Supersede Report No.: N/A

Applicant	PCD, LLC	
Product Name	3G Feature Phone	
Model No.	PH201Q	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; ANSI/TIA-603-D: 2010	
Test Date	June 13 to June 29, 2017	
Issue Date	June 30, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
<p>This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070412-FCC-R1
Page	3 of 87

This page has been left blank intentionally.

# CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	10
6.1 RF EXPOSURE (SAR) .....	10
6.2 RF OUTPUT POWER.....	11
6.3 PEAK-AVERAGE RATIO.....	22
6.4 OCCUPIED BANDWIDTH .....	26
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....	37
6.6 SPURIOUS RADIATED EMISSIONS.....	50
6.7 BAND EDGE .....	56
6.8 FREQUENCY STABILITY.....	66
ANNEX A. TEST INSTRUMENT .....	70
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	72
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	83
ANNEX C.II. EUT OPERATING CONKITIONS .....	85
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	86
ANNEX E. DECLARATION OF SIMILARITY .....	87

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070412-FCC-R1	NONE	Original	June 30, 2017

## 2. Customer information

Applicant Name	PCD, LLC
Applicant Add	1500 Tradeport Drive, Suite A, Orlando, Florida, United States, 32824
Manufacturer	Shenzhen Haierhea Telecom Co.,Ltd.
Manufacturer Add	Room 418,Block M-3,Middle of Hi-Tech Park,Nanshan,Shenzhen,China 518057

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen(ICP-03A1)

## 4. Equipment under Test (EUT) Information

Description of EUT:	3G Feature Phone
Main Model:	PH201Q
Serial Model:	N/A
Date EUT received:	June 12, 2017
Test Date(s):	June 13 to June 29, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: -3dBi PCS1900: -3dBi UMTS-FDD Band V: -3dBi UMTS-FDD Band II: -3dBi Bluetooth: -1dBi
Antenna Type:	BT: Monopole antenna GSM: PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz Bluetooth: 2402-2480 MHz
Maximum Conducted	GSM Voice: GSM850: 31.99 dBm PCS1900: 29.47 dBm
AV Power to Antenna:	GPRS: GSM850: 31.98 dBm PCS1900: 29.39 dBm

Test Report	17070412-FCC-R1
Page	7 of 87

EGPRS(MCS1):GSM850: 31.91 dBm

PCS1900: 29.35 dBm

RMC:UMTS-FDD Band 5: 23.31 dBm

UMTS-FDD Band 2: 23.73 dBm

HSUPA:UMTS-FDD Band 5: 22.26 dBm

UMTS-FDD Band 2: 22.89 dBm

HSDPA:UMTS-FDD Band 5: 22.28 dBm

UMTS-FDD Band 2: 22.73 dBm

GSM Voce:GSM850: 26.89 dBm / ERP

PCS1900: 26.47 dBm / EIRP

GPRS:GSM850: 26.88 dBm / ERP

PCS1900: 26.39 dBm / EIRP

EGPRS(MCS1):GSM850: 26.81 dBm / ERP

PCS1900: 26.35 dBm / EIRP

ERP/EIRP:

RMC:UMTS-FDD Band 5: 18.21 dBm / ERP

UMTS-FDD Band 2: 20.73 dBm / EIRP

HSDPA:UMTS-FDD Band 5: 17.18 dBm / ERP

UMTS-FDD Band 2: 19.73 dBm / EIRP

HSUPA:UMTS-FDD Band 5: 17.16 dBm / ERP

UMTS-FDD Band 2: 19.89 dBm / EIRP

GSM 850: 124CH

PCS1900: 299CH

Number of Channels:

UMTS-FDD Band V : 102CH

UMTS-FDD Band II : 277CH

Bluetooth: 79CH

Port:

USB Port, Earphone Port

Adapter:

Model: PH201Q

Input: AC100-240V~50/60Hz,0.2A

Input Power:

Output: DC 5.0V, 500mA

Battery:

Model: PH201Q

Spec : 3.7V,600mAh,2.22Wh



Test Report	17070412-FCC-R1
Page	8 of 87

---

Trade Name : N/A

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2ALJPH201Q



## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## 6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

### 6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;


Please refer to RF Exposure Evaluation Report: 17070412-FCC-H.

## 6.2 RF Output Power

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	June 19, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station                      EUT</p>
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> <li>- The transmitter output port was connected to base station.</li> <li>- Set EUT at maximum power through base station.</li> <li>- Select lowest, middle, and highest channels for each band and different test mode.</li> </ul> <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> <li>- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>- The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>- The frequency range up to tenth harmonic of the fundamental frequency was investigated.</li> </ul>
----------------	---

	<ul style="list-style-type: none"> <li>- Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> <li>- Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level</li> <li>- Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts).</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A  
 Test Plot      Yes (See below)             N/A

## Conducted Power

### GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	<b>31.99</b>	31.76	31.58	31.5±1	29.34	29.35	<b>29.47</b>	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	<b>31.98</b>	31.7	31.52	31.5±1	29.27	29.28	<b>29.39</b>	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.19	30.95	30.78	30.5±1	28.48	28.49	28.65	28.5±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	28.37	28.06	27.89	28±1	25.42	25.47	25.65	25.5±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	<b>31.91</b>	31.67	31.51	31.5±1	29.23	29.24	<b>29.35</b>	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.18	30.93	30.73	30.5±1	28.44	28.47	28.64	28.5±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	28.23	27.98	27.84	28±1	25.32	25.4	25.57	25.5±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

## UMTS Mode:

### UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	<b>23.31</b>	23±1
	4175	835	23.27	23±1
	4233	846.6	23.28	23±1
HSDPA Subtest1	4132	826.4	22.06	22±1
	4175	835	22.17	22±1
	4233	846.6	22.09	22±1
HSDPA Subtest2	4132	826.4	22.15	22±1
	4175	835	22.18	22±1
	4233	846.6	22.12	22±1
HSDPA Subtest3	4132	826.4	22.09	22±1
	4175	835	22.06	22±1
	4233	846.6	22.04	22±1
HSDPA Subtest4	4132	826.4	22.26	22±1
	4175	835	<b>22.28</b>	22±1
	4233	846.6	22.22	22±1
HSUPA Subtest1	4132	826.4	21.96	22±1
	4175	835	21.93	22±1
	4233	846.6	21.99	22±1
HSUPA Subtest2	4132	826.4	22.18	22±1
	4175	835	22.12	22±1
	4233	846.6	22.11	22±1
HSUPA Subtest3	4132	826.4	22.13	22±1
	4175	835	22.1	22±1
	4233	846.6	22.09	22±1
HSUPA Subtest4	4132	826.4	<b>22.26</b>	22±1
	4175	835	22.19	22±1
	4233	846.6	22.23	22±1
HSUPA Subtest5	4132	826.4	22.09	22±1
	4175	835	22.16	22±1
	4233	846.6	22.12	22±1

## UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	<b>23.73</b>	23±1
	9400	1880	23.03	23±1
	9538	1907.6	22.92	23±1
HSDPA Subtest1	9262	1852.4	22.62	22.3±1
	9400	1880	22.34	22.3±1
	9538	1907.6	22.13	22.3±1
HSDPA Subtest2	9262	1852.4	22.57	22.3±1
	9400	1880	22.06	22.3±1
	9538	1907.6	21.93	22.3±1
HSDPA Subtest3	9262	1852.4	<b>22.73</b>	22.3±1
	9400	1880	22.16	22.3±1
	9538	1907.6	22.08	22.3±1
HSDPA Subtest4	9262	1852.4	22.62	22.3±1
	9400	1880	22.24	22.3±1
	9538	1907.6	22.13	22.3±1
HSUPA Subtest1	9262	1852.4	<b>22.89</b>	22.3±1
	9400	1880	22.42	22.3±1
	9538	1907.6	22.35	22.3±1
HSUPA Subtest2	9262	1852.4	22.43	22.3±1
	9400	1880	21.95	22.3±1
	9538	1907.6	21.83	22.3±1
HSUPA Subtest3	9262	1852.4	22.66	22.3±1
	9400	1880	22.13	22.3±1
	9538	1907.6	22.06	22.3±1
HSUPA Subtest4	9262	1852.4	22.73	22.3±1
	9400	1880	22.28	22.3±1
	9538	1907.6	22.19	22.3±1
HSUPA Subtest5	9262	1852.4	22.55	22.3±1
	9400	1880	22.09	22.3±1
	9538	1907.6	21.93	22.3±1

## ERP & EIRP

### GSM Voice

#### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.62	V	6.8	0.53	<b>26.89</b>	38.45
824.2	18.68	H	6.8	0.53	24.95	38.45
836.6	20.39	V	6.8	0.53	26.66	38.45
836.6	18.46	H	6.8	0.53	24.73	38.45
848.8	20.11	V	6.9	0.53	26.48	38.45
848.8	18.19	H	6.9	0.53	24.56	38.45

#### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.31	V	7.88	0.85	26.34	33
1850.2	17.35	H	7.88	0.85	24.38	33
1880	19.32	V	7.88	0.85	26.35	33
1880	17.36	H	7.88	0.85	24.39	33
1909.8	19.46	V	7.86	0.85	<b>26.47</b>	33
1909.8	17.51	H	7.86	0.85	24.52	33



**GPRS:**

**ERP for Cellular Band (Part 22H)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.61	V	6.8	0.53	<b>26.88</b>	38.45
824.2	18.66	H	6.8	0.53	24.93	38.45
836.6	20.33	V	6.8	0.53	26.6	38.45
836.6	18.37	H	6.8	0.53	24.64	38.45
848.8	20.05	V	6.9	0.53	26.42	38.45
848.8	18.12	H	6.9	0.53	24.49	38.45

**EIRP for PCS Band (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.24	V	7.88	0.85	26.27	33
1850.2	17.23	H	7.88	0.85	24.26	33
1880	19.25	V	7.88	0.85	26.28	33
1880	17.28	H	7.88	0.85	24.31	33
1909.8	19.38	V	7.86	0.85	<b>26.39</b>	33
1909.8	17.44	H	7.86	0.85	24.45	33

**EGPRS (MCS1):**

**ERP for Cellular Band (Part 22H)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.54	V	6.8	0.53	<b>26.81</b>	38.45
824.2	18.6	H	6.8	0.53	24.87	38.45
836.6	20.3	V	6.8	0.53	26.57	38.45
836.6	18.36	H	6.8	0.53	24.63	38.45
848.8	20.04	V	6.9	0.53	26.41	38.45
848.8	18.1	H	6.9	0.53	24.47	38.45

**EIRP for PCS Band (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.2	V	7.88	0.85	26.23	33
1850.2	17.24	H	7.88	0.85	24.27	33
1880	19.21	V	7.88	0.85	26.24	33
1880	17.28	H	7.88	0.85	24.31	33
1909.8	19.34	V	7.86	0.85	<b>26.35</b>	33
1909.8	17.39	H	7.86	0.85	24.4	33

## RMC

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	11.94	V	6.8	0.53	<b>18.21</b>	38.45
826.4	10.96	H	6.8	0.53	17.23	38.45
835	11.9	V	6.8	0.53	18.17	38.45
835	10.93	H	6.8	0.53	17.2	38.45
846.6	11.81	V	6.9	0.53	18.18	38.45
846.6	10.85	H	6.9	0.53	17.22	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.7	V	7.88	0.85	<b>20.73</b>	33
1852.4	12.72	H	7.88	0.85	19.75	33
1880	13	V	7.88	0.85	20.03	33
1880	12.06	H	7.88	0.85	19.09	33
1907.6	12.91	V	7.86	0.85	19.92	33
1907.6	12.01	H	7.86	0.85	19.02	33

## HSDPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.89	V	6.8	0.53	17.16	38.45
826.4	9.97	H	6.8	0.53	16.24	38.45
835	10.91	V	6.8	0.53	<b>17.18</b>	38.45
835	9.98	H	6.8	0.53	16.25	38.45
846.6	10.75	V	6.9	0.53	17.12	38.45
846.6	9.82	H	6.9	0.53	16.19	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.7	V	7.88	0.85	<b>19.73</b>	33
1852.4	11.83	H	7.88	0.85	18.86	33
1880	12.31	V	7.88	0.85	19.34	33
1880	11.39	H	7.88	0.85	18.42	33
1907.6	12.12	V	7.86	0.85	19.13	33
1907.6	11.22	H	7.86	0.85	18.23	33

## HSUPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.89	V	6.8	0.53	<b>17.16</b>	38.45
826.4	9.96	H	6.8	0.53	16.23	38.45
835	10.82	V	6.8	0.53	17.09	38.45
835	9.88	H	6.8	0.53	16.15	38.45
846.6	10.76	V	6.9	0.53	17.13	38.45
846.6	9.8	H	6.9	0.53	16.17	38.45

### EIRP for UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.86	V	7.88	0.85	<b>19.89</b>	33
1852.4	11.91	H	7.88	0.85	18.94	33
1880	12.39	V	7.88	0.85	19.42	33
1880	11.43	H	7.88	0.85	18.46	33
1907.6	12.34	V	7.86	0.85	19.35	33
1907.6	11.37	H	7.86	0.85	18.38	33

### 6.3 Peak-Average Ratio

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	June 19, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>

Test Setup	 <p>The diagram shows a Base Station (green box) connected to a Spectrum Analyzer (green box), which is then connected to an EUT (blue box). The connections are made via cables and a small black component, likely a coupler or adapter.</p>
------------	---

Test Procedure	<p>According with KDB 971168 v02r02</p> <p><b>5.7.2 Alternate procedure for PAPR</b></p> <p><b>5.1.2 Peak power measurements with a peak power meter</b></p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p><b>5.2.3 Average power measurement with average power meter</b></p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle <math>\geq 98\%</math>) and at all times the EUT is transmitting at its maximum output</p>
----------------	---

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle &lt; 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than <math>\pm 2</math> percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to <math>10\log(1/\text{duty cycle})</math></p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

**Test Data**     Yes                       N/A  
**Test Plot**     Yes (See below)             N/A

**GSM : GSM 1900 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.68	29.34	0.34
1880	29.72	29.35	0.37
1909.8	29.78	29.47	0.31

**GPRS 1900 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.59	29.27	0.32
1880	29.6	29.28	0.32
1909.8	29.64	29.39	0.25

**EGPRS (MSC1) 1900 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.56	29.23	0.33
1880	29.63	29.24	0.39
1909.8	29.6	29.35	0.25

**RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.1	23.73	0.37
1880	23.31	23.03	0.28
1907.6	23.21	22.92	0.29

**HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	22.95	22.62	0.33
1880	22.63	22.34	0.29
1907.6	22.4	22.13	0.27




**HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.05	22.89	0.16
1880	22.76	22.42	0.34
1907.6	22.68	22.35	0.33

## 6.4 Occupied Bandwidth

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	June 20, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Base Station      Spectrum Analyzer      EUT</p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.6102	319.668
190	836.6	247.9914	317.035
251	848.8	244.2251	317.918

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	248.5655	320.106
661	1880.0	247.0460	319.597
810	1909.8	243.2543	319.749

**GPRS:**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.7910	318.634
190	836.6	246.4037	320.047
251	848.8	246.2153	317.861

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	244.4955	319.380
661	1880.0	247.3781	324.302
810	1909.8	246.1877	321.986

**EGPRS (MCS 1):**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.0178	323.077
190	836.6	244.8582	323.106
251	848.8	246.4225	322.806

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	244.2251	317.918
661	1880.0	247.2077	320.267
810	1909.8	246.6539	322.831

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1607	4.707
4175	835.0	4.1605	4.704
4233	846.6	4.1504	4.706

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1737	4.716
9400	1880.0	4.1710	4.719
9538	1907.6	4.1746	4.726

**HSDPA:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1640	4.717
4175	835.0	4.1587	4.738
4233	846.6	4.1619	4.702

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1737	4.720
9400	1880.0	4.1665	4.711
9538	1907.6	4.1687	4.732

**HSUPA:**

**UMTS-FDD Band V (Part 22H)**


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1630	4.712
4175	835.0	4.1612	4.761
4233	846.6	4.1732	4.708

**UMTS-FDD Band II (Part 24E)**


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1761	4.720
9400	1880.0	4.1659	4.727
9538	1907.6	4.1613	4.724

### Test Plots


#### GSM Voice:




### GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz




### EGPRS (MCS1):




RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz




Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz


HSDPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz




Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz


HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz



Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz

## 6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	June 20, 2017
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;"> <span style="margin-right: 100px;">Base Station</span> <span style="margin-right: 100px;">Spectrum Analyzer</span> <span>EUT</span> </p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured.</li> <li>- Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes                       N/A  
 Test Plot     Yes (See below)       N/A


### Test Plots

#### GSM Voice:


#### Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


### PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1



PCS 1900 - High Channel-2


GPRS:

Cellular Band (Part 22H) result







### PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2





PCS1900 - High Channel-1





PCS 1900 - High Channel-2

**EGPRS (MCS1):  
Cellular Band (Part 22H) result**





GSM 850 - Low Channel-1

GSM 850 - Low Channel-2



GSM 850 Middle Channel-1


GSM 850 Middle Channel-2



GSM 850 - High Channel-1



GSM 850 - High Channel-2

### PCS Band (Part24E) result





RMC

UMTS-FDD Band V (Part 22H)





Band V - Low Channel-1

Band V - Low Channel-2



Band V - Middle Channel-1


Band V - Middle Channel-2




Band V - High Channel-1

Band V - High Channel-2


### UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2





Band II - High Channel-1



Band II - High Channel-2



HSDPA:

UMTS-FDD Band V (Part 22H)





Band V - Low Channel-1

Band V - Low Channel-2



Band V - Middle Channel-1


Band V - Middle Channel-2




Band V - High Channel-1

Band V - High Channel-2


### UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2





Band II - High Channel-1



Band II - High Channel-2



HSUPA:

UMTS-FDD Band V (Part 22H)





Band V - Low Channel-1

Band V - Low Channel-2



Band V - Middle Channel-1

Band V - Middle Channel-2




Band V - High Channel-1


Band V - High Channel-2




### UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

## 6.6 Spurious Radiated Emissions

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	June 19, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> <li>The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> </ol> <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dB<math>\mu</math>V/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	--

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A

## Cellular Band (Part 22H) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.78	V	7.95	0.78	-36.61	-13	-23.61
1648.4	-44.32	H	7.95	0.78	-37.15	-13	-24.15
325.6	-53.61	V	6.4	0.26	-47.47	-13	-34.47
604.2	-52.98	H	6.8	0.37	-46.55	-13	-33.55

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-46.28	V	7.95	0.78	-39.11	-13	-26.11
1673.2	-44.06	H	7.95	0.78	-36.89	-13	-23.89
327.9	-52.97	V	6.4	0.26	-46.83	-13	-33.83
608.3	-53.62	H	6.8	0.37	-47.19	-13	-34.19

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.67	V	7.95	0.78	-36.5	-13	-23.5
1697.6	-44.65	H	7.95	0.78	-37.48	-13	-24.48
325.1	-53.16	V	6.4	0.26	-47.02	-13	-34.02
604.2	-52.68	H	6.8	0.37	-46.25	-13	-33.25

#### Note:

- 1, The testing has been conformed to  $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## PCS Band (Part24E) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.76	V	10.25	2.73	-41.24	-13	-28.24
3700.4	-49.25	H	10.25	2.73	-41.73	-13	-28.73
325.9	-53.64	V	6.4	0.26	-47.5	-13	-34.5
605.3	-54.12	H	6.8	0.37	-47.69	-13	-34.69

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.69	V	10.25	2.73	-41.17	-13	-28.17
3760	-49.67	H	10.25	2.73	-42.15	-13	-29.15
326.7	-53.64	V	6.4	0.26	-47.5	-13	-34.5
609.3	-54.28	H	6.8	0.37	-47.85	-13	-34.85

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.76	V	10.36	2.73	-41.13	-13	-28.13
3819.6	-50.21	H	10.36	2.73	-42.58	-13	-29.58
321.7	-53.94	V	6.4	0.26	-47.8	-13	-34.8
608.2	-52.03	H	6.8	0.37	-45.6	-13	-32.6

#### Note:

- 1, The testing has been conformed to  $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band V (Part 22H)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.89	V	7.95	0.78	-39.72	-13	-26.72
1652.8	-56.02	H	7.95	0.78	-48.85	-13	-35.85
325.5	-52.63	V	6.4	0.26	-46.49	-13	-33.49
604.2	-53.97	H	6.8	0.37	-47.54	-13	-34.54

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.87	V	7.95	0.78	-39.7	-13	-26.7
1670	-45.86	H	7.95	0.78	-38.69	-13	-25.69
326.8	-52.91	V	6.4	0.26	-46.77	-13	-33.77
604.3	-52.84	H	6.8	0.37	-46.41	-13	-33.41

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.98	V	7.95	0.78	-39.81	-13	-26.81
1693.2	-45.67	H	7.95	0.78	-38.5	-13	-25.5
326.4	-52.64	V	6.4	0.26	-46.5	-13	-33.5
604.2	-53.04	H	6.8	0.37	-46.61	-13	-33.61

**Note:**

1, The testing has been conformed to  $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band II (Part 24E)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.65	V	10.25	2.73	-42.13	-13	-29.13
3704.8	-50.47	H	10.25	2.73	-42.95	-13	-29.95
327.9	-53.48	V	6.4	0.26	-47.34	-13	-34.34
605.3	-53.67	H	6.8	0.37	-47.24	-13	-34.24

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.86	V	10.25	2.73	-42.34	-13	-29.34
3760	-49.72	H	10.25	2.73	-42.2	-13	-29.2
324.1	-53.62	V	6.4	0.26	-47.48	-13	-34.48
603.7	-53.87	H	6.8	0.37	-47.44	-13	-34.44

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-49.22	V	10.36	2.73	-41.59	-13	-28.59
3815.2	-49.87	H	10.36	2.73	-42.24	-13	-29.24
328.6	-53.16	V	6.4	0.26	-47.02	-13	-34.02
603.8	-54.28	H	6.8	0.37	-47.85	-13	-34.85

**Note:**

1, The testing has been conformed to  $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

## 6.7 Band Edge

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	June 20, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram shows a Base Station (green box) and a Spectrum Analyzer (green box) connected to an EUT (blue box) via a power divider (black box). The Base Station and Spectrum Analyzer are connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A



**GSM Voice:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.12	-13
849.0025	-17.60	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.08	-13
1910.0225	-18.33	-13

**GPRS:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9800	-17.05	-13
849.0200	-17.82	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.19	-13
1910.0250	-18.10	-13

**EGPRS (MCS1):**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9989	-17.34	-13
849.0025	-17.05	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.61	-13
1910.0200	-18.60	-13

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824.000	-20.98	-13
849.275	-26.42	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-19.74	-13
1910.075	-20.60	-13

**HSDPA:**

**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.550	-20.99	-13
849.200	-25.16	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.900	-19.26	-13
1910.050	-21.07	-13

**HSUPA:**


**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.825	-21.22	-13
849.875	-27.27	-13

**UMTS-FDD Band II (Part 24E)**


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-19.99	-13
1910.025	-20.29	-13

**GSM Voice:  
Test Plots**




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.19/3)=4.0+0.3=4.3\text{dB}$




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.17/3)=4.0+0.3=4.3\text{dB}$



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.20/3)=4.5+0.3=4.8\text{dB}$




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.19/3)=4.5+0.3=4.8\text{dB}$


**GPRS:**

**Test Plots**




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.18/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.17/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(3.19/3)=4.5+0.3=4.8dB




PCS Band - High Channel


Note: Offset=Cable loss (4.5) + 10log  
(3.21/3)=4.5+0.3=4.8dB

## EGPRS (MCS1):

### Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.07/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.06/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.16/30)=4.5+2.0=6.5 dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.26/30)=4.5+2.0=6.5 dB

**HSDPA:**




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 (47.17/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 (47.02/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
 (47.20/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
 (47.32/30)=4.5+2.0=6.5 dB




**HSUPA:**




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.12/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.08/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.20/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.24/30)=4.5+2.0=6.5 dB

## 6.8 Frequency Stability

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	June 19, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th> <th>Base, fixed (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> </tr> </thead> <tbody> <tr> <td>25 to 50</td> <td>20.0</td> <td>20.0</td> <td>50.0</td> </tr> <tr> <td>50 to 450</td> <td>5.0</td> <td>5.0</td> <td>50.0</td> </tr> <tr> <td>450 to 512</td> <td>2.5</td> <td>5.0</td> <td>50.0</td> </tr> <tr> <td>821 to 896</td> <td>1.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>928 to 929</td> <td>5.0</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>929 to 960</td> <td>1.5</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>2110 to 2220</td> <td>10.0</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	50.0	821 to 896	1.5	2.5	2.5	928 to 929	5.0	N/A	N/A	929 to 960	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
		Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																														
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
450 to 512	2.5	5.0	50.0																																
821 to 896	1.5	2.5	2.5																																
928 to 929	5.0	N/A	N/A																																
929 to 960	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup		 <p>The diagram illustrates the test setup. On the left, a green rectangular box labeled 'Base Station' is shown. A line connects it to a blue rectangular box labeled 'EUT' (Equipment Under Test) which is enclosed within a dashed-line box labeled 'Thermal Chamber'.</p>																																	

Procedure	<p>A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage.</p> <p>Limit: The frequency stability of the transmitter shall be maintained within <math>\pm 0.00025\%</math> (<math>\pm 2.5\text{ppm}</math>) of the center frequency.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot     Yes (See below)             N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		19	0.0227	2.5
10		15	0.0179	2.5
20		13	0.0155	2.5
30		16	0.0191	2.5
40		15	0.0179	2.5
50		21	0.0251	2.5
55		18	0.0215	2.5
25	4.2	20	0.0239	2.5
	3.5	19	0.0227	2.5

**PCS Band (Part 24E) result**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	11	0.0059	2.5
0		13	0.0069	2.5
10		12	0.0064	2.5
20		13	0.0069	2.5
30		14	0.0074	2.5
40		16	0.0085	2.5
50		15	0.0080	2.5
55		16	0.0085	2.5
25	4.2	14	0.0074	2.5
	3.5	21	0.0112	2.5

RMC:

**UMTS-FDD Band V (Part 22H)**

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	12	0.0144	2.5
0		13	0.0156	2.5
10		14	0.0168	2.5
20		15	0.0180	2.5
30		12	0.0144	2.5
40		11	0.0132	2.5
50		18	0.0216	2.5
55		14	0.0168	2.5
25	4.2	17	0.0204	2.5
	3.5	11	0.0132	2.5

**UMTS-FDD Band II (Part 24E)**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0085	2.5
0		15	0.0080	2.5
10		13	0.0069	2.5
20		11	0.0059	2.5
30		12	0.0064	2.5
40		15	0.0080	2.5
50		11	0.0059	2.5
55		15	0.0080	2.5
25	4.2	16	0.0085	2.5
	3.5	12	0.0064	2.5

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>RF Conducted Test</b>					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/26/2017	05/25/2018	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>



Test Report	17070412-FCC-R1
Page	71 of 87

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View






EUT - Front View




EUT - Rear View




EUT - Top View




EUT - Bottom View



EUT - Left View



EUT - Right View



**Annex B.ii. Photograph: EUT Internal Photo**


Cover Off - Top View 1



Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with button - Front View



Mainboard with Shielding - Rear View




Mainboard without button - Front View




Mainboard without Shielding - Rear View



LCD – Front View




LCD – Rear View






BT - Antenna View




GSM/WCDMA - Antenna View



**Annex B.iii. Photograph: Test Setup Photo**



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK

#### Block Configuration Diagram for Radiated Emissions



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
PCD, LLC	Adapter	PH201Q	N/A
PCD, LLC	headset	PH201Q	N/A

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

## Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	17070412-FCC-R1
Page	86 of 87

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	17070412-FCC-R1
Page	87 of 87

## Annex E. DECLARATION OF SIMILARITY

N/A