| Applicant/Grantee ShenZhen Gather Genius Technology Limited / 2ALLF |  |                                   |              |                                      |              |  |  |  |  |
|---|--|-----------------------------------|--------------|--------------------------------------|--------------|--|--|--|--|
| FCC ID  |  | 2ALLFMMP                          |              |                                      |              |  |  |  |  |
| Section 15.212 Modular Transmitters                                 |  |                                   |              |                                      |              |  |  |  |  |
| Request   | for Modular  | Approval                          | Requ         | est for Limited Modular Approval     |              |  |  |  |  |
| •   |  | Requirements                      |              | EUT Conditions                       | Comply (Y/N) |  |  |  |  |
|   |  |                                   |              | Approval Requirements                |              |  |  |  |  |
| 1   | The radio elements of the modular  |                                   |              | The modular has shielded, Please see | Yes          |  |  |  |  |
|   | transmitter must have their own  |                                   |              | external photos.                     |              |  |  |  |  |
|   | shielding. The physical crystal and  |                                   | stal and     | 1                                    |              |  |  |  |  |
|   | tuning capacitors may be located external to the shielded radio elements.    |                                   |              |                                      |              |  |  |  |  |
|   |  |                                   |              |                                      |              |  |  |  |  |
| 2   | The modular transmitter must have  |                                   |              | The modular has its buffered         | Yes          |  |  |  |  |
|   | buffered modulation/data inputs (if such                                     |                                   |              | modulation. Please see the Schematic |              |  |  |  |  |
|   | inputs are pr  | ovided) to ensu                   | ire that the | Diagram.                             |              |  |  |  |  |
|   |  | comply with Pa                    |              |                                      |              |  |  |  |  |
|   | requirements under conditions of excessive data rates or over-modulation.    |                                   |              |                                      |              |  |  |  |  |
|   |  |                                   |              |                                      |              |  |  |  |  |
| 3   | The modular transmitter must have its  |                                   |              | The modular has its own power supply | Yes          |  |  |  |  |
|   | own power supply regulation.   |                                   | on.          | regulation, please see the Schematic |              |  |  |  |  |
|   |  |                                   |              | Diagram.                             |              |  |  |  |  |
| 4   | The modular  | r transmitter mu                  | ist comply   | The modular meets the FCC antenna    | Yes          |  |  |  |  |
|   | with the ante  | enna and transn                   | nission      | requirements. It has a PCB antenna.  |              |  |  |  |  |
|   |  | irements of Sec                   |              | Please see internal photos.          |              |  |  |  |  |
|   |  | nd 15.204(c). Tl                  |              |                                      |              |  |  |  |  |
|   |  | oe permanently                    |              |                                      |              |  |  |  |  |
|   |  | nique" antenna                    |              |                                      |              |  |  |  |  |
|   |  | ons between the                   |              |                                      |              |  |  |  |  |
|   |  | including the c                   |              |                                      |              |  |  |  |  |
|   |  | l installation" p                 |              |                                      |              |  |  |  |  |
|   |  | 03 is not applic                  |              |                                      |              |  |  |  |  |
|   |  | can apply to lin                  |              |                                      |              |  |  |  |  |
|   | modular approvals under paragraph (b)  |                                   | aragraph (b) |                                      |              |  |  |  |  |
|   | of this section.  The modular transmitter must be tested                     |                                   | .1 1         | D' 1 1 1 1 1 1 A E                   | *7           |  |  |  |  |
| 5   |  |                                   |              | Distance between modular and all AEs | Yes          |  |  |  |  |
|   |  | one configurati                   |              | are longer than 10cm refer to setup  |              |  |  |  |  |
|   |  | t not be inside a                 |              | photos.                              |              |  |  |  |  |
|   |  | g testing for co                  | -            |                                      |              |  |  |  |  |
|   |  | requirements. In nodule will be l |              |                                      |              |  |  |  |  |
|   |  | must comply w                     | •            |                                      |              |  |  |  |  |
|   |  | ed requirement                    |              |                                      |              |  |  |  |  |
|   |  | .07. AC or DC                     |              |                                      |              |  |  |  |  |
|   |  | ut/output lines                   |              |                                      |              |  |  |  |  |
|   | -  | nust not contain                  |              |                                      |              |  |  |  |  |
|   |  | will be markete                   | *            |                                      |              |  |  |  |  |
|   | _  | Section 15.27(                    |              |                                      |              |  |  |  |  |
|   |  | ese lines shall be                |              |                                      |              |  |  |  |  |
|   | _  | tual use or, if the               | _            |                                      |              |  |  |  |  |
|   | * -  |                                   | _            |                                      |              |  |  |  |  |
|   | unknown, at least 10 centimeters to insure that there is no coupling between |                                   |              |                                      |              |  |  |  |  |
|   | I moure mai u  | 1010 15 110 coupi                 | ing octwooli |                                      |              |  |  |  |  |

|   | the case of the module and supporting  |  | <u></u> |
|---|--|--|---------|
|   |  |  |         |
|   | equipment. Any accessories, peripherals,   |  |         |
|   | or support equipment connected to the  |  |         |
|   | module during testing shall be   |  |         |
|   | unmodified and commercially available  |  |         |
|   | (see Section 15.31(i)).  |  |         |
| 6 | The modular transmitter must be  | The modular has a permanent fixed        | Yes     |
|   | equipped with either a permanently   | label, and below statement was listed in |         |
|   | affixed label or must be capable of  | the User Manual; The host device         |         |
|   | electronically displaying its FCC  | must be labeled to display the FCC ID of |         |
|   | identification number.   | the module Contains                      |         |
|   | (A) If using a permanently affixed label, the  | FCC ID: 2ALLFMMBQ13                      |         |
|   | modular transmitter must be labeled with its own   | TOO ID. 21 IEEE WIND Q 13                |         |
|   | FCC identification number, and, if the FCC   |  |         |
|   | identification number is not visible when the  |  |         |
|   | module is installed inside another device, then  |  |         |
|   | the outside of the device into which the module is   |  |         |
|   | installed must also display a label referring to<br>the enclosed module. This exterior label can use |  |         |
|   | wording such as the following: "Contains   |  |         |
|   | Transmitter Module   |  |         |
|   | FCC ID: XYZMODEL1" or "Contains FCC ID:  |  |         |
|   | XYZMODEL1." Any similar wording  |  |         |
|   | that expresses the same meaning may be used.   |  |         |
|   | The Grantee may either provide such a label, an  |  |         |
|   | example of which must be included in the   |  |         |
|   | application for equipment  |  |         |
|   | authorization, or, must provide adequate instructions along with the module which explain            |  |         |
|   | this requirement. In the latter case, a copy of  |  |         |
|   | these instructions must be included in the   |  |         |
|   | application for equipment authorization.   |  |         |
|   | (B) If the modular transmitter uses an electronic  |  |         |
|   | display of the FCC identification number, the  |  |         |
|   | information must be readily accessible and   |  |         |
|   | visible on the modular transmitter or on the   |  |         |
|   | device in which it is installed. If the module is installed inside another device, then the outside  |  |         |
|   | of the device into which the module is installed   |  |         |
|   | must display a label referring to the enclosed   |  |         |
|   | module. This exterior label can use wording such   |  |         |
|   | as the following:  |  |         |
|   | "Contains FCC certified transmitter module(s)."  |  |         |
|   | Any similar wording that expresses the same  |  |         |
|   | meaning may be used. The user manual must  |  |         |
|   | include instructions on how to access the  |  |         |
|   | electronic display. A copy of these instructions<br>must be included in the application for          |  |         |
|   | equipment authorization.   |  |         |
| 7 | The modular transmitter must comply  | The modular is compliant with all        | Yes     |
| , | with any specific rules or operating   | applicable FCC rules. Detail             | 2 00    |
|   | requirements that  | instructions are given in the Users      |         |
|   | =  |  |         |
|   | ordinarily apply to a complete   | Manual                                   |         |
|   | transmitter and the manufacturer must  |  |         |
|   | provide adequate instructions along with   |  |         |
|   | the module to explain any such   |  |         |
|   | requirements. A copy of these  |  |         |
|   | instructions must be included in the   |  |         |
|   | instructions must be included in the   |  |         |

|   | application for equipment authorization. |                                      |     |
|---|--|--------------------------------------|-----|
| 8 | The modular transmitter must comply      | The modular comply with applicable   | Yes |
|   | with any applicable RF exposure          | KDB447498 RF exposure                |     |
|   | requirements in its final configuration. | requirements. Please see RF Exposure |     |
|   |  | report.                              |     |

A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Sincerely,

[Name] Xiantao.Chen

Xiantoo Chen

[Title] manager

[Company] ShenZhen Gather Genius Technology Limited