

# MPE CALCULATION

FCC ID: 2ALLL242A

RF Exposure Requirements:

47 CFR §1.1307(b)

RF Radiation Exposure Limits:

47 CFR §1.1310

RF Radiation Exposure Guidelines:

FCC OST/OET Bulletin Number 65

EUT Frequency Band:

24075 - 24175 MHz ,

Limits for General Population/Uncontrolled Exposure in the band of:

Power Density Limit: 1 mW / cm<sup>2</sup>

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

---

EUT: Radar Sensor , Model No.: OPS-242A

Antenna Type: Patch

Prediction distance 20cm

Power = 2.20 dBm, Antenna Gain = 7 dBi, Power density = 0.002084 mW/cm<sup>2</sup>

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Pass/ Fail
Radar	24125	2.20	7	±1dB	3.20	20	0.002084	1	Pass

The Above Result had shown that the Device complied with MPE requirement at 20 cm measurement distance.



Completed By: Benjamin Jing

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 07/26/2018