

FCC Radio Test Report

FCC ID: 2ALN5RL-13004-8

Report No. : TB-FCC152220
Applicant : Southern Imperial, Inc.
Equipment Under Test (EUT)
EUT Name : SONOR HOOK
Model No. : RL-13004-8
Serial No. : N/A
Brand Name : N/A
Receipt Date : 2017-01-12
Test Date : 2017-01-13 to 2017-03-30
Issue Date : 2017-03-31
Standards : FCC Part 15, Subpart C (15.231(a):2016)
Test Method : ANSI C63.10:2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer :

WANG SU

Approved & Authorized :

Ray



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	5
1.6 Description of Test Software Setting.....	6
1.7 Measurement Uncertainty.....	6
1.8 Test Facility	7
2. TEST SUMMARY	8
3. TEST EQUIPMENT	9
4. CONDUCTED EMISSION TEST	10
4.1 Test Standard and Limit.....	10
4.2 Test Setup.....	10
4.3 Test Procedure.....	10
4.4 Test Data.....	11
5. RADIATED EMISSION TEST	12
5.1 Test Standard and Limit.....	12
5.2 Test Setup.....	13
5.3 Test Procedure.....	14
5.4 EUT Operating Condition	15
5.5 Test Data.....	15
6. BANDWIDTH	35
6.1 Test Standard and Limit.....	35
6.2 Test Setup.....	35
6.3 Test Procedure.....	35
6.4 EUT Operating Condition	35
6.5 Test Condition	35
6.6 Test Data.....	36
7. RELEASE TIME MEASUREMENT	37
7.1 Test Standard and Limit.....	37
7.2 Test Setup.....	37
7.3 Test Procedure.....	37
7.4 EUT Operating Condition	37
7.5 Test Condition	38
7.6 Test Data.....	38
8. DUTY CYCLE	39

8.1 Test Standard and Limit.....	39
8.2 Test Setup.....	39
8.3 Test Procedure.....	39
8.4 EUT Operating Condition	39
8.5 Test Condition	39
8.6 Test Data.....	40
9. ANTENNA REQUIREMENT.....	42
9.1 Standard Requirement.....	42
9.2 Antenna Connected Construction	42

1. General Information about EUT

1.1 Client Information

Applicant	:	Southern Imperial, Inc.
Address	:	1400 Eddy Avenue Rockford, IL61103 USA
Manufacturer	:	Shenzhen Allcomm Electronic Company Limited
Address	:	Guangtian Road Left Side Tangxiayong community, Songgang Street, Shenzhen City, Guangdong Province, P.R. China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	SONOR HOOK	
Models No.	:	RL-13004-8	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	433.92 MHz
		Max Out Power:	90.68 dBuV/m (PK Max.) 78.59 dBuV/m (AV Max.)
		Antenna Gain:	Integral Antenna(0 dBi) see note 2
		Modulation Type:	ASK
Power Supply	:	DC power by Li-ion battery.	
Power Rating	:	DC 3.0V by Li-ion Battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	


Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Antenna description

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)	Note
ANT.1	N/A	N/A	Integral Ant.	0	12 inch
ANT.2	N/A	N/A	Integral Ant.	0	10inch
ANT.3	N/A	N/A	Integral Ant.	0	8inch
ANT.4	N/A	N/A	Integral Ant.	0	6inch
Note: The EUT can use difference Antenna, Antenna only difference is size.					

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

The EUT has been test as an independent unit.

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Test Items	Note
Conducted Emission	N/A
Radiated Emission	Continuously transmitting
Bandwidth	Continuously transmitting
Duty Cycle	Continuously transmitting
Release Time	Normal Mode

Note:

- (1) During the testing procedure, the continuously transmitting mode was programmed by the customer.
- (2) The EUT is considered a fixed unit, and it was pre-tested on the positioned of each 3 axis: X axis, Y axis and Z axis. The worst case was found positioned on Z-plane. There for only the test data of this Z-plane were used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of transmitting mode.

RF Power Setting in Test SW:	DEF
-------------------------------------	-----

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart (15.231(a))/ RSS 210 Issue 8: Annex 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 8.8	Conducted Emission	N/A	N/A
15.231	RSS-210 Annex 1 RSS-GEN 8.9/8.10	Release Time	PASS	N/A
		Radiation Emission	PASS	N/A
		20 dB Bandwidth	PASS	N/A
		Duty Cycle	PASS	N/A
Note: N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 25, 2017	Mar. 24, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar. 25, 2017	Mar. 24, 2018
Pre-amplifier	Sonoma	310N	185903	Mar. 24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar. 29, 2017	Mar. 28, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 29, 2017	Mar. 28, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC 15.207/RSS Gen 8.8

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 Test Data

The EUT is powered by DC battery, no requirement for this test item.

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC 15.231/RSS 210 Annex 1

5.1.2 Test Limit

According to RSS 210 A1.1 Table A requirement:

In addition to the provisions of RSS Gen 8.9 and 8.10, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolt/meter) at 3m	Field Strength of Spurious Emissions (microvolt/meter) at 3m
40.66~40.70	2250	225
70~130	1250	125
130~174	1250 to 3750(**)	125 to 375(**)
174~260	3750	375
260~470	3750 to 12500(**)	375 to 1250(**)
Above 470	12500	1250

** Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

- (1) for the band 130~174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$;
- (2) for the band 260~470 MHz, $\mu\text{V/m}$ at 3 meter = $41.6667(F) - 7083.3333$.
- (3) The maximum permitted unwanted emissions level is 20 dB below the maximum permitted fundamental level. In addition field strength of any emissions which appear inside of the restriction band shall not exceed the general radiated emissions limits in RSS Gen 8.9.

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	2400/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3

216~960	200	3
Above 960	500	3


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


So the field strength of emission limits have been calculated in below table.

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolt/meter) at 3m
433.92 MHz	80.82 (Average)
433.92 MHz	100.82 (Peak)


5.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by

3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values.
Average Values=Peak Values+20log (Duty Cycle)
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Test data please refer the following pages.


9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Fundamental and Harmonics emissions(30MHz~1GHz)


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	Standby Mode(Antenna 1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		36.2541	27.47	-17.99	9.48	40.00	-30.52	peak
2		106.3850	27.78	-21.85	5.93	43.50	-37.57	peak
3		230.9068	28.18	-18.62	9.56	46.00	-36.44	peak
4		397.6334	28.26	-12.49	15.77	46.00	-30.23	peak
5		711.6734	26.86	-5.70	21.16	46.00	-24.84	peak
6	*	872.1832	32.34	-4.71	27.63	46.00	-18.37	peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	Standby Mode(Antenna 1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		33.9174	27.04	-16.55	10.49	40.00	-29.51	peak
2		107.5101	26.89	-21.86	5.03	43.50	-38.47	peak
3		159.7844	28.21	-20.29	7.92	43.50	-35.58	peak
4		253.8367	28.86	-17.62	11.24	46.00	-34.76	peak
5		570.6100	27.87	-9.46	18.41	46.00	-27.59	peak
6	*	793.3958	26.94	-5.37	21.57	46.00	-24.43	peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	Standby Mode(Antenna 2)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		36.7662	27.21	-18.32	8.89	40.00	-31.11	peak
2		109.7960	27.76	-21.86	5.90	43.50	-37.60	peak
3		254.7284	27.69	-17.60	10.09	46.00	-35.91	peak
4		403.2500	28.50	-12.35	16.15	46.00	-29.85	peak
5		552.8832	28.28	-9.50	18.78	46.00	-27.22	peak
6	*	701.7610	27.17	-5.42	21.75	46.00	-24.25	peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	Standby Mode(Antenna 2)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		35.2512	26.32	-17.37	8.95	40.00	-31.05 peak
2		94.0979	27.53	-22.37	5.16	43.50	-38.34 peak
3		160.9089	28.41	-20.34	8.07	43.50	-35.43 peak
4		221.3921	27.25	-19.05	8.20	46.00	-37.80 peak
5		552.8832	28.27	-9.50	18.77	46.00	-27.23 peak
6	*	721.7259	28.33	-6.07	22.26	46.00	-23.74 peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	Standby Mode(Antenna 3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		32.0667	26.31	-15.42	10.89	40.00	-29.11	peak
2		94.0979	28.42	-22.37	6.05	43.50	-37.45	peak
3		160.9089	27.02	-20.34	6.68	43.50	-36.82	peak
4		246.8149	28.46	-17.85	10.61	46.00	-35.39	peak
5		414.7223	27.40	-12.41	14.99	46.00	-31.01	peak
6	*	696.8567	28.26	-5.53	22.73	46.00	-23.27	peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	Standby Mode(Antenna 3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	34.6385	26.61	-17.01	9.60	40.00	-30.40	peak
2	99.8777	28.22	-21.86	6.36	43.50	-37.14	peak
3	159.2251	27.44	-20.34	7.10	43.50	-36.40	peak
4	323.3204	27.04	-15.76	11.28	46.00	-34.72	peak
5	625.0780	27.29	-7.71	19.58	46.00	-26.42	peak
6 *	793.3960	28.56	-5.37	23.19	46.00	-22.81	peak

Emission Level= Read Level+ Correct Factor


EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	Standby Mode(Antenna 4)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		43.2017	27.05	-21.65	5.40	40.00	-34.60	peak
2		107.5101	30.73	-21.86	8.87	43.50	-34.63	peak
3		178.7584	28.46	-20.33	8.13	43.50	-35.37	peak
4		345.5952	26.56	-14.43	12.13	46.00	-33.87	peak
5		522.7180	25.96	-9.74	16.22	46.00	-29.78	peak
6	*	747.4825	27.41	-5.99	21.42	46.00	-24.58	peak

Emission Level= Read Level+ Correct Factor

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	Standby Mode(Antenna 4)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		35.3750	27.61	-17.45	10.16	40.00	-29.84	peak
2		97.7983	27.15	-22.04	5.11	43.50	-38.39	peak
3		247.6819	27.52	-17.81	9.71	46.00	-36.29	peak
4		462.3455	28.88	-11.54	17.34	46.00	-28.66	peak
5		706.6999	27.10	-5.94	21.16	46.00	-24.84	peak
6	*	900.1474	27.31	-3.60	23.71	46.00	-22.29	peak

Emission Level= Read Level+ Correct Factor

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss
 - (3) The QP measurement was not performed when the peak measured data under the limit of QP detection.

Fundamental and Harmonics emissions

Below 1G

EUT:		SONOR HOOK		Model Name :		RL-13004-8	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.0V					
Test Mode:		TX Mode(Antenna 1)					
Freq. (MHz)	Ant.Pol H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
325.5958	H	44.97	/	46.00	/	-1.03	/
434.0651	H	88.30	76.21	100.82	80.82	-28.20	-13.62
869.1302	H	57.28	45.19	80.82	60.82	-32.00	-17.42
325.5958	H	31.20	/	46.00	/	-14.80	/
434.0650	V	75.26	63.17	100.82	80.82	-25.56	-17.65
869.1302	V	38.03	25.94	80.82	60.82	-42.79	-34.88
Average Value=Peak Value-12.09							
Margin=Emission Level-Limit							


EUT:		SONOR HOOK		Model Name :		RL-13004-8	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.0V					
Test Mode:		TX Mode(Antenna 2)					
Freq. (MHz)	Ant.Pol H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
434.0651	H	90.68	78.59	100.82	80.82	-10.14	-2.23
869.1302	H	61.45	49.36	80.82	60.82	-19.37	-11.46
434.0651	V	79.98	67.89	100.82	80.82	-20.84	-12.93
869.1302	V	40.82	28.73	80.82	60.82	-40.00	-32.09
Average Value=Peak Value-12.09							
Margin=Emission Level-Limit							

EUT:		SONOR HOOK		Model Name :		RL-13004-8	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.0V					
Test Mode:		TX Mode(Antenna 3)					
Freq. (MHz)	Ant.Pol H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
434.0651	H	84.02	71.93	100.82	80.82	-16.8	-8.89
869.1302	H	50.81	38.72	80.82	60.82	-30.01	-22.1
434.0651	V	74.99	62.9	100.82	80.82	-25.83	-17.92
869.1302	V	51.27	39.18	80.82	60.82	-29.55	-21.64
Average Value=Peak Value-12.09							
Margin=Emission Level-Limit							

EUT:		SONOR HOOK		Model Name :		RL-13004-8	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.0V					
Test Mode:		TX Mode(Antenna 4)					
Freq. (MHz)	Ant.Pol H/V	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
434.0651	H	75.07	62.98	100.82	80.82	-25.75	-17.84
869.1302	H	44.41	32.32	80.82	60.82	-36.41	-28.5
434.0651	V	75.37	63.28	100.82	80.82	-25.45	-17.54
869.1302	V	39.09	27	80.82	60.82	-41.73	-33.82
Average Value=Peak Value-12.09							
Margin=Emission Level-Limit							

Above 1G

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode(Antenna 1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		1300.000	50.73	-5.39	45.34	74.00	-28.66	peak
2	*	1300.000	38.64	-5.39	33.25	54.00	-20.75	AVG
3		1736.000	47.79	-3.12	44.67	74.00	-29.33	peak
4		1736.000	35.70	-3.12	32.58	54.00	-21.42	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode(Antenna 1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1300.000	55.67	-5.39	50.28	74.00	-23.72	peak
2	*	1300.000	43.58	-5.39	38.19	54.00	-15.81	AVG
3		1735.718	49.28	-3.12	46.16	74.00	-27.84	peak
4		1735.718	37.19	-3.12	34.07	54.00	-19.93	AVG
5		2164.000	42.55	-0.18	42.37	74.00	-31.63	peak
6		2164.000	30.46	-0.18	30.28	54.00	-23.72	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode(Antenna 2)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1300.000	53.84	-5.39	48.45	74.00	-25.55	peak
2	*	1300.000	41.75	-5.39	36.36	54.00	-17.64	AVG
3		1736.000	49.11	-3.12	45.99	74.00	-28.01	peak
4		1736.000	37.02	-3.12	33.90	54.00	-20.10	AVG
5		2168.000	45.34	-0.16	45.18	74.00	-28.82	peak
6		2168.000	33.35	-0.16	33.19	54.00	-20.81	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode(Antenna 2)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1300.000	55.49	-5.39	50.10	74.00	-23.90	peak
2	*	1300.000	43.40	-5.39	38.01	54.00	-15.99	AVG
3		1736.000	49.25	-3.12	46.13	74.00	-27.87	peak
4		1736.000	37.16	-3.12	34.04	54.00	-19.96	AVG
5		2168.000	45.58	-0.16	45.42	74.00	-28.58	peak
6		2168.000	33.49	-0.16	33.33	54.00	-20.67	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode(Antenna 3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		1300.000	50.33	-5.39	44.94	74.00	-29.06 peak
2	*	1300.000	38.24	-5.39	32.85	54.00	-21.15 AVG
3		1736.000	45.80	-3.12	42.68	74.00	-31.32 peak
4		1736.000	33.71	-3.12	30.59	54.00	-23.41 AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode(Antenna 3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1300.000	51.19	-5.39	45.80	74.00	-28.20	peak
2		1300.000	39.10	-5.39	33.71	54.00	-20.29	AVG
3		1736.000	48.77	-3.12	45.65	74.00	-28.35	peak
4		1736.000	36.78	-3.12	33.66	54.00	-20.34	AVG
5		2168.000	46.00	-0.16	45.84	74.00	-28.16	peak
6	*	2168.000	33.91	-0.16	33.75	54.00	-20.25	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode(Antenna 4)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		1300.000	51.30	-5.39	45.91	74.00	-28.09	peak
2	*	1300.000	39.21	-5.39	33.82	54.00	-20.18	AVG
3		1732.000	46.09	-3.11	42.98	74.00	-31.02	peak
4		1732.000	34.00	-3.11	30.89	54.00	-23.11	AVG
5		2164.000	44.87	-0.18	44.69	74.00	-29.31	peak
6		2164.000	32.78	-0.18	32.60	54.00	-21.40	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

EUT:	SONOR HOOK	Model Name :	RL-13004-8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.0V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode(Antenna 4)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1300.000	56.48	-5.39	51.09	74.00	-22.91	peak
2	*	1300.000	44.39	-5.39	39.00	54.00	-15.00	AVG
3		1732.000	45.09	-3.11	41.98	74.00	-32.02	peak
4		1732.000	33.00	-3.11	29.89	54.00	-24.11	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-12.09

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV. And AV is calculated by the following:
Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values.
Average Values=Peak Values+20log (Duty Cycle)
 - (2) Emission Level= Reading Level + Probe Factor +Cable Loss
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Pulse Desensitization Correction Factor

Note:

- (1) The Smallest Pulse Width (PW)= 0.2484ms
- (2) $2/PW = 2/0.2484 \text{ (ms)} = 8.05 \text{ kHz} < 100 \text{ kHz}$

Because $2/PW < RBW$, so the PDCF is not needed.

6. Bandwidth

6.1 Test Standard and Limit

6.1.1 Test Standard


FCC 15.231/RSS 210 Annex 1

6.1.2 Test Limit

The 99% bandwidth of the emissions shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. So the emission bandwidth limits have been calculated in below table.

Fundamental Frequency	20 dB Bandwidth Limits (MHz)
433.92 MHz	1.0847

6.2 Test Setup



6.3 Test Procedure

- (1) Set Spectrum Analyzer Center Frequency= Fundamental Frequency, RBW=10 kHz, VBW= 30 kHz, Span= 1 MHz.
- (2) Measured the spectrum width with power higher than 20 dB below carrier.

6.4 EUT Operating Condition


The Equipment Under Test was Programmed to be in continuously transmitting mode.

6.5 Test Condition

Temperature	:	25 °C
Relative Humidity	:	65 %
Pressure	:	1010 hPa
Test Power	:	DC 3.0V

6.6 Test Data

Frequency (MHz)	20 dBc Bandwidth (kHz)	Limit (MHz)	Result
433.92	48	1.0847	PASS



Date: 30.MAR.2017 15:15:38

7. Release Time Measurement

7.1 Test Standard and Limit


7.1.1 Test Standard

FCC 15.231/RSS 210 Annex 1

7.1.2 Test Limit

According to RSS 210 Annex 1 A1.1.1, A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

7.2 Test Setup



7.3 Test Procedure

- (1) Setup the EUT as show in the block diagram above.
- (2) Set Spectrum Analyzer Centre Frequency= Fundamental Frequency, RBW=100 kHz, VBW= 300 kHz, Span= 0 Hz. Sweep Time= 5 Seconds.
- (3) Setup the EUT as normal operation and press Transmitter button.
- (4) Set Spectrum Analyzer View, Delta Mark time.

7.4 EUT Operating Condition


The EUT was set to work in transmitting mode.

7.5 Test Condition

Temperature	:	25 °C
Relative Humidity	:	65 %
Pressure	:	1010 hPa
Test Power	:	DC 3.0V

7.6 Test Data

Release Time (s)	Limit (s)	Result
0.83	5	PASS



Date: 30.MAR.2017 15:23:53


8. Duty Cycle

8.1 Test Standard and Limit

5.1.1 Test Standard

FCC 15.231/RSS 210 Annex 1

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was placed on a turntable which is 0.8m above ground plane.
- (2) Set EUT operating in continuous transmitting mode.
- (3) Set the Spectrum Analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth (RBW) to 100 kHz and video bandwidth (VBW) to 300 kHz, Span was set to 0 Hz.
- (4) The Duty Cycle was measured and recorded.

8.4 EUT Operating Condition

The EUT was programmed to be in transmitting mode.

8.5 Test Condition

Temperature	:	25 °C
Relative Humidity	:	65 %
Pressure	:	1010 hPa
Test Power	:	DC 3.0V

8.6 Test Data

Please refer the following pages:

Plot 1: transmit once in 100ms, and each cycle is 100 ms there are two kinds of pulse in each cycle, the large pulses total 27, the small pulses total 27.

Plot 2: one large pulse in a time period of 0.32 ms


Plot 3: one middle pulse in a time period of 0.60 ms

Duty Cycle=ON/Total= $(27 \times 0.32 + 27 \times 0.60) / 100 = 24.84 / 100 = 24.84\%$

20 log(Duty Cycle)=-12.09


Average=Peak Value+ 20log(Duty Cycle), AV=PK-12.09

Plot 1




Date: 30.MAR.2017 15:25:22

Plot 2



Date: 30.MAR.2017 15:26:06

Plot 3



Date: 30.MAR.2017 15:26:36

9. Antenna Requirement

9.1 Standard Requirement

9.1.1 Standard

FCC Part 15.203

9.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is an Integral Antenna. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☒ Unique connector antenna
☐ Professional installation antenna

-----END OF REPORT-----