

	TEST REPOR	T						
FCC ID:	2ALNA-BTH99							
Test Report No::	TCT240604E028							
Date of issue::	Jun. 21, 2024							
Testing laboratory:	SHENZHEN TONGCE TESTING LAB							
Testing location/ address:	cation/ address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China							
Applicant's name::	Shenzhen Thousandshores Ted	hnology Co., Ltd.						
Address::	Room 1101, Building B, Lotus Plaza, No. 3186 Nanshan Avenue, Majialong Community, Nantou Street, Nanshan District, Shenzhen, China							
Manufacturer's name:	Shenzhen Thousandshores Teo	Shenzhen Thousandshores Technology Co., Ltd.						
Address:	Room 1101, Building B, Lotus Plaza, No. 3186 Nanshan Avenue, Majialong Community, Nantou Street, Nanshan District, Shenzhen, China							
Standard(s):	KDB 447498 D01 General RF E	xposure Guidance v06						
Product Name::	True Wireless Earbuds							
Trade Mark:	Sportneer	(c)						
Model/Type reference:	ВТН99							
Rating(s)::	Rechargeable Li-ion Battery DC	3.7V						
Date of receipt of test item:	Jun. 04, 2024							
Date (s) of performance of test:	Jun. 04, 2024 ~ Jun. 21, 2024							
Tested by (+signature):	Onnado YE	Onrado JANGCE						
Check by (+signature):	Beryl ZHAO	Boy( TCT)						
Approved by (+signature):	Tomsin	Tomsies &						

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





# **Table of Contents**

1.1 1.2 2. Ge 2.1 2.2 3. Fa 3.1 3.2	. EUT desc.  . Model(s)  eneral Info  . Test envi  . Descripti  cilities ar  . Facilities  . Location	cription list ormation ironment a ion of Sup nd Accre	and mode. port Units	ent Data		



## 1. General Product Information

## 1.1. EUT description

Product Name:	True Wireless Earbuds		(,c <sup>(1)</sup> )
Model/Type reference:	ВТН99		
Sample Number	TCT240604E022-0101		
Operation Frequency:	2402MHz~2480MHz	(6)	
Modulation Type	For BT: GFSK, π/4-DQPSK, 8DPSK For BLE: GFSK		
Antenna Type	Internal Antenna		
Antenna Gain:	0.31dBi		
Rating(s):	Rechargeable Li-ion Battery DC 3.7V	(0)	

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.





## 2. General Information

## 2.1. Test environment and mode

Item	Normal condition								
Temperature	+25°C								
Voltage	DC 3.7V								
Humidity	56%								
Atmospheric Pressure:	1008 mbar								
Test Mode:									
Engineering mode:	Keep the EUT in continuous transmitting by select channel								

## 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Equipment Model No.		FCC ID	D Trade Name		
1	1		1	1		

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Page 4 of 6



## 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





### 4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

#### BDR+EDR:

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 39	2.441	1.50	1±1	2	1.58	5	0.50	3.0

#### BLE(1M):

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 19	2.440	3.89	3±1	4	2.51	5	0.78	3.0

BLE(2M):

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 19	2.440	3.94	3±1	4	2.51	5	0.78	3.0

#### Result:

Base on the calculation value, No SAR measurement is required.

\*\*\*\*\*END OF REPORT\*\*\*\*

Page 6 of 6