





<b>TEST REPORT nr. R19090601</b>	
<b>Federal Communication Commission (FCC)</b>	
<b>Test item</b>	
Description .....	KEYFOB-TYPE BLUETOOTH LOW ENERGY BEACON
Trademark .....	BLUEUP
Model/Type .....	BlueBeacon Tag Gen2 (BlueBeacon 05/02)
FCC ID .....	2ALP7BB0502
<b>Test Specification</b>	
Standard.....	KDB 447498 D01 General RF Exposure Guidance v06
<b>Client's name</b> .....	
Address .....	BLUEUP S.r.l.s. Loc. Belvedere, Ingresso 2 – 53034 Colle Val d'Elsa (SI) – ITALY
<b>Manufacturer's name</b> :	
Address .....	Same as client --
<b>Report</b>	
Tested by .....	M. Segalla 
Approved by .....	R. Beghetto – <i>Laboratory Manager</i> 
Date of issue .....	18.06.19
Contents.....	13 pages

This test report shall not be reproduced except in full without the written approval of CMC.  
 The test results presented in this report relate only to the item tested.

CMC Centro Misure Compatibilità S.r.l.



## Index

<b>1. SUMMARY</b> .....	<b>3</b>
<b>2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)</b> .....	<b>4</b>
2.1 TEST SITE .....	4
<b>3. TESTING AND SAMPLING</b> .....	<b>4</b>
<b>4. OPERATIVE CONDITIONS</b> .....	<b>4</b>
<b>5. PHOTOGRAPH(S) OF EUT</b> .....	<b>5</b>
5.1 PHOTOGRAPH(S) OF EUT .....	5
<b>6. EQUIPMENT LIST</b> .....	<b>6</b>
<b>7. MEASUREMENT UNCERTAINTY</b> .....	<b>7</b>
<b>8. REFERENCE DOCUMENTS</b> .....	<b>9</b>
<b>9. DEVIATION FROM TEST SPECIFICATION</b> .....	<b>10</b>
<b>10. TEST CASE VERDICTS</b> .....	<b>10</b>
<b>11. RESULTS</b> .....	<b>11</b>
11.1 RF EXPOSURE ANALYSIS.....	12



## 1. Summary

Standard:

KDB 447498 D01 General RF Exposure Guidance v06

Test specifications	Environmental Phenomena	Tests sequence	Result
KDB 447498 D01 cl. 4	RF Exposure Analysis	1	Complies


The Test Report was given to the Client representatives for necessary documentation of ratification of the tested equipment and it is valid for the FCC certification





## 5. Photograph(s) of EUT

### 5.1 Photograph(s) of EUT



CMC Centro Misure Compatibilità S.r.l.



## 6. Equipment list

<i>Id. number</i>	<i>Manufacturer</i>	<i>Model</i>	<i>Description</i>	<i>Serial number</i>	<i>Last calibration</i>	<i>Due date calibration</i>
CMC S164	Rohde & Schwarz	ESU26	EMC interference receiver	100052	January '18	January '19





## 7. Measurement uncertainty

Test	Test Setup	Expanded uncertainty	Note
Conducted emission CISPR 16 LISN 50uH 0,009-0,0150MHz	PE001_01	3,4 dB	1
Conducted emission CISPR 16 LISN 50uH 0,150-30,0MHz	PE001_01	3,0 dB	1
Conducted emission CISPR 16 Voltage Probe 0,15-30MHz	PE001_02	2,9 dB	1
Conducted emission CISPR 16 Current Probe 0,15-30MHz	PE001_03	2,6 dB	1
Conducted emission CISPR 16 ISN 0,15-30MHz	PE001_04	4,7 dB	1
Clic CISPR 16 LISN 50uH 0,150-30,0MHz	PE001_05	3,1 dB	1
Disturbance Power 30-300 MHz	PE002_01	3,6 dB	1
Radiated Emission LAS 0,15-30MHz	PE003_01	2,0 dB	1
Radiated Emission CISPR 16 Loop Ant. 0,15-30MHz	PE004_01	4,0 dB	1
Radiated Emission CISPR 16 Bicon. Ant. 30-300MHz	PE004_02	3,9 dB	1
Radiated Emission CISPR 16 LogP. Ant. 300-1000MHz	PE004_03	3,8 dB	1
Radiated Emission CISPR 16 Horn Ant. 1-18GHz	PE004_04	4,2 dB	1
Human Exposure to electromagnetic fields	PE005_01	23,6 %	1
Harmonic current emissions test	PE006_01	10 mA + 2,6 %	1
Voltage fluctuation and flicker test	PE007_01	4,8 %	1
Radiated Immunity 80MHz-6GHz	PE102_XX	2,1 dB 0,82 V/m a 3V/m	1
Conducted Immunity 0,15-230MHz	PE105_XX	1,2 dB 0,44 V a 3V	1
AC Magnetic field	PE106_01	1,55 % 0,15 A/m a 10A/m	1
Pulse Magnetic field	PE107_01	6,25 % 18,7 A/m a 300A/m	1
Dumped Magnetic field	PE108_01	6,25 % 1,87 A/m a 30A/m	1
Common mode conducted immunity	PE112_01	2,21 % 0,22 V a 10V	1



Test	Test Setup	Expanded uncertainty	Note
Power/Spurious 9kHz-30MHz	PR001_01	4,0 dB	1
Power/Spurious ERP 30-1000MHz d=10m	PR001_02+03	4,7 dB	1
Misura della potenza EIRP 1-18GHz d=3m	PR001_04	4,7 dB	1
Misura della potenza EIRP 18-40GHz d=3m	PR001_05	5,4 dB	1
Frequency error	PR002_01+02	< 1x10 <sup>-7</sup>	1
Timing zero span (1001pts.)	PR002_01+02	0,2 % SWT	1
Modulation bandwidth	PR002_01+02	< 1x10 <sup>-7</sup>	1
Conducted RF power and spurious emission	PR002_01+02	1,1 dB	1
Adjacent channel power	PR002_01+02	1,1 dB	1
Blocking	PR002_01+02	1,1 dB	1

Test	Test Setup	Expanded uncertainty	Note
Electrostatic discharge immunity test	PE101_0X		2
Electrical fast transients / burst immunity test	PE103_0X		2
Surge immunity test	PE104_0X		2
Short interruption immunity test	PE109_01		2

Rev\_19\_02 date 27/03/2019

**Note 1:**

The expanded uncertainty reported according to the document EA-4-02 is based on a standard uncertainty multiplied by a coverage factor of K=2, providing a level of confidence of p = 95%

**Note 2:**

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor k = 2





## 8. Reference documents

Reference no.	Description
KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES
FCC Rules and Regulation Title 47 part 15:2017	--
ANSI C63.4:2014	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
ANSI C63.10:2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Internal Procedure PM001 rev. 3.0 (Quality Manual)	Measure Procedure
Internal procedure INC_M rev. 9.0 (Quality Manual)	Measurement uncertainty calculation



## 9. Deviation from test specification

None

## 10. Test case verdicts

Test case does not apply to the test object ..... : N.A.

Test item does meet the requirement ..... : Complies

Test item does not meet the requirement ..... : Does not comply

Test not performed ..... : N.E.







## 11. Results

In this clause tests results are reported.

Measurement uncertainty is in accordance with document CMC INC\_M rev. 9.0.

*Judgement of compliance:*

Case 1	Case 2	Case 3	Case 4
			
<p>The sample complies with the requirement.</p> <p>The measurement results is within the specification limit when the measurement uncertainty is taken into account.</p>	<p>The sample complies with the requirement.</p> <p>It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.</p>	<p>The sample does not comply with the requirement.</p> <p>It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is upper the limit.</p>	<p>The sample does not comply with the requirement.</p> <p>The measurement results is outside the specification limit when the measurement uncertainty is taken into account.</p>

In agreement with ILAC-G8: 03/2009 Guidelines on the Reporting of Compliance with Specification.



## 11.1 RF Exposure Analysis

### Test set-up and execution

- KDB 447498 D01 cl. 4
- ANSI C63.10
- Internal procedure PM001
- See clause 4 of this test report

### Test configuration and test method

Test site:  
 Laboratory

Auxiliary equipment:  
 See clause 4 of this test report

### EUT exercising

See clause 4 of this test report

### Test equipment used

CMC S164  
 Measurement uncertainty: See clause 7 of this test report

### Test specification

Port: Enclosure

### Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
22	100	42

### Acceptance limits:

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. separation distance, mm})] \times \sqrt{f(\text{GHz})} \leq 3$  for 1-g SAR and  $\leq 7,5$  for 10-g SAR



MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

10-g Extremity SAR Test Exclusion Power Thresholds are 2,5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above.

### Result

Transmission channel (MHz)	Measured level (dB $\mu$ V/m)	Peak Output Conducted Power (mW)
2401	92,69	0,557
2441	100,36	3,259
2480	98,37	2,061

**Remarks:** the measured level and the peak output conducted power levels have been reported on Test Report nr. R19090501

Using separation distance of 5 mm with the formula above results:

$$(3,259 \text{ mW} / 5 \text{ mm}) * \sqrt{2,441 \text{ GHz}} = 1,018 \leq 3$$

Thus for portable use the SAR exclusion condition is fulfilled and SAR evaluation is not required for separation distance of 5 mm or more

**Result:** The requirements are met