



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20201001193E-02  
**Applicant:** Chengdu Ebyte Electronic Technology Co., Ltd.  
**Address of Applicant:** Building B5, Mould Industrial Park, 199# Xiqu Ave, West High-tech Zone, Chengdu, 611731, Sichuan, China  
**Equipment Under Test (EUT):**  
**EUT Name:** Wireless transceiver  
**Model No.:** E22-900T30S  
**Brand Name:** EBYTE  
**FCC ID:** 2ALPH-E22900T30S  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-10-13  
**Date of Test:** 2020-10-13 to 2020-11-06  
**Date of Issue:** 2020-11-09  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Tiny You  
( Tiny You )  
**Reviewed By:** Sheek Luo  
(Sheek Luo)  
**Approved By:** Jack Ai  
(Jack Ai)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20201001193E-02	Rev.01	Initial report	2020-11-09

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 RF EXPOSURE EVALUATION .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 <i>Limits</i> .....	5
4.1.2 <i>Test Procedure</i> .....	5
4.2 EUT RF EXPOSURE EVALUATION.....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Chengdu Ebyte Electronic Technology Co., Ltd.
Address of Applicant:	Building B5, Mould Industrial Park, 199# Xiqu Ave, West High-tech Zone, Chengdu, 611731, Sichuan, China
Manufacturer:	Chengdu Ebyte Electronic Technology Co., Ltd.
Address of Manufacturer:	Building B5, Mould Industrial Park, 199# Xiqu Ave, West High-tech Zone, Chengdu, 611731, Sichuan, China

#### 3.2 General Description of EUT

Product Name:	Wireless transceiver
Model No.:	E22-900T30S
Trade Mark:	EBYTE
Hardware Version:	V1.0
Software Version:	V1.0
Test sample SN:	W020285O02072
Frequency Range:	903~927MHz
Modulation Type:	LoRa
Number of Channels:	25 (declared by the client)
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	External antenna
Antenna Gain:	0 dBi
Power Supply:	DC 5V

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 4.2 EUT RF Exposure Evaluation

### 1) For LoRa

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

### Measurement Data

LoRa(DTS) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest	11.76	11±1	12	15.849
Middle	11.74	11±1	12	15.849
Highest	9.94	10±1	11	12.589

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
15.849	0	0.0032	0.6	PASS

Note: 1) Refer to report No. CQASZ20201001193E-01 for EUT test Max Conducted Peak Output Power value.

$$2) P_d = (P_{out} * G) / (4 * \pi * R^2) = (15.849 * 1) / (4 * 3.1416 * 20^2) = 0.0032$$