

# TEST REPORT

**Application No.:** HKEM2110001107AT  
**Applicant:** Accutime Watch Corp.  
**Address of Applicant:** 1001 Avenue of the Americas, 6<sup>th</sup> FL New York NY-10018 USA  
**Equipment Under Test (EUT):**  
**EUT Name:** NON-CHILD EARBUDS (WIRELESS)  
**Model No.:** 81386-5, 81387-3, 81379-0, 81385-7  
 Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**FCC ID:** 2ALPLEARBUDS  
**Standard(s) :** 47 CFR Part 1.1307, Part 1.1310  
 KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2022-01-14  
**Date of Test:** 2022-01-15 to 2022-01-28  
**Date of Issue:** 2022-01-28

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



**Law Man Kit**  
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2022-01-28		Original

<b>Authorized for issue by:</b>			
			
		<hr/> <b>Panny Leung</b> /Project Engineer	Date: 2022-01-28
			
		<hr/> <b>Law Man Kit</b> /Reviewer	Date: 2022-01-28

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
RF Exposure	47 CFR Part 1.1307, Part 1.1310	CFR 47 Part 1.1310	CFR 47 Part 1.1310	Pass

### Declaration of EUT Family Grouping:

Item no.: 81386-5, 81387-3, 81379-0, 81385-7

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout, electrical components used, internal wiring and functions. The difference is in color only.

Therefore, only the model 81386-5 was tested in this report

### Abbreviation:

- Tx: In this whole report Tx (or tx) means Transmitter.
- Rx: In this whole report Rx (or rx) means Receiver.
- RF: In this whole report RF means Radiated Frequency.
- CH: In this whole report CH means channel.
- Volt: In this whole report Volt means Voltage.
- Temp: In this whole report Temp means Temperature.
- Humid: In this whole report Humid means humidity.
- Press: In this whole report Press means Pressure.
- N/A: In this whole report not application.



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>5</b>
4.1 DETAILS OF E.U.T.....	5
4.2 DESCRIPTION OF SUPPORT UNITS.....	5
4.3 MODULATION CONFIGURE.....	6
4.4 MEASUREMENT UNCERTAINTY .....	7
4.5 TEST LOCATION .....	8
4.6 TEST FACILITY .....	8
4.7 DEVIATION FROM STANDARDS .....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
<b>5 EQUIPMENT LIST .....</b>	<b>9</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>10</b>
6.1 RF EXPOSURE .....	10
6.1.1 <i>Test Requirement:</i> .....	10
6.1.2 <i>Conclusion</i> .....	10
6.1.3 <i>Test Requirement:</i> .....	<b><i>Error! Bookmark not defined.</i></b>
6.1.4 <i>Conclusion</i> .....	<b><i>Error! Bookmark not defined.</i></b>
<b>7 PHOTOGRAPHS .....</b>	<b>11</b>
7.1 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS) .....	11

---

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	Charging case: USB 5.0VDC  Headsets: Lithium-Ion Battery Rated capacity: 40mAh, 0.148Wh Voltage: 3.7VDC
Test voltage:	3.7VDC
Cable:	N/A
Antenna Gain:	1.75 dBi
Antenna Type:	PIFA
Bluetooth Version:	5.0
Channel Spacing:	BT: 1MHz BLE: 2MHz
Modulation Type:	BT: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK
Number of Channels:	BT: 79 BLE: 40
Operation Frequency:	2402MHz to 2480MHz
Series number:	A1
Hardware Version:	TW1-AD6973d4-v1.0
Software Version:	218012_AC73D4E_TWS_XHJ_223_XHJ_EN_BT

### 4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

Description	Manufacturer	Model No.	SN/Certificate NO
FCC_Assist	N/A	Version 1.0.2.2	N/A

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook (EMC4)	Dell	P75F	N/A

### 4.3 Modulation configure

BT:

<b>RF software:</b>	FCC_Assist.exe			
<b>Modulation</b>	<b>Packet</b>	<b>Packet Type</b>	<b>Packet Size</b>	<b>Power</b>
GFSK	DH1	Pn9	Default	10
	DH3	Pn9	Default	10
	DH5	Pn9	Default	10
π/4DQPSK	2DH1	Pn9	Default	10
	2DH3	Pn9	Default	10
	2DH5	Pn9	Default	10
8DPSK	3DH1	Pn9	Default	10
	3DH3	Pn9	Default	10
	3DH5	Pn9	Default	10
Remark: 1. default value was set in test software as maximum output power setting.				

BLE:

<b>RF software:</b>	FCC_Assist.exe			
<b>Modulation</b>	<b>Packet</b>	<b>Packet Type</b>	<b>Packet Size</b>	<b>Power</b>
GFSK	Default	Default	Default	10
Remark: 1. default value was set in test software as maximum output power setting.				

#### 4.4 Measurement Uncertainty

RF

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power (30MHz-40GHz)	1.5dB
5	RF power density	1.5dB
6	Conducted Spurious emissions	1.5dB
7	RF Radiated power & Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.7dB (1GHz-6GHz)
		4.7dB (6GHz-18GHz)
		5.7dB (18GHz-40GHz)
8	Temperature test	$\pm 1^\circ\text{C}$
9	Humidity test	$\pm 3\%$
10	Supply voltages	$\pm 1.5\%$
11	Time	$\pm 3\%$

Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR}}$  (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

According to decision rule based on Clause 4.2 of CISPR 16-4-2, the EUT complied with the standards specified above.

#### 4.5 Test Location

All tests were performed at:

SGS Hong Kong Limited  
Unit 2 and 3, G/F, Block A, Po Lung Centre,  
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong  
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

#### 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website ([www.iasonline.org](http://www.iasonline.org)).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• **FCC Recognized Accredited Test Firm(CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

#### 4.7 Deviation from Standards

None

#### 4.8 Abnormalities from Standard Conditions

None

---



## 5 Equipment List

<b>Conducted Peak Output Power</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
SMBV100A VECTOR SIGNAL GENERATOR	Rohde & Schwarz	SMBV100A	E234	2021/08/16	2022/08/15
FSV40 SIGNAL ANALYZER 40GHz	Rohde & Schwarz	FSV40	E235	2021/08/16	2022/08/15
OSP	Rohde & Schwarz	OSP-B157W8	E242	2021/08/16	2022/08/15
Cable	Rohde & Schwarz	J12J103539-00-2	E239	2021/07/15	2022/07/14
WMS32 Test software	Rohde & Schwarz	N/A	Version 11	N/A	N/A

<b>General used equipment</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Digital temperature & humidity data logger	SATO	SK-L200TH II	E232	2021/08/16	2022/08/15
Electronic Digital Thermometer with Hygrometer	nil	2074/2075	E159	2021/08/16	2022/08/15
Barometer with digital thermometer	SATO	7612-00	E218	2021/03/29	2022/03/28
Conditional Chamber	Zhong Zhi Testing Instruments	CZ-E-608D	E216	2021/08/17	2022/08/16

## 6 Radio Spectrum Technical Requirement

### 6.1 RF Exposure

#### 6.1.1 Test Requirement:

CFR 47 Part 2.1093

Limit:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 6.1.2 Conclusion

According to the formula. calculate the test exclusion thresholds:

BT:

$$\text{General RF Exposure} = (1.479\text{mW} / 5\text{ mm}) \times \sqrt{2.480\text{ GHz}} = 0.47 \quad (1)$$

BLE:

$$\text{General RF Exposure} = (0.794\text{mW} / 5\text{ mm}) \times \sqrt{2.480\text{ GHz}} = 0.25 \quad (2)$$

SAR requirement:

$$S = 3.0 \quad (3)$$

(1), (2)  $<$  (3)

So the SAR report is not required.

Remark: 1.479mW and 0.794mW are worst conducted output power from report HKEM211000110702 & HKEM211000110703.



## **7 Photographs**

### **7.1 EUT Constructional Details (EUT Photos)**

Refer to the appendices: setup, external and internal photos.

- End of the Report -

---