

Maximum Permissible Exposure Report

1. Product Information

FCC ID	2ALPX-PE-4GA
Name of EUT	Wireless Door Intercom
Model Number	PRIME6-PROX-IMPX-PE-4GA, PRIME6-ABK-4GA, PRIME6-PROX-ABK-4GA, PRIME6-PROX-IMPX-PE-4GA, PRIME6-ASK-4GA, PRIME6-PROX-ASK-4GA, PRIME6-MODK-4GA, PRIME6-PROX-MODK-4GA, PRIME6-MODK-PE-4GA, PRIME6-PROX-MODK-PE-4GA, PRIME6-X1K, PRIME6-PROX-X1K, PRIME6-Z1K, PRIME6-PROX-Z1K, PRIME6-P1K, PRIME6-PROX-P1K, PRIME6-MULTI-LT-4GA, PRIME6-MULTI-LT-PE-4GA, PRIME6-MULTI-PX-LT-4GA, PRIME6-MULTI-PX-LT-PE-4GA, PRIME6-MULTI-CL-4GA, PRIME6-MULTI-CL-PE-4GA, PRIME6-MULTI-PX-CL-4GA, PRIME6-MULTI-PX-CL-PE-4GA
Model Declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Test Model	PRIME6-PROX-IMPX-PE-4GA
Modulation Type	QPSK for UMTS, QPSK, 16QAM for LTE
Antenna Gain	2 dBi (max.) For WCDMA Band II, V; 2 dBi (max.) For LTE Band 2, 4, 17
Hardware version	4GD00RPV09
Software version	4GKC9D1831V43
GSM/EDGE/GPRS Operation Frequency Band	Not Supported
UMTS Operation Frequency Band	UMTS FDD Band II/ V
LTE Operation Frequency Band	LTE FDD band 2, 4, 17
GSM/EDGE/GPRS	Not Supported
GSM Release Version	Not Supported
GSM/EDGE/GPRS Power Class	Not Supported
GPRS/EDGE Multislot Class	Not Supported
GPRS operation mode	Not Supported
WCDMA Release Version	R8
HSDPA Release Version	Release 8
HSUPA Release Version	Release 6
DC-HSUPA Release Version	Not Supported
LTE Release Version	R9
LTE/UMTS Power Class	Class 3
WLAN FCC Modulation Type	Not Supported
WLAN FCC Operation frequency	Not Supported
Antenna Type	External Antenna
BT Modulation Type	Not Supported
Extreme temp. Tolerance	-20°C to +55°C
Extreme vol. Limits	21.60VDC to 26.4VDC (nominal: 24.0VDC)
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

ES-D4 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna 0	External Antenna	600 MHz – 3000 MHz	2.00 dBi	WCDMA/LTE Antenna

6. Conducted Power

[WCDMA Max Conducted Power]

Test Mode	Channel	Frequency (MHz)	Max Average Power (dBm)
WCDMA Band II	Low	1852.4	23.40
	Middle	1880	23.54
	High	1907.6	23.65
WCDMA Band V	Low	826.4	23.41
	Middle	836.4	23.20
	High	846.6	23.22

[LTE Max Conducted Power]

Test Mode	Channel	Frequency (MHz)	Max Average Power (dBm)	
LTE	Band 2	LCH	1850.7	25.45
		MCH	1880.0	25.90
		HCH	1909.3	25.71
	Band 4	LCH	1710.7	23.09
		MCH	1732.5	22.78
		HCH	1754.3	22.87
	Band 17	LCH	706.5	25.83
		MCH	710.0	26.16
		HCH	713.5	26.30

7. Manufacturing Tolerance

[WCDMA Max Conducted Power]

Test Mode		Channel	Max Conducted Power (dBm)	ANT Max. Tune Up Power (dBm)
WCDMA	Band II	LCH	23.40	23.0±1.0
		MCH	23.54	23.0±1.0
		HCH	23.65	23.0±1.0
	Band V	LCH	23.41	23.0±1.0
		MCH	23.20	23.0±1.0
		HCH	23.22	23.0±1.0

<LTE Max Conducted Power>

Test Mode		Channel	Max Conducted Power (dBm)	ANT Max. Tune Up Power (dBm)
LTE	Band 2	LCH	25.45	25.0±1.0
		MCH	25.90	25.0±1.0
		HCH	25.71	25.0±1.0
	Band 4	LCH	23.09	23.0±1.0
		MCH	22.78	22.0±1.0
		HCH	22.87	22.0±1.0
	Band 17	LCH	25.83	25.0±1.0
		MCH	26.16	26.0±1.0
		HCH	26.36	26.0±1.0

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
WCDMA Band II	24.00	251.1886	2.0000	1.5849	0.079241	1.0000
WCDMA Band V	24.00	251.1886	2.0000	1.5849	0.079241	0.5576
LTE Band 2	26.00	398.1072	2.0000	1.5849	0.125589	1.0000
LTE Band 4	24.00	251.1886	2.0000	1.5849	0.079241	1.0000
LTE Band 17	27.00	501.1872	2.0000	1.5849	0.158107	0.4733

Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. MPE values = $PG/4\pi R^2$

8.2 Simultaneous Transmission MPE

The sample support one LTE&WCDMA transmit antenna, so no need consider simultaneous transmission;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----