

Maximum Permissible Exposure Report

1. Product Information

FCC ID : 2ALPX-PRIME7-4GQA
 EUT : CellCOM Prime 7 4G
 Test Model : PRIME7-PX-IMPK-PED/4GA
 Additional Model No. : PRIME7-IMP-PED/4GA, PRIME7-PX-IMP-PED/4GA,
 PRIME7-IMPK-PED/4GA, PRIME7-PX-IMPK-PED/4GA,
 PRIME7-AB/4GA, PRIME7-PX-AB/4GA, PRIME7-ABK/4GA,
 PRIME7-PX-ABK/4GA
 Model declaration : PCB board, structure and internal of these model(s) are the same,
 So no additional models were tested.
 Power Supply : For Adapter Model: GEO451DA-240200
 Adapter Input: 100-240V~, 50/60Hz, 1.2A
 Adapter Output: 24V---2A
 Hardware Version : 4GDOORPV16
 Software Version : Cellcom Prime V2.1.2
LTE :
 Support Band : E-UTRA Band 2(U.S.-Band)
E-UTRA Band 4(U.S.-Band)
E-UTRA Band 5(U.S.-Band)
E-UTRA Band 12(U.S.-Band)
E-UTRA Band 13(U.S.-Band)
E-UTRA Band 14(U.S.-Band)
E-UTRA Band 66(U.S.-Band)
E-UTRA Band 71(U.S.-Band)
 LTE Release Version : R11
 Type Of Modulation : QPSK/16QAM
 Antenna Description : PIFA Antenna;
 0dBi (max.) For E-UTRA Band 2;
 0dBi (max.) For E-UTRA Band 4;
 0dBi (max.) For E-UTRA Band 5;
 0dBi (max.) For E-UTRA Band 12;
 0dBi (max.) For E-UTRA Band 13;
 0dBi (max.) For E-UTRA Band 14;
 0dBi (max.) For E-UTRA Band 66;
 0dBi (max.) For E-UTRA Band 71.
 Power Class : Class 3
 Exposure category : General population/uncontrolled environment
 EUT Type : Production Unit
 Device Type : Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

Jiangmen Todaair Electronics Co., Ltd can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
PIFA Antenna	1850~1910 MHz	0dBi	LTE ANT
PIFA Antenna	1710~1755 MHz	0dBi	LTE ANT
PIFA Antenna	824~849 MHz	0dBi	LTE ANT
PIFA Antenna	669~716 MHz	0dBi	LTE ANT
PIFA Antenna	777~787 MHz	0dBi	LTE ANT
PIFA Antenna	788~798 MHz	0dBi	LTE ANT
PIFA Antenna	1710~1780 MHz	0dBi	LTE ANT
PIFA Antenna	663~698 MHz	0dBi	LTE ANT

6. Conducted Power

[LTE Max Average Power]

Test Mode		Channel	Max Average Power (dBm)
LTE	Band 2	LCH	23.25
		MCH	23.81
		HCH	23.23
	Band 4	LCH	23.69
		MCH	23.81
		HCH	23.91
	Band 5	LCH	23.92
		MCH	24.20
		HCH	24.39
	Band 12	LCH	22.71
		MCH	24.10
		HCH	25.04
	Band 13	LCH	24.44
		MCH	24.91
		HCH	25.03
	Band 14	LCH	23.52
		MCH	23.93
		HCH	23.74
	Band 66	LCH	23.97
		MCH	23.97
		HCH	24.00
	Band 71	LCH	23.98
		MCH	24.00
		HCH	23.99

7. Manufacturing Tolerance

<LTE Max Average Power>

Test Mode		Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
LTE	Band 2	LCH	23.64	23.0±1.0
		MCH	23.97	23.0±1.0
		HCH	24.50	24.0±1.0
	Band 4	LCH	23.01	23.0±1.0
		MCH	22.03	22.0±1.0
		HCH	22.86	22.0±1.0
	Band 5	LCH	23.09	23.0±1.0
		MCH	22.65	22.0±1.0
		HCH	22.49	22.0±1.0
	Band 12	LCH	23.08	23.0±1.0
		MCH	23.13	23.0±1.0
		HCH	23.49	23.0±1.0
	Band 13	LCH	22.51	22.0±1.0
		MCH	23.01	23.0±1.0
		HCH	22.57	22.0±1.0
	Band 14	LCH	23.52	23.0±1.0
		MCH	23.93	23.0±1.0
		HCH	23.74	23.0±1.0
	Band 66	LCH	24.46	24.0±1.0
		MCH	24.12	24.0±1.0
		HCH	24.02	24.0±1.0
Band 71	LCH	23.99	23.0±1.0	
	MCH	24.07	24.0±1.0	
	HCH	23.98	23.0±1.0	

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
LTE Band 2	25.0	316.2278	0	1.4962	0.0629	1.0
LTE Band 4	24.0	251.1886	0	1.3996	0.0500	1.0
LTE Band 5	24.0	251.1886	0	0.7194	0.0500	0.55
LTE Band 12	24.0	251.1886	0	0.6714	0.0500	0.47
LTE Band 13	24.0	251.1886	0	0.9226	0.0500	0.52
LTE Band 14	24.0	251.1886	0	1.1482	0.0500	0.53
LTE Band 66	25.0	316.2278	0	1.3996	0.0629	1.0
LTE Band 71	25.0	316.2278	0	0.6714	0.0629	0.44

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;
3. We choose the lowest frequency operate to calculate MPE limit as higher frequency will have higher MPE limits;
4. MPE values = $PG/4\pi R^2$.

8.2 Simultaneous Transmission MPE

The sample support one LTE Antenna, so not need consider simultaneous transmission;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----