

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Dongguan City MeiZhiZun Electronics Technology Co., Ltd

SAPPHIRE BLUETOOTH SPEAKER

Model Number: MUZ6009

Additional Model: DT20, DT202, A618

FCC ID: 2ALS7MUZ6009

Prepared for:	Dongguan City MeiZhiZun Electronics Technology Co., Ltd
	No. 33, Hehe Road, Xiangxi Village, Liaobu Town, Dongguan,
	Guangdong. China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R1904080
Date of Test:	Apr. 11~23, 2019
Date of Report:	Apr. 24, 2019

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram.....	8
2.6. Test mode	9
2.7. Channel List.....	9
2.8. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER.....	12
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Result	12
3.4. Test Data.....	13
4. 20 DB BANDWIDTH	17
4.1. Limit	17
4.2. Test Procedure	17
4.3. Test Result	17
4.4. Test Data.....	18
5. CARRIER FREQUENCY SEPARATION.....	22
5.1. Limit	22
5.2. Test Procedure	22
5.3. Test Result	22
5.4. Test Data.....	23
6. NUMBER OF HOPPING CHANNEL	27
6.1. Limit	27
6.2. Test Procedure	27
6.3. Test Result	27
6.4. Test Data.....	28
7. DWELL TIME.....	29
7.1. Limit	29
7.2. Test Procedure	29
7.3. Test Result	29
7.4. Test Data.....	30
8. RADIATED EMISSIONS	34
8.1. Limit	34
8.2. Block Diagram of Test setup	35
8.3. Test Procedure	36
8.4. Test Result	36
8.5. Test Data.....	37

9. BAND EDGE COMPLIANCE 47

 9.1. Limit 47

 9.2. Block Diagram of Test setup 47

 9.3. Test Procedure 47

 9.4. Test Result 47

 9.5. Test Data 48

10. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST 56

 10.1. Limit 56

 10.2. Test Procedure 56

 10.3. Test Result 56

11. POWER LINE CONDUCTED EMISSIONS 61

 11.1. Limit 61

 11.2. Test Procedure 61

12. ANTENNA REQUIREMENTS 66




 12.1. Limit 66

 12.2. Result 66

13. TEST SETUP PHOTO 67

14. PHOTO EUT 69

EST Technology Co., Ltd.

Applicant:	Dongguan City MeiZhiZun Electronics Technology Co., Ltd		
Address:	No. 33, Hehe Road, Xiangxi Village, Liaobu Town, Dongguan, Guangdong. China		
Manufacturer:	YALANSHI INTERNATIONAL(HONG KONG) LIMITED		
Address:	FLAT/RM 1301, BLK A 13/F, NEW MANDARIN PLAZA,14 SCIENCE MUSEUM ROAD, TSIMSHATSUI EAST, KL		
Factory:	Dongguan City MeiZhiZun Electronics Technology Co., Ltd		
Address:	No. 33, Hehe Road, Xiangxi Village, Liaobu Town, Dongguan, Guangdong. China		
E.U.T:	SAPPHIRE BLUETOOTH SPEAKER		
Model Number:	MUZ6009		
Additional Model:	DT20, DT202, A618 Note: These models have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, except the different model number and appearance.		
Power Supply:	DC 5V From Adapter Input AC 100-240V ~50/60Hz DC 3.7V From Battery		
Test Voltage:	DC 5V From Adapter Input AC 120V/60Hz DC 5V From Adapter Input AC 240V/60Hz DC 3.7V		
Trade Name:	MUZE , EARISE	Serial No.:	-----
Date of Receipt:	Apr. 11, 2019	Date of Test:	Apr. 11~23, 2019
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2018 ANSI C63.10:2013		
Test Result:	<p>The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p> <p style="text-align: right;">Date: Apr. 24, 2019</p>		
Prepared by:	Reviewed by:	Approved by:	
 _____ Ring / Assistant	 _____ Tony / Engineer	 _____ Ice-man / H.O Manager	
Other Aspects: None.			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	SAPPHIRE BLUETOOTH SPEAKER
FCC ID	:	2ALS7MUZ6009
Model Number	:	MUZ6009
Operation frequency	:	2402MHz~2480MHz
Number of channel	:	79
Antenna	:	PCB antenna, -0.58dBi Gain
Modulation	:	BT 5.0 BDR: GFSK EDR: $\pi/4$ -DQPSK
Sample Type	:	Prototype production

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) KDB 558074	PASS
20dB Bandwidth	FCC Part 15: 15.247a1 KDB 558074	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) KDB 558074	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) KDB 558074	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) KDB 558074	PASS
Radiated Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) KDB 558074	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: KDB 558074 D01 15.247 Meas Guidance v05		

2.2. Test Facilities

EMC Lab

: Certificated by CNAS, CHINA
Registration No.: L5288
Date of registration: November 13, 2017

Certificated by FCC, USA
Designation Number: CN1215
Test Firm Registration Number: 722932
Date of registration: November 21, 2017

Certificated by A2LA, USA
Registration No.: 4366.01
Date of registration: November 07, 2017

Certificated by Industry Canada
CAB identifier No.: CN0035
Date of registration: January 04, 2019

Certificated by VCCI, Japan
Registration No.: R-13663; C-14103
Date of registration: July 25, 2017
This Certificate is valid until: July 24, 2020

Certificated by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Certificated by TUV/PS, Shenzhen
Registration No.: SCN1017
Date of registration: January 27, 2011

Certificated by Intertek ETL SEMKO
Registration No.: 2011-RTL-L2-64
Date of registration: April 28, 2011

Certificated by Nemko, Hong Kong
Registration No.: 175193
Date of registration: May 4, 2011

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	±3.48dB
Uncertainty for spurious emissions test (30MHz-1GHz)	±4.60 dB(Polarize: H)
	±4.68 dB(Polarize: V)
Uncertainty for spurious emissions test (1GHz to 18GHz)	±4.96dB
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.4. Assistant equipment used for test

2.4.1. N/A

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.



(EUT: SAPPHIRE BLUETOOTH SPEAKER)

2.6. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
$\pi/4$ -DQPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

2.7. Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

2.8. Test Equipment

2.8.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	CEPREI	June 15,18	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	101260	CEPREI	June 15,18	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	CEPREI	June 15,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 15,18	1 Year
Active Loop Antenna	SCHWARZECK	FMZB 1519B	1519B-088	N/A	Aug. 01,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 15,18	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	CEPREI	June 15,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.4. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZECK	BBHA 9120 D	BBHA9120D1002	CEPREI	June 18,18	1 Year
Horn Antenna	SCHWARZECK	BBHA9170	BBHA9170242	CEPREI	June 18,18	1Year
Signal Amplifier	SCHWARZECK	BBV9718	9718-212	CEPREI	June 15,18	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV	103173	CEPREI	June 15,18	1 Year
PSA Series Spertrum Analyzer	Agilent	E4447A	MY50180031	CEPREI	June 15,18	1Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.5. For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 15,18	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211 139	CEPREI	June 15,18	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset employing at least 75 non-overlapping hopping channels; shall not exceed 0.125 W if the hopset employing at greater than or equal to 15 and less than 75 non-overlapping hopping channels.

3.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.

3.3. Test Result


EUT: SAPPHIRE BLUETOOTH SPEAKER					
M/N: MUZ6009					
Test date: 2019-04-12		Test site: RF site		Tested by: Viking	
Mode	Freq (MHz)	Result (dBm)	Limit		Conclusion
			dBm	W	
GFSK	2402	-0.22	30.00	1	Pass
	2441	-0.67	30.00	1	Pass
	2480	-1.64	30.00	1	Pass
$\pi/4$ -DQPSK	2402	0.47	30.00	1	Pass
	2441	0.03	30.00	1	Pass
	2480	-0.98	30.00	1	Pass

3.4. Test Data


GFSK 2402 MHz




GFSK 2441 MHz




GFSK 2480 MHz




π /4-DQPSK 2402 MHz



π /4-DQPSK 2441 MHz



π /4-DQPSK 2480 MHz



4. 20 DB BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: SAPPHIRE BLUETOOTH SPEAKER				
M/N: MUZ6009				
Test date: 2019-04-12		Test site: RF site		Tested by: Viking
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	0.877	/	PASS
	2441	0.857	/	PASS
	2480	0.876	/	PASS
$\pi/4$ -DQPSK	2402	1.225	/	PASS
	2441	1.227	/	PASS
	2480	1.225	/	PASS

4.4. Test Data


GFSK 2402MHz



GFSK 2441MHz




GFSK 2480MHz




$\pi/4$ -DQPSK 2402MHz



$\pi/4$ -DQPSK 2441MHz



π /4-DQPSK 2480MHz



5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.

5.3. Test Result


EUT: SAPPHIRE BLUETOOTH SPEAKER				
M/N: MUZ6009				
Test date: 2019-04-12			Test site: RF site	Tested by: Viking
Mode	Channel	Channel separation (MHz)	Limit (MHz)	Conclusion
GFSK	Low CH	1.000	0.877	PASS
	Mid CH	1.000	0.857	PASS
	High CH	1.000	0.876	PASS
$\pi/4$ -DQPSK	Low CH	1.000	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS

5.4. Test Data


GFSK Low Channel




Mid Channel




High Channel




$\pi/4$ -DQPSK Low Channel



Mid Channel



High Channel



6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

6.3. Test Result


EUT: SAPPHIRE BLUETOOTH SPEAKER			
M/N: MUZ6009			
Test date: 2019-04-12		Test site: RF site	Tested by: Viking
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
π /4-DQPSK	79	>15	PASS

6.4. Test Data

GFSK



$\pi/4$ -DQPSK



7. DWELL TIME

7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2. Test Procedure


1. The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW= 1MHz, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.

7.3. Test Result


EUT: SAPPHIRE BLUETOOTH SPEAKER					
M/N: MUZ6009					
Test date: 2019-04-12		Test site: RF site		Tested by: Viking	
Mode	Hops in Observation Period(hops)	Pulse Duration (ms)	Dwell time (ms)	Limit	Conclusion
GFSK DH1	320	0.40	128.0	<400ms	PASS
GFSK DH3	160	1.66	265.6	<400ms	PASS
GFSK DH5	106.67	2.91	310.4	<400ms	PASS
$\pi/4$ -DQPSK 2DH1	320	0.43	137.6	<400ms	PASS
$\pi/4$ -DQPSK 2DH3	160	1.66	265.6	<400ms	PASS
$\pi/4$ -DQPSK 2DH5	106.67	2.92	311.5	<400ms	PASS
1. DH1 Packet permit maximum 1600 hops/s with 2 timeslot in 79 channels (1 timeslot TX, 1 timeslot RX),So the hops in Observation Period($0.4s \times 79$ channel) $= (1600/79/2)hops/s \times 0.4s \times 79 = 320$ hops. 2. DH3 Packet permit maximum 1600 hops/s with 4 timeslot in 79 channels (3 timeslot TX, 1 timeslot RX),So the hops in Observation Period($0.4s \times 79$ channel) $= (1600/79/4)hops/s \times 0.4s \times 79 = 160$ hops. 3. DH5 Packet permit maximum 1600 hops/s with 6 timeslot in 79 channels (5 timeslot TX, 1 timeslot RX),So the hops in Observation Period($0.4s \times 79$ channel) $= (1600/79/5)hops/s \times 0.4s \times 79 = 106.67$ hops. 4. Dwell Time= Hops in Observation Period \times Pulse Duration.					

7.4. Test Data


GFSK DH1




GFSK DH3




GSFK DH5




$\pi/4$ -DQPSK 2DH1



$\pi/4$ -DQPSK 2DH3



π /4-DQPSK 2DH5



8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


- Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Block Diagram of Test setup


9kHz~30MHz



30~1000MHz



Above 1GHz



8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,
PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

8.4. Test Result

Pass

- Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
- 2、 The frequency 2402MHz , 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.
- 3、 all modes have been tested , only worse case is reported.

8.5. Test Data

9 kHz – 30 MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30 MHz – 1000 MHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 31 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 31
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : TX Mode


	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	47.46	9.40	0.29	12.26	21.95	40.00	18.05	QP
2	143.49	11.83	1.06	12.87	25.76	43.50	17.74	QP
3	288.02	13.26	1.82	15.60	30.68	46.00	15.32	QP
4	312.27	13.90	1.90	13.90	29.70	46.00	16.30	QP
5	480.08	16.80	2.63	12.98	32.41	46.00	13.59	QP
6	527.61	18.76	2.77	8.32	29.85	46.00	16.15	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 32 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 32
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.97	17.50	0.14	13.57	31.21	40.00	8.79	QP
2	131.85	11.76	0.99	14.73	27.48	43.50	16.02	QP
3	143.49	11.83	1.06	19.17	32.06	43.50	11.44	QP
4	480.08	16.80	2.63	7.83	27.26	46.00	18.74	QP
5	527.61	18.76	2.77	6.79	28.32	46.00	17.68	QP
6	563.50	19.57	2.87	4.86	27.30	46.00	18.70	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

1000-18000MHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 25 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17




Site no. : 1# 966 Chamber Data no. : 25
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : n/4-DQPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.26	2.89	34.68	93.61	89.08	74.00	-15.08	Peak
2	4804.00	31.16	4.51	34.68	45.36	46.35	74.00	27.65	Peak
3	7206.00	36.05	5.84	34.58	38.51	45.82	74.00	28.18	Peak
4	10044.00	38.58	6.77	34.59	39.08	49.84	74.00	24.16	Peak
5	14600.00	41.04	8.34	34.26	35.56	50.68	74.00	23.32	Peak
6	17966.00	47.87	9.75	34.30	26.70	50.02	74.00	23.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 26 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17




Site no. : 1# 966 Chamber Data no. : 26
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.26	2.89	34.68	95.75	91.22	74.00	-17.22	Peak
2	4804.00	31.16	4.51	34.68	44.60	45.59	74.00	28.41	Peak
3	7206.00	36.05	5.84	34.58	37.82	45.13	74.00	28.87	Peak
4	10707.00	39.57	7.01	34.39	37.22	49.41	74.00	24.59	Peak
5	14566.00	41.04	8.35	34.26	34.25	49.38	74.00	24.62	Peak
6	17779.00	46.60	9.63	34.28	28.97	50.92	74.00	23.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 27 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 27
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2441MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.33	2.90	34.67	95.96	91.52	74.00	-17.52	Peak
2	4882.00	31.39	4.71	34.69	43.85	45.26	74.00	28.74	Peak
3	7323.00	36.19	5.88	34.57	39.86	47.36	74.00	26.64	Peak
4	10979.00	39.97	7.10	34.31	36.72	49.48	74.00	24.52	Peak
5	14566.00	41.04	8.35	34.26	35.88	51.01	74.00	22.99	Peak
6	17881.00	47.29	9.70	34.29	27.63	50.33	74.00	23.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 28 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17




Site no. : 1# 966 Chamber Data no. : 28
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.33	2.90	34.67	94.62	90.18	74.00	-16.18	Peak
2	4882.00	31.39	4.71	34.69	42.27	43.68	74.00	30.32	Peak
3	7323.00	36.19	5.88	34.57	36.95	44.45	74.00	29.55	Peak
4	10911.00	39.87	7.07	34.33	36.13	48.74	74.00	25.26	Peak
5	15042.00	40.88	8.42	34.29	34.59	49.60	74.00	24.40	Peak
6	17983.00	47.98	9.76	34.30	25.61	49.05	74.00	24.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 29 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17




Site no. : 1# 966 Chamber Data no. : 29
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.38	2.93	34.66	94.51	90.16	74.00	-16.16	Peak
2	4960.00	31.68	4.60	34.70	43.72	45.30	74.00	28.70	Peak
3	7440.00	36.34	6.02	34.56	38.16	45.96	74.00	28.04	Peak
4	9449.00	37.40	6.55	34.60	40.70	50.05	74.00	23.95	Peak
5	14634.00	41.04	8.33	34.26	34.12	49.23	74.00	24.77	Peak
6	17864.00	47.18	9.69	34.29	27.28	49.86	74.00	24.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 30 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 30
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.38	2.93	34.66	96.41	92.06	74.00	-18.06	Peak
2	4960.00	31.68	4.60	34.70	44.36	45.94	74.00	28.06	Peak
3	7440.00	36.34	6.02	34.56	38.62	46.42	74.00	27.58	Peak
4	10299.00	38.96	6.81	34.51	37.34	48.60	74.00	25.40	Peak
5	15144.00	40.53	8.49	34.27	34.95	49.70	74.00	24.30	Peak
6	17966.00	47.87	9.75	34.30	26.03	49.35	74.00	24.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

18000MHz – 25000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

9. BAND EDGE COMPLIANCE

9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.2. Block Diagram of Test setup



9.3. Test Procedure

EUT was placed on a turn table, which is 1.5 m high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.

9.4. Test Result

Pass (The testing data was attached in the next pages.)

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.


2、 The frequency 2402MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

3、 all modes have been tested , only worse case is reported.

9.5. Test Data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no. : 1# 966 Chamber Data no. : 17
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : n/4-DQPSK TX 2402MHz(No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2380.85	27.23	2.88	34.69	47.50	42.92	74.00	31.08	Peak
2	2390.00	27.26	2.89	34.68	44.98	40.45	74.00	33.55	Peak
3	2400.00	27.26	2.89	34.68	47.89	43.36	54.00	10.64	Average
4	2400.00	27.26	2.89	34.68	66.61	62.08	74.00	11.92	Peak
5	2401.86	27.26	2.89	34.68	93.53	89.00	74.00	-15.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 18 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 18
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2402MHz (No Hopping)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2337.40	27.18	2.85	34.70	46.33	41.66	74.00	32.34	Peak
2	2390.00	27.26	2.89	34.68	43.27	38.74	74.00	35.26	Peak
3	2400.00	27.26	2.89	34.68	50.02	45.49	54.00	8.51	Average
4	2400.00	27.26	2.89	34.68	69.35	64.82	74.00	9.18	Peak
5	2401.86	27.26	2.89	34.68	96.09	91.56	74.00	-17.56	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 19 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17




Site no. : 1# 966 Chamber Data no. : 19
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.78	27.38	2.93	34.66	96.78	92.43	74.00	-18.43	Peak
2	2483.50	27.38	2.93	34.66	48.39	44.04	74.00	29.96	Peak
3	2483.60	27.38	2.93	34.66	50.23	45.88	74.00	28.12	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no. : 1# 966 Chamber Data no. : 20
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.83	27.38	2.93	34.66	95.17	90.82	74.00	-16.82	Peak
2	2483.50	27.38	2.93	34.66	48.84	44.49	74.00	29.51	Peak
3	2483.73	27.38	2.93	34.66	50.50	46.15	74.00	27.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no. : 1# 966 Chamber Data no. : 21
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2359.73	27.21	2.86	34.69	47.96	43.34	74.00	30.66	Peak
2	2390.00	27.26	2.89	34.68	45.67	41.14	74.00	32.86	Peak
3	2400.00	27.26	2.89	34.68	45.54	41.01	54.00	12.99	Average
4	2400.00	27.26	2.89	34.68	64.47	59.94	74.00	14.06	Peak
5	2404.94	27.28	2.89	34.68	94.14	89.63	74.00	-15.63	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no. : 1# 966 Chamber Data no. : 22
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2335.20	27.18	2.85	34.70	47.91	43.24	74.00	30.76	Peak
2	2390.00	27.26	2.89	34.68	46.07	41.54	74.00	32.46	Peak
3	2400.00	27.26	2.89	34.68	47.24	42.71	54.00	11.29	Average
4	2400.00	27.26	2.89	34.68	65.02	60.49	74.00	13.51	Peak
5	2402.30	27.26	2.89	34.68	96.42	91.89	74.00	-17.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 23 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 23
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz (Hopping On)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2477.78	27.38	2.93	34.66	96.64	92.29	74.00	-18.29	Peak
2	2483.50	27.38	2.93	34.66	49.43	45.08	74.00	28.92	Peak
3	2486.58	27.38	2.93	34.65	50.01	45.67	74.00	28.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 24 File: \\Emc-966-1\test data\2019\RF\MM\MeiZhiZun.EM6 (32) Date: 2019-04-17



Site no. : 1# 966 Chamber Data no. : 24
 Dis. / Ant. : 3m 9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:22.9';Humi:50%;Press:101.52kPa
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 3.7V
 M/N : MUZ6009
 Test Mode : π/4-DQPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2478.80	27.38	2.93	34.66	94.63	90.28	74.00	-16.28	Peak
2	2483.50	27.38	2.93	34.66	48.18	43.83	74.00	30.17	Peak
3	2484.90	27.38	2.93	34.66	49.94	45.59	74.00	28.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

10. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST

10.1. Limit

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

10.2. Test Procedure

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


10.3. Test Result

Pass (The testing data was attached in the next pages.)


Note: 1、 all modes have been tested , only worse case is reported.

Test Data
 Conducted Spurious Emissions


Test Mode: $\pi/4$ -DQPSK 2402MHz



Test Mode: $\pi/4$ -DQPSK 2441MHz





Test Mode: π /4-DQPSK 2480MHz





Band-edge measurements for conducted emissions

Test Mode: π /4-DQPSK 2402MHz



Test Mode: $\pi/4$ -DQPSK 2480MHz



11. POWER LINE CONDUCTED EMISSIONS

11.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

11.2. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.


11.3. Test Result

PASS. (All emissions not reported below are too low against the prescribed limits.)

11.4. Test data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no : 844 Shield Room Data no. : 319
 Env. / Ins. : Temp:23.2'C Humi:51% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : MUZ6009
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	9.50	9.69	18.20	37.39	55.25	17.86	Average
2	0.16	9.50	9.69	21.58	40.77	65.25	24.48	QP
3	0.22	9.53	9.84	13.42	32.79	52.79	20.00	Average
4	0.22	9.53	9.84	17.74	37.11	62.79	25.68	QP
5	0.28	9.54	9.92	12.35	31.81	50.94	19.13	Average
6	0.28	9.54	9.92	16.61	36.07	60.94	24.87	QP
7	0.34	9.55	9.92	9.53	29.00	49.27	20.27	Average
8	0.34	9.55	9.92	15.81	35.28	59.27	23.99	QP
9	0.45	9.55	9.92	7.87	27.34	46.85	19.51	Average
10	0.45	9.55	9.92	15.73	35.20	56.85	21.65	QP
11	0.60	9.56	9.92	9.72	29.20	46.00	16.80	Average
12	0.60	9.56	9.92	18.09	37.57	56.00	18.43	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 321 File: \\Emc-ce-1\Test data\2019\MM\MeiZhiZun.EM6 (334) Date: 2019-04-15



Site no : 844 Shield Room Data no. : 321
 Env. / Ins. : Temp:23.2°C Humi:51% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : MUZ6009
 Test Mode : TX Mode


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17	9.59	9.69	17.20	36.48	55.16	18.68	Average
2	0.17	9.59	9.69	20.61	39.89	65.16	25.27	QP
3	0.22	9.61	9.84	11.17	30.62	52.66	22.04	Average
4	0.22	9.61	9.84	15.58	35.03	62.66	27.63	QP
5	0.28	9.61	9.92	9.60	29.13	50.94	21.81	Average
6	0.28	9.61	9.92	13.48	33.01	60.94	27.93	QP
7	0.59	9.63	9.92	3.30	22.85	46.00	23.15	Average
8	0.59	9.63	9.92	12.86	32.41	56.00	23.59	QP
9	1.91	9.65	9.96	1.29	20.90	46.00	25.10	Average
10	1.91	9.65	9.96	13.49	33.10	56.00	22.90	QP
11	8.11	9.73	10.04	6.43	26.20	50.00	23.80	Average
12	8.11	9.73	10.04	13.41	33.18	60.00	26.82	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 323 File: \\Emc-ce-1\Test data\2019\MM\MeiZhiZun.EM6 (334) Date: 2019-04-15



Site no : 844 Shield Room Data no. : 323
 Env. / Ins. : Temp:23.2°C Humi:51% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : MUZ6009
 Test Mode : TX Mode


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	9.59	9.69	16.01	35.29	55.25	19.96	Average
2	0.16	9.59	9.69	19.37	38.65	65.25	26.60	QP
3	0.22	9.61	9.84	12.17	31.62	52.79	21.17	Average
4	0.22	9.61	9.84	18.22	37.67	62.79	25.12	QP
5	0.30	9.62	9.92	8.33	27.87	50.24	22.37	Average
6	0.30	9.62	9.92	15.33	34.87	60.24	25.37	QP
7	0.37	9.63	9.92	1.43	20.98	48.56	27.58	Average
8	0.37	9.63	9.92	14.25	33.80	58.56	24.76	QP
9	0.52	9.63	9.92	5.93	25.48	46.00	20.52	Average
10	0.52	9.63	9.92	13.30	32.85	56.00	23.15	QP
11	0.63	9.63	9.92	6.95	26.50	46.00	19.50	Average
12	0.63	9.63	9.92	15.62	35.17	56.00	20.83	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 325 File: \\Emc-ce-1\Test data\2019\MM\MeiZhiZun.EM6 (334) Date: 2019-04-15



Site no : 844 Shield Room Data no. : 325
 Env. / Ins. : Temp:23.2°C Humi:51% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Viking
 EUT : SAPPHIRE BLUETOOTH SPEAKER
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : MUZ6009
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.50	9.69	10.20	29.39	55.96	26.57	Average
2	0.15	9.50	9.69	18.76	37.95	65.96	28.01	QP
3	0.21	9.53	9.84	11.42	30.79	53.10	22.31	Average
4	0.21	9.53	9.84	17.06	36.43	63.10	26.67	QP
5	0.28	9.54	9.92	8.35	27.81	50.81	23.00	Average
6	0.28	9.54	9.92	14.69	34.15	60.81	26.66	QP
7	0.35	9.55	9.92	1.53	21.00	48.91	27.91	Average
8	0.35	9.55	9.92	13.61	33.08	58.91	25.83	QP
9	0.55	9.55	9.92	2.52	21.99	46.00	24.01	Average
10	0.55	9.55	9.92	13.14	32.61	56.00	23.39	QP
11	1.90	9.55	9.96	1.11	20.62	46.00	25.38	Average
12	1.90	9.55	9.96	12.27	31.78	56.00	24.22	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

12. ANTENNA REQUIREMENTS

12.1. Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Result


The antennas used for this product are PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only -0.58dBi.

13. TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (Above 1GHz)



14. PHOTO EUT


External Photos
M/N: MUZ6009



External Photos
M/N: MUZ6009




External Photos
M/N: MUZ6009





External Photos
M/N: MUZ6009





Internal Photos
M/N: MUZ6009




Internal Photos
M/N: MUZ6009




Internal Photos
M/N: MUZ6009



Internal Photos
M/N: MUZ6009



Bluetooth
Antenna



Internal Photos
M/N: MUZ6009

