

# FCC RF Exposure

EUT Description : Wireless Presentation Transmitter

Model No.: G130 TX

FCC ID: 2ALU5-G130TX

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
2.4GWIFI	5.96	5±1(6)	3.981	5	1.237	3.0	Pass
5.2GWIFI	7.44	6.5±1(7.5)	5.623	5	2.560	3.0	Pass
5.8GWIFI	7.45	6.5±1(7.5)	5.623	5	2.696	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report HK2108233061-1E/2E/3E,

2.4GWIFI antenna gain = 1.72dBi

5GWIFI antenna gain = 1.52dBi

The device could not transmit simultaneously in 2.4G and 5G.

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.696 which is  $\leq 3$ , SAR testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm