

Xiamen Four-Faith Communication Technology Co., Ltd.

Modular Transmitter Approval Request

Federal Communications Commission
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD21046

Company name: Xiamen Four-Faith Communication Technology Co., Ltd.
FCC ID: 2ALUW-F8L10D-N

Gentlemen,

In accordance with 47CFR 15.212 Modular Transmitters and KDB 996369 D01 'Module Certification Guide v01r04'. FCC ID: 2ALUW-F8L10D-N has been examined against the following requirements.

Requirement per 15.212 and KDB 996369 D01 'Modular Certification Guide v01r04'	Explanation from Grantee (do not write yes/no, but explain why product complies/how it is achieved)
The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly	The modular transmitter must have its own RF shielding. The radio portion of this module has been shielded, please see exhibition External Photo
The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal	The modular transmitter must have buffered modulation/data inputs. The EUT have buffered data input, it is integrated in chip SX1276_QFN28
The module must contain power supply regulation on the module	Module chipset incorporates voltage regulation to transceiver circuitry
The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b)	The modular meets the FCC antenna requirements. The requirements of antenna connector and spurious emission have been fulfilled. Please reference the exhibition Test Report. SMA connector is not a special connector. OEM integrator needs to be reminded that the end product still needs to meet the requirements of 15.203 in the future
The module must demonstrate compliance in a stand-alone configuration	Device is tested in a test fixture in a standalone configuration
The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements)	FCC ID label format will be included in the filling. Host ID label will be displayed on the host system.
The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee	Please refer to "User Manual" Exhibit
The module must comply with RF exposure requirements	RF exposure evaluation is exempted because of low output power .

Name: Harven Chen



Date: 2018/11/24

Title: Manager

Signature of applicant