

Report No.: SEWM2209000178RG01

Rev.: 01 Page: 1 of 49

TEST REPORT

Application No.: SEWM2209000178RG

Applicant: Xiamen Four-Faith Communication Technology Co., Ltd.

Address of Applicant: 11th Floor, A-06 Area, No.370, Chengyi Street, Jimei, Xiamen, Fujian, China.

Manufacturer: Xiamen Four-Faith Communication Technology Co., Ltd.

Address of Manufacturer: 11th Floor, A-06 Area, No.370, Chengyi Street, Jimei, Xiamen, Fujian, China.

EUT Description: 5G CPE

Model No.: F-NR300

Trade Mark: Four-Faith

 FCC ID:
 2ALUW-FNR300

 Standards:
 47 CFR Part 2

 47 CFR Part 24
 47 CFR Part 24

47 CFR Part 24 47 CFR Part 27 47 CFR Part 90

Date of Receipt: 2022/09/26

Date of Test: 2022/10/01 to 2022/11/24

Date of Issue: 2022/12/22

Test Result : PASS *

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Panta Sun Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.for for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Termd-Conditions/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-e-Document.sgs.com/en/Terms-end-Conditions.sgs.com/en

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
中国 - 苏州 - 中国 (江苏) 自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 ww t (86–512) 62992980 sg

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 2 of 49

Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
01		2022/12/20		Original	





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set



Report No.: SEWM2209000178RG01

01 Page: 3 of 49

Contents

1	Version	on	2
2	Test S	Summary	5
	2.1	UMTS Band 5/LTE Band 5/26(824~849 MHz)	5
	2.2	UMTS Band 2 /LTE Band 2 /25	6
	2.3	UMTS Band 4 /LTE Band 4 /66	7
	2.4	LTE Band 7/41/ CA_41C	8
	2.5	LTE Band 12/17	12
	2.6	LTE Band 13	13
	2.7	LTE Band 14	14
	2.8	LTE Band 26(814~824 MHz)	16
	2.9	LTE Band 30	17
	2.10	LTE Band 71	19
3	Gener	ral Information	20
	3.1	Details of Client	20
	3.2	Test Location	20
	3.3	Test Facility	20
	3.4	General Description of EUT	21
	3.5	Test Mode	22
	3.6	Test Environment	22
	3.7	Description of Support Units	22
	3.8	Technical Specification	23
	3.9	Test Frequencies	25
4	Descr	iption of Tests	34
	4.1	Conducted Output Power	34
	4.2	Effective (Isotropic) Radiated Power of Transmitter	35
	4.3	EIRP Power Density	36
	4.4	Occupied Bandwidth	37
	4.5	Band Edge at Antenna Terminals	38
	4.6	Spurious And Harmonic Emissions at Antenna Terminal	
	4.7	Peak-Average Ratio	
	4.8	Field Strength of Spurious Radiation	41



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sold responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@gs.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 www.sgsgroup.com.cn t (86-512) 62992980



Rev.:	01
Page:	4 of 49

	4.9 Frequ	uency Stability / Temperature Variation	42
	•	Setups	
		Test Setup 1	
		Test Setup 2	
	4.10.3	Test Setup 3	44
		Conditions	
5	Main Test Ins	struments	46
6	Measuremen	t Uncertainty	48
		,	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are reading for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ss.com

or email: <u>UNIDOCENECK(図SGS.COM</u> South of No. Flort, No. 1, Funcheng röses, Surbun ludsstein Park, Surbun Lee, China (Jiangsu) Pind Free Trade Zone 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 卓第: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 5 of 49

2 Test Summary

2.1 UMTS Band 5/LTE Band 5/26(824~849 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power	§2.1046, §22.913(a)(5)	ERP ≤ 7 W	Section 1 of Appendix	Pass
Output Data			B.1&B.4&B.12	
Peak-Average Ratio	§22.913(d)	Limit≤13 dB	Reference r SAR202140	
Modulation Characteristics	§2.1047	Digital modulation	Reference r SAR202140	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference r SAR202140	
Band Edges Compliance	§2.1051, §22.917(a)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference r SAR202140	
Spurious Emission at Antenna Terminals	§2.1051, §22.917(a)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Reference r SAR2021400	
Field Strength of Spurious Radiation	§2.1053, §22.917(a)	FCC: ≤ -13 dBm/100 kHz.	Section 2 of Appendix B.1&B.4&B.12	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1) §22.355	≤ ±2.5ppm.	Reference report SAR20214000901	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Co



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 6 of 49

2.2 UMTS Band 2 /LTE Band 2 /25

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic)	§2.1046,		Section 1 of	
Radiated Power Output	§24.232(c)	EIRP ≤ 2 W	Appendix	Pass
Data			B.1&B.2&B.10	
Peak-Average Ratio	§24.232(d)	Limit≤13 dB	Reference i SAR202140	
Modulation Characteristics	§2.1047	Digital modulation	Reference i SAR202140	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference report SAR20214000901	
Band Edges Compliance	§2.1051, §24.238(a)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference report SAR20214000901	
Spurious Emission at Antenna Terminals	§2.1051, §24.238(a)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Reference i SAR202140	
Field Strength of Spurious Radiation	§2.1053, §24.238(a)	≤ -13 dBm/1 MHz.	Section 2 of Appendix B.1&B.2&B.10	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§24.235	Within authorized bands of operation/frequency block.	Reference i SAR202140	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 7 of 49

2.3 UMTS Band 4 /LTE Band 4 /66

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power	§2.1046, §27.50(d)(4)	EIRP ≤ 1 W	Section 1 of Appendix	Pass
Output Data			B.1&B.3&B.15	
Peak-Average Ratio	§27.50(d)(5)	Limit≤13 dB	Reference r SAR2021400	
Modulation Characteristics	§2.1047	Digital modulation	Reference r SAR2021400	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference r SAR2021400	
Band Edges Compliance	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference r SAR2021400	
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Reference r SAR2021400	
Field Strength of Spurious Radiation	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	Section 2 of Appendix B.1&B.3&B.15	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§27.54	Within authorized bands of operation/frequency block.	Reference r SAR2021400	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 8 of 49

2.4 LTE Band 7/41/ CA_41C

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective				
(Isotropic)	§2.1046,	FIRE LOW	Section 1 of	
Radiated Power Output	§27.50(h)(2)	EIRP ≤ 2W	Appendix	Pass
Data			B.5&B.14&B.17	
Peak-Average		≤13 dB	Reference re	
Ratio		_ 10 dB	SAR2021400	
Modulation Characteristics	§2.1047	Digital modulation	Reference re SAR2021400	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference re SAR2021400	
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as de □ ned in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.	Reference re SAR2021400	
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	Channel Edge -25dBm/ 1 MHz 1 MHz 1 MHz 9 kHz 9 5 MHz X=Max {6MHz, EBW}	Reference re SAR2021400	
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	Channel Edge -25dBm/ 1 MHz 1 MHz 9 kHz 95 MHz X=Max {6MHz, EBW}	Section 2 of Appendix B.5&B.14&B.17	Pass
Frequency	§2.1055(a)(1)(b)	Within authorized bands of	Reference re	
Stability	§2.1055(d)(1)§27.54	operation/frequency block.	SAR2021400	0901



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falisfication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CV. Doccheck@ss.com

Ore mail: <u>U.N.Doceneck(図SGS.-com</u> South of No. Flort, No.1, Funcheng Post, Suzhou Indose Park, Suzhou Area, China (Jangsu) Plot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区泊胜路1号的6号厂房南部 邮集: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 9 of 49

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 10 of 49

2.5 LTE CA_41C(PC2)

	2.5 LTE CA_4TC(PC2)						
Test Item	FCC Rule No.	Requirements	Test Result	Verdict			
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)(2)	EIRP ≤ 2W	Section 1 of Appendix B.5&B.14&B.17	Pass			
Peak-Average Ratio		≤13 dB	Reference re SUZR202170				
Modulation Characteristics	§2.1047	Digital modulation	Reference re SUZR202170				
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference re SUZR202170				
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as de □ ned in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.	Reference re SUZR202170				
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	Channel Edge -25dBm/ 1 MHz 1	Reference re SUZR202170				
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	Channel Edge -25dBm/ 1 MHz 1 MHz 1 MHz 9 kHz 9 5 MHz X MHz 10th harmonics X=Max {6MHz, EBW}	Section 2 of Appendix B.5&B.14&B.17	Pass			
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§27.54	Within authorized bands of operation/frequency block.	Reference re SUZR202170				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falisfication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CV. Doccheck@ss.com

Ore mail: <u>U.N.Doceneck(図SGS.-com</u> South of No. Flort, No.1, Funcheng Post, Suzhou Indose Park, Suzhou Area, China (Jangsu) Plot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区泊胜路1号的6号厂房南部 邮集: 215000



Report No.: SEWM2209000178RG01

Rev.: Page: 11 of 49

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SUZR20217002001 issued by S GS-CSTC Standards Technical Services (Suzhou) Co., Ltd. on 2021/10/30.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 www.sgsgroup.com.cn t (86-512) 62992980



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 12 of 49

2.6 LTE Band 12/17

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power	§2.1046 §27.50(c)(10)	ERP≤3W.	Section 1 of Appendix	Pass
Output Data	327.00(0)(10)		B.6&B.9	
Peak-Average Ratio		Limit≤13 dB	Reference re SAR2021400	
Modulation Characteristics	§2.1047	Digital modulation	Reference re SAR2021400	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference report SAR20214000901	
Band Edges Compliance	§2.1051, §27.53(g)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference re SAR2021400	
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Reference re SAR2021400	
Field Strength of Spurious Radiation	§2.1053, §27.53(g)	FCC: ≤ -13 dBm/100 kHz.	Section 2 of Appendix B.6&B.9	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§27.54	Within authorized bands of operation/frequency block.	Reference re SAR2021400	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falisfication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CM.Doccheck@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 13 of 49

2.7 LTE Band 13

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(b)(10)	ERP ≤ 3 W.	Section 1 of Appendix B.7	Pass
Peak-Average Ratio		Limit≤13 dB	Reference SAR202140	
Modulation Characteristics	§2.1047	Digital modulation	Reference SAR202140	000901
Bandwidth	§2.1049,	OBW: No limit. EBW: No limit.	Reference SAR202140	
Band Edges Compliance	§2.1051, §27.53(c)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference SAR202140	
Spurious Emission at Antenna Terminals	§2.1051, §27.53(c) §27.53(f)	≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations. For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.	Reference SAR202140	
Field Strength of Spurious Radiation	§2.1053, §27.53(c) §27.53(f)	FCC: ≤ -13 dBm/100 kHz. For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.	Section 2 of Appendix B.7	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1) §27.54	Within authorized bands of operation/frequency block.	Reference SAR202140	

Remark

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 w t (86–512) 62992980 s

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 14 of 49

2.8 LTE Band 14

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	
Effective (Isotropic) Radiated Power Output Data	§2.1046 §90.542(d)	ERP ≤ 3 W.	Section 1 of Appendix B.8		
Peak-Average Ratio		Limit≤13 dB	Reference SAR202140		
Modulation Characteristics	§2.1047	Digital modulation	Reference SAR202140	000901	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference SAR202140		
Emission Mask	§2.1051 §90.210(n)	Transmitters designed for operation under this part on frequencies other than listed in this section must meet the emission mask requirements of Emission Mask B. Equipment operating under this part on frequencies allocated to but shared with the Federal Government, must meet the applicable Federal Government technical standards (b) Emission Mask B. For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows: (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.(2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB(3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.	Reference SAR202140		
Band Edges Compliance	§2.1051 §90.543(e)(2)(3)	(1) On all frequencies between 769- 775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.(2) On all	Reference SAR202140		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ass.com

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 15 of 49

		raye.	15 01 49	
Spurious Emission at Antenna Terminals	§2.1051, §90.543(c) §90.543(f)	frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB. FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges. For operations in the 758–775 MHz and 788–805 MHz bands, all emissions including harmonics in the band 1559– 1610 MHz shall be limited to -70 dBW/ MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700	Reference SAR202140	•
Field Strength of Spurious Radiation	§2.1053, §90.543(c) §90.543(f)	Hz bandwidth. FCC: ≤ -13 dBm/100 kHz. For operations in the 758–775 MHz and 788–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/ MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.	Section 2 of Appendix B.8	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§90.213	Within authorized bands of operation/frequency block.	Reference SAR202140	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industria Park, Suchou Area, China (Jiangsu) Pikot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号约6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 16 of 49

2.9 LTE Band 26(814~824 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	
Transmitter Conducted	§2.1046, §90.635(b)	< 100 W.	Section 1 of		
Power Output	3()		Appendix B.11		
Peak-Average Ratio		Limit≤13 dB	Reference r SAR202140		
Modulation Characteristics	§2.1047	Digital modulation	Reference i SAR202140	eport	
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference i SAR202140		
Emission Mask	§2.1051 § 90.691(a)	For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log10(f/6.1) decibels or 50+10Log10(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.	Reference report SAR20214000901		
Spurious Emission at Antenna Terminals	§2.1051, §90.691	< 43 + 10Log10(P[Watts]) for all out-of-band emissions	Reference report SAR20214000901		
Field Strength of Spurious Radiation	§2.1053, §90.691			Pass	
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§90.213	Within authorized bands of operation/frequency block.	Reference report SAR20214000901		

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Liness otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(a) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区海胜路1号的6号厂房南部 邮编: 215000 t (86–512) 62992980 ww t (86–512) 62992980 sg

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 17 of 49

2.10 LTE Band 30

Test Item	FCC Rule No.	Test Result	Verdict	
Effective (Isotropic)	§2.1046,	Requirements EIRP ≤ 50mW/1MHz	Section 1 of	
Radiated Power Output Data	§27.50(a)(3)	EIRP ≤ 250mW/5MHz	Appendix B.13	Pass
Peak-Average Ratio		FCC: Limit≤13 dB	Reference SAR202140	
Modulation Characteristics	§2.1047	Digital modulation	Reference SAR202140	report
Bandwidth	§2.1049,	OBW: No limit. EBW: No limit.	Reference SAR202140	
Band Edges Compliance	§2.1051, §27.53(a)(4)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference SAR202140	
Spurious Emission at Antenna Terminals	§2.1051, §27.53(a)(4)	For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands: (i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2345 and 2324 MHz and on all frequencies between 2320 and 2324 MHz and on all frequencies between 2345 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2327 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz; (ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2396 and 2300 MHz, 61	Reference SAR202140	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ass.com

South of No. Fight No. 1, Runsherg Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pikol Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号约6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 18 of 49

		ı ago.	10 01 10	
		+ 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz;(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.		
Field Strength of Spurious Radiation	§2.1053, §27.53(a)(4)	≤ -13 dBm/1 MHz.	Section 2 of Appendix B.13	Pass
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§27.54	within the range of the operating frequency blocks	Reference SAR202140	

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industria Park, Suchou Area, China (Jiangsu) Pikot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号约6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 19 of 49

2.11 LTE Band 71

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	
Effective (Isotropic) Radiated Power Output Data	§2.1046 §27.50(c)(10)	ERP ≤ 3 W	Section 1 of Appendix B.16	Pass	
Peak-Average Ratio		Limit≤13 dB	Reference re SAR2021400		
Modulation Characteristics	§2.1047	Digital modulation	Reference re SAR2021400		
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Reference report SAR20214000901		
Band Edges Compliance	§2.1051, §27.53(g)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference report SAR20214000901		
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Reference report SAR20214000901		
Field Strength of Spurious Radiation	§2.1053, §27.53(g)	≤ -13 dBm/1 MHz.	Pass		
Frequency Stability	§2.1055(a)(1)(b) §2.1055(d)(1)§27.54	within the authorized bands of operation.	Reference report SAR20214000901		

Remark:

The Effective (Isotropic) Radiated Power Output Data and Field Strength of Spurious Radiation were fully tested in this report, and other items data please refer to the test report SAR20214000901 issued by SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch on 2021/06/14.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 20 of 49

3 General Information

3.1 Details of Client

Applicant:	Xiamen Four-Faith Communication Technology Co., Ltd.		
Address of Applicant:	11th Floor, A-06 Area, No.370, Chengyi Street, Jimei, Xiamen, Fujian, China.		
Manufacturer:	Xiamen Four-Faith Communication Technology Co., Ltd.		
Address of Manufacturer:	11th Floor, A-06 Area, No.370, Chengyi Street, Jimei, Xiamen, Fujian, China.		

3.2 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	Weller Liu, Tizzy Song

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

FCC –Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@ss.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 21 of 49

3.4 General Description of EUT

EUT Description:	5G CPE						
Model No.:	F-NR300						
Trade Mark:	Four-Faith						
Hardware Version:	V1.5						
Software Version:	FNR300-NA_A3112	294					
	RF Conducted		86242405	0044030			
IMEI:	RSE		86242403	0041085			
Antenna Type:	PCB Antenna		l				
,,	WCDMA Band II:	2.92dBi	(Ant0)	WCDMA Bar	nd IV:	3.3dBi(Ant0)	
	WCDMA Band V:	1.64dBi	(Ant0)				
	LTE Band 2:	2.92dBi	(Ant0)	LTE Band 4:		3.3dBi(Ant0)	
	LTE Band 5:	1.64dBi	(Ant0)	LTE Band 7:		2.77dBi(Ant0)	
	LTE Band 12:	0.63dBi	(Ant0)	LTE Band 13	B:	2.21dBi(Ant0)	
	LTE Band 14:	2.21dBi	(Ant0)	LTE Band 17	' :	0.63dBi(Ant0)	
Antenna Gain:	LTE Band 25:	2.92dBi	(Ant0)	LTE Band 26	6:	2.16dBi(Ant0)	
	LTE Band 30:	2.81dBi	(Ant0)	LTE Band 66	S:	3.3dBi(Ant0)	
	LTE Band 71:	0.36dBi	(Ant0)	LTE Band 41	:	3.2dBi(Ant1)	
	LTE CA_41C:	3.2dBi(/	Ant1)				
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.						
HPUE Power Class:	Class 2: Band 41, I	TE CA_4	1C				
RF Cable:	0.8dB(Below 1GHz) ^	1.0dB(1.0~2	.4GHz)	1.2dB	(2.4~3.4GHz)	
RE Cable.	1.5dB(Above 3.4GI	Hz)					
As above information is p suitability, reliability or/an			applicant. S	GS is not liable	to the	accuracy,	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration; forgery or falisfication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@as.com

Ore mani: CN. Doccneck (@:sgs.com Sudu fi No.6 Pfent, No.1, Runsheng Read, Sudou Industrial Park, Sudou Area, China (liangsu) Pikol Free Trade Zore 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号約6号厂房南部 厳樂: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 22 of 49

3.5 Test Mode

Test Mode	Test Modes Description				
UMTS/TM1	UMTS system, WCDMA, QPSK modulation				
LTE/TM1	TE system, QPSK modulation				
LTE/TM2	LTE system, 16QAM modulation				
LTE/TM3	LTE system, 64QAM modulation				
LTE/TM4	M4 LTE system, 256QAM modulation				
Remark: The test mode(s) are selected according to relevant radio technology specifications.					

3.6 Test Environment

Environment Parameter	101 kPa Selected Values During Tests				
Relative Humidity	44-46 % RH Ambient				
Value	Temperature(°C)	Voltage(V)			
NTNV	22~23	12			

Remark:

NV: Normal Voltage NT: Normal Temperature

3.7 Description of Support Units

The EUT has been tested as an independent unit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

or email: CM. <u>Doccheck@sgs.com</u> SubdndfNo.6 PBml, No.1, Runsheng Read, Subrub Industral Park, Suzbou Area, China (Jangsu) Pilot Free Trade Zone 中国 - 苏州 - 中国 (江苏) 自由贸易试验区苏州片区苏州工业园区溶胜路(号的6号厂房南部 鄭樂: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 23 of 49

3.8 Technical Specification

Characteristics	Description									
Radio System Type	☐ GSM ☐ UMTS			□ LTE						
	Band		TX		RX					
	UMTS Band II			1850 to 1910 MHz		1930 1	1930 to 1990 MHz			
	UMTS Band IV		17	10 to 17	55 MHz	2110 1	to 21	55 MHz		
	UMTS Band V	,		82	4 to 849	MHz	869 to	894	MHz	
	LTE Band 2			18	50 to 19	10 MHz	1930 1	to 19	90 MHz	
	LTE Band 4			17	10 to 17	55 MHz	21101	to 21	55 MHz	
	LTE Band 5			82	4 to 849	MHz	869 to	894	MHz	
	LTE Band 7			25	00 to 25	70 MHz	2620 1	to 26	90 MHz	
	LTE Band 12			69	9 to 716	MHz	729 to	746	MHz	
Supported Frequency Range	LTE Band 13			77	7 to 787	MHz	746 to	756	MHz	
	LTE Band 14		78	8 to 798	MHz	758 to	768	MHz		
	LTE Band 17		704 to 716 MHz			734 to	734 to 746 MHz			
	LTE Band 25		1850 to 1915MHz			1930 1	1930 to 1995 MHz			
	LTE Band 26 (814 to 824 MHz)		814 to 824MHz			859 to	859 to 869 MHz			
	LTE Band 26 (824 to 849 MHz)		824 to 849 MHz			869 to	869 to 894 MHz			
	LTE Band 30		2305 to 2315 MHz			2350 1	to 23	60 MHz		
	LTE Band 41		2496 to 2690MHz			2496 1	to 26	90MHz		
	LTE Band 66			1710 to 1780 MHz			2110 1	2110 to 2200 MHz		
	LTE Band 71			663 to 698 MHz			617 to	617 to 652 MHz		
	LTE CA_41C			2496 to 2690MHz			2496 1	2496 to 2690MHz		
	UMTS system	:		\boxtimes 5	5 MHz		<u> </u>			
	LTE Band 2			×	1.4 MHz	⊠3 MHz	⊠5 MHz	<u> </u>	⊠10 MHz	
	LIL Dallu Z			M,	15 MHz	⊠20 MHz				
Owner and a different and Developing	LTE Band 4			$\dot{\boxtimes}$	1.4 MHz	⊠3 MHz	⊠5 MHz	<u> </u>	⊠10 MHz	
Supported Channel Bandwidth	LIL Dallu 4			\boxtimes	15 MHz	⊠20 MHz				
	LTE Band 5		Ø,	1.4 MHz	⊠3 MHz	⊠5 MHz	<u> </u>	⊠10 MHz		
	LTE Band 7		\boxtimes	5 MHz	⊠10 MHz	⊠15 MH	lz [⊠20 MHz		
	LTE Band 12			\boxtimes	1.4 MHz	⊠3 MHz	⊠5 MHz	<u> </u>	⊠10 MHz	
	LTE Band 13			\boxtimes 5	5 MHz	⊠10 MHz				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ass.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 24 of 49

LTE Band 14	⊠10 MHz	
LTE Band 25	⊠10 MHz	
LTE Band 25	⊠10 MHz	
□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □		
LTE Band 26(814-824)	⊠10 MHz	
☐ 1.4 MHz ☐ 3 MHz ☐ 5 MHz	⊠10 MHz	
LTE Band 26(824-849)		
LTE Band30 ⊠5 MHz ⊠10 MHz		
LTE Band41 ⊠5 MHz ⊠10 MHz ⊠15 MHz	2 ⊠20 MHz	
LTE Band 66	⊠10 MHz	
☐ 15MHz ☐ 20MHz		
LTE Band 71 ⊠5MHz ⊠10MHz ⊠15MHz	z ⊠20MHz	
⊠5MHz+20MHz ⊠10MHz	⊠10MHz+15MHz	
LTE Band CA_41C ⊠10MHz+20MHz ⊠15MHz	⊠15MHz+15MHz	
□ 15MHz+20MHz □ 20MHz	z+20MHz	
CA: CA_2A-12A;CA_12A-66A		
ULCA intra-band Only test RSE, report only show worst mode.		
Note: WCDMA supports HSUPA, HSDPA, DC-HSDPA,HSPA+ worst case was tested and the data displayed in this report.	, but only the	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 25 of 49

3.9 Test Frequencies

Test Mode	TX / RX		RF Channel	
i est ivioue	IA / IXA	Low (L)	Middle (M)	High (H)
	TX	Channel 9262	Channel 9400	Channel 9538
WCDMA Band II		1852.4 MHz	1880.0 MHz	1907.6 MHz
WCDIMA Band II	RX	Channel 9662	Channel 9800	Channel 9938
		1932.4 MHz	1960.0 MHz	1987.6 MHz

Test Mode	TX / RX	TY / PY RF Channel			
i est ivioue	IX/IX	Low (L)	Middle (M)	High (H)	
		Channel 1312	Channel 1413	Channel 1513	
WCDMA Band IV	TX	1712.4MHz	1732.6 MHz	1752.6 MHz	
WCDIVIA Ballu IV	DV	Channel 1537	Channel 1638	Channel 1738	
	RX	2112.4 MHz	2132.6 MHz	2152.6 MHz	

Test Mode	TX / RX RF Channel				
rest wode	IA/ NA	Low (L)	Middle (M)	High (H)	
	TX	Channel 4132	Channel 4182	Channel 4233	
WCDMA Band V	1^	826.4MHz	836.4 MHz	846.6 MHz	
	RX	Channel 4357	Channel 4407	Channel 4458	
		871.4 MHz	881.4 MHz	891.6 MHz	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 26 of 49

T (M)	5 1 : 111	TV / DV		RF Channel	
Test Mode	Bandwidth	TX / RX	Low (L)	Middle (M)	High (H)
			Channel 18607	Channel 18900	Channel 19193
		TX	1850.7 MHz	1880 MHz	1909.3 MHz
	1.4MHz	DV	Channel 607	Channel 900	Channel 1193
		RX	1930.7 MHz	1960 MHz	1989.3 MHz
			Channel 18615	Channel 18900	Channel 19185
		TX	1851.5 MHz	1880 MHz	1908.5 MHz
	3MHz	DV	Channel 615	Channel 900	Channel 1185
		RX	1931.5 MHz	1960 MHz	1988.5 MHz
	5MHz		Channel 18625	Channel 18900	Channel 19175
		TX	1852.5 MHz	1880 MHz	1907.5 MHz
		RX	Channel 625	Channel 900	Channel1175
LTE Band 2			1932.5 MHz	1960 MHz	1987.5 MHz
LIE Dallu Z			Channel 18650	Channel 18900	Channel 19150
	10MHz	TX	1855 MHz	1880 MHz	1905 MHz
		RX	Channel 650	Channel 900	Channel 1150
			1935 MHz	1960 MHz	1985 MHz
			Channel 18675	Channel 18900	Channel 19125
		TX	1857.5 MHz	1880 MHz	1902.5 MHz
	15MHz	RX	Channel 675	Channel 900	Channel 1125
		NA.	1937.5 MHz	1960 MHz	1982.5 MHz
			Channel 18700	Channel 18900	Channel 19100
		TX	1860 MHz	1880 MHz	1900 MHz
	20MHz	DV	Channel 700	Channel 900	Channel 1100
		RX	1940 MHz	1960 MHz	1980 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) test earlied of 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.boccheck@gs.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 芬州・中国(江苏)自由贸易试验区芬州片区芬州工业园区消胜数1号的6号厂房南部 輸集: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 27 of 49

			raye. 21 01 49			
Test Mode	Bandwidth	TX / RX	RF Channel			
rest Mode	Dariuwiutii	IA/IX	Low (L)	Middle (M)	High (H)	
			Channel 19957	Channel 20175	Channel 20393	
		TX	1710.7 MHz	1732.5 MHz	1754.3 MHz	
	1.4MHz	RX	Channel 1975	Channel 2175	Channel 2375	
		NA.	2112.5 MHz	2132.5MHz	2152.5 MHz	
			Channel 19965	Channel 20175	Channel 20385	
		TX	1711.5 MHz	1732.5 MHz	1753.5 MHz	
	3MHz	DV	Channel 2000	Channel 2175	Channel 2350	
		RX	2115 MHz	2132.5MHz	2150 MHz	
			Channel 19975	Channel 20175	Channel 20375	
	5MHz	TX	1712.5 MHz	1732.5 MHz	1752.5 MHz	
		RX	Channel 1975	Channel 2175	Channel 2375	
LTE David 4			2112.5 MHz	2132.5MHz	2152.5 MHz	
LTE Band 4	10MHz		Channel 20000	Channel 20175	Channel 20350	
		TX	1715 MHz	1732.5 MHz	1750 MHz	
		RX	Channel 2000	Channel 2175	Channel 2350	
			2115 MHz	2132.5MHz	2150 MHz	
			Channel 20025	Channel 20175	Channel 20325	
		TX	1717.5 MHz	1732.5 MHz	1747.5 MHz	
	15MHz	RX	Channel 2025	Channel 2175	Channel 2325	
		100	2117.5 MHz	2132.5MHz	2147.5 MHz	
			Channel 20050	Channel 20175	Channel 20300	
		TX	1720 MHz	1732.5 MHz	1745 MHz	
	20MHz	DV	Channel 2050	Channel 2175	Channel 2300	
		RX	2120 MHz	2132.5MHz	2145 MHz	

Took Mode	Donalysialth	TV / DV		RF Channel	
Test Mode	Bandwidth	TX / RX	Low (L)	Middle (M)	High (H)
			Channel 20407	Channel 20525	Channel 20643
		TX	824.7 MHz	836.5 MHz	848.3 MHz
	1.4MHz	RX	Channel 2407	Channel 2525	Channel 2643
		KA.	869.7 MHz	881.5 MHz	893.3 MHz
			Channel 20415	Channel 20525	Channel 20635
	3MHz	TX	825.5 MHz	836.5 MHz	847.5 MHz
		RX	Channel 2415	Channel 2525	Channel 2635
LTE Davide			870.5 MHz	881.5 MHz	892.5 MHz
LTE Band 5		TX	Channel 20425	Channel 20525	Channel 20625
			826.5 MHz	836.5 MHz	846.5 MHz
	5MHz	RX	Channel 2425	Channel 2525	Channel 2625
		KA	871.5 MHz	881.5 MHz	891.5 MHz
			Channel 20450	Channel 20525	Channel 20600
		TX	829 MHz	836.5 MHz	844 MHz
	10MHz	RX	Channel 2450	Channel 2525	Channel 2600
		INA	874 MHz	881.5 MHz	889 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon relects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@gs.com

 South of No. (Plant No. 1, Runsheng (Road, Suzhou Industrial Park, Suzhou Area, China (Jángsu) Plot Free Trade Zone
 215000
 t (86—512) 62992980
 www.sgsgroup.com.cn

 中国 - 苏州 - 中国 (江苏) 自由贸易试量区苏州 I 区苏州 工业园区测胜路 I 号的号厂 房南部
 邮编:
 215000
 t (86—512) 62992980
 sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 28 of 49

			гау	e. 20 01 43	<u> </u>
Test Mode	Bandwidth	TX / RX		RF Channel	
rest Mode	Dandwidth	IA/ NA	Low (L)	Middle (M)	High (H)
			Channel 20775	Channel 21100	Channel 21425
		TX	2502.5 MHz	2535 MHz	2567.5 MHz
	5MHz	RX	Channel 2775	Channel 3100	Channel 5825
		ĽΛ	2622.5 MHz	2655 MHz	2687.5 MHz
			Channel 20800	Channel 21100	Channel 21400
		TX	2505 MHz	2535 MHz	2565 MHz
	10MHz	RX	Channel 2800	Channel 3100	Channel 3400
1.TE D 1.7			2625 MHz	2655 MHz	2685 MHz
LTE Band 7		TX	Channel 20825	Channel 21100	Channel 21375
			2507.5 MHz	2535 MHz	2562.5 MHz
	15MHz	RX	Channel 2825	Channel 3100	Channel 3375
		ĽΛ	2627.5 MHz	2655 MHz	2682.5 MHz
			Channel 20850	Channel 21100	Channel 21350
		TX	2510 MHz	2535 MHz	2560 MHz
	20MHz	DV	Channel 2850	Channel 3100	Channel 3350
		RX	2630 MHz	2655 MHz	2680 MHz

Took Mode	Danduidth	TV / DV		RF Channel	
Test Mode	Bandwidth	TX / RX	Low (L)	Middle (M)	High (H)
			Channel 23017	Channel 23095	Channel 23173
		TX	699.7 MHz	707.5 MHz	715.3 MHz
	1.4MHz	RX	Channel 5017	Channel 5095	Channel 5173
		KA.	729.7 MHz	737.5 MHz	745.3 MHz
	3MHz		Channel 23025	Channel 23095	Channel 23165
		TX	700.5 MHz	707.5 MHz	714.5 MHz
		RX	Channel 5025	Channel 5095	Channel 5165
LTE David 40			730.5 MHz	737.5 MHz	744.5 MHz
LTE Band 12		TX	Channel 23035	Channel 23095	Channel 23155
	51411		701.5 MHz	707.5 MHz	713.5 MHz
	5MHz	DV	Channel 5035	Channel 5095	Channel 5155
		RX	731.5 MHz	737.5 MHz	743.5 MHz
			Channel 23060	Channel 23095	Channel 23130
		TX	704 MHz	707.5 MHz	711 MHz
	10MHz	RX	Channel 5060	Channel 5095	Channel 5130
		INA	734 MHz	737.5 MHz	741 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-end-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-end-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document one one exceptare parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@gs.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Pank, Suzhou Area, China (Jängsu) Pind Free Trade Zone 215000 t (86-512 中国 - 苏州・中国(江苏)自由原家试验区苏州片区苏州工业园区测胜路1号約6号厂房南部 邮線: 215000 t (86-512



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 29 of 49

			9		
Toot Made	Bandwidth	TX / RX		RF Channel	
Test Mode	de Bandwidth	IA/KA	Low (L)	Middle (M)	High (H)
			Channel 23025	Channel 23230	Channel 23255
		TX	779.5 MHz	782 MHz	784.5 MHz
	5MHz	RX	Channel 5205	Channel 5230	Channel 5255
LTE Band 13			748.5 MHz	751 MHz	753.5 MHz
LIE Danu 13		TX	Channel 23230	Channel 23230	Channel 23230
	10MHz		782 MHz	782 MHz	782 MHz
		DV	Channel 5230	Channel 5230	Channel 5230
		RX	751 MHz	751 MHz	751 MHz

Toot Made	Bandwidth	TX / RX		RF Channel	
Test Mode	Dandwidth	IA/KA	Low (L)	Middle (M)	High (H)
			Channel 23305	Channel 23330	Channel 23355
		TX	790.5 MHz	793 MHz	795.5 MHz
	5MHz	RX	Channel 5305	Channel 5330	Channel 5355
LTE Band 14			760.5 MHz	763 MHz	765.5 MHz
LIE Daliu 14			Channel 23330	Channel 23330	Channel 23330
		TX	793MHz	793 MHz	793 MHz
	10MHz	DV	Channel 5330	Channel 5330	Channel 5330
		RX	763MHz	763 MHz	763 MHz

Test Mode	Bandwidth	TX / RX		RF Channel	
rest wode	Danuwidin	IA/KA	Low (L)	Middle (M)	High (H)
	5MHz		Channel 23755	Channel 23790	Channel 23825
		TX	706.5 MHz	710 MHz	713.5 MHz
		RX	Channel 5755	Channel 5790	Channel 5825
LTC Band 17			736.5 MHz	740 MHz	743.5 MHz
LTE Band 17		TX	Channel 23780	Channel 23790	Channel 23800
			709 MHz	710 MHz	711 MHz
	10MHz	DV	Channel 5780	Channel 5790	Channel 5800
		RX	739 MHz	740 MHz	741 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents a thitp://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-75) 8307 1443, **Attention:**To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-75) 8307 1443, **Total Company and the company and the company and the content or appearance contact us at telephone: (86-75) 8307 1443, **Total Company and the company an

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pitol Free Trade Zone 215000 th 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州广区苏州工业园区测胜路1号的6号厂房南部 邮编: 215000 th



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 30 of 49

Test Mode	Bandwidth	TX / RX		RF Channel	
rest Mode	Dariuwiutii		Low (L)	Middle (M)	High (H)
		TX	Channel 26047	Channel 26365	Channel 26683
			1850.7 MHz	1882.5 MHz	1914.3 MHz
	1.4MHz	RX	Channel 8047	Channel 8365	Channel 8683
		KA.	1930.7 MHz	1962.5 MHz	1994.3 MHz
			Channel 26055	Channel 26365	Channel 26675
		TX	1851.5 MHz	1882.5 MHz	1913.5 MHz
	3MHz	DV	Channel 8055	Channel 8365	Channel 8675
		RX	1931.5 MHz	1962.5 MHz	1993.5 MHz
			Channel 26065	Channel 26365	Channel 26665
	5MHz	TX	1852.5 MHz	1882.5 MHz	1912.5 MHz
		RX	Channel 8065	Channel 8365	Channel 8665
1 TE Daniel 05			1932.5 MHz	1962.5 MHz	1992.5 MHz
LTE Band 25	10MHz	TX	Channel 26090	Channel 26365	Channel 26640
			1855 MHz	1882.5 MHz	1910 MHz
		RX	Channel 8090	Channel 8365	Channel 8640
			1935 MHz	1962.5 MHz	1990 MHz
	15MHz	TX	Channel 26115	Channel 26365	Channel 26615
			1857.5 MHz	1882.5 MHz	1907.5 MHz
		RX	Channel 8115	Channel 8365	Channel 8615
			1937.5 MHz	1962.5 MHz	1987.5 MHz
			Channel 26140	Channel 26365	Channel 26590
		TX	1860 MHz	1882.5 MHz	1905 MHz
	20MHz	RX	Channel 8140	Channel 8365	Channel 8590
		ΓΛ	1940 MHz	1962.5 MHz	1985 MHz

Tack Made	Bandwidth	TV / DV	RF Channel			
Test Mode		TX / RX	Low (L)	Middle (M)	High (H)	
		TX	Channel 26697	Channel 26740	Channel 26783	
			814.7 MHz	819 MHz	823.3 MHz	
	1.4MHz	RX	Channel 8697	Channel 8740	Channel 8783	
		KA	859.7 MHz	864MHz	868.3 MHz	
			Channel 26705	Channel 26740	Channel 26775	
	3MHz	TX	815.5 MHz	819 MHz	822.5 MHz	
		RX	Channel 8705	Channel 8740	Channel 8775	
LTE Band 26			860.5 MHz	864MHz	867.5 MHz	
(814-824)	5MHz	TX	Channel 26715	Channel 26740	Channel 26765	
(0 : : 0 = :)			816.5 MHz	819 MHz	821.5 MHz	
		RX	Channel 8715	Channel 8740	Channel 8755	
			861.5 MHz	864MHz	866.5 MHz	
			Channel 26740	Channel 26740	Channel 26740	
		TX	819 MHz	819 MHz	819 MHz	
	10MHz	DV	Channel 8740	Channel 8740	Channel 8740	
		RX	864MHz	864MHz	864MHz	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ass.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 31 of 49

			ı ag	C. 0101+c	_	
Test Mode	Bandwidth	TX / RX	RF Channel			
i est ivioue			Low (L)	Middle (M)	High (H)	
		TX	Channel 26797	Channel 26915	Channel 27033	
			824.7 MHz	836.5 MHz	848.3 MHz	
	1.4MHz	RX	Channel 8697	Channel 8915	Channel 9033	
		KA	859.7 MHz	881.5 MHz	893.3 MHz	
			Channel 26805	Channel 26915	Channel 27025	
		TX	825.5 MHz	836.5 MHz	847.5 MHz	
	3MHz	RX	Channel 8805	Channel 8915	Channel 9025	
			860.5 MHz	881.5 MHz	892.5 MHz	
	5MHz	TX	Channel 26815	Channel 26915	Channel 27015	
LTE Band26			826.5 MHz	836.5 MHz	846.5 MHz	
(824-849)		RX	Channel 8815	Channel 8915	Channel 9015	
(02:0:0)			871.5 MHz	881.5 MHz	891.5 MHz	
	10MHz	TX	Channel 26840	Channel 26915	Channel 26990	
			829 MHz	836.5 MHz	844 MHz	
		RX	Channel 8840	Channel 8915	Channel 8990	
			874 MHz	881.5 MHz	889 MHz	
		TX	Channel 26865	Channel 26915	Channel 26965	
	15MHz		831.5 MHz	836.5 MHz	841.5 MHz	
		RX	Channel 8865	Channel 8915	Channel 8965	
			876.5 MHz	881.5 MHz	886.5 MHz	

Test Mode	Bandwidth	TX / RX	RF Channel			
	Dandwidth		Low (L)	Middle (M)	High (H)	
			Channel 27685	Channel27710	Channel 27735	
	5MHz	TX	2307.5 MHz	2310MHz	2312.5 MHz	
		RX	Channel 9795	Channel 9820	Channel 9845	
LTE Band 30			2352.5MHz	2355 MHz	2357.5MHz	
LIE Daliu 30	10MHz	TX	Channel 27710	Channel27710	Channel27710	
			2310 MHz	2310MHz	2310MHz	
		RX	Channel 9820	Channel 9820	Channel 9820	
			2355 MHz	2355 MHz	2355 MHz	

Test Mode	Bandwidth	TX / RX		RF Channel	
rest Mode	Dandwidth	IA/KA	Low (L)	Middle (M)	High (H)
			Channel 39675	Channel40620	Channel 41565
	5MHz	TX / RX	2498.5 MHz	2593 MHz	2687.5 MHz
			Channel 39700	Channel40620	Channel 41540
LTE Band 41	10MHz	TX / RX	2501 MHz	2593 MHz	2685 MHz
(2496-2690)			Channel 39725	Channel40620	Channel 41515
,	15MHz	TX / RX	2503.5 MHz	2593 MHz	2682.5 MHz
			Channel 39750	Channel40620	Channel 41490
	20MHz	TX / RX	2506 MHz	2593 MHz	2680 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. Piert, No. 1, Funcheng röcks, Johan Unistania Park, Suhou Area, China (Jiangsu) Pind Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房商部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 32 of 49

			1 6	age. 32 01 4	.
Test Mode	Bandwidth	TX / RX		RF Channel	
rest wode	Dandwidth	IX/IX	Low (L)	Middle (M)	High (H)
			Channel 131979	Channel 132322	Channel 132665
		TX	1710.7 MHz	1745 MHz	1779.3 MHz
	1.4MHz	RX	Channel 66443	Channel 66786	Channel 67329
		NA.	2110.7 MHz	2145MHz	2199.3 MHz
			Channel 131987	Channel 132322	Channel 132657
		TX	1711.5 MHz	1745 MHz	1778.5MHz
	3MHz	DV	Channel 66451	Channel 66786	Channel 67321
		RX	2111.5 MHz	2145MHz	2198.5MHz
	5MHz		Channel 131997	Channel 132322	Channel 132647
		TX	1712.5 MHz	1745 MHz	1777.5 MHz
		RX	Channel 66461	Channel 66786	Channel 67311
LTE Danieloo			2112.5 MHz	2145MHz	2197.5 MHz
LTE Band66	10MHz	TX	Channel 132022	Channel 132322	Channel 132622
			1715 MHz	1745 MHz	1775 MHz
		RX	Channel 66486	Channel 66786	Channel 67286
			2115 MHz	2145MHz	2195 MHz
	15MHz	TX	Channel 132047	Channel 132322	Channel 132597
			1717.5 MHz	1745 MHz	1772.5 MHz
		RX	Channel 66511	Channel 66786	Channel 67261
		100	2117.5 MHz	2145MHz	2192.5 MHz
			Channel 132072	Channel 132322	Channel 132572
		TX	1720 MHz	1745 MHz	1770 MHz
	20MHz	DV	Channel 66536	Channel 66786	Channel 67236
	ļ	RX	2120 MHz	2145MHz	2190 MHz

Took Mode	Bandwidth	TX / RX		RF Channel	
Test Mode	Danuwiuin	IA/RA	Low (L)	Middle (M)	High (H)
		TX	Channel 133147	Channel 133297	Channel 133447
			665.5 MHz	680.5 MHz	695.5 MHz
	5MHz	RX	Channel 68611	Channel 68761	Channel 68911
		KA	619.5 MHz	634.5 MHz	649.5 MHz
			Channel 133172	Channel 133297	Channel 133422
	10MHz	TX	668 MHz	680.5 MHz	693 MHz
		RX	Channel 68636	Channel 68761	Channel 68886
LTE D 174			622 MHz	634.5 MHz	647 MHz
LTE Band71	15MHz	TX	Channel 133197	Channel 133297	Channel 133397
			670.5 MHz	680.5 MHz	690.5 MHz
		RX	Channel 68661	Channel 68761	Channel 68861
			624.5 MHz	634.5 MHz	644.5 MHz
		TX	Channel 133222	Channel 133297	Channel 133372
			673 MHz	680.5 MHz	688 MHz
	20MHz	RX	Channel 68686	Channel 68761	Channel 68836
		INA	627 MHz	634.5 MHz	642 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 33 of 49

Table 4.3.1.2.9A-1: Test frequencies for CA 41C

Range	CC- Combo / N _{RB_agg} [RB]	CC1 Note1				CC2 Note1		
		BW		f UL/DL	BW		f UL/DL	
		[RB]	N _{UL/DL}	[MHz]	[RB]	N _{UL/DL}	[MHz]	
Low	25+100	25	39683	2499.3	100	39800	2511	
		100	39750	2506	25	39867	2517.7	
	50+75	50	39703	2501.3	75	39823	2513.3	
		75	39725	2503.5	50	39845	2515.5	
	50+100	50	39705	2501.5	100	39849	2515.9	
		100	39750	2506	50	39894	2520.4	
	75+75	75	39725	2503.5	75	39875	2518.5	
	75+100	75	39728	2503.8	100	39899	2520.9	
		100	39750	2506	75	39921	2523.1	
	100+100	100	39750	2506	100	39948	2525.8	
Mid	25+100	25	40528	2583.8	100	40645	2595.5	
		100	40595	2590.5	25	40712	2602.2	
	50+75	50	40549	2585.9	75	40669	2597.9	
		75	40571	2588.1	50	40691	2600.1	
	50+100	50	40526	2583.6	100	40670	2598.0	
	[100	40571	2588.1	50	40715	2602.5	
	75+75	75	40545	2585.5	75	40695	2600.5	
	75+100	75	40523	2583.3	100	40694	2600.4	
		100	40546	2585.6	75	40717	2602.7	
	100+100	100	40521	2583.1	100	40719	2602.9	
High	25+100	25	41373	2668.3	100	41490	2680	
		100	41440	2675	25	41557	2686.7	
	50+75	50	41395	2670.5	75	41515	2682.5	
		75	41417	2672.7	50	41537	2684.7	
	50+100	50	41346	2665.6	100	41490	2680	
		100	41391	2670.1	50	41535	2684.5	
	75+75	75	41365	2667.5	75	41515	2682.5	
	75+100	75	41319	2662.9	100	41490	2680	
		100	41341	2665.1	75	41512	2682.2	
	100+100	100	41292	2660.2	100	41490	2680	
Note 1:		ncreasing fr	equency order.					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND Doccheck@sqs.com"

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国。苏州。中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980

t (86-512) 62992980 www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 34 of 49

4 Description of Tests

4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.2.1

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Liness otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 83071443,



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 35 of 49

4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.8.4

Calculate power in dBm by the following formula:

ERP (dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP=ERP+2.15dB



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Liness otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(a) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

South of No. 6 Plant, No. 1, Runshang Rosad, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国·苏州·中国(江苏)自由贸易试验区苏州片区苏州工业园区河胜路1号的6号厂房南部 邮编: 215000 t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01

Page: 36 of 49

4.3 EIRP Power Density

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.3

Test Settings

- 1. Set instrument center frequency to OBW center frequency.
- 2. Set span to at least 1.5 times the OBW.
- 3. Set the RBW to the specified reference bandwidth (often 1 MHz).
- 4. Set VBW ≥ 3 × RBW.
- 5. Detector = RMS (power averaging).
- 6. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- 7. Sweep time = auto couple.
- 8. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- 9. Use the peak marker function to determine the maximum amplitude level within the reference bandwidth (PSD).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@ss.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 37 of 49

4.4 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2 & 4.3

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Remark: Reference test setup 1

Test Settings

- The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within
 - 1 5% of the 99% occupied bandwidth observed in Step 7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.acx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.acx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) \$3071443.



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 38 of 49

4.5 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to rms.

Remark: Reference test setup 1

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW ≥ 1% of the emission bandwidth
- VBW > 3 x RBW
- 5. Detector = RMS
- Number of sweep points ≥ 2 x Span/RBW
- Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.acx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.acx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) \$3071443.



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 39 of 49

4.6 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Remark: Reference test setup 1

Test Settings

- 1. Start frequency was set to 9kHz and stop frequency was set to at least 10* the fundamental frequency(Separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissinos, max hold for pulse emissions
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions of Telectronic Documents at http://www.sgs.com/en/Terms-en/Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law length of the company. Attention: To check the authenticity of testing finsection report & certificate, please contact us at telephone: (86-755183701443.



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 40 of 49

4.7 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.2

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Remark: Reference test setup 1

Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- 3. Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.acx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.acx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) \$3071443.



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 41 of 49

4.8 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.8

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). Test the EUT in the lowest channel, the middle channel ,the Highest channel.
- 5). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 6). Repeat above procedures until all frequencies measured was complete.

E (dB μ V/m) = Measured amplitude level (dB μ V) + (Cable Loss (dB) + Antenna Factor (dB/m) – AMP(dB)) EIRP (dBm) = E (dB μ V/m) + 20 log D – 104.8; where D is the measurement distance in meters

Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

E (dB μ V/m) = Measured amplitude level (dB μ V) + (Cable Loss (dB) + Antenna Factor (dB/m) – AMP(dB)) EIRP (dBm) = E (dB μ V/m) + 20 log D – 104.8; where D is the measurement distance in meters

- 3). Test the EUT in the lowest channel, the middle channel the Highest channel
- 4). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5). Repeat above procedures until all frequencies measured was complete

Remark1: Reference test setup 2

Remark2: The emission below 18G were measured at a 3m test distance, while emissions above 18GHz were measured at a 1m test distance. At a measurement distance of 1 meter the limit line was increased by 20*LOG(3/1) = 9.54 dB.

Remark: Reference test setup 2

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:

Level = Reading Level + AF(dB/m) + Factor(dB)

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier gain (dB)

Margin = Limit(dBm) - Level(dBm)

2) Scan from 9kHz to 40GHz, The disturbance between 9KHz to 30MHz and 18GHz to 40GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) All modes have been tested, but only the worst case data displayed in this report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Conditions-And-Conditions-And-Conditions-and-Conditions-and-Conditions-and-Conditions-And-Conditions-

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 t (86–512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 42 of 49

4.9 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; Section 9

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Remark: Reference test setup 3



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions of Telectronic Documents at http://www.sgs.com/en/Terms-en/Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law length of the company. Attention: To check the authenticity of testing finsection report & certificate, please contact us at telephone: (86-755183701443.




Report No.: SEWM2209000178RG01


Rev.: 01 Page: 43 of 49

4.10Test Setups

4.10.1 Test Setup 1



4.10.2 Test Setup 2





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.forElectronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions.forElectronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions.forElectronic Documents and Tutti-//www.sgs.com/en/Terms-and-Conditions/Terms-and-Con

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区海胜路1号的6号厂房南部 邮编: 215000


i: 215000 t (86–512) 62992980



Report No.: SEWM2209000178RG01

Rev.: 01 44 of 49 Page:

4.10.3 Test Setup 3





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Liness otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(a) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 45 of 49

4.11Test Conditions

Transmit Output Power Data - Average Power, Total			
Test Case	Test Conditions		
Test Environment	Ambient Climate & Rated Voltage		
Test Setup	Test Setup 1		
RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
Test Mode	UMTS/TM1;LTE/TM2; LTE/TM3; LTE/TM4		
Field Strength of Spurious Radiation			
Test Case	ase Test Conditions		
Test Environment	Ambient Climate & Rated Voltage		
Test Setup	Test Setup 2		
RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
Test Mode	UMTS/TM1;LTE/TM1; Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, frogery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 46 of 49

5 Main Test Instruments

RF conducted test					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Shielding Room	Brilliant-emc	N/A	SUWI-04-01-06	2021/05/08	2024/05/07
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2022/02/16	2023/02/15
Signal Analyzer	ROHDE&SCHWARZ	FSV3030	SUWI-01-02-02	2022/05/17	2023/05/16
Measurement Software	Tonscend	JS1120-3 Test System V 2.6.88.0336	SUWI-02-09-09	NCR	NCR
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	2021/12/04	2022/12/03
Wideband Radio Communication Test Ststion	Anritsu	MT8000A	SUWI-01-34-02	2022/09/16	2023/09/15
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-05	2022/02/14	2023/02/13
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	2022/02/15	2023/02/14
Temperature Chamber	ESPEC	SU-242	SUWI-01-13-01	2022/02/15	2023/02/14
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	2022/05/28	2023/05/27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.apx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Clients' instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

On the procedure of the sample of the set of the set of the sample of the set of the set

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Liangsu) Pitot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: Page: 47 of 49

RSE Test System					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date (yyyy/mm/dd)	Cal Due Date (yyyy/mm/dd)
Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	2021/05/08	2024/05/07
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2022/02/16	2023/02/15
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	2022/05/28	2023/05/27
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-05	2021/12/04	2022/12/03
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	2022/02/19	2023/02/18
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	VULB 9163	SUWI-01-11-01	2021/05/16	2023/05/15
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	2021/05/16	2023/05/15
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9170	SUWI-01-11-03	2021/05/14	2023/05/13
Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	2022/02/14	2023/02/13
Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	2022/02/14	2023/02/13
Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	2022/02/19	2023/02/18
Active Loop Antenna	SCHWRZBECK MESS- ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	2021/06/10	2023/06/09
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	2021/12/04	2022/12/03
Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-16-08	2022/02/14	2023/02/13
Measurement Software	Tonscend	JS32-RE V4.0.0.0	SUWI-02-09-04	NCR	NCR



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, frogery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 48 of 49

6 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	±0.54dB
2		± 3.13dB (9k -30MHz)
	Radiated Emission	± 4.8dB (30M -1GHz)
		± 4.8dB (1GHz to 18 GHz)
		± 4.8dB (Above 18GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{cispr/ETSI}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;

- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND.occheck@ss.com

or email: CM. Doccheck (愛Sg.s.com Suth of No. Flent, No. 1, Runsheng Rose, Subroin Indiate Park, Sudnou Area, Clinie (Jángsu) Pint Free Trade Zone 中国・苏州・中国(江苏)自由贸易式全区苏州上区苏州工业国区沟胜路1号的6号厂房南部 - 邮操: 215000



Report No.: SEWM2209000178RG01

Rev.: 01 Page: 49 of 49

7 Appendixes

Appendix A.3	WWAN Setup Photos
Appendix B.1	WCDMA Band II & IV & V
Appendix B.2	LTE Band 2
Appendix B.3	LTE Band 4
Appendix B.4	LTE Band 5
Appendix B.5	LTE Band 7
Appendix B.6	LTE Band 12
Appendix B.7	LTE Band 13
Appendix B.8	LTE Band 14
Appendix B.9	LTE Band 17
Appendix B.10	LTE Band 25
Appendix B.11	LTE Band 26(814-824)
Appendix B.12	LTE Band 26(824-849)
Appendix B.13	LTE Band 30
Appendix B.14	LTE Band 41
Appendix B.15	LTE Band 66
Appendix B.16	LTE Band 71
Appendix B.17	LTE CA_41C

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@ass.com