

## BT

### DUT: HA-A03T2

Communication System: BT ; Frequency: 2441 MHz;Duty Cycle: 1:1.30208

Medium: H2450 Medium parameters used:  $f = 2441$  MHz;  $\sigma = 1.76$  S/m;  $\epsilon_r = 40.25$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; Calibrated: 2023/5/17;
- Electronics: DAE4 Sn1418; Calibrated: 2023/4/25
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1794
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Right-DH5/Area Scan (6x7x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.114 W/kg

**Right-DH5/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.187 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.211 W/kg

**SAR(1 g) = 0.086 W/kg; SAR(10 g) = 0.037 W/kg**

Maximum value of SAR (measured) = 0.140 W/kg



