

BT

DUT: HA-A4T

Communication System:BT; Frequency: 2480 MHz;Duty Cycle: 1:1.2975
Medium: H2450 Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.79 \text{ S/m}$; $\epsilon_r = 40.02$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $22.7 \text{ }^\circ\text{C}$; Liquid Temperature : $22.5 \text{ }^\circ\text{C}$

DASY5 Configuration:
- Probe: EX3DV4 - SN7624;Calibrated: 2023/9/6;
- Electronics: DAE4 Sn1286; Calibrated: 2023/7/27
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1794
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Back-DH5/Area Scan (7x7x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (measured) = 0.0190 W/kg

Back-DH5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.891 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.0490 W/kg
SAR(1 g) = 0.025 W/kg; SAR(10 g) = 0.00987 W/kg
Maximum value of SAR (measured) = 0.0238 W/kg

