

RF TEST REPORT

ISED

APPLICANT

Owl Labs Inc.

MODEL NAME

MTW405

ISED ID

22676-MTW405

REPORT NUMBER

HA240429-OWL-001-R12-1

TEST REPORT

Date of Issue
June 27, 2024

Test Site
Hyundai C-Tech, Inc. dba HCT America, Inc.
1726 Ringwood Ave, San Jose, CA 95131, USA

Applicant	Owl Labs Inc.
Applicant Address	33-1/2 Union Square Somerville, MA 02143 U.S.A.
ISED ID	22676-MTW405
Model Name	MTW405
EUT Type	360-Degree Video Conferencing Platform
Modulation Type	OFDMA
ISED Classification	Unlicensed National Information Infrastructure (NII)
ISED Rule Part(s)	RSS-247 Issue 3 (August 2023) RSS-Gen Issue 5 Amd 2 (February 2021)
Test Procedure	ANSI C63.10-2013, KDB 789033 D02 v02r01, KDB 662911 D01

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures required. The results of testing in this report apply only to the product which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Hyundai C-Tech, Inc. dba HCT America, Inc. certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



John Park

Test Engineer

Reviewed By



Yongsoo Park

Technical Manager

REVISION HISTORY

The revision history for this document is shown in table.

TEST REPORT NO.	DATE	DESCRIPTION
HA240429-OWL-001-R12	June 8, 2024	Initial Issue
HA240429-OWL-001-R12-1	June 27, 2024	Page 4 : Corrected the Max. output power value Page 30 – 31 : According to ISED regulations, both Total Power values and Limit values are modified to e.i.r.p. values Page 32 – 33 : According to ISED regulations, both Total PSD values and Limit values are modified to e.i.r.p. values

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
2. METHODOLOGY	7
3. INSTRUMENT CALIBRATION	7
4. FACILITIES AND ACCREDITATIONS	8
5. ANTENNA REQUIREMENTS	9
6. MEASUREMENT UNCERTAINTY	10
7. DESCRIPTION OF TESTS	11
8. SUMMARY OF TEST RESULTS	23
9. TEST RESULT	26
9.1 DUTY CYCLE	26
9.2 26 dB BANDWIDTH / 99% BANDWIDTH	27
9.3 OUTPUT POWER	30
9.4 POWER SPECTRAL DENSITY	32
9.5 RADIATED SPURIOUS EMISSIONS	37
9.6 RADIATED RESTRICTED BAND EDGES	44
9.7 RECEIVER SPURIOUS EMISSIONS	47
10. LIST OF TEST EQUIPMENT	50
APPENDIX A. TEST SETUP PHOTOS	51
APPENDIX B. PHOTOGRAPHS OF EUT	52

1. GENERAL INFORMATION

EUT DESCRIPTION

Model	MTW405
Product Name	Meeting Owl 4+
Serial Number	Conducted : M4FC1324001C Radiated :M4FV13240003
Power Supply	20 V d.c. (USB type C - External adaptor)
RF Specification	WIFI 2.4 GHz : 802.11b/g/ n(HT20, HT40)/ ac(VHT20, VHT40)/ ax(HE20, HE40) WIFI 5 GHz : 802.11a/n(HT20/40)/ ac(VHT20/40/80)/ ax(HE20, HE40, HE80) Bluetooth 5.0 LE (1M / BR / EDR)
Transmitter Chain	WIFI 2.4 GHz / 5 GHz : 2x2 MIMO Bluetooth LE / Bluetooth BR/EDR : SISO
Operating Environment	Indoor
Operating Temperature	5 °C ~ +30 °C

RF SPECIFICATION SUBJECT TO THE REPORT

RF Specification	IEEE 802.11ax (HE20, HE40, HE80)	
Transmitter Chain	2 x 2 MIMO	
Frequency Range	U-NII 1	20 MHz BW : 5180 MHz – 5240 MHz 40 MHz BW : 5190 MHz – 5230 MHz 80 MHz BW : 5210 MHz
Max. RF Output Power	21.24 dBm e.i.r.p. (0.133 W e.i.r.p.)	
Modulation Type	OFDM : 802.11a/n/ac	
Antenna Specification ¹⁾	ANT1	Antenna Type : PCB Antenna Antenna Model : CU23001-1 Antenna Brand: antenova Peak Gain : 3.8 dBi
	ANT2	Antenna Type : PCB Antenna Antenna Model : CU23002-1 Antenna Brand: antenova Peak Gain : 3.2 dBi
Firmware Version ²⁾	6.4.21.22	
Hardware Version ²⁾	OWL-900-00027 Rev 5	
Date(s) of Tests	May 12, 2024 ~ June 8, 2024	

ANTENNA CONFIGURATION

The device employs 2x2 MIMO technologies with possible configurations below.

Frequency	Configuration	SDM	Beamforming	CDD
		ANT1 + ANT2	ANT1 + ANT2	ANT1 + ANT2
2.4 GHz	802.11b	-	-	O
	802.11g	-	-	O
	802.11n	O	-	O
	802.11ac	O	O	O
	802.11ax	O	O	O
5 GHz	802.11a	-	-	O
	802.11n	O	-	O
	802.11ac	O	O	O
	802.11ax	O	O	O

The equipment under test supports Cyclic Diversity mode.

CDD mode was picked as worst case for testing even though the device support both CDD and SDM, Beamforming.

ANTENNA DIRECTIONAL GAIN

Antenna Type	Type	RF Technology	Frequency	Gain (Ant 1)	Gain (Ant 2)
PCB	Dipole	802.11b/g/n	2.4 GHz	2.90 dBi	2.90 dBi
PCB	Dipole	802.11a/n/ac	5 GHz	3.80 dBi	3.20 dBi

Directional Gain (2.4 GHz : Uncorrelated) = $10 \log[(10^{(2.90/10)} + 10^{(2.90/10)}) / 2] = 2.90 \text{ dBi}$

Directional Gain (5 GHz : Uncorrelated) = $10 \log[(10^{(3.80/10)} + 10^{(3.20/10)}) / 2] = 3.51 \text{ dBi}$

Directional Gain (2.4 GHz : Correlated) = $10 \log[(10^{(2.90/20)} + 10^{(2.90/20)})^2 / 2] = 5.91 \text{ dBi}$

Directional Gain (5 GHz : Correlated) = $10 \log[(10^{(3.80/20)} + 10^{(3.20/20)})^2 / 2] = 6.52 \text{ dBi}$

Beamforming Directional Gain (2.4 GHz) = $2.90 \text{ dBi} + 10 \log(2) = 5.91 \text{ dBi}$

Beamforming Directional Gain (5 GHz) = $3.51 \text{ dBi} + 10 \log(2) = 6.52 \text{ dBi}$

OPERATING FREQUENCY CHANNELS

Band	Frequency (MHz)	Channel	802.11a	802.11n HT20	802.11ac VHT20	802.11ax HE20
U-NII 1	5180	36	O	O	O	O
	5200	40	O	O	O	O
	5220	44	O	O	O	O
	5240	48	O	O	O	O

Band	Frequency (MHz)	Channel	802.11n HT40	802.11ac VHT40	802.11ax HE40
U-NII 1	5190	38	O	O	O
	5230	46	O	O	O

Band	Frequency (MHz)	Channel	802.11ac VHT80	802.11ax HE80
U-NII 1	5210	42	O	O

SUMMARY OF TARGET POWER TABLE

U-NII 2 Band		Target Power / Chain
Mode	Tone	
802.11ax HE20	SU	10 dBm \pm 2 dB
	242T	10 dBm \pm 2 dB
	106T	7 dBm \pm 2 dB
	52T	4 dBm \pm 2 dB
	26T	1 dBm \pm 2 dB
802.11ax HE40	SU	11.5 dBm \pm 2 dB
	484T	11.5 dBm \pm 2 dB
	242T	10 dBm \pm 2 dB
	106T	7 dBm \pm 2 dB
	52T	4 dBm \pm 2 dB
	26T	1 dBm \pm 2 dB
802.11ax HE80	Full	11.5 dBm \pm 2 dB
	996T	11.5 dBm \pm 2 dB
	484T	11.5 dBm \pm 2 dB
	242T	10 dBm \pm 2 dB
	106T	7 dBm \pm 2 dB
	52T	4 dBm \pm 2 dB
	26T	1 dBm \pm 2 dB

2. METHODOLOGY

The measurement procedure described in FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 dated December 14, 2017 entitled "Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part15, Subpart E" and ANSI C63.10 (Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices' were used in the measurement.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of RSS-Gen issue 5 and 2, RSS-247 issue 3.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. Also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emission, the relative positions of this hand-held transmitter (EUT) were rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested at 5 GHz WLAN test mode. Qualcomm Radio Control Tool was used to control the channels, power level setting at continuous TX and normal RX mode.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC (Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at 1726 Ringwood Avenue, San Jose, California 95131, USA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

CABID : 25729



EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to RSS-Gen Issue 5 Amd 2 (Section 6.8) :

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.


All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Output Power, Conducted	± 0.54 dB
Frequency Tolerance	± 16.78 kHz
Occupied Bandwidth	± 120.66 kHz
Unwanted Emissions, Conducted	± 0.54 dB
Radiated Emissions (below 1 GHz)	± 5.70 dB
Radiated Emissions (Above 1 GHz)	± 5.25 dB

7. DESCRIPTION OF TESTS

7.1. DUTY CYCLE

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.
Measurement is performed in accordance with the section B.2 in KDB 789033 D02 v02r01.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


- RBW = 8 MHz (the largest available value)
- VBW = 8 MHz (\geq RBW)
- SPAN = 0 Hz
- Detector = Peak
- Number of points in sweep > 100
- Trace mode = Clear write
- Measure T_{total} and T_{on}
- Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 * \log(1/\text{Duty Cycle})$

7.2. 26 dB BANDWIDTH / 99 % OCCUPIED BANDWIDTH

LIMIT

Emission bandwidth was measured to define the minimum frequency range which the spectrum is integrated for maximum conducted output power measurement.

TEST SETUP



TEST PROCEDURE (26 dB Bandwidth)

Testing was performed according to the section C.1 in KDB 789033 D02 v02r01.

The transmitter output is connected to the spectrum analyzer.

The Spectrum Analyzer setting :

- RBW = Approximately 1 % of the emission bandwidth
- VBW > RBW
- Detector = Peak
- Trace mode = max hold
- Sweep = auto couple
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

TEST PROCEDURE (99% Bandwidth)

Testing was performed according to the section D in KDB 789033 D02 v02r01.

The transmitter output is connected to the spectrum analyzer.

- RBW = 1% ~ 5% of the occupied bandwidth
- VBW \approx 3 x RBW
- Detector = Peak
- Trace mode = max hold
- Sweep = auto couple
- Allow the trace to stabilize

Note(s) :


1. The bandwidth measurement function from the spectrum analyzer is used to measure X dB bandwidth.
2. 99% Emission bandwidth is used to determine the conducted output power limits.

7.3. OUTPUT POWER

LIMIT

Band	RSS-247, Section 6.2.2.1
U-NII 1	$\leq 200 \text{ mW e.i.r.p.}$ or $\leq 10 + 10 \log(B) \text{ dBm e.i.r.p.}$ whichever power is less, where B is 99% bandwidth in MHz

TEST SETUP



TEST PROCEDURE (Power Meter)

Refer to the section E.3 in KDB 789033 D02 v02r01

The transmitter output is connected to the Average Power Meter

- Measure the duty cycle.
- Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.


Add $10\log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times

7.4. POWER SPECTRAL DENSITY

LIMIT

Band	RSS-247, Section 6.2.2.1
U-NII 1	$\leq 10 \text{ dBm/MHz e.i.r.p.}$

TEST SETUP



TEST PROCEDURE

Refer to the section F in KDB 789033 D02 v02r01.

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- RBW = 1 MHz (510 kHz for UNII 3)
- VBW $\geq 3 \text{ MHz}$
- Number of points in sweep $\geq 2 \cdot \text{span} / \text{RBW}$.
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- Do not use sweep triggering. Allow the sweep to “free run”.
- Trace average at least 100 traces in power averaging (RMS) mode
- Use the peak search function on the spectrum analyzer to find the peak of the spectrum.
- If Method SA-2 was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.

Sample Calculation

Total PSD (Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor


7.5. FREQUENCY STABILITY

LIMIT

RSS-Gen, Section 8.11

Fundamental emissions of the radio devices should be kept within at least the central 80% of its permitted operating frequency band to minimize the possibility of out of band operation.

TEST SETUP



TEST PROCEDURE

- The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between - 30 °C and 50 °C.
- The temperature was incremented by 10 °C intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.
- The primary supply voltage is varied from 85% to 115% of the nominal value for non-hand carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.
- While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

7.6. UNDESIRABLE EMISSION

LIMIT

Band	RSS-247, Section 6.2.2.2
U-NII 1	In accordance with RSS-247, Section 6.2.2.2 All emissions outside the 5.15-5.35 GHz band shall not exceed an -27 dBm/MHz e.i.r.p.

Note(s) :

For ISSED, The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

RADIATION EMISSION LIMIT

ISED : RSS-GEN Section 8.9		
Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	6.37/F(kHz)	300
0.490 – 1.705	63.7/F(kHz)	30
1.705 – 30	0.08	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

RECEIVER RADIATED EMISSION LIMIT


ISED : RSS-GEN Section 7.3		
Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

RESTRICTED BANDS OF OPERATION


ISED : RSS-GEN Section 8.10				
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
0.090 - 0.110	8.37625 - 8.38675	108 – 138	1660 - 1710	8025 - 8500
0.495 - 0.505	8.41425 - 8.41475	149.9 - 150.05	1718.8 - 1722.2	9000 - 9200
2.1735 - 2.1905	12.29 - 12.293	156.52475 - 156.52525	2200 - 2300	9300 - 9500
3.020 - 3.026	12.51975 - 12.52025	156.7 - 156.9	2310 - 2390	10600 - 12700
4.125 - 4.128	12.57675 - 12.57725	162.0125 - 167.17	2483.5 - 2500	13250 - 13400
4.17725 - 4.17775	13.36 - 13.41	167.72 - 173.2	2655 - 2900	14470 - 14500
4.20725 - 4.20775	16.42 - 16.423	240 - 285	3260 - 3267	15350 - 16200
5.677 - 5.683	16.69475 - 16.69525	322 - 335.4	3332 - 3339	17700 - 21400
6.215 - 6.218	16.80425 - 16.80475	399.9 - 410	3345.8 - 3358	22010 - 23120
6.26775 - 6.26825	25.5 - 25.67	608 - 614	3500 - 4400	23600 - 24000
6.31175 - 6.31225	37.5 - 38.25	960 - 1427	4500 - 5150	31200 - 31800
8.291 - 8.294	73 - 74.6	1435 - 1626.5	5350 - 5460	36430 - 36500
8.362 - 8.366	74.8 - 75.2	1645.5 - 1646.5	7250 - 7750	Above 38600

TEST SETUP


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (BELOW 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor (0.009 MHz – 0.490 MHz) = $40 \cdot \log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$
Measurement Distance: 3 m
7. Distance Correction Factor (0.490 MHz – 30 MHz) = $40 \cdot \log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$
Measurement Distance: 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 9 kHz
 - VBW $\geq 3 \cdot \text{RBW}$
9. Total = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L)
10. There is a comparison data both open-field test site and alternative test site – semi-Anechoic chamber according to 414788 D01. And the results are properly calibrated.

TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (30 MHz – 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting
 - (1) Measurement Type (Peak):
 - Measured Frequency Range: 30 MHz – 1 GHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 100 kHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - (2) Measurement Type(Quasi-peak):
 - Measured Frequency Range: 30 MHz – 1 GHz
 - Detector = Quasi-Peak
 - RBW = 120 kHz
6. Total = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L)

TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (ABOVE 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting

(1) Measurement Type(Peak, G.5 in KDB 789033 v02r01):

- RBW = 1 MHz
- VBW \geq 3 MHz
- Detector = Peak
- Sweep Time = auto
- Trace mode = Max hold
- Allow sweeps to continue until the trace stabilizes.
- Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle.

(2) Measurement Type(Average, G.6.d in KDB 789033 v02r01):

- RBW = 1 MHz
- VBW(Duty cycle \geq 98 percent) = VBW \leq RBW/100(i.e., 10 kHz) but not less than 10 Hz.
- VBW(Duty cycle is < 98 percent) = VBW \geq $1/T$, where T is the minimum transmission duration.
- The analyzer is set to linear detector mode.
- Detector = Peak.
- Sweep time = auto.
- Trace mode = Max hold.
- Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of $1/x$, where x is the duty cycle.

9. Measurement value only up to 6 maximum emissions noted or would be lesser if no specific emissions from the EUT are recorded (i.e.: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor
10. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency (or 40 GHz whichever comes first)
11. Sample Calculation

(1) Total (Peak) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G)

(2) Total (Average, Duty \geq 98%) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G)

(3) Total (Average, Duty < 98%) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Duty Cycle Factor

TEST PROCEDURE OF RADIATED RESTRICTED BAND EDGE

1. Radiated test is performed with hopping off (if there is any)
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting

(1) Measurement Type(Peak, G.5 in KDB 789033 v02r01):

- RBW = 1 MHz
- VBW \geq 3 MHz
- Detector = Peak
- Sweep Time = auto
- Trace mode = Max hold
- Allow sweeps to continue until the trace stabilizes.
- Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle.

(2) Measurement Type(Average, G.6.d in KDB 789033 v02r01):

- RBW = 1 MHz
- VBW(Duty cycle \geq 98 percent) = VBW \leq RBW/100(i.e., 10 kHz) but not less than 10 Hz.
- VBW(Duty cycle is < 98 percent) = VBW \geq $1/T$, where T is the minimum transmission duration.
- The analyzer is set to linear detector mode.
- Detector = Peak.
- Sweep time = auto.
- Trace mode = Max hold.
- Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of $1/x$, where x is the duty cycle.

9. Sample Calculation

(1) Total (Peak) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

(2) Total (Average, Duty \geq 98%) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G)

(3) Total (Average, Duty < 98%) = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Duty Cycle Factor

7.7. AC POWER LINE CONDUCTED EMISSIONS

LIMIT

RSS-GEN Section 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

TEST SETUP

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

According to FCC KDB 174176 D01 Line Conducted FAQ v01r01 :

Devices Operating Above 30 MHz

For a device with a permanent or detachable antenna operating above 30 MHz, measurements must be performed with the antenna connected as specified in clause 6.2 of ANSI C63.10-2013.

Devices Operating Below 30 MHz

For a device with a permanent or detachable antenna operating at or below 30 MHz, the FCC will accept measurements performed with a suitable dummy load in lieu of the antenna under the following conditions:

- (1) Perform the AC power-line conducted tests with the antenna connected to determine compliance with Section 15.207 limits outside the transmitter's fundamental emission band;
- (2) Retest with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network which simulates the antenna in the fundamental frequency band. All measurements must be performed as specified in clause 6.2 of ANSI C63.10-2013.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

8. SUMMARY OF TEST RESULTS

Test Description	ISED Part Section(s)	Test Limit	Test Condition	Test Result
Occupied Bandwidth	RSS-Gen, 6.7	N/A (For power measurement)	Conducted	-
Maximum e.i.r.p.	RSS-247, 6.2.2.1	≤ 200 mW e.i.r.p. or $10+10 \log(B)$ dBm e.i.r.p. whichever power is less (B is 99% bandwidth)		PASS
Power Spectral Density	RSS-247, 6.2.2.1	≤ 10 dBm/MHz e.i.r.p.		PASS
Frequency Stability	RSS-Gen, 8.11	Maintained within the band		PASS ⁽¹⁾
AC Power line Conducted Emissions	RSS-Gen, 8.8	cf. Section 7.7		PASS ⁽¹⁾
Undesirable Emissions	RSS-247, 6.2.3.2	cf. Section 7.6	Radiated	PASS
Radiated Spurious Emissions	RSS-Gen, 8.9	cf. Section 7.6		PASS
Radiated Restricted Band Edge	RSS-Gen, 8.10	cf. Section 7.6		PASS
Receiver Spurious Emissions	RSS-Gen, 7.3	cf. Section 7.6		PASS

Note :

1. Evaluated on original certification.

WORST CASE CONFIGURATION

1. EUT Axis

- All X, Y, and Z positions for horizontal / vertical antenna polarization were investigated to find the worst-case position.
- X position was selected for the final evaluation.

2. Operations with all the data rates available were investigated for each different channel BW mode. Lowest data rate was selected as the worst case.

3. Radiated test was performed at the worst case 2 x TX CDD mode

- The target power of SISO mode per chain is the same as the target power of MIMO mode per chain.

4. Worst-case test mode

- All the RU tone for each bandwidth were investigated, and the modes below were reported as the worst-case conditions.

U-NII 2 Band		Tone	RU Offset
Test	Mode		
All Conducted Tests	802.11ax HE20	SU	-
		106T	53, 54
		52T	37, 38, 40
		26T	0, 4, 8
	802.11ax HE40	SU	-
		242T	61, 62
		106T	53, 54, 56
	802.11ax HE80	SU	-
Radiated Emission Tests	802.11ax HE20	SU	-
		106T	53, 54
		26T	0, 4, 8
	802.11ax HE40	SU	-
		242T	61, 62
	802.11ax HE80	SU	-
		484T	65, 66


WORST CASE DATA RATE

Mode	Worst Case Data Rate
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

CHANNEL UNDER TEST

Mode (U-NII 1)	Low Channel (MHz)	Mid Channel (MHz)	High Channel (MHz)
802.11a	5180	5220	5240
802.11n	5180	5220	5240
	5190	-	5230
802.11ac	5210		

TEST CONFIGURATION



LIST OF SUPPORT EQUIPMENT

Equipment Type	Model No.	Serial No.	Manufacturer	Qty	Note
Power Supply	PA-1650-58	165058LT33803287PEA01	LITEON	1	Input : 100-240 V a.c., 50-60 Hz, 1.6 A Output : 20 V d.c., 3.25 A
Laptop	14-dq1038wrn	5CD04524LL	HP	1	For EUT control

9. TEST RESULT


9.1 DUTY CYCLE

Duty cycle is 100 % continuous.

9.2 26 dB BANDWIDTH / 99% BANDWIDTH

U-NII 1 Band				99% Bandwidth (MHz)		26 dB Bandwidth (MHz)	
Mode / Tone	Frequency (MHz)	Channel	Offset	Chain 0	Chain 1	Chain 0	Chain 1
802.11ax HE20 / SU	5180	36	-	18.900	18.884	20.243	20.425
	5220	44	-	18.892	18.884	20.528	20.480
	5240	48	-	18.875	18.878	20.310	20.309
802.11ax HE20 / 106T	5180	36	53	14.804	18.013	16.899	18.999
			54	15.918	17.105	17.235	18.418
	5220	44	53	17.189	14.557	20.937	20.045
			54	12.579	17.591	17.473	18.832
	5240	48	53	16.733	17.892	18.412	20.378
			54	17.937	18.103	20.194	19.495
802.11ax HE20 / 52T	5180	36	37	18.288	17.579	19.685	18.892
			38	13.798	16.609	14.428	18.910
			40	14.651	13.716	15.672	15.360
	5220	44	37	15.619	18.070	16.796	19.616
			38	17.243	16.231	18.839	16.792
			40	18.275	16.411	19.556	17.996
	5240	48	37	16.804	18.278	18.119	19.990
			38	17.195	14.583	18.480	15.747
			40	18.288	14.690	19.458	15.892
802.11ax HE20 / 26T	5180	36	0	17.731	10.106	19.530	12.268
			4	15.066	17.288	15.559	18.009
			8	17.926	15.598	18.800	16.692
	5220	44	0	13.766	15.826	14.738	16.825
			4	14.998	12.439	18.210	14.627
			8	14.818	17.306	15.881	18.303
	5240	48	0	17.818	18.368	18.696	19.615
			4	16.245	14.586	17.154	18.283
			8	15.884	17.604	19.451	18.720
802.11ax HE40 / SU	5190	38	-	37.716	37.655	39.736	39.769
	5230	46	-	37.765	37.643	40.151	40.038
802.11ax HE40 / 242T	5190	38	61	27.167	28.432	32.128	34.635
			62	36.225	36.822	39.320	40.900
	5230	46	61	33.877	35.528	36.127	37.519
			62	36.611	35.289	39.393	37.870
802.11ax HE40 / 106T	5190	38	53	36.592	33.829	38.781	35.424
			54	28.717	31.718	33.066	33.093
			56	36.519	37.245	40.089	39.706
	5230	46	53	37.457	33.064	39.714	34.975
			54	28.607	34.461	34.549	37.211
			56	30.339	37.477	32.899	39.809
802.11ax HE80 / SU	5210	42	-	77.144	76.934	81.403	81.512

TEST PLOTS



Note :

The worst plots are reported for each tone and bandwidth

TEST PLOTS



Note :

The worst plots are reported for each tone and bandwidth

9.3 OUTPUT POWER

U-NII 1 Band				Test Result				Limit ⁽²⁾ (dBm e.i.r.p.)
Mode / Tone	Frequency (MHz)	Channel	Offset	Measured Conducted Power (dBm)		Duty Factor (dB)	Total Power ⁽¹⁾ (dBm e.i.r.p.)	
				Chain 0	Chain 1		All Chain	
802.11ax HE20 / SU	5180	36	-	10.41	9.62	-	19.57	22.76
	5220	44	-	10.84	9.73	-	19.85	22.76
	5240	48	-	10.88	9.78	-	19.90	22.76
802.11ax HE20 / 106T	5180	36	53	7.49	6.23	-	16.43	21.70
			54	7.73	6.81	-	16.82	22.02
	5220	44	53	8.49	7.09	-	17.38	21.63
			54	8.33	7.27	-	17.36	21.00
	5240	48	53	8.35	7.06	-	17.29	22.24
			54	8.56	7.30	-	17.50	22.54
802.11ax HE20 / 52T	5180	36	37	4.28	2.93	-	13.19	22.45
			38	4.51	3.26	-	13.46	21.40
			40	4.58	3.59	-	13.64	21.37
	5220	44	37	5.53	3.91	-	14.32	21.94
			38	5.55	4.11	-	14.42	22.10
			40	5.06	3.82	-	14.01	22.15
	5240	48	37	5.13	3.96	-	14.11	22.25
			38	5.36	4.25	-	14.37	21.64
			40	5.09	3.97	-	14.10	21.67
802.11ax HE20 / 26T	5180	36	0	1.29	0.62	-	10.50	20.05
			4	1.33	1.01	-	10.70	21.78
			8	1.16	0.89	-	10.56	21.93
	5220	44	0	2.53	2.34	-	11.96	21.39
			4	2.48	2.41	-	11.98	20.95
			8	2.19	1.95	-	11.60	21.71
	5240	48	0	2.15	1.91	-	11.56	22.51
			4	2.54	2.20	-	11.90	21.64
			8	2.04	1.81	-	11.46	22.01

Note(s) :

1. Total Power (dBm e.i.r.p.) = (Chain 0 dBm + Chain 1 dBm) + Directional Antenna Gain
2. Limit : MIN [10 log(200 mW = 23.01 dBm), 10+10log(OBW)]
3. Duty factor is not applied since the duty cycle is 100 %.

U-NII 1 Band				Test Result				Limit ⁽²⁾ (dBm e.i.r.p.)
Mode / Tone	Frequency (MHz)	Channel	Offset	Measured Conducted Power (dBm)		Duty Factor (dB)	Total Power ⁽¹⁾ (dBm e.i.r.p.)	
				Chain 0	Chain 1		All Chain	
802.11ax HE40 /SU	5190	38	-	11.90	10.92	-	20.97	23.01
	5230	46	-	12.25	11.10	-	21.24	23.01
802.11ax HE40 / 242T	5190	38	61	10.41	9.11	-	19.34	23.01
			62	11.21	9.92	-	20.14	23.01
	5230	46	61	11.53	9.84	-	20.30	23.01
			62	11.88	10.45	-	20.76	23.01
802.11ax HE40 / 106T	5190	38	53	7.06	5.60	-	15.92	23.01
			54	7.72	6.60	-	16.73	23.01
			56	8.19	6.83	-	17.09	23.01
	5230	46	53	8.21	6.51	-	16.97	23.01
			54	8.50	7.13	-	17.40	23.01
			56	8.49	7.35	-	17.49	23.01
802.11ax HE80 /SU	5210	42	-	12.05	11.00	-	21.09	23.01

Note(s) :

1. Total Power (dBm e.i.r.p.) = (Chain 0 dBm + Chain 1 dBm) + Directional Antenna Gain
2. Limit : MIN [10 log(200 mW = 23.01 dBm), 10+10log(OBW)]
3. Duty factor is not applied since the duty cycle is 100 %.

9.4 POWER SPECTRAL DENSITY

U-NII 1 Band				Test Result				Limit (dBm/MHz e.i.r.p.)
Mode / Tone	Frequency (MHz)	Channel	Offset	Measured Conducted PSD (dBm/MHz)		Duty Factor (dB)	Total PSD ⁽¹⁾ (dBm/MHz e.i.r.p.)	
				Chain 0	Chain 1		All Chain	
802.11ax HE20 / SU	5180	36	-	-0.64	-1.47	-	8.50	10
	5220	44	-	-0.33	-1.56	-	8.63	10
	5240	48	-	0.04	-1.59	-	8.84	10
802.11ax HE20 / 106T	5180	36	53	-0.59	-1.65	-	8.44	10
			54	-0.49	-1.34	-	8.63	10
	5220	44	53	0.26	-1.05	-	9.18	10
			54	0.18	-1.14	-	9.10	10
	5240	48	53	0.17	-1.22	-	9.06	10
			54	0.27	-1.05	-	9.19	10
802.11ax HE20 / 52T	5180	36	37	-1.02	-2.19	-	7.97	10
			38	-0.72	-2.10	-	8.17	10
			40	-0.58	-1.79	-	8.39	10
	5220	44	37	0.30	-1.34	-	9.09	10
			38	0.14	-1.38	-	8.98	10
			40	-0.20	-1.26	-	8.83	10
	5240	48	37	-0.12	-1.04	-	8.97	10
			38	0.25	-0.98	-	9.21	10
			40	-0.10	-1.08	-	8.97	10
802.11ax HE20 / 26T	5180	36	0	-0.94	-1.89	-	8.14	10
			4	-2.72	-2.63	-	6.86	10
			8	-1.44	-1.51	-	8.05	10
	5220	44	0	-0.14	-0.12	-	9.40	10
			4	-0.98	-1.31	-	8.39	10
			8	-0.13	-0.43	-	9.25	10
	5240	48	0	-0.41	-0.56	-	9.05	10
			4	-1.10	-1.57	-	8.20	10
			8	-0.51	-0.80	-	8.88	10

Note(s) :


1. Total PSD (dBm/MHz e.i.r.p.) = (Chain 0 dBm + Chain 1 dBm) + Directional Antenna Gain
2. Duty factor is not applied since the duty cycle is 100 %.

U-NII 1 Band				Test Result				Limit (dBm/MHz e.i.r.p.)
Mode / Tone	Frequency (MHz)	Channel	Offset	Measured PSD (dBm/MHz)		Duty Factor (dB)	Total PSD ⁽¹⁾ (dBm/MHz e.i.r.p.)	
				Chain 0	Chain 1		All Chain	
802.11ax HE40 / SU	5190	38	-	-1.70	-2.99	-	7.23	10
	5230	46	-	-1.78	-2.96	-	7.20	10
802.11ax HE40 / 242T	5190	38	61	-1.13	-2.32	-	7.85	10
			62	-0.57	-1.79	-	8.39	10
	5230	46	61	-0.11	-1.74	-	8.68	10
			62	0.03	-1.19	-	8.99	10
802.11ax HE40 / 106T	5190	38	53	-1.16	-2.55	-	7.73	10
			54	-0.63	-1.79	-	8.36	10
			56	-0.19	-1.40	-	8.78	10
	5230	46	53	0.01	-1.73	-	8.76	10
			54	0.23	-0.85	-	9.25	10
			56	0.17	-0.73	-	9.27	10
802.11ax HE80 / SU	5210	42	-	-4.88	-6.12	-	4.07	10

Note(s) :


1. Total PSD (dBm/MHz e.i.r.p.) = (Chain 0 dBm + Chain 1 dBm) + Directional Antenna Gain
2. Duty factor is not applied since the duty cycle is 100 %.

TEST PLOTS



Note :
The worst plots are reported for each tone and bandwidth


TEST PLOTS



Note :

The worst plots are reported for each tone and bandwidth

TEST PLOTS



Note :

The worst plots are reported for each tone and bandwidth

9.5 RADIATED SPURIOUS EMISSIONS

Frequency Range : Below 1 GHz

Test Mode 802.11ax HE20 (SU) : TX mode
 Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (SU) : TX mode
 Operating Frequency 5200 MHz (CH 40)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (SU) : TX mode
 Operating Frequency 5240 MHz (CH 48)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Note(s) :

1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain

Frequency Range : Above 1 GHz

Test Mode 802.11ax HE20 (SU) : TX mode
Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (SU) : TX mode
Operating Frequency 5220 MHz (CH 44)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (SU) : TX mode
Operating Frequency 5240 MHz (CH 48)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (26T Offset : 0) : TX mode
Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (26T Offset : 0) : TX mode
Operating Frequency 5220 MHz (CH 44)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Test Mode 802.11ax HE20 (26T Offset : 0) : TX mode
Operating Frequency 5240 MHz (CH 48)


Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Note(s) :


1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain
2. AV Level = Measured Power(dBm) + Correction Factor(dB) + Duty Cycle Factor(dB).

■ TEST PLOTS

Radiated Spurious Emission 9 kHz – 30 MHz (Antenna Position 90°) : 802.11ax HE20 (SU) (CH 36)



Radiated Spurious Emission 9 kHz – 30 MHz (Antenna Position 180°) : 802.11ax HE20 (SU) (CH 36)




Note:


1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

■ TEST PLOTS (Continued)

Radiated Spurious Emission 9 kHz – 30 MHz (Antenna Position Bent over) : 802.11ax HE20 (SU) (CH 36)



Radiated Spurious Emission 30 MHz – 1 GHz : 802.11ax HE20 (SU) (CH 36)




Note:


1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

■ TEST PLOTS (Continued)

Radiated Spurious Emission 1 GHz - 7 GHz : 802.11ax HE20 (SU) (CH 36)



Radiated Spurious Emission 7 GHz - 18 GHz : 802.11ax HE20 (SU) (CH 36)




Note:


1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

■ TEST PLOTS (Continued)

Radiated Spurious Emission 1 GHz - 7 GHz : 802.11ax HE20 (26T Offset : 4) (CH 48)




Radiated Spurious Emission 7 GHz - 18 GHz : 802.11ax HE20 (26T Offset : 4) (CH 48)



Note:

1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

▣ TEST PLOTS (Continued)



Note:

1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

9.6 RADIATED RESTRICTED BAND EDGES

Test Mode 802.11ax HE20 (SU) : TX mode
Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
5149.822	H	40.1	56.5	1.3	-	41.4	57.8	54	74	12.6	16.2
5149.883	V	35.4	50.4	1.3	-	36.7	51.7	54	74	17.3	22.3


Test Mode 802.11ax HE20 (106T Offset : 53) : TX mode
Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
4992.283	V	34.1	46.9	0.7	-	34.8	47.6	54	74	19.2	26.4
5148.776	H	35.1	54.2	1.3	-	36.4	55.5	54	74	17.6	18.5

Note(s) :

1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain
2. AV Level = Measured Power(dBm) + Correction Factor(dB) + Duty Cycle Factor(dB).
3. Duty factor is not applied since the duty cycle is 100 %.

TEST PLOTS



Test Mode 802.11ax HE40 (SU) : TX mode
 Operating Frequency 5190 MHz (CH 38)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
5149.817	V	41.3	56.0	1.3	-	42.6	57.3	54	74	11.4	16.7
5149.953	H	50.7	66.6	1.3	-	52.0	67.9	54	74	2.0	6.1


Test Mode 802.11ax HE40 (242T Offset : 61) : TX mode
 Operating Frequency 5190 MHz (CH 38)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
5147.680	V	33.2	60.0	1.3		34.5	61.3	54	74	19.5	12.7
5149.881	H	41.9	65.2	1.3		43.2	66.5	54	74	10.8	7.5

Note(s) :

1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain
2. AV Level = Measured Power(dBm) + Correction Factor(dB) + Duty Cycle Factor(dB).
3. Duty factor is not applied since the duty cycle is 100 %.

TEST PLOTS



Test Mode 802.11ax HE80 (SU) : TX mode
Operating Frequency 5210 MHz (CH 42)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
5148.138	H	50.7	67.8	1.3		52.0	69.1	54	74	2.0	4.9
5149.693	V	41.6	55.8	1.3		42.9	57.1	54	74	11.1	16.9


Test Mode 802.11ax HE80 (484T Offset : 65) : TX mode
Operating Frequency 5210 MHz (CH 42)

Frequency (MHz)	Polarization	Reading (dBuV)		Factor (dB)		Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
		AV	PK	Corr. ¹⁾	Duty	AV	PK	AV	PK	AV	PK
5149.556	V	39.1	59.3	1.3		40.4	60.6	54	74	13.6	13.4
5149.968	H	50.7	70.4	1.3		52.0	71.7	54	74	2.0	2.3

Note(s) :

1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain
2. AV Level = Measured Power(dBm) + Correction Factor(dB) + Duty Cycle Factor(dB).
3. Duty factor is not applied since the duty cycle is 100 %.

TEST PLOTS



9.7 RECEIVER SPURIOUS EMISSIONS

Frequency Range : Below 1 GHz

Test Mode 802.11ax HE20 (SU) : RX mode
 Operating Frequency 5180 MHz (CH 36)

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Frequency Range : Above 1 GHz

Test Mode 802.11ax HE20 (SU) : RX mode
 Operating Frequency 5180 MHz (CH 36)


Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
No major peaks found							

Note:


1. Correction Factor: Antenna Factor + Cable loss + Preamplifier

■ TEST PLOTS

Radiated Receiver Spurious Emission 30 MHz - 1 GHz : 802.11ax HE20 (SU) (CH 36)




Radiated Receiver Spurious Emission 1 GHz - 18 GHz : 802.11ax HE20 (SU) (CH 36)



Note:

1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

■ TEST PLOTS



Note:

1. There were no major peaks and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

10. LIST OF TEST EQUIPMENT

No.	Instrument	Model No.	Calibration Due (mm/dd/yy)	Manufacture	Serial No.
<input checked="" type="checkbox"/>	Signal Analyzer (20 Hz ~ 40.0 GHz)	ESU40	12/01/2024	Rohde & Schwarz	100529
<input checked="" type="checkbox"/>	Signal Analyzer (1 Hz ~ 40.0 GHz)	ESW44	10/24/2024	Rohde & Schwarz	102015
<input checked="" type="checkbox"/>	Signal Analyzer (3 Hz ~ 50 GHz)	N9030A	06/30/2024	Keysight	MY53311083
<input type="checkbox"/>	Attenuator (20 dB, DC ~ 26.5 GHz)	8493C 20 dB	02/16/2025	KEYSIGHT	89401
<input checked="" type="checkbox"/>	Attenuator (10 dB, DC ~ 26.5 GHz)	8493C 10 dB	09/05/2024	KEYSIGHT	89576
<input checked="" type="checkbox"/>	Open Switch with Power Sensor	OSP150	04/01/2025	Rohde & Schwarz	100872
<input checked="" type="checkbox"/>	Loop Antenna (0.009 ~ 30 MHz)	HLA 6121	09/12/2025	TESEQ	43964
<input checked="" type="checkbox"/>	BI-LOG Antenna (30 MHz ~ 6 GHz)	JB6	03/06/2025	Sunol	A060916
<input checked="" type="checkbox"/>	LNA (30 MHz ~ 1GHz)	PAM-103	05/03/2025	Com-Power	18020254
<input checked="" type="checkbox"/>	Horn Antenna (1 GHz ~ 18 GHz)	DRH-118	01/03/2025	Sunol	A061616
<input checked="" type="checkbox"/>	LNA (1 GHz ~ 18 GHz)	PAM-118A	03/13/2025	Com-Power	18040074
<input checked="" type="checkbox"/>	Horn Antenna (18 GHz ~ 40 GHz)	DRH-1840	01/20/2025	Sunol	17121
<input checked="" type="checkbox"/>	LNA (18 GHz ~ 40 GHz)	CBL18405045-01	01/05/2025	CERNEX, Inc.	27973
<input checked="" type="checkbox"/>	High Pass Filter	WHKX8-6090- 7000-18000-40SS	11/20/2024	Wainwright	23
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR3	12/14/2024	Rohde & Schwarz	102363
<input checked="" type="checkbox"/>	LISN	ENV216	10/23/2024	Rohde & Schwarz	101550
<input checked="" type="checkbox"/>	Temperature & Humidity Chamber	SH-641	08/01/2024	ESPEC	92002929
<input checked="" type="checkbox"/>	DC Power Supply	E3632A	06/12/2024	Agilent	MY40028636

Note(s) :

- Equipment listed above that calibrated during the testing period was set for test after the calibration.
- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

APPENDIX A. TEST SETUP PHOTOS

The setup photos are provided as a separate document.

APPENDIX B. PHOTOGRAPHS OF EUT

B.1. EXTERNAL PHOTOS

The external photos are provided as a separate document.

B.2. INTERNAL PHOTOS

The internal photos are provided as a separate document.

END OF TEST REPORT