


FCC Test Report

FCC ID : 2ALXJ-WBC100
Equipment : Whiteboard Owl
Model No. : WBC100
Brand Name : OWLLabs™
Applicant : Owl Labs Inc
Address : 33-1/2 Union Sq
Somerville US 02143 United States Of America
Standard : 47 CFR FCC Part 15.247
Received Date : Dec. 14, 2020
Tested Date : Jan. 22 ~ Jan. 26, 2021

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards	9
1.6	Reference Guidance	9
1.7	Deviation from Test Standard and Measurement Procedure.....	9
1.8	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Facility.....	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	19
3.4	Power Spectral Density	21
3.5	Emissions in Restricted Frequency Bands.....	26
3.6	Emissions in non-restricted Frequency Bands.....	42
4	TEST LABORATORY INFORMATION	46

Release Record

Report No.	Version	Description	Issued Date
FR0D1401AE	Rev. 01	Initial issue	Feb. 08, 2021

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.507MHz 42.48 (Margin -3.52dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 46.49MHz 32.47 (Margin -7.53dB) – PK	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: 6.79	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	1 Mbps
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	2 Mbps

Note 1: Bluetooth LE (Low energy) uses GFSK modulation.

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Gain (dBi)	Remarks
1	WPANT101 40-S1 A	Metal	IPX/MHF	1.8	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter
-------------------	--------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	Adapter	Brand: APX Model: PS120I1000 Power Rating: I/P: 100-240Vac, 50/60Hz, 0.5A Max O/P: 12Vdc, 1.0A, 12W Power Line: 6.06m non-shielded without core
2	Meeting Owl Pro	Brand: OWLLabs™ Model: MTW200

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test Tool	Qualcomm Radio Control Tool, Version: 4.0.00134.0	
Modulation Mode	Duty Cycle Of Test Signal (%)	Duty Factor (dB)
GFSK-1Mbps	68.35%	1.65
GFSK-2Mbps	40.72%	3.90


1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	default	default	default
GFSK/2Mbps	default	default	default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude 5400	DoC	---

1.3 Test Setup Chart



1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
LISN	R&S	ENV216	101579	Mar. 12, 2020	Mar. 11, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 21, 2020	Oct. 20, 2021
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 29, 2020	Apr. 28, 2021
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Dec. 22, 2020	Dec. 21, 2021
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 06, 2020	Nov. 05, 2021
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2020	Nov. 16, 2021
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 06, 2020	Oct. 05, 2021
Preamplifier	EMC	EMC02325	980187	Aug. 05, 2020	Aug. 04, 2021
Preamplifier	Agilent	83017A	MY39501309	Sep. 02, 2020	Sep. 01, 2021
Preamplifier	EMC	EMC184045B	980192	Jul. 21, 2020	Jul. 20, 2021
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Sep. 26, 2020	Sep. 25, 2021
RF cable-8M	EMC	EMC104-SM-SM-8000	181107	Sep. 26, 2020	Sep. 25, 2021
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Sep. 26, 2020	Sep. 25, 2021
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Sep. 26, 2020	Sep. 25, 2021
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Sep. 26, 2020	Sep. 25, 2021
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Sep. 26, 2020	Sep. 25, 2021
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Power Meter	Anritsu	ML2495A	1241002	Nov. 04, 2020	Nov. 03, 2021
Power Sensor	Anritsu	MA2411B	1207366	Nov. 04, 2020	Nov. 03, 2021
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 04, 2020	Dec. 03, 2021
Measurement Software	--	SENSE-15247_DTS	V5.10.7	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247

ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.130 Hz
Conducted power	±0.808 dB
Power density	±0.583 dB
Conducted emission	±2.715 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.96 dB
Radiated emission > 1GHz	±4.51 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corp.
Test Site	CO01-WS, TH01-WS
Address of Test Site	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.
Test Site	03CH03-WS
Address of Test Site	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2480	1Mbps	---
Radiated Emissions ≤ 1GHz	BT LE	2480	1Mbps	---
Maximum Output Power				
6dB bandwidth	BT LE	2402, 2440, 2480	1Mbps	---
Power spectral density	BT LE	2402, 2440, 2480	2Mbps	---
Radiated Emissions > 1GHz				

NOTE:

- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2480																																																																																																																																																																																						
Power Phase	Line																																																																																																																																																																																								
Test by : Alex Tsai Temperature: 22°C Humidity: 61%																																																																																																																																																																																									
																																																																																																																																																																																									
	<table border="1"> <thead> <tr> <th>1</th> <th>2*</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> <th>7</th> <th>8</th> <th>9</th> <th>10</th> <th>11</th> <th>12</th> </tr> <tr> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>Factor dB</th> <th>Cable loss dB</th> <th>Remark</th> <th colspan="5"></th> </tr> </thead> <tbody> <tr> <td>0.153</td> <td>41.60</td> <td>55.82</td> <td>-14.22</td> <td>31.74</td> <td>9.81</td> <td>0.05</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>0.153</td> <td>57.87</td> <td>65.82</td> <td>-7.95</td> <td>48.01</td> <td>9.81</td> <td>0.05</td> <td>QP</td> <td colspan="5"></td> </tr> <tr> <td>0.159</td> <td>40.95</td> <td>55.52</td> <td>-14.57</td> <td>31.09</td> <td>9.81</td> <td>0.05</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>0.159</td> <td>57.51</td> <td>65.52</td> <td>-8.01</td> <td>47.65</td> <td>9.81</td> <td>0.05</td> <td>QP</td> <td colspan="5"></td> </tr> <tr> <td>0.180</td> <td>39.61</td> <td>54.50</td> <td>-14.89</td> <td>29.73</td> <td>9.82</td> <td>0.06</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>0.180</td> <td>55.88</td> <td>64.50</td> <td>-8.62</td> <td>46.00</td> <td>9.82</td> <td>0.06</td> <td>QP</td> <td colspan="5"></td> </tr> <tr> <td>0.510</td> <td>34.85</td> <td>46.00</td> <td>-11.15</td> <td>24.86</td> <td>9.90</td> <td>0.09</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>0.510</td> <td>44.04</td> <td>56.00</td> <td>-11.96</td> <td>34.05</td> <td>9.90</td> <td>0.09</td> <td>QP</td> <td colspan="5"></td> </tr> <tr> <td>14.750</td> <td>31.40</td> <td>50.00</td> <td>-18.60</td> <td>20.62</td> <td>10.19</td> <td>0.59</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>14.750</td> <td>41.27</td> <td>60.00</td> <td>-18.73</td> <td>30.49</td> <td>10.19</td> <td>0.59</td> <td>QP</td> <td colspan="5"></td> </tr> <tr> <td>15.885</td> <td>33.97</td> <td>50.00</td> <td>-16.03</td> <td>23.15</td> <td>10.21</td> <td>0.61</td> <td>Average</td> <td colspan="5"></td> </tr> <tr> <td>15.885</td> <td>41.87</td> <td>60.00</td> <td>-18.13</td> <td>31.05</td> <td>10.21</td> <td>0.61</td> <td>QP</td> <td colspan="5"></td> </tr> </tbody> </table>	1	2*	3	4	5	6	7	8	9	10	11	12	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark						0.153	41.60	55.82	-14.22	31.74	9.81	0.05	Average						0.153	57.87	65.82	-7.95	48.01	9.81	0.05	QP						0.159	40.95	55.52	-14.57	31.09	9.81	0.05	Average						0.159	57.51	65.52	-8.01	47.65	9.81	0.05	QP						0.180	39.61	54.50	-14.89	29.73	9.82	0.06	Average						0.180	55.88	64.50	-8.62	46.00	9.82	0.06	QP						0.510	34.85	46.00	-11.15	24.86	9.90	0.09	Average						0.510	44.04	56.00	-11.96	34.05	9.90	0.09	QP						14.750	31.40	50.00	-18.60	20.62	10.19	0.59	Average						14.750	41.27	60.00	-18.73	30.49	10.19	0.59	QP						15.885	33.97	50.00	-16.03	23.15	10.21	0.61	Average						15.885	41.87	60.00	-18.13	31.05	10.21	0.61	QP								
1	2*	3	4	5	6	7	8	9	10	11	12																																																																																																																																																																														
Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark																																																																																																																																																																																		
0.153	41.60	55.82	-14.22	31.74	9.81	0.05	Average																																																																																																																																																																																		
0.153	57.87	65.82	-7.95	48.01	9.81	0.05	QP																																																																																																																																																																																		
0.159	40.95	55.52	-14.57	31.09	9.81	0.05	Average																																																																																																																																																																																		
0.159	57.51	65.52	-8.01	47.65	9.81	0.05	QP																																																																																																																																																																																		
0.180	39.61	54.50	-14.89	29.73	9.82	0.06	Average																																																																																																																																																																																		
0.180	55.88	64.50	-8.62	46.00	9.82	0.06	QP																																																																																																																																																																																		
0.510	34.85	46.00	-11.15	24.86	9.90	0.09	Average																																																																																																																																																																																		
0.510	44.04	56.00	-11.96	34.05	9.90	0.09	QP																																																																																																																																																																																		
14.750	31.40	50.00	-18.60	20.62	10.19	0.59	Average																																																																																																																																																																																		
14.750	41.27	60.00	-18.73	30.49	10.19	0.59	QP																																																																																																																																																																																		
15.885	33.97	50.00	-16.03	23.15	10.21	0.61	Average																																																																																																																																																																																		
15.885	41.87	60.00	-18.13	31.05	10.21	0.61	QP																																																																																																																																																																																		
Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).																																																																																																																																																																																									

Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2480
Power Phase	Neutral		

Test by : Alex Tsai Temperature: 22°C Humidity: 61%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark
1	0.156	39.26	55.69	-16.43	29.42	9.79	0.05	Average
2	0.156	58.24	65.69	-7.45	48.40	9.79	0.05	QP
3	0.180	37.55	54.50	-16.95	27.69	9.80	0.06	Average
4	0.180	56.21	64.50	-8.29	46.35	9.80	0.06	QP
5	0.189	37.67	54.06	-16.39	27.81	9.80	0.06	Average
6	0.189	55.01	64.06	-9.05	45.15	9.80	0.06	QP
7*	0.507	42.48	46.00	-3.52	32.55	9.84	0.09	Average
8	0.507	47.48	56.00	-8.52	37.55	9.84	0.09	QP
9	14.828	32.21	50.00	-17.79	21.46	10.16	0.59	Average
10	14.828	41.17	60.00	-18.83	30.42	10.16	0.59	QP
11	15.801	33.43	50.00	-16.57	22.63	10.19	0.61	Average
12	15.801	41.49	60.00	-18.51	30.69	10.19	0.61	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Ambient Condition	22°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	666.667k	1.027M	1M03F1D	663.043k	1.024M
BT-LE(2Mbps)	1.145M	2.033M	2M03F1D	1.138M	2.026M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	666.667k	1.027M
2440MHz	Pass	500k	663.043k	1.024M
2480MHz	Pass	500k	663.043k	1.027M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	1.138M	2.026M
2440MHz	Pass	500k	1.145M	2.026M
2480MHz	Pass	500k	1.145M	2.033M

Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

BT-LE(1Mbps)

EBW-DTS


2402MHz



BT-LE(1Mbps)

EBW-DTS


2440MHz



BT-LE(1Mbps)

EBW-DTS


2480MHz



BT-LE(2Mbps)

EBW-DTS


2402MHz



BT-LE(2Mbps)

EBW-DTS


2440MHz



BT-LE(2Mbps)

EBW-DTS

2480MHz



3.3 RF Output Power

3.3.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.3.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Ambient Condition	22°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	6.55	0.00452
BT-LE(2Mbps)	6.79	0.00478

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	1.80	4.78	30.00
2440MHz	Pass	1.80	4.23	30.00
2480MHz	Pass	1.80	6.55	30.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	1.80	4.99	30.00
2440MHz	Pass	1.80	4.38	30.00
2480MHz	Pass	1.80	6.79	30.00

DG = Directional Gain; Port X = Port X output power

Summary of Conducted (Average) Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	6.37	0.00434
BT-LE(2Mbps)	6.37	0.00434

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	1.80	4.56	-
2440MHz	Pass	1.80	3.95	-
2480MHz	Pass	1.80	6.37	-
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	1.80	4.52	-
2440MHz	Pass	1.80	3.93	-
2480MHz	Pass	1.80	6.37	-

Note: Average power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Ambient Condition	22°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-9.47
BT-LE(2Mbps)	-13.14

RBW = 3kHz;

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	1.80	-11.27	8.00
2440MHz	Pass	1.80	-11.83	8.00
2480MHz	Pass	1.80	-9.47	8.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	1.80	-14.99	8.00
2440MHz	Pass	1.80	-15.58	8.00
2480MHz	Pass	1.80	-13.14	8.00


DG = Directional Gain; RBW = 3kHz;

PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

BT-LE(1Mbps)

PSD

2402MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-11.27	-11.27	-11.27

BT-LE(1Mbps)

PSD

2440MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-11.83	-11.83	-11.83

BT-LE(1Mbps)

PSD

2480MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.47	-9.47	-9.47

BT-LE(2Mbps)

PSD

2402MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-14.99	-14.99	-14.99

BT-LE(2Mbps)

PSD

2440MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-15.58	-15.58	-15.58

BT-LE(2Mbps)

PSD

2480MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-13.14	-13.14	-13.14

3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup


Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz




3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):22 Humidity(%):68									
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	46.49	23.34	40.00	-16.66	32.09	-8.75	Peak	---	---
2	74.62	24.75	40.00	-15.25	36.81	-12.06	Peak	---	---
3	136.70	29.66	43.50	-13.84	39.14	-9.48	Peak	---	---
4	248.25	30.06	46.00	-15.94	40.29	-10.23	Peak	---	---
5	270.56	31.77	46.00	-14.23	41.28	-9.51	Peak	---	---
6	336.52	27.19	46.00	-18.81	34.48	-7.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):22 Humidity(%):68



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	32.47	40.00	-7.53	41.22	-8.75	Peak	---	---
2	91.11	26.99	43.50	-16.51	41.93	-14.94	Peak	---	---
3	126.03	31.43	43.50	-12.07	42.04	-10.61	Peak	---	---
4	136.70	30.64	43.50	-12.86	40.12	-9.48	Peak	---	---
5	276.38	28.92	46.00	-17.08	38.09	-9.17	Peak	---	---
6	305.48	27.14	46.00	-18.86	35.59	-8.45	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2402						
Polarization	Horizontal								
Test By :BRAD WU Temperature(°C):23 Humidity(%):63									
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	39.41	54.00	-14.59	41.07	-1.66	Average	100	324
2	2390.00	52.97	74.00	-21.03	54.63	-1.66	Peak	100	324
3	4804.00	34.01	54.00	-19.99	29.01	5.00	Average	154	21
4	4804.00	45.62	74.00	-28.38	40.62	5.00	Peak	154	21
5	12010.00	44.66	54.00	-9.34	29.98	14.68	Average	100	55
6	12010.00	56.97	74.00	-17.03	42.29	14.68	Peak	100	55
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2402
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.28	54.00	-14.72	40.94	-1.66	Average	106	189
2	2390.00	52.34	74.00	-21.66	54.00	-1.66	Peak	106	189
3	4804.00	33.21	54.00	-20.79	28.21	5.00	Average	100	28
4	4804.00	45.06	74.00	-28.94	40.06	5.00	Peak	100	28
5	12010.00	44.54	54.00	-9.46	29.86	14.68	Average	100	35
6	12010.00	56.44	74.00	-17.56	41.76	14.68	Peak	100	35


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2440
Polarization	Horizontal		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.26	54.00	-14.74	40.92	-1.66	Average	100	325
2	2390.00	52.67	74.00	-21.33	54.33	-1.66	Peak	100	325
3	2483.50	39.12	54.00	-14.88	40.98	-1.86	Average	100	325
4	2483.50	52.08	74.00	-21.92	53.94	-1.86	Peak	100	325
5	4880.00	33.90	54.00	-20.10	28.83	5.07	Average	168	16
6	4880.00	45.57	74.00	-28.43	40.50	5.07	Peak	168	16
7	7320.00	39.04	54.00	-14.96	28.64	10.40	Average	100	34
8	7320.00	52.64	74.00	-21.36	42.24	10.40	Peak	100	34


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2440
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.25	54.00	-14.75	40.91	-1.66	Average	105	188
2	2390.00	52.27	74.00	-21.73	53.93	-1.66	Peak	105	188
3	2483.50	39.00	54.00	-15.00	40.86	-1.86	Average	105	188
4	2483.50	51.39	74.00	-22.61	53.25	-1.86	Peak	105	188
5	4880.00	32.97	54.00	-21.03	27.90	5.07	Average	100	24
6	4880.00	44.93	74.00	-29.07	39.86	5.07	Peak	100	24
7	7320.00	38.92	54.00	-15.08	28.52	10.40	Average	100	59
8	7320.00	52.18	74.00	-21.82	41.78	10.40	Peak	100	59


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Horizontal		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.32	54.00	-14.68	41.18	-1.86	Average	108	339
2	2483.50	53.27	74.00	-20.73	55.13	-1.86	Peak	108	339
3	4960.00	33.65	54.00	-20.35	28.35	5.30	Average	104	22
4	4960.00	45.26	74.00	-28.74	39.96	5.30	Peak	104	22
5	7440.00	39.77	54.00	-14.23	29.62	10.15	Average	100	38
6	7440.00	52.69	74.00	-21.31	42.54	10.15	Peak	100	38


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (1Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.14	54.00	-14.86	41.00	-1.86	Average	108	191
2	2483.50	53.06	74.00	-20.94	54.92	-1.86	Peak	108	191
3	4960.00	32.95	54.00	-21.05	27.65	5.30	Average	100	26
4	4960.00	45.04	74.00	-28.96	39.74	5.30	Peak	100	26
5	7440.00	38.96	54.00	-15.04	28.81	10.15	Average	100	45
6	7440.00	52.24	74.00	-21.76	42.09	10.15	Peak	100	45

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2402						
Polarization	Horizontal								
Test By : BRAD WU		Temperature(°C): 23			Humidity(%): 63				
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB		High	Table
		dBuV/m			dBuV			cm	deg
1	2390.00	39.49	54.00	-14.51	41.15	-1.66	Average	100	323
2	2390.00	52.91	74.00	-21.09	54.57	-1.66	Peak	100	323
3	4804.00	34.26	54.00	-19.74	29.26	5.00	Average	148	25
4	4804.00	45.81	74.00	-28.19	40.81	5.00	Peak	148	25
5	12010.00	44.52	54.00	-9.48	29.84	14.68	Average	100	23
6	12010.00	56.81	74.00	-17.19	42.13	14.68	Peak	100	23
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2402
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.41	54.00	-14.59	41.07	-1.66	Average	105	188
2	2390.00	52.46	74.00	-21.54	54.12	-1.66	Peak	105	188
3	4804.00	33.46	54.00	-20.54	28.46	5.00	Average	100	31
4	4804.00	45.21	74.00	-28.79	40.21	5.00	Peak	100	31
5	12010.00	44.62	54.00	-9.38	29.94	14.68	Average	100	65
6	12010.00	56.58	74.00	-17.42	41.90	14.68	Peak	100	65

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2440						
Polarization	Horizontal								
Test By :BRAD WU Temperature(°C):23 Humidity(%):63									
 <p>The graph displays emission levels in dBuV/m on the y-axis (0 to 90) against frequency in MHz on the x-axis (1000 to 25000). Two horizontal red lines represent the limits: CLASS-B at approximately 74 dBuV/m and CLASS-B (AVG) at approximately 54 dBuV/m. Eight vertical blue lines indicate measured emission levels at various frequencies, labeled 1 through 8. The measured levels are: 1 (2390 MHz, 39.35 dBuV/m), 2 (2390 MHz, 52.74 dBuV/m), 3 (2483.5 MHz, 39.24 dBuV/m), 4 (2483.5 MHz, 52.15 dBuV/m), 5 (4880 MHz, 33.84 dBuV/m), 6 (4880 MHz, 45.25 dBuV/m), 7 (7320 MHz, 39.18 dBuV/m), and 8 (7320 MHz, 52.75 dBuV/m). All measured levels are below the CLASS-B limit.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.35	54.00	-14.65	41.01	-1.66	Average	100	326
2	2390.00	52.74	74.00	-21.26	54.40	-1.66	Peak	100	326
3	2483.50	39.24	54.00	-14.76	41.10	-1.86	Average	100	326
4	2483.50	52.15	74.00	-21.85	54.01	-1.86	Peak	100	326
5	4880.00	33.84	54.00	-20.16	28.77	5.07	Average	156	22
6	4880.00	45.25	74.00	-28.75	40.18	5.07	Peak	156	22
7	7320.00	39.18	54.00	-14.82	28.78	10.40	Average	100	29
8	7320.00	52.75	74.00	-21.25	42.35	10.40	Peak	100	29
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2440
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.44	54.00	-14.56	41.10	-1.66	Average	103	192
2	2390.00	52.48	74.00	-21.52	54.14	-1.66	Peak	103	192
3	2483.50	39.25	54.00	-14.75	41.11	-1.86	Average	103	192
4	2483.50	51.56	74.00	-22.44	53.42	-1.86	Peak	103	192
5	4880.00	32.85	54.00	-21.15	27.78	5.07	Average	100	31
6	4880.00	44.89	74.00	-29.11	39.82	5.07	Peak	100	31
7	7320.00	39.14	54.00	-14.86	28.74	10.40	Average	100	46
8	7320.00	52.35	74.00	-21.65	41.95	10.40	Peak	100	46


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Horizontal		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.79	54.00	-14.21	41.65	-1.86	Average	109	338
2	2483.50	54.69	74.00	-19.31	56.55	-1.86	Peak	109	338
3	4960.00	33.54	54.00	-20.46	28.24	5.30	Average	106	28
4	4960.00	45.12	74.00	-28.88	39.82	5.30	Peak	106	28
5	7440.00	39.94	54.00	-14.06	29.79	10.15	Average	100	33
6	7440.00	52.78	74.00	-21.22	42.63	10.15	Peak	100	33


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	BT-LE (2Mbps)	Test Freq. (MHz)	2480
Polarization	Vertical		

Test By :BRAD WU Temperature(°C):23 Humidity(%):63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.36	54.00	-14.64	41.22	-1.86	Average	106	192
2	2483.50	53.21	74.00	-20.79	55.07	-1.86	Peak	106	192
3	4960.00	33.15	54.00	-20.85	27.85	5.30	Average	100	47
4	4960.00	45.26	74.00	-28.74	39.96	5.30	Peak	100	47
5	7440.00	39.04	54.00	-14.96	28.89	10.15	Average	100	61
6	7440.00	52.35	74.00	-21.65	42.20	10.15	Peak	100	61

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement



1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.3 Test Setup



3.6.4 Test Result of Emissions in non-restricted Frequency Bands


Ambient Condition	22°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------



BT-LE(1Mbps)

CSENdB-DTS


2480MHz



BT-LE(2Mbps)

CSENdB-DTS


2402MHz



BT-LE(2Mbps)

CSENdB-DTS


2440MHz



BT-LE(2Mbps)

CSENdB-DTS

2480MHz



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==