

RF EXPOSURE EXEMPT REPORT

APPLICANT : Shenzhen Airsmart Technology Co., Ltd.

PRODUCT NAME : BUTTON PORTABLE BLUETOOTH SPEAKER

MODEL NAME : MW-P1I, MW-P1S

BRAND NAME : MUZEN

FCC ID : 2ALXL-P1

47CFR 2.1093 STANDARD(S) KDB 447498

RECEIPT DATE : 2019-02-28

TEST DATE : 2019-03-07 to 2019-03-12

ISSUE DATE : 2019-03-18

Edited by:

Liang Yumei (Rapporteur)

Approved by:

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Fax: 86-755-36698525

Tel: 86-755-36698555 Http://www.morlab.cn

E-mail: service@morlab.cn





DIRECTORY

1.	Technical Information	•3
1.1	Applicant and Manufacturer Information	•3
1.2	Equipment Under Test (EUT) Description	•3
1.3	Identification of all used EUT	•4
1.4	Applied Reference Documents	•4
2.	Device Category and RF Exposure Limit	. 5
3.	Measurement of RF Output Power	•6
4.	RF Exposure Evaluation	٠7
An	nex A General Information	.8

Change History				
Version	Date	Reason for change		
1.0	2019-03-18	First edition		



1. Technical Information

Note: Provide by Applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Shenzhen Airsmart Technology Co., Ltd.	
Applicant Address.	Unit 616,Ant's Union Start-up Accelerator,No.9 Keji Road,Science	
Applicant Address:	and Technology Park, Nanshan District Shenzhen China	
Manufacturer:	Shenzhen Airsmart Technology Co., Ltd.	
Manufacturan Address	Unit 616,Ant's Union Start-up Accelerator,No.9 Keji Road,Science	
Manufacturer Address:	and Technology Park, Nanshan District Shenzhen China	

1.2 Equipment Under Test (EUT) Description

EUT Type:	BUTTON PORTABLE BLUETOOTH SPEAKER	
Hardware Version:	A/I	
Software Version: 1.0		
Frequency Bands:	Bluetooth: 2402MHz-2480MHz	
Modulation Mode:	Bluetooth BR+EDR: GFSK, π/4-DQPSK, 8-DPSK	
wodulation wode:	Bluetooth LE: GFSK	
Antenna Type:	FPC Antenna	
Antenna Gain:	2.01dBi	

Note: The model MW-P1I and MW-P1S are accordant in both hardware and software, only differ in model number.



Tel: 86-755-36698555

Http://www.morlab.cn



1.3 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version	
1#	A/I	1.0	

1.4 Applied Reference Documents

Leading reference documents for testing:

No. Identity		Document Title
1	47 CFR§2.1093	Radio Frequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. Device Category and RF Exposure Limit

Per user manual, this device is BUTTON PORTABLE BLUETOOTH SPEAKER. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





3. Measurement of RF Output Power

1. Bluetooth output power

Mode	Channel	Frequency	Peak power (dBm)		
iviode		(MHz)	1Mbps	2Mbps	3Mbps
	CH 00	2402	-0.76	0.45	0.92
BR / EDR	CH 39	2441	-1.50	-0.23	0.27
	CH 78	2480	-2.13	-0.83	-0.35
Tune-up Limit (dBm)		-0.50	1.00	1.00	

Mode	Channel	Frequency	Peak power (dBm)	
iviode		(MHz)	GFSK	
	CH 00	2402	3.17	
LE	CH 19	2440	2.88	
	CH 39	2480	2.44	
Tune-up Limit (dBm)		3m)	4.00	

Note: According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.





4. RF Exposure Evaluation

The device only incorporates a BUTTON PORTABLE BLUETOOTH SPEAKER so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] ≤ 3.0

The maximum tune-up limit power is 2.51mW @ 2.402GHz

The BUTTON PORTABLE BLUETOOTH SPEAKER is used on the hand/head, so use **5mm** as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] =0.78 \leq 3.0

So SAR evaluation is not required for this device.

Note: Declaration of the tune-up limit is 4.00dBm.





Annex A General Information

1. Identification of the Responsible Testing Laboratory

- radination of the responsible resumg Laboratory				
Shenzhen Morlab Communications Technology Co.,				
Ltd.Morlab Laboratory				
FL.3, Building A, FeiYang Science Park, No.8 LongChang				
Road, Block 67, BaoAn District, ShenZhen, GuangDong				
Province, P. R. China				
+86 755 36698555				
+86 755 36698525				

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

END OF REPORT	
 LIND OF INLEGINE	

