



# FCC Part 15C Test Report

## FCC ID: 2ALYRHG-C01B

Product Name:	Amigo Wireless Remote Control
Trademark:	 高巨创新 HIGH GREAT
Model Name :	HG-C01B
Prepared For :	<b>Shenzhen HighGreat Innovation Technology Development Co., Ltd.</b>
Address :	NO.6 Yuanlingzai Park, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	Jun. 22–Jul. 03, 2017
Date of Report :	Jul. 03, 2017
Report No.:	BCTC-LH170602435-1E



### TEST RESULT CERTIFICATION

**Applicant's name** ..... : **Shenzhen HighGreat Innovation Technology Development Co., Ltd.**  
**Address** ..... : NO.6 Yuanlingzai Park, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China  
**Manufacture's Name**..... : **Shenzhen HighGreat Innovation Technology Development Co., Ltd.**  
**Address** ..... : NO.6 Yuanlingzai Park, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China

**Product description**

**Product name** ..... : Amigo Wireless Remote Control  
**Model and/or type reference** : HG-C01B

**Standards** ..... : FCC Part15.247  
 ANSI C63.10:2013  
 KDB 558074 D01 DTS Meas Guidance v03r03

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by ( <b>Engineer</b> )	Eric Yang	
Reviewer(Supervisor)	Jade Yang	
Approved(Manager)	Carson Zhang	

**Table of Contents**

	<b>Page</b>
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
<b>2 . GENERAL INFORMATION</b>	<b>7</b>
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
<b>3 . EMC EMISSION TEST</b>	<b>12</b>
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.1.2 TEST PROCEDURE	12
3.1.3 DEVIATION FROM TEST STANDARD	12
3.1.4 TEST SETUP	13
3.1.5 EUT OPERATING CONDITIONS	13
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP	17
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	19
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	20
3.2.8 TEST RESULTS (1GHZ~25GHZ)	22
3.3 CONDUCTED EMISSION MEASUREMENT	27
3.3 RADIATED BAND EMISSION MEASUREMENT	47
3.3.1 TEST REQUIREMENT:	47
3.3.2 TEST PROCEDURE	47
3.3.3 DEVIATION FROM TEST STANDARD	48
3.3.4 TEST SETUP	48
3.3.5 EUT OPERATING CONDITIONS	48



<b>Table of Contents</b>		<b>Page</b>
<b>4 . POWER SPECTRAL DENSITY TEST</b>		<b>57</b>
<b>4.1 APPLIED PROCEDURES / LIMIT</b>		<b>57</b>
4.1.1 TEST PROCEDURE		57
4.1.2 DEVIATION FROM STANDARD		57
4.1.3 TEST SETUP		57
4.1.4 EUT OPERATION CONDITIONS		57
4.1.5 TEST RESULTS		58
<b>5 . BANDWIDTH TEST</b>		<b>66</b>
<b>5.1 APPLIED PROCEDURES / LIMIT</b>		<b>66</b>
5.1.1 TEST PROCEDURE		66
5.1.2 DEVIATION FROM STANDARD		66
5.1.3 TEST SETUP		66
5.1.4 EUT OPERATION CONDITIONS		66
5.1.5 TEST RESULTS		67
<b>6 . PEAK OUTPUT POWER TEST</b>		<b>75</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>		<b>75</b>
6.1.1 TEST PROCEDURE		75
6.1.2 DEVIATION FROM STANDARD		75
6.1.3 TEST SETUP		75
6.1.4 EUT OPERATION CONDITIONS		75
6.1.5 TEST RESULTS		76
<b>7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>		<b>77</b>
7.1 APPLICABLE STANDARD		77
7.2 TEST PROCEDURE		77
7.3 DEVIATION FROM STANDARD		77
7.4 TEST SETUP		77
7.5 EUT OPERATION CONDITIONS		78
7.1 TEST RESULTS		78
<b>8 . ANTENNA REQUIREMENT</b>		<b>83</b>
8.1 STANDARD REQUIREMENT		83
8.2 EUT ANTENNA		83
<b>9 . EUT TEST PHOTO</b>		<b>84</b>
<b>10 . EUT PHOTO</b>		<b>86</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>		



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

<b>FCC Part15 (15.247) , Subpart C</b>			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



## 1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add. : No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registered No.: 187086

## 1.2 MEASUREMENT UNCERTAINTY


The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated (<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated (>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Amigo Wireless Remote Control	
Trade Name	 高巨创新 HIGH GREAT	
Model Name	HG-C01B	
Model Difference	N/A	
Product Description	The EUT is a Amigo Wireless Remote Control	
	Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
	Modulation Type:	WIFI: OFDM/DSSS
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n:Up to 150Mbps
	Number Of Channel	802.11b/g/n20MHz:11 CH 802.1140MHz:7 CH
	Antenna Designation:	Please see Note 3.
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.	
Power supply	DC3.7V	
hardware version	--	
Software version	--	
Serial number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	05	2432	07	2442	09	2452
04	2427	06	2437	08	2447		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Integrated antenna	N/A	3.0	WIFI antenna

**2.2 DESCRIPTION OF TEST MODES**

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9


Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.




### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Conducted Emission/



Radiated Spurious Emission Test




RF test setup:





## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Amigo Wireless Remote Control	 高巨创新 HIGH GREAT	HG-C01B	N/A	EUT
E-2	Transfrom board	N/A	N/A	N/A	N/A
E-3	Notebook	Lenovo	S2	N/A	Lab Provide
E-4	Adapter	N/A	KA25-0501000CN	N/A	Lab Provide

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	USB cable unshielded
C2	NO	NO	0.5M	Connection cable unshielded
C3	NO	NO	1.2M	USB cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

## Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45108040	2016.08.27	2017.08.26
2	Test Receiver (9kHz-7GHz)	R&S	ESPI	101318	2016.08.27	2017.08.26
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB 9168	VULB91 68-438	2016.08.27	2017.08.26
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1201	2016.09.03	2017.09.03
5	Horn Antenna (14GHz-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	2016.09.03	2017.09.03
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2016.08.27	2017.08.26
7	Amplifier (1GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2016.08.27	2017.08.26
8	Amplifier (18GHz-40GHz)	SCHWARZBECK	BBV 9721	9721-205	2016.08.27	2017.08.26
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	00014	2016.09.03	2017.09.03
10	RF cables1 (9kHz-1GHz)	R&S	R203	R20X	2016.08.27	2017.08.26
11	RF cables2 (1GHz-40GHz)	R&S	R204	R21X	2016.08.27	2017.08.26
12	Antenna connector	Florida RF Labs	N/A	RF 01#	2016.08.27	2017.08.26
13	Power Metter	ANRITSU	ML2487A	6K00001568	2016.08.27	2017.08.26
14	Power Sensor (AV)	ANRITSU	ML2491A	030989	2016.08.27	2017.08.26
15	Signal Analyzer 9kHz-26.5GHz	Agilent	N9010A	MY48030494	2016.08.27	2017.08.26
16	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	2016.08.27	2017.08.26
17	D.C. Power Supply	LongWei	PS-305D	010964729	2016.08.27	2017.08.26

## Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-1 01165-ha	2016.08.27	2017.08.26
2	LISN	SCHWARZBECK	NSLK8127	8127739	2016.08.27	2017.08.26
3	LISN	R&S	NSLK8126	8126487	2016.08.27	2017.08.26
4	RF cables	R&S	R204	R20X	2016.08.27	2017.08.26
5	Attenuator	R&S	ESH3-Z2	143206	2016.08.27	2017.08.26



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


##### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



### 3.1.6 TEST RESULTS

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 5




**Remark:**

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1635	46.64	9.66	56.30	65.28	-8.98	QP	
2	0.1635	34.19	9.66	43.85	55.28	-11.43	AVG	
3	0.2445	41.48	9.65	51.13	61.94	-10.81	QP	
4	0.2445	27.86	9.65	37.51	51.94	-14.43	AVG	
5	0.3209	37.45	9.66	47.11	59.68	-12.57	QP	
6	0.3209	22.56	9.66	32.22	49.68	-17.46	AVG	
7 *	0.6495	41.20	9.68	50.88	56.00	-5.12	QP	
8	0.6495	26.86	9.68	36.54	46.00	-9.46	AVG	
9	0.7665	40.23	9.68	49.91	56.00	-6.09	QP	
10	0.7665	25.89	9.68	35.57	46.00	-10.43	AVG	
11	2.8905	36.50	9.72	46.22	56.00	-9.78	QP	
12	2.8905	21.07	9.72	30.79	46.00	-15.21	AVG	



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 5



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1680	42.47	9.66	52.13	65.06	-12.93	QP	
2	0.1680	27.82	9.66	37.48	55.06	-17.58	AVG	
3	0.2445	39.52	9.65	49.17	61.94	-12.77	QP	
4	0.2445	30.20	9.65	39.85	51.94	-12.09	AVG	
5 *	0.6450	41.12	9.68	50.80	56.00	-5.20	QP	
6	0.6450	28.94	9.68	38.62	46.00	-7.38	AVG	
7	0.7620	40.95	9.68	50.63	56.00	-5.37	QP	
8	0.7620	28.28	9.68	37.96	46.00	-8.04	AVG	
9	0.9915	39.08	9.69	48.77	56.00	-7.23	QP	
10	0.9915	23.84	9.69	33.53	46.00	-12.47	AVG	
11	1.7070	38.13	9.70	47.83	56.00	-8.17	QP	
12	1.7070	20.99	9.70	30.69	46.00	-15.31	AVG	



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



### 3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC3.7V
Test Mode :	Mode 4	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{specific distance}/\text{test distance})$ (dB);


Limit line = specific limits(dBuv) + distance extrapolation factor.

Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier.



**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC3.7V		
Test Mode :	Mode 4		




Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		48.6719	24.80	-13.98	10.82	40.00	-29.18	QP
2		96.0986	27.40	-16.28	11.12	43.50	-32.38	QP
3		185.1379	44.30	-17.57	26.73	43.50	-16.77	QP
4		239.9874	40.18	-15.52	24.66	46.00	-21.34	QP
5		360.4476	33.32	-12.18	21.14	46.00	-24.86	QP
6	*	842.1296	33.48	-3.54	29.94	46.00	-16.06	QP



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC3.7V		
Test Mode :	Mode 4		



Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		42.4508	26.42	-14.39	12.03	40.00	-27.97	QP
2		96.0986	27.39	-16.28	11.11	43.50	-32.39	QP
3		185.7882	38.07	-17.50	20.57	43.50	-22.93	QP
4	*	213.0151	41.26	-16.21	25.05	43.50	-18.45	QP
5		239.9874	35.40	-15.52	19.88	46.00	-26.12	QP
6		742.2587	29.57	-5.03	24.54	46.00	-21.46	QP



3.2.8 TEST RESULTS (1GHZ~25GHZ)

802.11b									
Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel 2412MHz									
V	4824.00	68.79	39.55	7.85	25.66	62.75	74.00	-11.25	PK
V	4824.00	51.64	39.55	7.85	25.66	45.60	54.00	-8.40	AV
V	7236.00	64.13	38.33	7.52	24.55	57.87	74.00	-16.13	PK
V	7236.00	46.70	38.33	7.52	24.55	40.44	54.00	-13.56	AV
V	15450.00	50.83	35.23	6.75	26.59	48.94	74.00	-25.06	PK
H	4824.00	64.36	39.55	7.85	25.66	58.32	74.00	-15.68	PK
H	4824.00	49.26	39.55	7.85	25.66	43.22	54.00	-10.78	AV
H	7236.00	62.76	38.33	7.52	23.55	55.50	74.00	-18.50	PK
H	7236.00	49.77	38.33	7.52	23.22	42.18	54.00	-11.82	AV
H	15450.00	47.24	35.45	6.75	27.88	46.42	74.00	-27.58	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Mid Channel 2437MHz									
V	4874.00	69.14	38.89	7.57	25.45	63.27	74.00	-10.73	PK
V	4874.00	52.58	38.89	7.57	25.45	46.71	54.00	-7.29	AV
V	7311.00	65.98	38.78	7.35	24.78	59.33	74.00	-14.67	PK
V	7311.00	47.23	38.78	7.35	24.78	40.58	54.00	-13.42	AV
V	15450.00	52.37	35.89	6.42	26.47	49.37	74.00	-24.63	PK
H	4874.00	65.72	38.89	7.57	25.45	59.85	74.00	-14.15	PK
H	4874.00	50.84	38.89	7.57	25.45	44.97	54.00	-9.03	AV
H	7311.00	64.12	38.78	7.35	24.78	57.47	74.00	-16.53	PK
H	7311.00	49.73	38.78	7.35	24.78	43.08	54.00	-10.92	AV
H	15450.00	50.95	36.68	6.45	26.65	47.37	74.00	-26.63	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel 2462MHz									
V	4924.00	66.54	38.75	7.46	25.45	60.70	74.00	-13.3	PK
V	4924.00	48.88	38.75	7.46	25.45	43.04	54.00	-10.96	AV
V	7386.00	67.67	38.65	7.22	24.78	61.02	74.00	-12.98	PK
V	7386.00	48.99	38.65	7.22	24.78	42.34	54.00	-11.66	AV
V	15450.00	51.06	35.58	6.35	26.47	48.30	74.00	-25.70	PK
H	4924.00	63.31	38.75	7.46	25.45	57.47	74.00	-16.53	PK
H	4924.00	47.24	38.75	7.46	25.45	41.40	54.00	-12.60	AV
H	7386.00	53.39	38.65	7.22	24.78	46.74	74.00	-27.26	PK
H	7386.00	46.67	38.65	7.22	24.78	40.02	54.00	-13.98	AV
H	15450.00	48.95	36.42	6.32	26.65	45.50	74.00	-28.50	PK



**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g									
Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
<b>Low Channel 2412MHz</b>									
V	4824.00	65.83	39.55	7.85	25.66	59.79	74.00	-14.21	PK
V	4824.00	49.28	39.55	7.85	25.66	43.24	54.00	-10.76	AV
V	7236.00	60.05	38.33	7.52	24.55	53.79	74.00	-20.21	PK
V	7236.00	47.38	38.33	7.52	24.55	41.12	54.00	-12.88	AV
V	15450.00	48.71	35.23	6.75	26.59	46.82	74.00	-27.18	PK
H	4824.00	64.75	39.55	7.85	25.66	58.71	74.00	-15.29	PK
H	4824.00	50.16	39.55	7.85	25.66	44.12	54.00	-9.88	AV
H	7236.00	50.25	38.33	7.52	23.55	42.99	74.00	-31.01	PK
H	7236.00	49.68	38.33	7.52	23.22	42.09	54.00	-11.91	AV
H	15450.00	49.54	35.45	6.75	27.88	48.72	74.00	-25.28	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
<b>Mid Channel 2437MHz</b>									
V	4874.00	67.94	38.89	7.57	25.45	62.07	74.00	-11.93	PK
V	4874.00	49.38	38.89	7.57	25.45	43.51	54.00	-10.49	AV
V	7311.00	57.07	38.78	7.35	24.78	50.42	74.00	-23.58	PK
V	7311.00	49.79	38.78	7.35	24.78	43.14	54.00	-10.86	AV
V	15450.00	51.06	35.89	6.42	26.47	48.06	74.00	-25.94	PK
H	4874.00	64.99	38.89	7.57	25.45	59.12	74.00	-14.88	PK
H	4874.00	50.58	38.89	7.57	25.45	44.71	54.00	-9.29	AV
H	7311.00	51.72	38.78	7.35	24.78	45.07	74.00	-28.93	PK
H	7311.00	50.31	38.78	7.35	24.78	43.66	54.00	-10.34	AV
H	15450.00	51.25	36.68	6.45	26.65	47.67	74.00	-26.33	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
<b>High Channel 2462MHz</b>									
V	4924.00	64.42	38.75	7.46	25.45	58.58	74.00	-15.42	PK
V	4924.00	50.80	38.75	7.46	25.45	44.96	54.00	-9.04	AV
V	7386.00	54.59	38.65	7.22	24.78	47.94	74.00	-26.06	PK
V	7386.00	48.79	38.65	7.22	24.78	42.14	54.00	-11.86	AV
V	15450.00	50.03	35.58	6.35	26.47	47.27	74.00	-26.73	PK
H	4924.00	62.21	38.75	7.46	25.45	56.37	74.00	-17.63	PK
H	4924.00	47.76	38.75	7.46	25.45	41.92	54.00	-12.08	AV
H	7386.00	51.69	38.65	7.22	24.78	45.04	74.00	-28.96	PK
H	7386.00	47.38	38.65	7.22	24.78	40.73	54.00	-13.27	AV
H	15450.00	48.65	36.42	6.32	26.65	45.20	74.00	-28.80	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.





**802.11n(20MHz)**

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>Low Channel 2412MHz</b>									
V	4824.00	64.25	39.55	7.85	25.66	58.21	74.00	-15.79	PK
V	4824.00	47.70	39.55	7.85	25.66	41.66	54.00	-12.34	AV
V	7236.00	52.64	38.33	7.52	24.55	46.38	74.00	-27.62	PK
V	7236.00	49.32	38.33	7.52	24.55	43.06	54.00	-10.94	AV
V	15450.00	48.40	35.23	6.75	26.59	46.51	74.00	-27.49	PK
H	4824.00	61.88	39.55	7.85	25.66	55.84	74.00	-18.16	PK
H	4824.00	46.98	39.55	7.85	25.66	40.94	54.00	-13.06	AV
H	7236.00	52.60	38.33	7.52	23.55	45.34	74.00	-28.66	PK
H	7236.00	49.52	38.33	7.52	23.22	41.93	54.00	-12.07	AV
H	15450.00	48.53	35.45	6.75	27.88	47.71	74.00	-26.29	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>Mid Channel 2437MHz</b>									
V	4874.00	66.14	38.89	7.57	25.45	60.27	74.00	-13.73	PK
V	4874.00	54.87	38.89	7.57	25.45	49.00	54.00	-5.00	AV
V	7311.00	55.65	38.78	7.35	24.78	49.00	74.00	-25.00	PK
V	7311.00	49.24	38.78	7.35	24.78	42.59	54.00	-11.41	AV
V	15450.00	50.30	35.89	6.42	26.47	47.30	74.00	-26.70	PK
H	4874.00	64.29	38.89	7.57	25.45	58.42	74.00	-15.58	PK
H	4874.00	49.75	38.89	7.57	25.45	43.88	54.00	-10.12	AV
H	7311.00	53.35	38.78	7.35	24.78	46.70	74.00	-27.30	PK
H	7311.00	50.88	38.78	7.35	24.78	44.23	54.00	-9.77	AV
H	15450.00	51.59	36.68	6.45	26.65	48.01	74.00	-25.99	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>High Channel 2462MHz</b>									
V	4924.00	67.52	38.75	7.46	25.45	61.68	74.00	-12.32	PK
V	4924.00	51.92	38.75	7.46	25.45	46.08	54.00	-7.92	AV
V	7386.00	57.44	38.65	7.22	24.78	50.79	74.00	-23.21	PK
V	7386.00	50.64	38.65	7.22	24.78	43.99	54.00	-10.01	AV
V	15450.00	53.83	35.58	6.35	26.47	51.07	74.00	-22.93	PK
H	4924.00	62.54	38.75	7.46	25.45	56.70	74.00	-17.30	PK
H	4924.00	49.72	38.75	7.46	25.45	43.88	54.00	-10.12	AV
H	7386.00	52.49	38.65	7.22	24.78	45.84	74.00	-28.16	PK
H	7386.00	50.25	38.65	7.22	24.78	43.60	54.00	-10.40	AV
H	15450.00	51.48	36.42	6.32	26.65	48.03	74.00	-25.97	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



**802.11n(40MHz)**

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>Low Channel:2422</b>									
V	4844.000	68.65	39.55	7.77	25.66	62.53	74.00	-11.47	PK
V	4844.000	48.37	39.55	7.77	25.66	42.25	54.00	-11.75	AV
V	7266.000	67.68	38.33	7.30	24.55	61.20	74.00	-12.80	PK
V	7266.000	48.53	38.33	7.30	24.55	42.05	54.00	-11.95	AV
V	15450.00	49.25	35.23	6.60	26.59	47.21	74.00	-26.79	PK
H	4844.000	69.83	39.55	7.77	25.66	63.71	74.00	-10.29	PK
H	4844.000	48.94	39.55	7.77	25.66	42.82	54.00	-11.18	AV
H	7266.000	68.78	38.33	7.30	23.55	61.30	74.00	-12.70	PK
H	7266.000	51.42	38.33	7.30	23.22	43.61	54.00	-10.39	AV
H	15450.00	48.08	35.45	6.60	27.88	47.11	74.00	-26.89	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>Middle Channel:2437</b>									
V	4874.00	67.83	38.89	7.57	25.45	61.96	74.00	-12.04	PK
V	4874.00	50.06	38.89	7.57	25.45	44.19	54.00	-9.81	AV
V	7311.00	68.15	38.78	7.35	24.78	61.50	74.00	-12.50	PK
V	7311.00	48.27	38.78	7.35	24.78	41.62	54.00	-12.38	AV
V	15450.00	51.67	35.89	6.42	26.47	48.67	74.00	-25.33	PK
H	4874.00	66.28	38.89	7.57	25.45	60.41	74.00	-13.59	PK
H	4874.00	48.84	38.89	7.57	25.45	42.97	54.00	-11.03	AV
H	7311.00	69.91	38.78	7.35	24.78	63.26	74.00	-10.74	PK
H	7311.00	48.35	38.78	7.35	24.78	41.70	54.00	-12.30	AV
H	15450.00	50.13	36.68	6.42	26.65	46.52	74.00	-27.48	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>High Channel:2452</b>									
V	4904.00	68.71	38.75	7.38	25.45	62.79	74.00	-11.21	PK
V	4904.00	48.95	38.75	7.38	25.45	43.03	54.00	-10.97	AV
V	7356.00	67.46	38.65	7.15	24.78	60.74	74.00	-13.26	PK
V	7356.00	47.56	38.65	7.15	24.78	40.84	54.00	-13.16	AV
V	15450.00	50.13	35.58	6.25	26.47	47.27	74.00	-26.73	PK
H	4904.00	65.43	38.75	7.38	25.45	59.51	74.00	-14.49	PK
H	4904.00	50.25	38.75	7.38	25.45	44.33	54.00	-9.67	AV
H	7356.00	69.64	38.65	7.15	24.78	62.92	74.00	-11.08	PK
H	7356.00	47.12	38.65	7.15	24.78	40.40	54.00	-13.60	AV
H	15450.00	47.31	36.42	6.25	26.65	43.79	74.00	-30.21	PK

**Remark:**


1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




### 3.3 CONDUCTED EMISSION MEASUREMENT

Operation Mode: 802.11B mode(CH1, CH6, CH11)

**CH 1 (B mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 1 (B mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**






**CH 1 (B mode) - Frequency Band 3 (3000 MHz <math> < f \leq 25000 \text{ MHz}</math>)**




**CH 6 (B mode) - Frequency Band 1 (30 MHz <math> \leq f \leq 1000 \text{ MHz}</math>)**






**CH 6 (B mode) - Frequency Band 2 (1000 MHz < f ≦ 3000 MHz)**




**CH 6 (B mode) - Frequency Band 3 (3000 MHz < f ≦ 25000 MHz)**






**CH 11 (B mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 11 (B mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**






**CH 11 (B mode) - Frequency Band 3 (3000 MHz <math>f \leq 25000 \text{ MHz}</math>)**






Operation Mode: 802.11 G mode(CH1, CH6, CH11)

**CH 1 (G mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 1 (G mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**








**CH 1 (G mode) - Frequency Band 3 (3000 MHz <math>< f \leq 25000 \text{ MHz}</math>)**




**CH 6 (G mode) - Frequency Band 1 (30 MHz <math>\leq f \leq 1000 \text{ MHz}</math>)**






**CH 6 (G mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)**




**CH 6 (G mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)**






**CH 11 (G mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 11 (G mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**






### CH 11 (G mode) - Frequency Band 3 (3000 MHz <math>f \leq 25000 \text{ MHz}</math>)






Operation Mode: 802.11 n20 mode(CH1, CH6, CH11)

**CH 1 (n20 mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 1 (n20 mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**






**CH 1 (n20 mode) - Frequency Band 3 (3000 MHz <math> < f \leq 25000 \text{ MHz}</math>)**




**CH 6 (n20 mode) - Frequency Band 1 (30 MHz <math> \leq f \leq 1000 \text{ MHz}</math>)**






**CH 6 (n20 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)**




**CH 6 (n20 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)**






**CH 11 (n20 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)**




**CH 11 (n20 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)**








CH 11 (n20 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)






Operation Mode: 802.11 n40 mode(CH3, CH6, CH9)

**CH 3 (n40 mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 3 (n40 mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**






**CH 3 (n40 mode) - Frequency Band 3 (3000 MHz <math>< f \leq 25000 \text{ MHz}</math>)**




**CH 6 (n40 mode) - Frequency Band 1 (30 MHz <math>\leq f \leq 1000 \text{ MHz}</math>)**






**CH 6 (n40 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)**




**CH 6 (n40 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)**






**CH 9 (n40 mode) - Frequency Band 1 (30 MHz  $\leq$  f  $\leq$  1000 MHz)**




**CH 9 (n40 mode) - Frequency Band 2 (1000 MHz < f  $\leq$  3000 MHz)**





**CH 9 (n40 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)**





### 3.3 RADIATED BAND EMISSION MEASUREMENT

#### 3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

#### 3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.3.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



### 3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.






**802.11b**

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBUV/m)	Limits (dBUV/m)		Result
						PK	PK	AV	
<b>Low Channel 2412MHz</b>									
H	2390.00	54.43	38.06	7.42	20.15	43.94	74.00	54.00	PASS
H	2400.00	58.57	38.06	7.42	20.15	48.08	74.00	54.00	PASS
V	2390.00	53.75	38.06	7.42	20.15	43.26	74.00	54.00	PASS
V	2400.00	57.35	38.06	7.42	20.15	46.86	74.00	54.00	PASS


**Remark:**

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**Horizontal**




**Vertical**






Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>High Channel 2462MHz</b>									
H	2483.50	55.12	38.17	7.42	20.51	44.88	74.00	54.00	PASS
H	2500.00	59.54	38.17	7.42	20.51	49.30	74.00	54.00	PASS
V	2485.50	53.93	38.2	7.45	20.54	43.72	74.00	54.00	PASS
V	2500.00	57.76	38.2	7.45	20.54	47.55	74.00	54.00	PASS

**Horizontal**



**Vertical**






802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>Low Channel 2412MHz</b>									
H	2390.00	58.77	38.06	7.42	20.15	48.28	74.00	54.00	PASS
H	2400.00	61.54	38.06	7.42	20.15	51.05	74.00	54.00	PASS
V	2390.00	59.23	38.06	7.42	20.15	48.74	74.00	54.00	PASS
V	2400.00	59.86	38.06	7.42	20.15	49.37	74.00	54.00	PASS


Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Horizontal




Vertical






Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>High Channel 2462MHz</b>									
H	2483.50	55.92	38.17	7.42	20.51	45.68	74.00	54.00	PASS
H	2500.00	57.79	38.17	7.42	20.51	47.55	74.00	54.00	PASS
V	2485.50	55.13	38.2	7.45	20.54	44.92	74.00	54.00	PASS
V	2500.00	55.76	38.2	7.45	20.54	45.55	74.00	54.00	PASS

**Horizontal**



**Vertical**






802.11n(20MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>Low Channel 2412MHz</b>									
H	2390.00	55.44	38.06	7.42	20.15	44.95	74.00	54.00	PASS
H	2400.00	58.26	38.06	7.42	20.15	47.77	74.00	54.00	PASS
V	2390.00	55.81	38.06	7.42	20.15	45.32	74.00	54.00	PASS
V	2400.00	58.72	38.06	7.42	20.15	48.23	74.00	54.00	PASS


Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Horizontal



Vertical






Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>High Channel 2462MHz</b>									
H	2483.50	59.36	38.17	7.42	20.51	49.12	74.00	54.00	PASS
H	2500.00	58.28	38.17	7.42	20.51	48.04	74.00	54.00	PASS
V	2485.50	56.17	38.2	7.45	20.54	45.96	74.00	54.00	PASS
V	2500.00	57.49	38.2	7.45	20.54	47.28	74.00	54.00	PASS


**Remark:**

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**Horizontal**



**Vertical**






802.11n(40MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>operation frequency:2422</b>									
H	2390.00	56.85	38.06	7.42	20.15	46.36	74.00	54.00	PASS
H	2400.00	59.48	38.06	7.42	20.15	48.99	74.00	54.00	PASS
V	2390.00	56.33	38.06	7.42	20.15	45.84	74.00	54.00	PASS
V	2400.00	58.95	38.06	7.42	20.15	48.46	74.00	54.00	PASS


Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Horizontal




Vertical






Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
						PK	PK	AV	
<b>High Channel 2452MHz</b>									
H	2483.50	57.78	38.17	7.42	20.51	47.54	74.00	54.00	PASS
H	2500.00	58.43	38.17	7.42	20.51	48.19	74.00	54.00	PASS
V	2485.50	56.57	38.2	7.45	20.54	46.36	74.00	54.00	PASS
V	2500.00	57.45	38.2	7.45	20.54	47.24	74.00	54.00	PASS

**Horizontal**



**Vertical**







## 4. POWER SPECTRAL DENSITY TEST

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


#### 4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### 4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.





### 4.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC3.7V
Test Mode :	TX b Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-0.918	8	PASS
2437 MHz	-2.36	8	PASS
2462 MHz	-1.7	8	PASS










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC3.7V
Test Mode :	TX g Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-6.15	8	PASS
2437 MHz	-6.498	8	PASS
2462 MHz	-4.659	8	PASS










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC3.7V
Test Mode :	TX n Mode(20M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-5.583	8	PASS
2437 MHz	-5.817	8	PASS
2462 MHz	-6.598	8	PASS










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC3.7V
Test Mode :	TX n Mode(40M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2422 MHz	-8.77	8	PASS
2437 MHz	-8.456	8	PASS
2452 MHz	-7.324	8	PASS









## 5. BANDWIDTH TEST

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


#### 5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V
Test Mode :	TX b Mode		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	7.545	500	Pass
Middle	2437	7.122	500	Pass
High	2462	6.604	500	Pass









Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V
Test Mode :	TX g Mode		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.534	500	Pass
Middle	2437	16.527	500	Pass
High	2462	16.559	500	Pass






### TX CH 06




### TX CH 11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V
Test Mode :	TX n Mode(20M)		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.758	500	Pass
Middle	2437	17.755	500	Pass
High	2462	17.751	500	Pass











Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V
Test Mode :	TX n Mode(40M)		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	35.391	500	Pass
Middle	2437	36.009	500	Pass
High	2452	35.879	500	Pass







## 6. PEAK OUTPUT POWER TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**6.1.5 TEST RESULTS**

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V

	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
802.11b	2412	8.65	30
	2437	8.37	30
	2462	8.43	30
802.11g	2412	7.66	30
	2437	7.25	30
	2462	7.84	30
802.11n20	2412	6.53	30
	2437	6.17	30
	2462	6.65	30
802.11n40	2422	5.76	30
	2437	5.49	30
	2452	5.71	30



## 7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### 7.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.2 TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP






## **7.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


## **7.1 TEST RESULTS**



802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side








802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side






802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side





## **8. ANTENNA REQUIREMENT**

### **8.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **8.2 EUT ANTENNA**


The EUT antenna is Integrated antenna antenna. It complies with the standard requirement.

## 9. EUT TEST PHOTO

### Radiated Measurement Photos



### Radiated Measurement Photos



### Conducted Measurement Photos



## 10. EUT PHOTO



\*\*\*\*\* END OF REPORT \*\*\*\*\*