

## RF Exposure Evaluation Report

**Report Reference No.**.....: **MTEB23050163-H**

**FCC ID**.....: **2ALZG-22**

Compiled by  
( position+printed name+signature)..: File administrators Alisa Luo



Supervised by  
( position+printed name+signature)..: Test Engineer Sunny Deng



Approved by  
( position+printed name+signature)..: Manager Yvette Zhou



Date of issue.....: **May 15,2023**

**Representative Laboratory Name** ..: **Shenzhen Most Technology Service Co., Ltd.**

Address .....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**.....: **Qingdao Magene Intelligence Technology Co., Ltd.**

Address .....: Room 302, Building 3, No.328A Chengkang Road, Xiazhuang  
Subdistrict, Chengyang District, Qingdao, Shandong, China.

**Test specification/ Standard** .....: **47 CFR Part 1.1307;47 CFR Part 1.1310**  
**KDB447498D01 General RF Exposure Guidance v06**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description** .....: SMART TRAINER

Trade Mark .....: Magene

Manufacturer .....: Qingdao Magene Intelligence Technology Co., Ltd.

Model/Type reference.....: P0102005

Listed Models .....: N/A

Modulation Type .....: GFSK

Operation Frequency.....: GFSK: From 2402 - 2480MHz

DC12V by Adapter

Rating .....: (Input: 100-240V~50/60Hz 2.0A

Output: 12V=4.0A)

Hardware version .....: 1.0

Software version .....: 1.0

Result.....: **PASS**

**TEST REPORT**

Equipment under Test : SMART TRAINER

Model /Type : P0102005

Listed Models : N/A

Remark : N/A

Applicant : Qingdao Magene Intelligence Technology Co., Ltd.

Address : Room 302, Building 3, No.328A Chengkang Road, Xiazhuang Subdistrict, Chengyang District, Qingdao, Shandong, China.

Manufacturer : Qingdao Magene Intelligence Technology Co., Ltd.

Address : Room 302, Building 3, No.328A Chengkang Road, Xiazhuang Subdistrict, Chengyang District, Qingdao, Shandong, China.

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2023.05.15	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

**2.1.3 EUT RF Exposure**

Antenna Gain: 1.55dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.4 in linear scale. Output Power Into Antenna &amp; RF Exposure Evaluation Distance:

BLE

Antenna Gain: 1.55dBi

GFSK				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.623	$0.623 \pm 1$	1.623	1.45
Middle(2440MHz)	-4.069	$-4.069 \pm 1$	-3.069	0.49
Highest(2480MHz)	-1.609	$-1.609 \pm 1$	-0.609	0.86

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Lowest (2402MHz)	1.623	1.45	1.55	0.0004	1.0	Pass

Note: 1) Refer to report **MTEB23050163-R1** for EUT test Max Conducted average Output Power value.Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.45 * 1.43) / (4 * 3.1416 * 20^2) = 0.0004$ 

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

ANT+

Antenna Gain: 1.55dBi

GFSK				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
CH1(2457MHz)	-0.154	-0.154 ± 1	0.846	1.22

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2440MHz)	0.846	1.22	1.55	0.0003	1.0	Pass

Note: 1) Refer to report **MTEB23050163-R2** for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.22 * 1.43) / (4 * 3.1416 * 20^2) = 0.0003$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

.....THE END OF REPORT.....