



RF Exposure Evaluation Report

Report Reference No..... : MTEB24060021-H

FCC ID..... : 2ALZG-A308

Compiled by

(position+printed name+signature)..: File administrators Alisa Luo

Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng

Approved by

(position+printed name+signature)..: Manager Yvette Zhou

Date of issue.....: **June.04,2024**

Representative Laboratory Name. : Shenzhen Most Technology Service Co., Ltd.

Address.....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name.....: Qingdao Magene Intelligence Technology Co., Ltd.

Address.....: Room 302, Building 3, No.328A Chengkang Road, Xiazhuang
Subdistrict, Chengyang District, Qingdao, Shandong, China.

**Test specification/ Standard.....: 47 CFR Part 1.1307;47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Display

Trade Mark.....: Magene

Manufacturer.....: Qingdao Magene Intelligence Technology Co., Ltd.

Model/Type reference.....: P0203288A

Listed Models: N/A

Modulation Type.....: GFSK

Operation Frequency.....: GFSK: From 2402 - 2480MHz

Rating.....: DC 36V,25mA or DC 48V,20mA

Hardware version.....: 1.0

Software version: 1.0

Result.....: **PASS**

TEST REPORT

Equipment under Test : Display

Model /Type : P0203288A

Listed Models : N/A

Remark : N/A

Applicant : Qingdao Magene Intelligence Technology Co., Ltd.

Address : Room 302, Building 3, No.328A Chengkang Road, Xiazhuang Subdistrict, Chengyang District, Qingdao, Shandong, China.

Manufacturer : Qingdao Magene Intelligence Technology Co., Ltd.

Address : Room 302, Building 3, No.328A Chengkang Road, Xiazhuang Subdistrict, Chengyang District, Qingdao, Shandong, China.

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.06.04	Initial Issue	Alisa Luo

2. SAR Evaluation

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

2.1.3 EUT RF Exposure

BLE

Antenna Gain: 1.69dBi

GFSK				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.450	1.450 ± 1	2.450	1.76
Middle(2440MHz)	0.164	0.164 ± 1	1.164	1.31
Highest(2480MHz)	1.186	1.186 ± 1	2.186	1.65

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold	SAR Test Exclusion
		(dBm)	(mW)			
Lowest(2402MHz)	1.450	2.450	1.76	0.55	3.0	Yes

Note: 1) Refer to report **MTEB24060021-R** for EUT test Max Conducted Peak Output Power value.

.....**THE END OF REPORT**.....