



REPORT No. : SZ19100260S01

Annex D Plots of RF Test Results

HAC RF_GSM850_GSM Voice_Ch128_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch128/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 59.90 V/m; Power Drift = -0.07 dB

Applied MIF = 3.63 dB

RF audio interference level = 37.20 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 35.98 dBV/m	Grid 2 M4 37.11 dBV/m	Grid 3 M4 37.07 dBV/m
Grid 4 M4 35.99 dBV/m	Grid 5 M4 37.2 dBV/m	Grid 6 M4 37.18 dBV/m
Grid 7 M4 35.36 dBV/m	Grid 8 M4 36.78 dBV/m	Grid 9 M4 36.77 dBV/m

Cursor:

Total = 37.20 dBV/m

E Category: M4

Location: -6.5, -4, 8.7 mm



0 dB = 72.41 V/m = 37.20 dBV/m

HAC RF_GSM850_GSM Voice_Ch189_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 836.4 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch189/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 55.17 V/m; Power Drift = 0.08 dB

Applied MIF = 3.63 dB

RF audio interference level = 36.67 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 35.36 dBV/m	Grid 2 M4 36.55 dBV/m	Grid 3 M4 36.52 dBV/m
Grid 4 M4 35.39 dBV/m	Grid 5 M4 36.67 dBV/m	Grid 6 M4 36.65 dBV/m
Grid 7 M4 34.86 dBV/m	Grid 8 M4 36.31 dBV/m	Grid 9 M4 36.3 dBV/m

Cursor:

Total = 36.67 dBV/m

E Category: M4

Location: -7, -3.5, 8.7 mm



0 dB = 68.13 V/m = 36.67 dBV/m

HAC RF_GSM850_GSM Voice_Ch251_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 848.6 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch251/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 54.83 V/m; Power Drift = 0.01 dB

Applied MIF = 3.63 dB

RF audio interference level = 36.43 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 35.18 dBV/m	Grid 2 M4 36.33 dBV/m	Grid 3 M4 36.28 dBV/m
Grid 4 M4 35.23 dBV/m	Grid 5 M4 36.43 dBV/m	Grid 6 M4 36.4 dBV/m
Grid 7 M4 34.69 dBV/m	Grid 8 M4 36.09 dBV/m	Grid 9 M4 36.05 dBV/m

Cursor:

Total = 36.43 dBV/m

E Category: M4

Location: -6.5, -2, 8.7 mm



0 dB = 66.28 V/m = 36.43 dBV/m

HAC RF_GSM1900_GSM Voice_Ch512_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch512/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 7.647 V/m; Power Drift = -0.06 dB

Applied MIF = 3.63 dB

RF audio interference level = 24.51 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 27.32 dBV/m	Grid 2 M4 27.33 dBV/m	Grid 3 M4 26.23 dBV/m
Grid 4 M4 23.17 dBV/m	Grid 5 M4 24.13 dBV/m	Grid 6 M4 24.09 dBV/m
Grid 7 M4 24.51 dBV/m	Grid 8 M4 24.03 dBV/m	Grid 9 M4 22.28 dBV/m

Cursor:

Total = 27.33 dBV/m

E Category: M4

Location: 7, -25, 8.7 mm



0 dB = 23.26 V/m = 27.33 dBV/m

HAC RF_GSM1900_GSM Voice_Ch661_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch661/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 8.215 V/m; Power Drift = -0.07 dB

Applied MIF = 3.63 dB

RF audio interference level = 25.88 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.23 dBV/m	Grid 2 M4 28.28 dBV/m	Grid 3 M4 27.46 dBV/m
Grid 4 M4 24.1 dBV/m	Grid 5 M4 25.48 dBV/m	Grid 6 M4 25.5 dBV/m
Grid 7 M4 25.88 dBV/m	Grid 8 M4 25.81 dBV/m	Grid 9 M4 24.65 dBV/m

Cursor:

Total = 28.28 dBV/m

E Category: M4

Location: 5.5, -25, 8.7 mm



0 dB = 25.93 V/m = 28.28 dBV/m

HAC RF_GSM1900_GSM Voice_Ch810_E

Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch810/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 6.307 V/m; Power Drift = -0.17 dB

Applied MIF = 3.63 dB

RF audio interference level = 25.53 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 26.97 dBV/m	Grid 2 M4 27.03 dBV/m	Grid 3 M4 26.02 dBV/m
Grid 4 M4 22.36 dBV/m	Grid 5 M4 23.41 dBV/m	Grid 6 M4 23.44 dBV/m
Grid 7 M4 25.53 dBV/m	Grid 8 M4 25.48 dBV/m	Grid 9 M4 23.89 dBV/m

Cursor:

Total = 27.03 dBV/m

E Category: M4

Location: 6, -25, 8.7 mm



0 dB = 22.46 V/m = 27.03 dBV/m

HAC RF_CDMA2000 BC0_RC1 SO3_Ch1013_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 815.04 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1013/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.91 V/m; Power Drift = -0.03 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.00 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.61 dBV/m	Grid 2 M4 27.84 dBV/m	Grid 3 M4 26.2 dBV/m
Grid 4 M4 28.7 dBV/m	Grid 5 M4 28 dBV/m	Grid 6 M4 26.43 dBV/m
Grid 7 M4 28.52 dBV/m	Grid 8 M4 27.74 dBV/m	Grid 9 M4 26.09 dBV/m

Cursor:

Total = 28.70 dBV/m

E Category: M4

Location: 25, -1, 8.7 mm



0 dB = 27.24 V/m = 28.70 dBV/m

HAC RF_CDMA2000 BC0_RC1 SO3_Ch384_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch384/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.80 V/m; Power Drift = -0.05 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.37 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.9 dBV/m	Grid 2 M4 28.26 dBV/m	Grid 3 M4 26.62 dBV/m
Grid 4 M4 28.99 dBV/m	Grid 5 M4 28.37 dBV/m	Grid 6 M4 26.78 dBV/m
Grid 7 M4 28.85 dBV/m	Grid 8 M4 28.11 dBV/m	Grid 9 M4 26.51 dBV/m

Cursor:

Total = 28.99 dBV/m

E Category: M4

Location: 25, -4, 8.7 mm



0 dB = 28.16 V/m = 28.99 dBV/m

HAC RF_CDMA2000 BC0_RC1 SO3_Ch777_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 848.97 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch777/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.38 V/m; Power Drift = 0.07 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.24 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.9 dBV/m	Grid 2 M4 27.97 dBV/m	Grid 3 M4 26.4 dBV/m
Grid 4 M4 29.12 dBV/m	Grid 5 M4 28.24 dBV/m	Grid 6 M4 26.58 dBV/m
Grid 7 M4 28.68 dBV/m	Grid 8 M4 27.96 dBV/m	Grid 9 M4 26.3 dBV/m

Cursor:

Total = 29.12 dBV/m

E Category: M4

Location: 25, -0.5, 8.7 mm



0 dB = 28.59 V/m = 29.12 dBV/m

HAC RF_CDMA2000 BC1_RC1 SO3_Ch25_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch25/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.58 V/m; Power Drift = -0.09 dB

Applied MIF = 3.26 dB

RF audio interference level = 27.82 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.4 dBV/m	Grid 2 M4 27.63 dBV/m	Grid 3 M4 25.96 dBV/m
Grid 4 M4 28.56 dBV/m	Grid 5 M4 27.82 dBV/m	Grid 6 M4 26.16 dBV/m
Grid 7 M4 28.35 dBV/m	Grid 8 M4 27.54 dBV/m	Grid 9 M4 25.92 dBV/m

Cursor:

Total = 28.56 dBV/m

E Category: M4

Location: 25, -3.5, 8.7 mm



0 dB = 26.79 V/m = 28.56 dBV/m

HAC RF_CDMA2000 BC1_RC1 SO3_Ch600_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch600/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.43 V/m; Power Drift = -0.15 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.15 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.67 dBV/m	Grid 2 M4 27.95 dBV/m	Grid 3 M4 26.28 dBV/m
Grid 4 M4 28.8 dBV/m	Grid 5 M4 28.15 dBV/m	Grid 6 M4 26.53 dBV/m
Grid 7 M4 28.6 dBV/m	Grid 8 M4 27.87 dBV/m	Grid 9 M4 26.22 dBV/m

Cursor:

Total = 28.80 dBV/m

E Category: M4

Location: 25, -4, 8.7 mm



0 dB = 27.54 V/m = 28.80 dBV/m

HAC RF_CDMA2000 BC1_RC1 SO3_Ch1175_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 1909.95 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1175/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.75 V/m; Power Drift = -0.13 dB

Applied MIF = 3.26 dB

RF audio interference level = 27.92 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.53 dBV/m	Grid 2 M4 27.72 dBV/m	Grid 3 M4 26.17 dBV/m
Grid 4 M4 28.64 dBV/m	Grid 5 M4 27.92 dBV/m	Grid 6 M4 26.36 dBV/m
Grid 7 M4 28.34 dBV/m	Grid 8 M4 27.59 dBV/m	Grid 9 M4 26.06 dBV/m

Cursor:

Total = 28.64 dBV/m

E Category: M4

Location: 25, -1, 8.7 mm



0 dB = 27.03 V/m = 28.64 dBV/m

HAC RF_CDMA2000 BC10_RC1 SO3_Ch476_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 817.9 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch476/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.61 V/m; Power Drift = 0.12 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.08 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.46 dBV/m	Grid 2 M4 27.88 dBV/m	Grid 3 M4 26.38 dBV/m
Grid 4 M4 28.58 dBV/m	Grid 5 M4 28.08 dBV/m	Grid 6 M4 26.61 dBV/m
Grid 7 M4 28.41 dBV/m	Grid 8 M4 27.79 dBV/m	Grid 9 M4 26.29 dBV/m

Cursor:

Total = 28.58 dBV/m

E Category: M4

Location: 25, 0, 8.7 mm



0 dB = 26.84 V/m = 28.58 dBV/m

HAC RF_CDMA2000 BC10_RC1 SO3_Ch580_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 820.5 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch580/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.93 V/m; Power Drift = -0.15 dB

Applied MIF = 3.26 dB

RF audio interference level = 27.96 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.51 dBV/m	Grid 2 M4 27.77 dBV/m	Grid 3 M4 26.01 dBV/m
Grid 4 M4 28.61 dBV/m	Grid 5 M4 27.96 dBV/m	Grid 6 M4 26.3 dBV/m
Grid 7 M4 28.42 dBV/m	Grid 8 M4 27.61 dBV/m	Grid 9 M4 25.85 dBV/m

Cursor:

Total = 28.61 dBV/m

E Category: M4

Location: 25, -1, 8.7 mm



0 dB = 26.96 V/m = 28.61 dBV/m

HAC RF_CDMA2000 BC10_RC1 SO3_Ch684_E

Communication System: UID 10295 - AAB, CDMA2000, RC1, SO3, 1/8th Rate 25 fr.; Frequency: 823.98 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch684/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.73 V/m; Power Drift = -0.12 dB

Applied MIF = 3.26 dB

RF audio interference level = 27.89 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 28.44 dBV/m	Grid 2 M4 27.73 dBV/m	Grid 3 M4 25.72 dBV/m
Grid 4 M4 28.55 dBV/m	Grid 5 M4 27.89 dBV/m	Grid 6 M4 25.92 dBV/m
Grid 7 M4 28.39 dBV/m	Grid 8 M4 27.64 dBV/m	Grid 9 M4 25.95 dBV/m

Cursor:

Total = 28.55 dBV/m

E Category: M4

Location: 24, -3, 8.7 mm



0 dB = 26.77 V/m = 28.55 dBV/m

HAC RF_LTE Band 41_20M_QPSK_1RB_0offset_12.2Kbps_Ch39750_E

Communication System: UID 10172 - CAB, LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK);
 Frequency: 2506 MHz; Duty Cycle: 1:1.59

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch39750/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 4.197 V/m; Power Drift = 0.11 dB

Applied MIF = -1.62 dB

RF audio interference level = 14.14 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 15.11 dBV/m	Grid 2 M4 12.9 dBV/m	Grid 3 M4 14.14 dBV/m
Grid 4 M4 13.77 dBV/m	Grid 5 M4 12.91 dBV/m	Grid 6 M4 14.13 dBV/m
Grid 7 M4 14.11 dBV/m	Grid 8 M4 12.51 dBV/m	Grid 9 M4 13.75 dBV/m

Cursor:

Total = 15.11 dBV/m

E Category: M4

Location: 25, -25, 8.7 mm



0 dB = 5.695 V/m = 15.11 dBV/m

HAC RF_LTE Band 41_20M_QPSK_1RB_0offset_12.2Kbps_Ch40185_E

Communication System: UID 10172 - CAB, LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK);
 Frequency: 2549.5 MHz; Duty Cycle: 1:1.59

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch40185/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 4.177 V/m; Power Drift = 0.08 dB

Applied MIF = -1.62 dB

RF audio interference level = 13.51 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 11.92 dBV/m	Grid 2 M4 13.14 dBV/m	Grid 3 M4 13.62 dBV/m
Grid 4 M4 11.9 dBV/m	Grid 5 M4 12.62 dBV/m	Grid 6 M4 13.54 dBV/m
Grid 7 M4 13.51 dBV/m	Grid 8 M4 11.85 dBV/m	Grid 9 M4 12.2 dBV/m

Cursor:

Total = 13.62 dBV/m

E Category: M4

Location: -15.5, -10.5, 8.7 mm



0 dB = 4.799 V/m = 13.62 dBV/m

HAC RF_LTE Band 41_20M_QPSK_1RB_0offset_12.2Kbps_Ch40620_E

Communication System: UID 10172 - CAB, LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK);
 Frequency: 2593 MHz; Duty Cycle: 1:1.59

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch40620/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 4.966 V/m; Power Drift = 0.06 dB

Applied MIF = -1.64 dB

RF audio interference level = 13.72 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 10.49 dBV/m	Grid 2 M4 13.49 dBV/m	Grid 3 M4 14.01 dBV/m
Grid 4 M4 11.55 dBV/m	Grid 5 M4 13.43 dBV/m	Grid 6 M4 13.99 dBV/m
Grid 7 M4 13.72 dBV/m	Grid 8 M4 12.91 dBV/m	Grid 9 M4 13.22 dBV/m

Cursor:

Total = 14.01 dBV/m

E Category: M4

Location: -15, -10, 8.7 mm



0 dB = 5.020 V/m = 14.01 dBV/m

HAC RF_LTE Band 41_20M_QPSK_1RB_0offset_12.2Kbps_Ch41055_E

Communication System: UID 10172 - CAB, LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK);
 Frequency: 2636.5 MHz; Duty Cycle: 1:1.59

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch41055/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 5.015 V/m; Power Drift = 0.15 dB

Applied MIF = -1.62 dB

RF audio interference level = 13.50 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 10.12 dBV/m	Grid 2 M4 12.51 dBV/m	Grid 3 M4 12.94 dBV/m
Grid 4 M4 12.18 dBV/m	Grid 5 M4 12.61 dBV/m	Grid 6 M4 13.5 dBV/m
Grid 7 M4 14.27 dBV/m	Grid 8 M4 14.52 dBV/m	Grid 9 M4 14.54 dBV/m

Cursor:

Total = 14.54 dBV/m

E Category: M4

Location: -10, 25, 8.7 mm



0 dB = 5.336 V/m = 14.54 dBV/m

HAC RF_LTE Band 41_20M_QPSK_1RB_0offset_12.2Kbps_Ch41490_E

Communication System: UID 10172 - CAB, LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK);
 Frequency: 2680 MHz; Duty Cycle: 1:1.59

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2019.04.11
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch41490/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 3.410 V/m; Power Drift = -0.18 dB

Applied MIF = -1.62 dB

RF audio interference level = 10.83 dBV/m

Emission category: M4

MIF scaled E-field



Grid 1 M4 9.26 dBV/m	Grid 2 M4 10.83 dBV/m	Grid 3 M4 10.79 dBV/m
Grid 4 M4 9.01 dBV/m	Grid 5 M4 9.64 dBV/m	Grid 6 M4 11 dBV/m
Grid 7 M4 10.37 dBV/m	Grid 8 M4 11.61 dBV/m	Grid 9 M4 12.24 dBV/m

Cursor:

Total = 12.24 dBV/m

E Category: M4

Location: -16, 25, 8.7 mm



0 dB = 4.095 V/m = 12.25 dBV/m