

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 1 of 28

HAC (T-Coil) Test Report

Application No.:	XEWM2203000061RG
Applicant:	Great Talent Technology Limited
Manufacturer:	Great Talent Technology Limited
Product Name:	feature phone
Model No.(EUT):	SC3218B
Trade Mark:	SCHOK
FCC ID:	2ALZM-SC3218B
Standards:	ANSI C63.19-2011 CFR 47 FCC Part 20
Date of Receipt:	2021-11-09
Date of Test:	2021-11-25 to 2022-01-03
Date of Issue:	2022-03-16
Test conclusion:	PASS *

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Sun

Panta Sun Wireless Laboratory Manager



vertear, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions</u>, aspx and, for electronic format documents, ubject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/</u>

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone	215000	t (86-512) 62992980	www.sgsgroup.com.cn
中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编:	215000	t (86–512) 62992980	sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 2 of 28

REVISION HISTORY

Report Number	Revision	Description	Issue Date
XEWM2203000061RG08	01	Original	2022-03-16



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sas.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, outpiect to Terms and Conditions for Electronic Documents at <u>http://www.sas.com/en/Terms-and-Conditions.aspx</u> and, for electronic format document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Client and this document is a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443,



 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 3 of 28

TEST SUMMARY

Frequency Band	T-rating
GSM850	T4
GSM1900	T4
WCDMA Band II	T4
WCDMA Band IV	T4
LTE Band 2	Т3
LTE Band 4	T3
LTE Band 5	Т3
LTE Band 12	Т3
LTE Band 25	Т3
LTE Band 26	Т3
LTE Band 41	Т3
LTE Band 66	T3
LTE Band 71	T3
HAC Rate Category:	Т3

Reviewed by

INCH

Prepared by

Nature Shen

Well Wei

Nature Shen



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are sted for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@ss.com

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号约6号厂房南部 邮编: 215000



 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 4 of 28

CONTENTS

1	GEN	IERAL INFORMATION	5
	1.1	Introduction	
	1.2	Details of Client	
	1.3	Test Location	
	1.4	Test Facility	
	1.5	General Description of EUT 1 DUT Antenna Locations(Back view)	
	1.5. 1.5.		
	1.6	Test Specification	
2		IBRATION CERTIFICATE	
3	HAC	(T-COIL) MEASUREMENT SYSTEM	
	3.1	Measurement System Diagram for SPEAG Robotic	
	3.2	T-Coil Measurement Set-up	
	3.3	System Calibration	
	3.4	Audio Magnetic Probe AM1DV3	
	3.5 3.6	Test Arch	
	3.0 3.7	AMCC- Audio Magnetic Calibration Coil	
	3.8	AMMI - Audio Magnetic Measurement Instrument	
		-	
4		SUREMENT UNCERTAINTY EVALUATION	
5	HAC	; (T-COIL) MEASUREMENT	18
	5.1	T-Coil Performance Requirements	18
	5.2	T-Coil measurement points and reference plane	
	5.3	T-Coil Measurement Procedure	21
6	T-C	DIL TESTING FOR CMRS VOICE	23
	6.1	General Description	23
	6.2	GSM Tests Results	
	6.3	UMTS Tests Results	
	6.4	VoLTE Tests Results	25
7	EQL	IIPMENT LIST	28
8	CAL	IBRATION CERTIFICATE	
9	PHC	TOGRAPHS	
Α	PPEND	X A: DETAILED TEST RESULTS	
		X B: CALIBRATION CERTIFICATE	
		X C: PHOTOGRAPHS	
A	FFEND		20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed, overleaf, available on request or accessible at <u>http://www.scs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, outpiect to Terms and Conditions for Electronic Documents at <u>http://www.scs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document to except in fully, without provide a the company's com



 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 5 of 28

1 General Information

1.1 Introduction

The purpose of this standard is to establish categories for hearing aids and for WD (wireless communications devices) that can indicate to health care practitioners and hearing aid users which hearing aids are compatible with which WD, and to provide tests that can be used to assess the electromagnetic characteristics of hearing aids and WD and assign them to these categories. The various parameters required, in order to demonstrate compatibility and accessibility are measured. The design of the standard is such that when a hearing aid and WD achieve one of the categories specified, as measured by the methodology of this standard, the indicated performance is realized.

In order to provide for the usability of a hearing aid with a WD, several factors must be coordinated:

a) Radio frequency (RF) measurements of the near-field electric and magnetic fields emitted by a WD to categorize these emissions for correlation with the RF immunity of a hearing aid.

b) Magnetic field measurements of a WD emitted via the audio transducer associated with the T-coil mode of the hearing aid, for assessment of hearing aid performance.

c) Measurements with the hearing aid and a simulation of the categorized WD T-coil emissions to assess the hearing aid RF immunity in the T-coil mode.

The WD radio frequency (RF) and audio band emissions are measured.

Hence, the following are measurements made for the WD:

a) RF E-Field emissions

b) T-coil mode, magnetic signal strength in the audio band

c) T-coil mode, magnetic signal and noise articulation index

d) T-coil mode, magnetic signal frequency response through the audio band

Corresponding to the WD measurements, the hearing aid is measured for:

a) RF immunity in microphone mode

b) RF immunity in T-coil mode

1.2 Details of Client

Applicant:	Great Talent Technology Limited
Address:	35F,HBC HuiLong Center Building-II Minzhi Street,Longhua, Shenzhen, P.R. China
Manufacturer:	Great Talent Technology Limited
Address:	35F,HBC HuiLong Center Building-II Minzhi Street,Longhua, Shenzhen, P.R. China

1.3 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test Engineer:	Nature Shen, Claire Shen





 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 6 of 28

1.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC – Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Diless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing/Inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 7 of 28

1.5 General Description of EUT

S

Device Type :	portable device			
Exposure Category:	uncontrolled environment / general population			
Product Name:	feature phone			
Model No.(EUT):	SC3218B			
FCC ID:	2ALZM-SC3218B			
Trade Mark:	SCHOK			
Product Phase:	Identical Prototype			
IMEI:	358476180000283			
Hardware Version:	Q3203_V1.0			
Software Version:	SC3218T_V1.0.0			
Antenna Type:	Integrated			
Device Operating Configuration	ons :			
Modulation Mode:	LTE: QPSK,16QAM	CDMA: QPSK, 16QAM(HSPA+); T: GFSK, π/4DQPSK,8DPSK		
Device Class:	В			
GPRS Multi-slots Class:	33	EGPRS Multi-slots Class:	33	
HSDPA UE Category:	24	HSUPA UE Category	7	
DC-HSDPA UE Category:	24			
Power Class	4,tested with power level 5(GSM850) 1,tested with power level 0(GSM1900) 3, tested with power control "all 1"(WCDMA Band) 3, tested with power control Max Power(LTE Band)			
	Band	Tx (MHz)	Rx (MHz)	
	GSM850	824~849	869~894	
	GSM1900	1850~1910	1930~1990	
	WCDMA Band II	1850~1910	1930~1990	
	WCDMA Band IV	1710~1755	2110~2155	
	LTE Band 2	1850 ~1910	1930 ~1990	
	LTE Band 4	1710~1755	2110~2155	
	LTE Band 5	824~849	869-894	
Frequency Bands:	LTE Band 12	699~716	729~746	
	LTE Band 25	1850~1915	1930~1995	
	LTE Band 26	814~849	859~894	
	LTE Band 41 (Class 2/3)	2496~2690	2496~2690	
	LTE Band 66	1710~1780	2110~2200	
	LTE Band 71	663~698	617~652	
	Bluetooth	2402~2480	2402~2480	
	Wi-Fi 2.4G	2412~2462	2412~2462	
RF Cable:	Provided	by the aplicant Provided by the	ne laboratory	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed subject to Terms and Conditions for Electronic Documents at <u>http://www.sac.com/en/Terms-and-Conditions_aspx</u> and, for electronic format document is advised to Terms and Conditions for Electronic Documents at <u>http://www.sac.com/en/Terms-and-Conditions_aspx</u>. Attention is document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Client and this document tes parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & critificate, please contact us at telephone: (86-755)83071443,

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号约6号厂房南部 邮编: 215000 t (86–512) 62992980 www.sgsgroup.com.cn t (86–512) 62992980 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 8 of 28

	Model:	SB2000
Battery Information:	Normal Voltage:	3.8V
	Rated capacity:	3000mAh
	Manufacturer:	Phenix New Energy (Huizhou) Co., Ltd.

Remark:

This test report (Report No.: XEWM2203000061RG08) is based on the original test report (Report No.: SUZR/2021/8005308). Review this report and original report, this report just changing the parts according to the declaration letter from client. Therefore, in this report all test data share the same test data on the previous report with Report No. SUZR/2021/8005308.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-and-Conditions</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 9 of 28



1.5.1 DUT Antenna Locations(Back view)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection reports & certificate, please contact us at telephone: (86-755) \$307 1443,

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industria Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号的6号厂房南部 邮编: 215000



 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 10 of 28

1.5.2 List of air interfaces/frequency bands

Air Interface	Band (MHz)	Туре	ANSI C63.19 Tested	Simultaneous Transmitter	Name of Voice Service	Power Reduction
	850	VO	Yes			
GSM	1900	~0	165	BT, Wi-Fi	CMRS Voice	NA
	EDGE	VD	Yes			
	Band II	VO	Vaa			NA
WCDMA	Band IV	VO	Yes	BT, Wi-Fi	CMRS Voice	
	HSPA	VD	Yes			
	Band 2		Yes			NA
	Band 4			BT, Wi-Fi	VoLTE	
	Band 5					
LTE	Band 12	VD				
(FDD)	Band 25					
	Band 26					
	Band 66					
	Band 71					
LTE (TDD)	Band 41	VD	Yes	BT, Wi-Fi	VoLTE	NA
Wi-Fi	2450	VD	NA	WWAN	NA	NA
BT	2450	DT	NA	WWAN	NA	NA

VO: Legacy Cellular Voice Service from Table 7.1 in 7.4.2.1 of ANSI C63.19-2011

DT: Digital Transport (no voice)

VD: IP Voice Service over Digital Transport

For protocols not listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation, the average speech level of -20 dBm0 should be used.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-and-Conditions</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号约6号厂房南部 邮编: 215000

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 11 of 28

1.6 Test Specification

S

Identity	Document Title
CFR 47 FCC Part 20	§20.19 Hearing aid-compatible mobile handsets.
ANSI C63.19-2011	American National Standard for Methods of Measurement of Compatibility between Wireless Communication Devices
KDB 285076 D01	HAC Guidance v05r01
KDB 285076 D02	T-Coil testing v03r01

2 Calibration certificate

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Table 4 The Architect Occulut	

Table 1: The Ambient Conditions



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Diless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing/Inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



Report No.:	XEWM2203000061RG08
Rev.:	01
Page:	12 of 28

3 HAC (T-Coil) Measurement System

3.1 Measurement System Diagram for SPEAG Robotic




Fig. 1. The SPEAG Robotic Diagram

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- An Audio Magnetic probe.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The Test Arch SAM phantom
- The device holder for handheld mobile phones.
- Validation dipole kits allowing to validate the proper functioning of the system.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions, Terms-and-Conditions, and the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the full elses otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) tester relatined for 30 days only. Attention: To check the authenticity of testing /Inspection report & certificate, please contact us at telephone: (86-75) 8307 1443, or anal: Ch.Doccheck@ess.com

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 13 of 28

3.2 T-Coil Measurement Set-up




Fig. 2. T-coil signal measurement test setup

The sequence of the measurement is T-Coil testing procedure over a wireless communication device:

- 1. Confirm Geometry & signal check. Probe phantom alignment and check of accuracy.
- 2. Background noise measurement in the area of the WD.
- 3. Perform 50x50mm area scan with narrow band signal to determine ABM1, ABM2 and SNR for axial and radial orientation positions.
- 4. For Axial position, perform optimal SNR point measurement with a broadband signal determine Frequency Response
- 5. Define the all applicable input audio level according to ANSI C63.19-2011 and KDB 285076 D02v03.

Note.

#. The EUT do not use the special HAC SW.

#. Setting the maximum volume for EUT during the measurement.

#. For the measurement, it don't use the "post-test measurement processing of results".

#. Per KDB 285076 D01v05, handsets that that have the ability to support concurrent connections using simultaneous transmissions shall be independently tested for each air interface/band given in ANSI C63.19-2011. At the present time ANSI C63.19 does not provide simultaneous transmission test procedures.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents,
subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is
advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of
Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a
transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced
except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or
appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the
results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,
or email: CN.Doccheck@sgs.com

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 14 of 28

3.3 System Calibration

For correct and calibrated measurement of the voltages and ABM field, DASY will perform a calibration job as below.

In phase 1, the audio output is switched off, and a 200 mVpp symmetric rectangular signal of 1 kHz is generated and internally connected directly to both channels of the sampling unit (Coil in, Probe in).

In phase 2, the audio output is off, and a 20 mVpp symmetric 100 Hz signal is internally connected. The signals during phases 1 and 2 are available at the output on the rear panel of the AMMI. However, the output must not be loaded, in order to avoid influencing the calibration. An RMS voltmeter would indicate 100 mVRMS during the first phase and 10 mVRMS during the second phase. After the first two phases, the two input channels are both calibrated for absolute measurements of voltages. The resulting factors are displayed above the multi-meter window.

After phases 1 and 2, the input channels are calibrated to measure exact voltages. This is required to use the inputs for measuring voltages with their peak and RMS value.

In phase 3, a multi-sine signal covering each third-octave band from 50 Hz to 10 kHz is generated and applied to both audio outputs. The probe should be positioned in the center of the AMCC and aligned in the z-direction, the field orientation of the AMCC. The "Coil In" channel is measuring the voltage over the AMCC internal shunt, which is proportional to the magnetic field in the AMCC. At the same time, the "Probe In" channel samples the amplified

signal picked up by the probe coil and provides it to a numerical integrator. The ratio of the two voltages in each third-octave filter leads to the spectral representation over the frequency band of interest. The Coil signal is scaled in dBV, and the Probe signal is first integrated and normalized to show dB A/m. The ratio probe-to-coil at the frequency of 1 kHz is the sensitivity which will be used in the consecutive T-Coil jobs.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days ony.

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 15 of 28

3.4 Audio Magnetic Probe AM1DV3

Description	Active single sensor probe for both axial and radial measurement scans- Fully RF shielded, compatible with DAE, with adapted probe cup	8
Dynamic Range	0.1 KHz to 20 KHz	
Sensitivity	<-50dB A/m @ 1KHz	
Internal Amp	20dB	4
Dimensions	300X18mm	
		AM1DV3 Audio Probe

3.5 Test Arch

S

Description	Enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot.	-
Dimensions	length: 370 mm width: 370 mm height: 370 mm	Test Arch

3.6 Phone Holder

Supports accurate and reliable positioning of any phone Effect on near field <+/- 0.5 dB	
	Phone Holder



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions</u>, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing/Inspection reports & certificate, please contact us at telehone: (86-755) 5307 1443,


 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 16 of 28

3.7 AMCC- Audio Magnetic Calibration Coil

S



3.8 AMMI - Audio Magnetic Measurement Instrument

	_	
Description	-USB interface to PC - Probe signal digitization and power supply- Test signal generation for wireless device (via base station simulator)- Auto- calibration and interfaces to AMCC for complete setup-calibration	
Data Rate	48 KHz / 24bit	
Dynamic Range	85 dB	
Dimensions:	19" X 65 X 270mm	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-and-Conditions</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

SGS

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 17 of 28

4 Measurement uncertainty evaluation

Error Description	Uncertainty Value (%)	Probability Dist.	Divisor	ci ABM1	ci ABM2	Standard Uncertainty ABM1 (%)	Standard Uncertainty ABM2 (%)
Related to probe sensitivity							
Reference level	±3.0	R	$\sqrt{3}$	1	1	±3.0	±3.0
AMCC geometry	±0.4	R	$\sqrt{3}$	1	1	±0.2	±0.2
AMCC current	±0.6	R	$\sqrt{3}$	1	1	±0.4	±0.4
Probe positioning during calibration	±0.2	R	$\sqrt{3}$	1	1	±0.1	±0.1
Noise distribution	±0.7	R	$\sqrt{3}$	0.0143	1	±0.0	±0.4
Frequency slope	±5.9	R	$\sqrt{3}$	0.1	1	±0.3	±3.5
Related to probe system							
Repeatability / drift	±1.0	R	$\sqrt{3}$	1	1	±0.6	±0.6
Linearity / dynamic range	±0.6	Ν	1	1	1	±0.4	±0.4
Audio noise	±1.0	R	$\sqrt{3}$	0.1	1	±0.1	±0.6
Probe angle	±2.3	R	$\sqrt{3}$	1	1	±1.4	±1.4
Spectral Processing	±0.9	R	$\sqrt{3}$	1	1	±0.5	±0.5
Integration time	±0.6	N	1	1	5	±0.6	±3.0
Field distribution	±0.2	R	$\sqrt{3}$	1	1	±0.1	±0.1
Test signal							
Reference signal spectrum response	±0.6	R	$\sqrt{3}$	0	1	±0.0	±0.4
Positioning							
Probe positioning	±1.9	R	$\sqrt{3}$	1	1	±1.1	±1.1
Phantom Thickness	±0.9	R	$\sqrt{3}$	1	1	±0.5	±0.5
DUT positioning	±1.9	R	$\sqrt{3}$	1	1	±1.1	±1.1
External Contributions							
RF interference	±0.0	R	$\sqrt{3}$	1	0.3	±0.0	±0.0
Test Signal Variation	±2.0	R	$\sqrt{3}$	1	1	±1.2	±1.2
Combined Std. Uncertainty (ABM Field)		$u_c' = \sqrt{\sum_{i=1}^{20}}$	$c_i^2 u_i^2$			±4.1	±6.2
Expanded Std. Uncertainty (K=2) Table 2: Measurem						±8.2	±12.4

Table 2: Measurement uncertainties for T-Coil



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sac.com/en/Terms-and-Conditions aspx</u> and, for electronic format documents, outpiect to Terms and Conditions for Electronic Documents at <u>http://www.sac.com/en/Terms-and-Conditions aspx</u> and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document to exceed the parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced exceept in full, without prior written approval of the Company, any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the faw. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443,

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, Chine (Jiangsu) Plot Free Trade Zone 215000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 18 of 28

5 HAC (T-Coil) Measurement

5.1 T-Coil Performance Requirements

In order to be rated for T-Coil use, a WD shall meet the requirements for signal level and signal quality contained in this part.

1) T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ -18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.

2) Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. Figure 1 and Figure 2 provide the boundaries for the specified frequency.

These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.




Figure 1—Magnetic field frequency response for WDs with a field ≤ –15 dB (A/m) at 1 kHz









Figure 2 —Magnetic field frequency response for WDs with a field that exceeds -15dB(A/m) at 1 kHz

3) Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 3

Category	Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: <u>Or beck the authenticity of testing finspection reports & certificate, please contact us at telefinone: (86-755) 8307 1443, </u>

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 20 of 28

5.2 T-Coil measurement points and reference plane

Figure 3 illustrate the references and reference plane that shall be used in a typical EUT emissions measurement. The principle of this section is applied to EUT with similar geometry. Please refer to Appendix C for the setup photographs.

- The area is 5 cm by 5 cm.
- The area is centered on the audio frequency output transducer of the EUT.

• The area is in a reference plane, which is defined as the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the EUT handset, which, in normal handset use, rest against the ear.

• The measurement plane is parallel to, and 10 mm in front of, the reference plane.





Figure 3 Axis and planes for WD audio frequency magnetic field measurements



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Diless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing/Inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

South of No. 8 Plant, No. 1, Runsheng Road, Suzhou Industria Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号的6号厂房南部 邮编: 215000



5.3 T-Coil Measurement Procedure

According to ANSI C63.19-2011, section 7.4:

This section describes the procedures used to measure the ABM (T-Coil) performance of the WD. In addition to measuring the absolute signal levels, the A-weighted magnitude of the unintended signal shall also be determined. To assure that the required signal quality is measured, the measurement of the intended signal and the measurement of the unintended signal must be made at the same location for each measurement position. In addition, the RF field strength at each measurement location must be at or below that required for the assigned category.

Measurements shall not include undesired properties from the WD's RF field; therefore, use of a coaxial connection to a base station simulator or nonradiating load might be necessary. However, even with a coaxial connection to a base station simulator or nonradiating load, there might still be RF leakage from the WD, which can interfere with the desired measurement. Premeasurement checks should be made to avoid this possibility. All measurements shall be performed with the WD operating on battery power with an appropriate normal speech audio signal input level given in ANSI C63.19-2011 Table 7.1. If the device display can be turned off during a phone call, then that may be done during the measurement as well.

Measurements shall be performed at two locations specified in ANSI C63.19-2011 A.3, with the correct probe orientation for aparticular location, in a multistage sequence by first measuring the field intensity of the desired T-Coil signal (ABM1) that is useful to a hearing aid T-Coil. The undesired magnetic components (ABM2) shall be examined for each probe orientation to determine the possible effects from the WD display and battery current paths that might disrupt the desired T-Coil signal. The undesired magnetic signal (ABM2) must be measured at the same location as the desired ABM or T-Coil signal (ABM1), and the ratio of desired to undesired ABM signals must be calculated. For the perpendicular field location, only the ABM1 frequency response shall be determined in a third measurement stage.

The following steps summarize the basic test flow for determining ABM1 and ABM2. These steps assume that a sine-wave or narrowband 1/3 octave signal can be used for the measurement of ABM1.

a) A validation of the test setup and instrumentation may be performed using a TMFS or Helmholtz coil. Measure the emissions and confirm that they are within the specified tolerance.

b) Position the WD in the test setup and connect the WD RF connector to a base station simulator or a nonradiating load as shown in ANSI C63.19-2011 Figure 7.1 or Figure 7.2. Confirm that the equipment that requires calibration has been calibrated and that the noise level meets the requirements of ANSI C63.19-2011 clause 7.3.1.

c) The drive level to the WD is set such that the reference input level specified in ANSI C63.19-2011Table 7.1 is input to the base station simulator (or manufacturer's test mode equivalent) in the 1 kHz, 1/3 octave band. This drive level shall be used for the T-Coil signal test (ABM1) at f = 1 kHz. Either a sine wave at 1025 Hz or a voice-like signal, band-limited to the 1 kHz 1/3 octave, as defined in C63.19-2011 clause 7.4.2, shall be used for the reference audio signal. If interference is found at 1025 Hz, an alternative nearby reference audio signal frequency may be used.47 The same drive level shall be used for the ABM1 frequency response measurements at each 1/3 octave band center frequency. The WD volume control may be set at any level up to maximum, provided that a signal at any frequency at maximum modulation would not result in clipping or signal overload.

d) Determine the magnetic measurement locations for the WD device (A.3), if not already specified by the manufacturer, as described in C63.19-2011 clause 7.4.4.1.1 and 7.4.4.2.

e) At each measurement location, measure and record the desired T-Coil magnetic signals (ABM1 at fi) as specified in C63.19-2011 clause 7.4.4.2 in each ISO 266-1975 R10 standard 1/3 octave band. The desired audio band input frequency (fi) shall be centered in each 1/3 octave band maintaining the same drive level as determined in item c) and the reading taken for that band.

f) Equivalent methods of determining the frequency response may also be employed, such as fast Fourier transform (FFT) analysis using noise excitation or input–output comparison using simulated speech. The full-band integrated or half-band integrated probe output, as specified in D.9, may be used, as long as the appropriate calibration curve is applied to the measured result, so as to yield an accurate measurement of the field magnitude. (The resulting measurement shall be an accurate measurement in dB A/m.)



Unless otherwise agreed in writing, this document is issued by the overleaf, available on request or accessible at <u>http://www.sgs.com/a</u> subject to Terms and Conditions for Electronic Documents at <u>http:</u> Attention is drawn to the limitation of liability, indemnification and j advised that information contained hereon reflects the Company's to Client's instructions, if any. The Company's sole responsibility is transaction from exercising all their rights and obligations under it except in full, without prior written approval of the Company. Any appearance of this document is unlawful and offenders may be pros- results shown in this test report refer only to the sample(s) tested and Attention: To check the authenticity of testing /inspection report or email: CN.Doccheck@sas.com	n/Terms-and-Condition //www.sgs.com/en/Term urisdiction issues defli- indings at the time of to its Client and this he transaction docume unauthorized alteratio ecuted to the fullest ex such sample(s) are ret	<u>Is.aspx</u> and, for electr <u>ns-and-Conditions/Te</u> ned therein. Any holi its intervention only document does not ents. This document on, forgery or falsific ctent of the law. Unle cained for 30 days onl	onic format documents, rms-e-Document.aspx. der of this document is and within the limits of exonerate parties to a cannot be reproduced ation of the content or ss otherwise stated the y.	
South of No. 6 Plant. No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jianosu) Pilot Free Trade Zone	215000	t (86-512) 62992980	www.sasaroup.com.cn	



Page: 22 of 28

g) All measurements of the desired signal shall be shown to be of the desired signal and not of an undesired signal. This may be shown by turning the desired signal ON and OFF with the probe measuring the same location. If the scanning method is used, the scans shall show that all measurement points selected for the ABM1 measurement meet the ambient and test system noise criteria in C63.19-2011 clause 7.3.1.

h) At the measurement location for each orientation, measure and record the undesired broadband audio magnetic signal (ABM2) as specified in C63.19-2011 clause 7.4.4.4 with no audio signal applied (or digital zero applied, if appropriate) using A-weighting49 and the half-band integrator. Calculate the ratio of the desired to undesired signal strength (i.e., signal quality).

g) Determine the category that properly classifies the signal quality, based on C63.19-2011 Table 8.5.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.ags.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 23 of 28

6 T-Coil testing for CMRS Voice

6.1 General Description

1. Codec Investigation:

For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel/band, the following worst investigation codec would be remarked to be used for the testing for the handset.

2. Air Interface Investigation:

a. Use the worst-case codec test and document a limited set of bands/channel/bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface.

b. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing for each orientation to determine worst HAC T-Coil rating.

6.2 GSM Tests Results

Codec Investigation:

Band	Test Mode	Codec Setting	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
	CSM Voico			Axial (Z)		-38.34	40.50	T4	0.18	PASS
GSINIODU	GSM Voice	HR V1	190/836.6	Axial (Z)	1.44	-40.13	41.57	T4	1.66	PASS

Remark: According to codec investigation, the worst codec is FR_V1

Air Interface Investigation:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
GSM850	GSM Voice	190/836.6	Axial (Z)	2.16	-38.34	40.50	T4	0.18	PASS
G310000			Transversal (Y)	-4.59	-40.60	36.01	T4	N/A	/
CSM1000	CCM Vaina	e 661/1880	Axial (Z)	1.58	-41.62	43.20	T4	2.00	PASS
G21011900	GSM Voice		Transversal (Y)	-4.51	-38.55	34.04	T4	N/A	/

Remark:

1. Phone Condition: Mute on; Backlight off; Max Volume

2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 24 of 28

6.3 UMTS Tests Results

Codec Investigation:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
WCDMA Band V	AMR Voice	4182/836.4	Axial (Z)	-2.38	-47.17	44.79	T4	0.26	PASS	4.75kbps
	AMR Voice	4182/836.4	Axial (Z)	-2.76	-46.84	44.08	T4	2.00	PASS	7.95kbps
	AMR Voice	4182/836.4	Axial (Z)	1.82	-41.32	43.14	T4	2.00	PASS	12.2kbps

Remark: According to codec investigation, the worst codec is AMR 12.2Kbps

Air Interface Investigation:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
WCDMA	AMR Voice	9400/1900	Axial (Z)	1.23	-44.26	45.49	T4	2.00	PASS
Band II	AIVIN VOICE	9400/1900	Transversal (Y)	-4.49	-40.21	35.72	T4	N/A	/
WCDMA	AMR Voice	1412/1732.4	Axial (Z)	1.82	-41.32	43.14	T4	2.00	PASS
Band IV	AIVIN VOICE	1412/1732.4	Transversal (Y)	-4.56	-41.94	37.38	T4	N/A	/


Remark:

1. Phone Condition: Mute on; Backlight off; Max Volume

2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx. Attention is drawn to the limitation of liability, indermification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CM.Doccheck@ss.com



6.4 VoLTE Tests Results

1. Codec Investigation:

For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel / band, the following worst investigation codec would be remarked to be used for the testing for the handset.

2. Air Interface Investigation:

a. Use the worst-case codec test and document a limited set of bands / channel / bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface and the following worst configure would be remarked to be used for the testing for the handset.

b. Select LTE FDD / TDD one frequency band to do measurement at the worst SNR position was additionally performed with varying the BWs/Modulations/RB size to verify the variation to find out worst configuration, the observed variation is very little to be within 1.5 dB which is much less than the margin from the rating threshold. c. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing for each orientation to determine worst HAC T-Coil rating.

Codec Investigation:

LTE FDD

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-0.63	-32.35	31.72	T4	1.45	PASS	WB AMR 6.60kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-1.51	-31.49	29.98	Т3	0.98	PASS	WB AMR 23.85kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-1.14	-43.95	42.81	T4	0.83	PASS	NB AMR 4.75kbps
LTE	20M QPSK 1RB_0	18900/1880	Axial (Z)	-1.37	-43.33	41.96	T4	2.00	PASS	NB AMR 12.2kbps
Band 2	20M QPSK 1RB_0	18900/1880	Axial (Z)	-2.59	-34.69	32.10	T4	1.44	PASS	WB EVS 5.90kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-8.57	-38.71	30.14	T4	0.90	PASS	WB EVS 24.4kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-4.65	-45.45	40.80	T4	1.11	PASS	NB EVS 5.90kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-2.10	-44.34	42.24	T4	0.13	PASS	NB EVS 24.4kbps

Remark: According to codec investigation, the worst codec is WB AMR 23.85kbps

LTE TDD

Band	Test Mode	Test Ch./Freq.	UL-DL configuration	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	1.69	-28.24	29.93	T3	1.90	PASS	WB AMR 6.60kbps
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	2.73	-24.87	27.60	Т3	0.88	PASS	WB AMR 23.85kbps
LTE	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	2.40	-35.25	37.65	T4	0.35	PASS	NB AMR 4.75kbps
Band 41	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	2.60	-35.46	38.06	T4	1.86	PASS	NB AMR 12.2kbps
PC3	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	-2.09	-26.82	24.73	T3	0.70	PASS	WB EVS 5.90kbps
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	0.03	-28.89	28.92	T3	1.25	PASS	WB EVS 24.4kbps
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	1.95	-33.44	35.39	T4	0.32	PASS	NB EVS 5.90kbps
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	2.30	-34.34	36.64	T4	0.37	PASS	NB EVS 24.4kbps

Remark: According to codec investigation, the worst codec is WB EVS 5.90kbps



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing/Inspection reports & certificate, please contact us at telehone: (86-755) 8307 1443,

South of No. 8 Plant, No. 1, Runsheng Road, Suzhou Industria Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 2150000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区调胜路1号的6号厂房南部 邮编: 215000

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 26 of 28

Air Interface Investigation:

LTE FDD

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-1.51	-31.49	29.98	Т3	0.98	PASS
	20M QPSK 1RB_50	18900/1880	Axial (Z)	-1.84	-32.21	30.37	T4	0.83	PASS
	20M QPSK 1RB_99	18900/1880	Axial (Z)	-2.02	-31.15	29.13	Т3	0.87	PASS
	20M QPSK 50RB_0	18900/1880	Axial (Z)	-1.77	-31.72	29.95	T3	1.29	PASS
	20M QPSK 50RB_25	18900/1880	Axial (Z)	-10.44	-38.45	28.01	Т3	1.33	PASS
	20M QPSK 50RB_50	18900/1880	Axial (Z)	-5.66	-33.37	27.71	Т3	1.23	PASS
LTE Band 2	20M QPSK 100RB_0	18900/1880	Axial (Z)	5.36	-17.04	22.40	Т3	0.14	PASS
	20M 16QAM 1RB_0	18900/1880	Axial (Z)	-10.61	-34.21	23.60	Т3	0.61	PASS
	15M QPSK 1RB_0	18900/1880	Axial (Z)	-12.76	-36.04	23.28	Т3	1.39	PASS
	10M QPSK 1RB_0	18900/1880	Axial (Z)	-9.02	-33.76	24.74	Т3	1.47	PASS
	5M QPSK 1RB_0	18900/1880	Axial (Z)	1.96	-22.26	24.22	Т3	0.64	PASS
	3M QPSK 1RB_0	18900/1880	Axial (Z)	1.45	-22.37	23.82	Т3	1.67	PASS
	1.4M QPSK 1RB_0	18900/1880	Axial (Z)	5.71	-20.21	25.92	T3	0.99	PASS


LTE TDD

Band	Test Mode	Test Ch./Freq.	UL-DL Configuration	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
	20M QPSK 1RB_0	40620/2593	0	Axial (Z)	-0.30	-24.84	24.54	T3	1.05	PASS
	20M QPSK 1RB_50	40620/2593	0	Axial (Z)	-3.13	-28.55	25.42	T3	0.39	PASS
	20M QPSK 1RB_99	40620/2593	0	Axial (Z)	-2.09	-26.82	24.73	T3	0.70	PASS
	20M QPSK 50RB_0	40620/2593	0	Axial (Z)	0.49	-31.65	32.14	T4	1.09	PASS
	20M QPSK 50RB_25	40620/2593	0	Axial (Z)	-0.77	-31.41	30.64	T4	0.48	PASS
	20M QPSK 50RB_50	40620/2593	0	Axial (Z)	2.39	-27.16	29.55	T3	0.69	PASS
	20M QPSK 100RB_0	40620/2593	0	Axial (Z)	0.28	-29.11	29.39	T3	0.84	PASS
	20M 16QAM 1RB_0	40620/2593	0	Axial (Z)	1.25	-25.62	26.87	T3	1.43	PASS
LTE Band 41 PC3	15M QPSK 1RB_0	40620/2593	0	Axial (Z)	2.03	-24.96	26.99	Т3	0.34	PASS
1.00	10M QPSK 1RB_0	40620/2593	0	Axial (Z)	1.43	-23.45	24.88	T3	0.92	PASS
	5M QPSK 1RB_0	40620/2593	0	Axial (Z)	-1.90	-27.04	25.14	Т3	1.52	PASS
	20M QPSK 1RB_0	40620/2593	1	Axial (Z)	0.58	-26.36	26.94	T3	1.12	PASS
	20M QPSK 1RB_0	40620/2593	2	Axial (Z)	-4.54	-30.07	25.53	Т3	1.52	PASS
	20M QPSK 1RB_0	40620/2593	3	Axial (Z)	-2.82	-28.96	26.14	T3	1.30	PASS
	20M QPSK 1RB_0	40620/2593	4	Axial (Z)	2.87	-23.46	26.33	T3	1.05	PASS
	20M QPSK 1RB_0	40620/2593	5	Axial (Z)	-1.49	-26.83	25.34	T3	0.68	PASS
	20M QPSK 1RB_0	40620/2593	6	Axial (Z)	0.66	-25.83	26.49	Т3	1.61	PASS
	20M QPSK 1RB_0	40620/2593	1	Axial (Z)	-0.39	-24.95	24.56	T3	1.66	PASS
	20M QPSK 1RB_0	40620/2593	2	Axial (Z)	-8.67	-33.27	24.60	T3	0.83	PASS
LTE Band 41 PC2	20M QPSK 1RB_0	40620/2593	3	Axial (Z)	-11.59	-36.44	24.85	T3	1.30	PASS
1.02	20M QPSK 1RB_0	40620/2593	4	Axial (Z)	-1.57	-26.34	24.77	T3	1.38	PASS
	20M QPSK 1RB_0	40620/2593	5	Axial (Z)	-7.97	-32.77	24.80	T3	0.62	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/terms-and-Co

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone 215000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Air interface: LTE FDD

S

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
LTE	20M QPSK	18900/1880	Axial (Z)	5.36	-17.04	22.40	T3	0.14	PASS
Band 2	100RB_0	18900/1880	Transversal (Y)	-8.13	-35.76	27.63	T3	/	/
LTE	20M QPSK	20175/1732.5	Axial (Z)	3.00	-20.69	23.69	T3	1.56	PASS
Band 4	100RB_0	20175/1752.5	Transversal (Y)	-8.27	-32.70	24.43	Т3	/	/
LTE	10M QPSK	20525/836.5	Axial (Z)	3.76	-20.80	24.56	T3	0.98	PASS
Band 5	50RB_0	20323/838.5	Transversal (Y)	-1.74	-26.51	24.77	T3	/	/
LTE	10M QPSK	23095/707.5	Axial (Z)	5.83	-18.35	24.18	T3	1.42	PASS
Band 12	50RB_0		Transversal (Y)	-2.68	-25.76	23.08	T3	/	/
LTE	20M QPSK	26365/1882.5	Axial (Z)	0.16	-23.62	23.78	T3	0.06	PASS
Band 25	50RB_0	20305/1002.5	Transversal (Y)	-3.76	-27.38	23.62	Т3	/	/
LTE	15M QPSK	26865/831.5	Axial (Z)	-3.91	-28.18	24.27	T3	1.41	PASS
Band 26	100RB_0	20000/031.0	Transversal (Y)	-4.39	-27.93	23.54	T3	/	/
LTE	20M QPSK	132322/1745	Axial (Z)	0.12	-25.79	25.91	T3	1.38	PASS
Band 66	100RB_0	132322/1745	Transversal (Y)	-3.73	-29.12	25.39	T3	/	/
LTE	20M QPSK	133297/680.5	Axial (Z)	3.95	-21.14	25.09	T3	0.90	PASS
Band 71	100RB_0	133297/080.5	Transversal (Y)	-1.79	-26.73	24.94	T3	/	/

LTE TDD

Band	Test Mode	Test Ch./Freq.	UL-DL Configuration	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response
LTE Band	20M QPSK	40620/2593	0	Axial (Z)	-0.30	-24.84	24.54	Т3	1.05	PASS
41 PC3	1RB_0	40020/2393	0	Transversal (Y)	-8.05	-31.29	23.24	Т3	/	PASS

Remark:

1. Phone Condition: Mute on; Backlight off; Max Volume

2. The detail frequency response results please refer to Appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction lissues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CM.Doccheck@ss.com

 Report No.:
 XEWM2203000061RG08

 Rev.:
 01

 Page:
 28 of 28

		JU				
	Equipment	Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
\boxtimes	Software	SPEAG	DASY52 52.10.4	NA	NCR	NCR
\boxtimes	DAE	SPEAG	DAE4	1663	2021-03-01	2022-02-28
\square	DAE	SPEAG	DAE4	1428	2021-04-09	2022-04-08
\boxtimes	Audio Magnetic 1D Field Probe	SPEAG	AM1DV3	3115	2021-06-01	2022-05-31
\boxtimes	Test Arch SD HAC	SPEAG	NA	NA	NCR	NCR
\boxtimes	Audio Magnetic Measuring Instrument	SPEAG	AMMI	1028	NCR	NCR
\boxtimes	Audio Magnetic	SPEAG	AMCC	1143	N/A	N/A
\boxtimes	Universal Radio Communication Tester	R&S	CMW500	111637	2021-04-14	2022-04-13
\boxtimes	Humidity and Temperature Indicator	MingGao	MingGao	NA	2021-06-16	2022-06-15

7 Equipment list

S

Note:

1. All the equipments are within the valid period when the tests are performed.

2. NCR: "No-Calibration Required".

8 Calibration certificate

Please see the Appendix B

9 Photographs

Please see the Appendix C

Appendix A: Detailed Test Results

Appendix B: Calibration certificate

Appendix C: Photographs



