

<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	CN21ZVBM(P15C-BR/EDR) 001	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	238496131	Seite 1 von 30 Page 1 of 30
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	2021-01-08	
<b>Auftraggeber:</b> <i>Client:</i>	RHA Technologies Limited 69 Haugh Road, Glasgow, G38TX, United Kingdom			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Bluetooth Headset			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	Atlas ANC			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC Part 15C Test report (BR/EDR)			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2021-01-06			
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A002981605-004 A002981605-006			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2021-01-07 - 2021-01-15			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	Taipei Testing Laboratories			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>überprüft von:</b> <i>reviewed by:</i>		<b>genehmigt von:</b> <i>authorized by:</i>		
<b>Datum:</b> <i>Date:</i>	2021-01-19	<b>Ausstellungsdatum:</b> <i>Issue date:</i>	2021-01-19	
<b>Stellung / Position:</b>	Mars Lin Senior Project Manager	<b>Stellung / Position:</b>	Brenda Chen Senior Project Manager	
<b>Sonstiges / Other:</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
<p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(all) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>* Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(all) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>				
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

## TEST SUMMARY

Report Section	ISED Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(1)	Peak Output Power	Pass
5.1.3	15.247(a)(1)	20 dB Bandwidth	Pass
5.1.4	15.247(d)	Conducted Spurious Emission and Band Edge	Pass
5.1.5	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edge	Pass
5.1.6	15.247(a)(1)	Hopping Channel Separation	Pass
5.1.7	15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass
5.1.8	15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

**Note:**

1. If the Frequency Hopping Systems operating in 2400-2483.5 MHz band and the output power less than 125 mW. The hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of hopping channel whichever is greater.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

## Contents

<b>HISTORY OF THIS TEST REPORT</b> .....	5
<b>1. GENERAL REMARKS</b> .....	6
<b>1.1 COMPLEMENTARY MATERIALS</b> .....	6
<b>1.2 DECISION RULE OF CONFORMITY</b> .....	6
<b>2. TEST SITES</b> .....	7
<b>2.1 TEST LABORATORY</b> .....	7
<b>2.2 TEST FACILITY</b> .....	7
<b>2.3 TRACEABILITY</b> .....	8
<b>2.4 CALIBRATION</b> .....	8
<b>2.5 MEASUREMENT UNCERTAINTY</b> .....	8
<b>3. GENERAL PRODUCT INFORMATION</b> .....	9
<b>3.1 PRODUCT FUNCTION AND INTENDED USE</b> .....	9
<b>3.2 SYSTEM DETAILS AND RATINGS</b> .....	9
<b>3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS</b> .....	10
<b>3.4 SUBMITTED DOCUMENTS</b> .....	10
<b>4. TEST SET-UP AND OPERATION MODES</b> .....	11
<b>4.1 PRINCIPLE OF CONFIGURATION SELECTION</b> .....	11
<b>4.2 CARRIER FREQUENCY AND CHANNEL</b> .....	11
<b>4.3 TEST OPERATION AND TEST SOFTWARE</b> .....	12
<b>4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT</b> .....	13
<b>4.5 TEST SETUP DIAGRAM</b> .....	14
<b>5. TEST RESULTS</b> .....	15
<b>5.1 TRANSMITTER REQUIREMENT &amp; TEST SUITES</b> .....	15
5.1.1 <i>Antenna Requirement</i> .....	15
5.1.2 <i>Peak Output Power</i> .....	16
5.1.3 <i>20 dB Bandwidth</i> .....	19
5.1.4 <i>Conducted Spurious Emissions and Frequency Band Edges Measured in 100 kHz Bandwidth</i> .....	20
5.1.5 <i>Radiated Spurious Emissions and Band Edges</i> .....	21
5.1.6 <i>Hopping Channel Separation</i> .....	26
5.1.7 <i>Number of Hopping Frequency</i> .....	27
5.1.8 <i>Dwell Time</i> .....	28
<b>5.2 MAINS EMISSION</b> .....	29
5.2.1 <i>Mains Conducted Emission</i> .....	29

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 4 von 30  
Page 4 of 30

**APPENDIX A - TEST RESULT OF CONDUCTED**

**APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION**

**APPENDIX SP - PHOTOGRAPHS OF TEST SETUP**

**APPENDIX EP - PHOTOGRAPHS OF EUT**

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 5 von 30  
Page 5 of 30

## HISTORY OF THIS TEST REPORT

Report No.	Description	Date Issued
CN21ZVBM(P15C-BR/EDR) 001	Original Release	2021-01-19

## 1. General Remarks

### 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

**Appendix A - Test Result of Conducted**

**Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission**

**Appendix SP - Photographs of Test Setup**

**Appendix EP - Photographs of EUT**

### Applied Standard and Test Levels

Radio
RSS-247 Issue 2 February 2017
RSS-Gen Issue 5, Amendment 1, March 2019
ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

### 1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

## 2. Test Sites

### 2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

### 2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,  
New Taipei City 244  
Taiwan (R.O.C.)  
FCC Registration No.: 226631  
ISED Registration No.: 25563

## 2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence.

### Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.30 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.30 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.54 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.52 dB
Mains Conducted Emission	± 1.65 dB

## 3. General Product Information

### 3.1 Product Function and Intended Use

The EUT is a Bluetooth Headset. It contains a Bluetooth compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

### 3.2 System Details and Ratings

#### Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Bluetooth Headset
Type Identification	Atlas ANC
FCC ID	2AM5A-ATLAS

#### Technical Specification of EUT

Item	EUT information
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Spacing	1 MHz
Channel Number	79
Operation Voltage	USB 5Vdc, tested at 3.7Vdc
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Maximum Output Power (mW)	5.47
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

### 3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

### 3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

**Table for Parameters of Test Software Setting**

Frequency (MHz)	Power Setting		
	GFSK	$\pi/4$ -DQPSK	8DPSK
2402	0/-5/0	0/-5/0	0/-5/0
2441	0/-5/0	0/-5/0	0/-5/0
2480	0/-4/0	0/-4/0	0/-4/0

### 4.2 Carrier Frequency and Channel

Channel	Freq. (MHz)						
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

## 4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	BlueTest3
---------------	-----------

The samples were used as follows:

A002981605-004 for radiated

A002981605-006 for conducted

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

1. For Radiated emission test, pre-tested GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.
2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on Y-plane.
3. "-" means no effect.

### Antenna Port Conducted Measurement

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Modulation Type	Packet Type
-	2402 to 2480	2402, 2441, 2480	GFSK	1DH5
-	2402 to 2480	2402, 2441, 2480	$\pi/4$ -DQPSK	2DH5
-	2402 to 2480	2402, 2441, 2480	8DPSK	3DH5

### Radiated Spurious Emissions (Above 1 GHz)

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Modulation Type	Packet Type
-	2402 to 2480	2402, 2441, 2480	GFSK	1DH5
-	2402 to 2480	2402, 2441, 2480	8DPSK	3DH5

### Radiated Spurious Emissions (Below 1 GHz)

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Modulation Type	Packet Type
-	2402 to 2480	2480	GFSK	1DH5

**Prüfbericht - Nr.: CN21ZVBM(P15C-BR/EDR) 001**  
*Test Report No.*
**Seite 13 von 30**  
*Page 13 of 30*
**Mains Conducted Emission Test**

Pre-Scan full test was applied on all test modes, but only worst case was shown.  
 Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Modulation Type	Packet Type
-	2402 to 2480	2480	GFSK	1DH5

**Test Condition**

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	22-26 °C	50-65 %	Stanislas Charles
Radiated Spurious Emissions above 1 GHz	13.4~16 °C	58.6~63.4 %	Simon Tsai
Radiated Spurious Emissions below 1 GHz	13.4~16 °C	58.6~63.4 %	Simon Tsai
Mains Conducted Emission	23 °C	60 %	Chun-Yi Wu

## 4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

**Accessory of EUT**


No.	Product	Brand	Model	Description
A	USB Cable	FPRTECHNOLOGY (SHENZHEN) CO.,LTD	USBA/M2.0 TO USB-C2.0	50 cm shielded cable with core
				Radiated and Mains Conducted Tests
-	Audio Cable	立貿極細電線有限公司	CP19031-1	2.5mm to 3.5mm
-	Flight Adapter	Fengyi Industry (HuiZhou) Co., Ltd	AD34J-2PMPG-RHA	-

**Support Unit**

Radiated Test					
No.	Description	Brand	Model	S/N	Remark
1	Notebook	Lenovo	TP00094A	PF-1GT015	-
2	Adapter	Lenovo	ADLX45YCC3A	-	180 cm shielded cable w/o core
Mains Conducted Test					
1	NoteBook	HP	TPN-C135	-	-
2	Adapter	HP	L2598-002	-	180 cm shielded cable w/o core
Conducted Test					
-	Notebook	HP	TPN-C139	CND93662WT	-


## 4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>



\*Table

<Mains Conducted Emission mode>



\* Table

## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**Requirement** Use of approved antennas only

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 4.61 dBi. The antenna is a printed PCB trace with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 16 von 30  
Page 16 of 30

## 5.1.2 Peak Output Power

### Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.  
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### Kind of Test Site

Shielded room

### Test Setup



### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2020/4/6	2021/4/5	2021/1/7	2021/1/7
Power Sensor	Anritsu	MA2411B	1725269	2020/4/7	2021/4/6	2021/1/7	2021/1/7

### Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
 Test Report No.

 Seite 17 von 30  
 Page 17 of 30

**Test Result**
**Peak Output Power**
**<GFSK>**

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(mW)	
Low Channel	2402	3.98	2.500	125
Middle Channel	2441	4.22	2.642	125
High Channel	2480	4.34	2.716	125

**<π/4-DQPSK>**

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(mW)	
Low Channel	2402	6.53	4.498	125
Middle Channel	2441	6.74	4.721	125
High Channel	2480	6.90	4.898	125

**<8DPSK>**

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(mW)	
Low Channel	2402	7.02	5.035	125
Middle Channel	2441	7.22	5.272	125
High Channel	2480	7.38	5.470	125

**Prüfbericht - Nr.: CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 18 von 30  
Page 18 of 30

**Average Power**

**<GFSK>**

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	3.89	2.449
Middle Channel	2441	4.10	2.570
High Channel	2480	4.26	2.667

**< $\pi/4$ -DQPSK>**

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	3.94	2.477
Middle Channel	2441	4.13	2.588
High Channel	2480	4.27	2.673

**<8DPSK>**

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	3.95	2.483
Middle Channel	2441	4.15	2.600
High Channel	2480	4.27	2.673

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
 Test Report No.


 Seite 19 von 30  
 Page 19 of 30

### 5.1.3 20 dB Bandwidth

Limit N/A

Kind of Test Site Shielded room

#### Test Setup



#### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Agilent	N9010A	MY53470241	2020/6/2	2021/6/1	2021/1/7	2021/1/7

#### Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.
- The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

#### Test Results

Please refer to Appendix A.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 20 von 30  
Page 20 of 30


### 5.1.4 Conducted Spurious Emissions and Frequency Band Edges Measured in 100 kHz Bandwidth

#### Limit

20 dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

**Kind of Test Site** Shielded room

#### Test Setup



#### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Agilent	N9010A	MY53470241	2020/6/2	2021/6/1	2021/1/7	2021/1/7

#### Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

#### Test Results

Please refer to Appendix A.

## 5.1.5 Radiated Spurious Emissions and Band Edges

### Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


**Kind of Test Site** 3m Semi-Anechoic Chamber

### Test Setup


**<Radiated Emissions below 30 MHz>**



**<Radiated Emissions 30 MHz to 1 GHz>**



**<Radiated Emissions above 1 GHz>**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**Prüfbericht - Nr.: CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 23 von 30  
Page 23 of 30

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Signal Analyzer	R&S	FSV40	101508	2020/3/16	2021/3/15
Receiver	R&S	ESR7	102108	2020/4/22	2021/4/21
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2020/2/14	2021/2/12
Horn Antenna	ETS-Lindgren	3117	00218930	2020/12/1	2021/11/30
LF-AMP	Agilent	8447D	2944A10772	2020/2/11	2021/2/9
HF-AMP + AC source	EMCI	EMC051845SE	980633	2020/2/17	2021/2/15
HF-AMP + AC source	EMCI	EMC184045SE	980657	2020/2/17	2021/2/15
Horn Antenna	SCHWARZBECK	BBHA 9170	00887	2020/4/10	2021/4/9
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104EA	800056/4EA	2020/3/25	2021/3/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	804680/4	2020/3/25	2021/3/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37202/4	2020/3/25	2021/3/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800898/2EA	2020/4/22	2021/4/21
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800901/2EA	2020/4/22	2021/4/21
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801027/2EA	2020/4/22	2021/4/21
Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-087	2020/9/21	2021/9/20

**Prüfbericht - Nr.: CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.

Seite 24 von 30  
Page 24 of 30

### Test Procedures

#### For Radiated Emissions below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

#### For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report.

**Prüfbericht - Nr.:****CN21ZVBM(P15C-BR/EDR) 001**

Test Report No.

**Seite 25 von 30**

Page 25 of 30

**Test Results**

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
Test Report No.


Seite 26 von 30  
Page 26 of 30

### 5.1.6 Hopping Channel Separation

**Limit**  $\geq 25 \text{ kHz}$  or  $2/3$  of  $20 \text{ dB}$  bandwidth, whichever is greater

**Kind of Test Site** Shielded room

**Test Setup**



#### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Agilent	N9010A	MY53470241	2020/6/2	2021/6/1	2021/1/7	2021/1/7

#### Test Procedure

##### Measurement Procedure REF

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

#### Test Results

Please refer to Appendix A.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
 Test Report No.


 Seite 27 von 30  
 Page 27 of 30

### 5.1.7 Number of Hopping Frequency

 Limit  $\geq 15$  non-overlapping channels

Kind of Test Site Shielded room

Test Setup



#### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Agilent	N9010A	MY53470241	2020/6/2	2021/6/1	2021/1/7	2021/1/7

#### Test Procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

#### Test Results

Please refer to Appendix A.

Prüfbericht - Nr.: **CN21ZVBM(P15C-BR/EDR) 001**  
 Test Report No.


 Seite 28 von 30  
 Page 28 of 30

### 5.1.8 Dwell Time

Limit 0.4s

Kind of Test Site Shielded room

#### Test Setup



#### Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Agilent	N9010A	MY53470241	2020/6/2	2021/6/1	2021/1/7	2021/1/7

#### Test Procedures

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

#### Test Results

Please refer to Appendix A.

## 5.2 Mains Emission


### 5.2.1 Mains Conducted Emission

## Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

**Kind of Test Site** Shielded room

## Test Setup



## Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
EMI Test Receiver	Rohde & Schwarz	ESR 7	102114	2020/04/13	2021/04/13
Two-Line V-Network (for EUT)	Rohde & Schwarz	ENV216	101262	2020/08/04	2021/08/04
Pulse Limiter	Schwarzbeck	VTSD 9561 F-N	00660	2020/02/24	2021/02/24
Test Software	Audix	e3	Ver. 9	N/A	N/A