



FCC TEST REPORT

**Test report
On Behalf of
Streamax Technology Co.,Ltd.
For
CAMERA
Model No.: C6D**

FCC ID: 2AM6L-C6D

Prepared for : Streamax Technology Co.,Ltd.
21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue, Nanshan District,
Shenzhen, Guangdong,P.R. China.

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Jul. 05, 2018 ~ Aug. 31, 2018

Date of Report: Aug. 31, 2018

Report Number: HUAK180823883E



TEST RESULT CERTIFICATION

Applicant's name : Streamax Technology Co.,Ltd.
Address : 21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue,
Nanshan District, Shenzhen, Guangdong,P.R. China.

Manufacture's Name..... : Streamax Electronics Co.,Ltd.
Address : 5th-6thFloor, West, Chuangxiang 2nd Building, Yanxiang
Technology Park, 11# High-tech West Road, Guangming District,
Shenzhen, Guangdong Province, P.R. China .


Product description

Trade Mark: Streamax
Product name..... : CAMERA
Model and/or type reference : C6D


Standards..... : FCC Part 15.247
KDB 558074 D01 DTS Meas Guidance v04

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test..... :
Date (s) of performance of tests..... : **Jul. 05, 2018 ~ Aug. 31, 2018**
Date of Issue..... : **Aug. 31, 2018**
Test Result : **Pass**

Testing Engineer : 

(Gary Qian)

Technical Manager : 

(Eden Hu)

Authorized Signatory : 

(Jason Zhou)



Revision History

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|-----------------------|--------------------|--------------------|----------------------|-----------------|
| V1.0 | / | Aug. 31, 2018 | Valid | Initial Release |



TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1. PRODUCT DESCRIPTION | 6 |
| 1.2. TABLE OF CARRIER FREQUENCYS | 6 |
| 1.3. IEEE 802.11N MODULATION SCHEME | 7 |
| 1.4. RELATED SUBMITTAL(S) / GRANT (S)..... | 7 |
| 1.5. TEST METHODOLOGY..... | 8 |
| 1.6. SPECIAL ACCESSORIES..... | 8 |
| 1.7. EQUIPMENT MODIFICATIONS | 8 |
| 2. MEASUREMENT UNCERTAINTY | 9 |
| 3. DESCRIPTION OF TEST MODES | 10 |
| 4. SYSTEM TEST CONFIGURATION..... | 11 |
| 4.1. CONFIGURATION OF EUT SYSTEM | 11 |
| 4.2. EQUIPMENT USED IN EUT SYSTEM | 11 |
| 4.3. SUMMARY OF TEST RESULTS | 11 |
| 5. TEST FACILITY | 12 |
| 6. OUTPUT POWER | 13 |
| 6.1. MEASUREMENT PROCEDURE | 13 |
| 6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 13 |
| 6.3. LIMITS AND MEASUREMENT RESULT..... | 14 |
| 7. 6dB BANDWIDTH..... | 15 |
| 7.1. MEASUREMENT PROCEDURE | 15 |
| 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 15 |
| 7.3. LIMITS AND MEASUREMENT RESULTS | 16 |
| 8. CONDUCTED SPURIOUS EMISSION..... | 19 |
| 8.1. MEASUREMENT PROCEDURE | 19 |
| 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 19 |
| 8.3. MEASUREMENT EQUIPMENT USED | 19 |
| 8.4. LIMITS AND MEASUREMENT RESULT..... | 20 |
| 9. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY | 27 |
| 9.1. MEASUREMENT PROCEDURE | 27 |
| 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 27 |
| 9.3. MEASUREMENT EQUIPMENT USED | 27 |
| 9.4. LIMITS AND MEASUREMENT RESULT..... | 28 |
| 10. RADIATED EMISSION..... | 31 |
| 10.1. MEASUREMENT PROCEDURE | 31 |



| | |
|--|-----------|
| 10.2. TEST SETUP | 32 |
| 10.3. LIMITS AND MEASUREMENT RESULT..... | 33 |
| 10.4. TEST RESULT | 34 |
| 11. BAND EDGE EMISSION..... | 37 |
| 11.1. MEASUREMENT PROCEDURE | 37 |
| 11.2. TEST SET-UP | 37 |
| 11.3. RADIATED TEST RESULT..... | 38 |
| 11.4. CONDUCTED TEST RESULT | 39 |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP | 41 |



1. GENERAL INFORMATION

1.1. PRODUCT DESCRIPTION

The EUT is designed as "CAMERA". It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

| | |
|----------------------------|--|
| Operation Frequency | 2.412 GHz~2.462GHz |
| Output Power | IEEE 802.11b: 13.63 dBm, IEEE 802.11g: 10.55 dBm; IEEE 802.11n(20): 10.67 dBm,IEEE 802.11n(40): 11.69 dBm |
| Modulation | DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM) |
| Number of channels | 11 Channels (IEEE802.11b/g/n20)& 7 Channels (IEEE802.11n40) |
| Hardware Version | 1439.02 |
| Software Version | V232 |
| Antenna Designation | PCB Antenna |
| Antenna Gain | 0.5dBi |
| Power Supply | DC 9~36V |
| Test Power Supply | DC 12V |

1.2. TABLE OF CARRIER FREQUENCIES

| Frequency Band | Channel Number | Frequency |
|----------------|----------------|-----------|
| 2400~2483.5MHZ | 1 | 2412 MHZ |
| | 2 | 2417 MHZ |
| | 3 | 2422 MHZ |
| | 4 | 2427 MHZ |
| | 5 | 2432 MHZ |
| | 6 | 2437 MHZ |
| | 7 | 2442 MHZ |
| | 8 | 2447 MHZ |
| | 9 | 2452 MHZ |
| | 10 | 2457 MHZ |
| | 11 | 2462 MHZ |

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11

For 802.11n 40MHZ bandwidth system use Channel 3 to Channel 9.

**1.3. IEEE 802.11N MODULATION SCHEME**

| MCS Index | Nss | Modulation | R | NBPSC | NCBPS | | NDBPS | | Data rate(Mbps) | | | |
|-----------|-----|------------|-----|-------|---------|-------|-------|-------|-----------------|-------|-------|-------|
| | | | | | 800nsGI | | 20MHz | 40MHz | 20MHz | 40MHz | 20MHz | 40MHz |
| | | | | | 20MHz | 40MHz | | | | | | |
| 0 | 1 | BPSK | 1/2 | 1 | 52 | 108 | 26 | 54 | 6.5 | 13.5 | | |
| 1 | 1 | QPSK | 1/2 | 2 | 104 | 216 | 52 | 108 | 13.0 | 27.0 | | |
| 2 | 1 | QPSK | 3/4 | 2 | 104 | 216 | 78 | 162 | 19.5 | 40.5 | | |
| 3 | 1 | 16-QAM | 1/2 | 4 | 208 | 432 | 104 | 216 | 26.0 | 54.0 | | |
| 4 | 1 | 16-QAM | 3/4 | 4 | 208 | 432 | 156 | 324 | 39.0 | 81.0 | | |
| 5 | 1 | 64-QAM | 2/3 | 6 | 312 | 648 | 208 | 432 | 52.0 | 108.0 | | |
| 6 | 1 | 64-QAM | 3/4 | 6 | 312 | 648 | 234 | 489 | 58.5 | 121.5 | | |
| 7 | 1 | 64-QAM | 5/6 | 6 | 312 | 648 | 260 | 540 | 65.0 | 135.0 | | |

| Symbol | Explanation |
|--------|---|
| NSS | Number of spatial streams |
| R | Code rate |
| NBPSC | Number of coded bits per single carrier |
| NCBPS | Number of coded bits per symbol |
| NDBPS | Number of data bits per symbol |
| GI | Guard interval |

1.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AM6L-C6D** filing to comply with the FCC Part 15 requirements.



1.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters. Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v04.

1.6. SPECIAL ACCESSORIES

Refer to section 4.2.

1.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



2. MEASUREMENT UNCERTAINTY

| Test | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted | ± 0.57 dB | (1) |
| Transmitter power Radiated | ± 2.20 dB | (1) |
| Conducted spurious emission 9KHz-40 GHz | ± 2.20 dB | (1) |
| Occupied Bandwidth | ± 0.01 ppm | (1) |
| Radiated Emission 30~1000MHz | ± 4.10 dB | (1) |
| Radiated Emission Above 1GHz | ± 4.32 dB | (1) |
| Conducted Disturbance 0.15~30MHz | ± 3.20 dB | (1) |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|-----|-----------------------|
| 1 | Low channel TX |
| 2 | Middle channel TX |
| 3 | High channel TX |
| 4 | Normal operating |

Note:
Transmit by 802.11b with Data rate (1/2/5.5/11)
Transmit by 802.11g with Data rate (6/9/12/18/24/36/48/54)
Transmit by 802.11n (20MHz) with Data rate (6.5/13/19.5/26/39/52/58.5/65)
Transmit by 802.11n (40MHz) with Data rate (13.5/27/40.5/54/81/108/121.5/135)

Note:


1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.



4. SYSTEM TEST CONFIGURATION

4.1. CONFIGURATION OF EUT SYSTEM

Configure:



4.2. EQUIPMENT USED IN EUT SYSTEM

| Item | Equipment | Model No. | ID or Specification | Remark |
|------|-----------|-----------|---------------------|-----------|
| 1 | CAMERA | C6D | 2AM6L-C6D | EUT |
| 2 | Antenna | N/A | N/A | Accessory |

Note: All the accessories have been used during the test in conduction emission test.

4.3. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|-----------|---|-----------|
| §15.247 | Output Power | Compliant |
| §15.247 | 6 dB Bandwidth | Compliant |
| §15.247 | Conducted Spurious Emission | Compliant |
| §15.247 | Maximum Conducted Output Power SPECTRAL Density | Compliant |
| §15.209 | Radiated Emission | Compliant |
| §15.247 | Band Edges | Compliant |
| §15.207 | Line Conduction Emission | Compliant |



5. TEST FACILITY

| | |
|----------------------------|---|
| Test Firm | Shenzhen HUAK Testing Technology Co., Ltd. |
| Address | 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China |
| Designation Number | CN1229 |
| Registration Number | 616276 |

ALL TEST EQUIPMENT LIST

| Equipment | Manufacturer | Model | S/N | Cal. Due |
|---------------------------|---------------------|-----------------|------------|-----------------|
| Receiver | R&S | ESCI 7 | HKE-010 | Dec. 28, 2018 |
| LISN | R&S | ENV216 | HKE-002 | Dec. 28, 2018 |
| Conducted test software | Tonscend | TS+ Rev 2.5.0.0 | HKE-081 | N/A |
| Power meter | Agilent | E4417B | HKE-107 | Dec. 28, 2018 |
| Power Sensor | Agilent | E9327A | HKE-113 | Dec. 28, 2018 |
| RF cable | Times | 1-40G | HKE-034 | Dec. 28, 2018 |
| RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Dec. 28, 2018 |
| Spectrum analyzer | Agilent | N9020A | HKE-048 | Dec. 28, 2018 |
| RF Cable (9KHz-26.5GHz) | Tonscend | 170660 | N/A | Dec. 28, 2018 |
| Signal generator | Agilent | N5183A | HKE-071 | Dec. 28, 2018 |
| Receiver | R&S | ESCI-7 | HKE-010 | Dec. 28, 2018 |
| Preamplifier | EMCI | EMC051845SE | HKE-015 | Dec. 28, 2018 |
| Preamplifier | Agilent | 83051A | HKE-016 | Dec. 28, 2018 |
| Loop antenna | Schwarzbeck | FMZB 1519 B | HKE-014 | Dec. 28, 2018 |
| Broadband antenna | Schwarzbeck | VULB 9163 | HKE-012 | Dec. 28, 2018 |
| Horn antenna | Schwarzbeck | 9120D | HKE-013 | Dec. 28, 2018 |
| Antenna Mast | Keleto | CC-A-4M | N/A | N/A |
| Position controller | Taiwan MF | MF7802 | HKE-011 | Dec. 28, 2018 |
| RF cable (9KHz-1GHz) | Times | 381806-001 | N/A | N/A |



6. OUTPUT POWER

6.1. MEASUREMENT PROCEDURE


For max average conducted output power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

AVERAGE POWER SETUP





6.3. LIMITS AND MEASUREMENT RESULT

| | |
|------------------|--------------------------|
| TEST ITEM | OUTPUT POWER |
| TEST MODE | 802.11b with data rate 1 |

| Frequency (GHz) | Average Power (dBm) | Applicable Limits (dBm) | Pass or Fail |
|-----------------|---------------------|-------------------------|--------------|
| 2.412 | 13.63 | 30 | Pass |
| 2.437 | 12.01 | 30 | Pass |
| 2.462 | 12.26 | 30 | Pass |

| | |
|------------------|--------------------------|
| TEST ITEM | OUTPUT POWER |
| TEST MODE | 802.11g with data rate 6 |

| Frequency (GHz) | Average Power (dBm) | Applicable Limits (dBm) | Pass or Fail |
|-----------------|---------------------|-------------------------|--------------|
| 2.412 | 9.58 | 30 | Pass |
| 2.437 | 8.32 | 30 | Pass |
| 2.462 | 10.55 | 30 | Pass |

| | |
|------------------|-------------------------------|
| TEST ITEM | OUTPUT POWER |
| TEST MODE | 802.11n 20 with data rate 6.5 |

| Frequency (GHz) | Average Power (dBm) | Applicable Limits (dBm) | Pass or Fail |
|-----------------|---------------------|-------------------------|--------------|
| 2.412 | 9.51 | 30 | Pass |
| 2.437 | 8.48 | 30 | Pass |
| 2.462 | 10.67 | 30 | Pass |

| | |
|------------------|--------------------------------|
| TEST ITEM | OUTPUT POWER |
| TEST MODE | 802.11n 40 with data rate 13.5 |

| Frequency (GHz) | Average Power (dBm) | Applicable Limits (dBm) | Pass or Fail |
|-----------------|---------------------|-------------------------|--------------|
| 2.422 | 11.66 | 30 | Pass |
| 2.437 | 11.69 | 30 | Pass |
| 2.452 | 11.56 | 30 | Pass |




7. 6dB BANDWIDTH

7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW $\geq 3 \times$ RBW.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)









**7.3. LIMITS AND MEASUREMENT RESULTS**

| Mode | Channel | 6dB Bandwidth [MHz] | Verdict |
|---------|---------|---------------------|---------|
| 11b | LCH | 10.09 | PASS |
| | MCH | 10.09 | PASS |
| | HCH | 10.05 | PASS |
| 11g | LCH | 16.40 | PASS |
| | MCH | 16.40 | PASS |
| | HCH | 16.39 | PASS |
| 11nHT20 | LCH | 17.63 | PASS |
| | MCH | 17.60 | PASS |
| | HCH | 17.62 | PASS |
| 11nHT40 | LCH | 35.87 | PASS |
| | MCH | 35.85 | PASS |
| | HCH | 35.82 | PASS |



Test Graph







8. CONDUCTED SPURIOUS EMISSION

8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the $RBW=1MHz$, $VBW > RBW$, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the $RBW=100KHz$, $VBW > RBW$) are conform to the requirement.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 6.2.

8.3. MEASUREMENT EQUIPMENT USED

The same as described in section 5.












8.4. LIMITS AND MEASUREMENT RESULT







| LIMITS AND MEASUREMENT RESULT | | |
|--|--|-----------------|
| Applicable Limits | Measurement Result | |
| | Test Data | Criteria |
| In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a)) | At least -20dBc than the limit Specified on the BOTTOM Channel | PASS |
| | At least -20dBc than the limit Specified on the TOP Channel | PASS |






Test Graph














11nHT20-HCH




11nHT20-HCH




11nHT20-HCH



11nHT40-LCH



11nHT40-LCH



11nHT40-LCH

