

TEST REPORT

Applicant: Fujian Newland Payment Technology Co.,Ltd.

Address: No. B602, Building #1, Haixia Jingmao Plaza, Fuzhou Bonded Area 350015, Fujian, China

Product Name: WiFi & Bluetooth Module


FCC ID: 2AM6U-FCS950U

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: XMDN240122-04868E-RF-00C

Report Date: 2024/4/17

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).



Reviewed By: Gavin Xu
Title: RF Engineer



Approved By: Ivan Cao
Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	7
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	9
3.7 MEASUREMENT UNCERTAINTY	9
4. REQUIREMENTS AND TEST PROCEDURES	10
4.1 AC LINE CONDUCTED EMISSIONS	10
4.1.1 Applicable Standard	10
4.1.2 EUT Setup	11
4.1.3 EMI Test Receiver Setup	11
4.1.4 Test Procedure	12
4.1.5 Corrected Result & Margin Calculation	12
4.1.6 Test Result	12
4.2 RADIATION SPURIOUS EMISSIONS	13
4.2.1 Applicable Standard	13
4.2.2 EUT Setup	13
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
4.2.4 Test Procedure	15
4.2.5 Corrected Result & Margin Calculation	15
4.2.6 Test Result	15
4.3 MAXIMUM CONDUCTED OUTPUT POWER	16
4.3.1 Applicable Standard	16
4.3.2 EUT Setup	16
4.3.3 Test Procedure	16
4.3.4 Test Result	16
4.4 DUTY CYCLE	17
4.4.1 EUT Setup	17
4.4.2 Test Procedure	17
4.4.3 Judgment	17
4.5 ANTENNA REQUIREMENT	18

4.5.1 Applicable Standard 18

4.5.2 Judgment 18

5. Test DATA AND RESULTS 19

5.1 AC LINE CONDUCTED EMISSIONS..... 19

5.2 RADIATION SPURIOUS EMISSIONS..... 22

5.3 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER 31

5.4 DUTY CYCLE 32

APPENDIX A - EUT PHOTOGRAPHS 33

APPENDIX B - TEST SETUP PHOTOGRAPHS 34

APPENDIX C - RF EXPOSURE EVALUATION 35

APPLICABLE STANDARD 35

CALCULATION FORMULA:..... 35

CALCULATED DATA: 36

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	XMDN240122-04868E-RF-00C	Class II Permissive Change Report	2024/4/17

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	WiFi & Bluetooth Module
EUT Model:	FCS950U
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	6.58 dBm
Modulation Type:	GFSK
Rated Input Voltage:	DC 3.3V
Serial Number:	2GZ2-1(Radiated Spurious Emission/AC Line Conducted Emission Test) 2GZ2-3 (RF Conducted Test)
EUT Received Date:	2024/1/24
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
ZHONGTIAN XUN Communication Technology Co.,Ltd	FPC	50	2.4~2.5GHz	1.04 dBi
The design of compliance with §15.203:				
<input checked="" type="checkbox"/> Unit uses a permanently attached antenna.				
<input type="checkbox"/> Unit uses a unique coupling to the intentional radiator.				
<input type="checkbox"/> Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result	Note
§15.207(a)	AC line conducted emissions	Compliant	/
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant	/
§15.247 (a)(2)	Minimum 6 dB Bandwidth	/	*
§15.247(b)(3)	Maximum Conducted Output Power	Reporting	
§15.247(e)	Power Spectral Density	/	*
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	/	*
§15.203	Antenna Requirement	Compliant	/

Note 1:

This is Class II permissive change application based on the Change ID device, model: FCS950U, FCC ID: 2AM6U-FCS950U. The Change ID device based on the original device, model: FCS950U, FCC ID:XMR2023FCS950U, which was tested by Sporton International Inc. (Kunshan). The change between the original equipment and the current equipment is stated and guaranteed by the applicant, as following:

1. Change the antenna.

Per Spot check with RF output power, the RF parameters are identical with the original device. Therefore, AC line conducted emissions and Radiated Spurious Emissions was tested based on the change.

*:Please refer to Report No: FR2D0802B.

The Bay Area Compliance Laboratories Corp. (Dongguan) is responsible for all the information provided in this report, except when information is provided by the customer as identified in this report.

Note 2: For AC line conducted emissions, the maximum output power channel was tested.

Note 3: For Radiated Spurious Emissions 9kHz~ 1GHz, the maximum output power channel was tested.

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

BLE 1M bps/2M bps:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

Note: tested with the frequencies in bold .

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:		cmd		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Power Level Setting			
	Lowest	Middle	Highest	
1Mbps	default	default	default	
2Mbps	default	default	default	

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TOTO Link	Router	LR1200	190924004S1
Lenovo	Laptop	T430	00331-10000-00001-AA887 02
Fujian Newland Payment Technology Co.,Ltd.	Fixture board	NXG-GC76WN5528	2GZ2-1

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DB9+RJ45+TypeA +Power mutifuction cable	no	no	3	Adapter/ Router/ Laptop serial port/ Laptop USB port	Fixture board

3.5 Block Diagram of Test Setup

AC Power Lines Conducted Emission:



Radiated Spurious Emissions:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Result & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions


4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2.2 EUT Setup


9kHz-30MHz:



30MHz~1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/
	QP	/	/	120 kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	≥1/T

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor
 Factor = Antenna Factor + Cable Loss - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.


4.3 Maximum Conducted Output Power

4.3.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer▲.

4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the $RBW \geq DTS$ bandwidth.
- b) Set $VBW \geq [3 \times RBW]$.
- c) Set $span \geq [3 \times RBW]$.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.


NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

4.3.4 Test Result

Please refer to section 5.3.

4.4 Duty Cycle

4.4.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.4.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.4.3 Judgment

Report only, please refer to section 5.4.

4.5 Antenna Requirement

4.5.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.5.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2GZ2-1	Test Date:	2024/3/26
Test Site:	CE	Test Mode:	Transmitting
Tester:	Wright Lai	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2	Relative Humidity: (%)	71	ATM Pressure: (kPa)	101.9
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2023/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2023/9/5	2024/9/4
R&S	EMI Test Receiver	ESCI	100035	2023/8/18	2024/8/17
R&S	Test Software	EMC32	V9.10.00	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Note: the maximum output power channel was tested.


Project No: XMDN240122-04868E-RF
 Test Engineer: Wright Lai
 Test Date: 2024-3-26
 Port: L
 Test Mode: Transmitting
 Power Source: AC 120V/60Hz
 Note: BLE 1M bps High channel



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.169919	37.34	---	64.96	27.62	9.000	L1	10.8
0.208474	33.71	---	63.27	29.56	9.000	L1	10.8
0.219135	35.33	---	62.85	27.52	9.000	L1	10.8
0.309151	---	23.92	49.99	26.07	9.000	L1	10.8
0.348462	---	23.45	49.00	25.55	9.000	L1	10.8
0.383099	---	24.80	48.21	23.41	9.000	L1	10.8
0.392773	31.18	---	58.00	26.82	9.000	L1	10.8
0.449391	31.67	---	56.89	25.22	9.000	L1	10.8
0.453897	---	24.74	46.80	22.06	9.000	L1	10.8
0.711054	---	16.69	46.00	29.31	9.000	L1	10.9
3.799262	22.05	---	56.00	33.95	9.000	L1	10.8
30.000000	---	21.32	50.00	28.68	9.000	L1	10.9

Project No: XMDN240122-04868E-RF
 Test Engineer: Wright Lai
 Test Date: 2024-3-26
 Port: N
 Test Mode: Transmitting
 Power Source: AC 120V/60Hz
 Note: BLE 1M bps High channel



Final Result

Frequency (MHz)	QuasiPeak (dB μV)	Average (dB μV)	Limit (dB μV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.152261	36.78	---	65.88	29.10	9.000	N	10.9
0.184035	33.24	---	64.30	31.06	9.000	N	10.9
0.199323	29.21	---	63.64	34.43	9.000	N	10.9
0.213738	30.89	---	63.06	32.17	9.000	N	10.8
0.309151	---	21.12	49.99	28.87	9.000	N	10.8
0.366283	---	21.67	48.58	26.91	9.000	N	10.8
0.386939	29.88	---	58.13	28.25	9.000	N	10.8
0.451638	---	18.24	46.84	28.60	9.000	N	10.8
0.829947	---	17.65	46.00	28.35	9.000	N	10.8
4.731578	20.87	---	56.00	35.13	9.000	N	10.8
28.073079	---	19.25	50.00	30.75	9.000	N	11.0
30.000000	---	19.94	50.00	30.06	9.000	N	11.0

5.2 Radiation Spurious Emissions

Serial Number:	2GZ2-1	Test Date:	Below 1GHz: 2024/4/7 Above 1GHz: 2024/4/12
Test Site:	Chamber 10m, Chamber B	Test Mode:	Transmitting
Tester:	Zoo Zou, Bill Yang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	22.1~24.4	Relative Humidity: (%)	44~58	ATM Pressure: (kPa)	100.4~100.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
9kHz~1000MHz					
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
Sonoma	Amplifier	310N	185914	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	101121	2023/10/18	2024/10/17
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2024/9/6
R&S	Spectrum Analyzer	FSV40	101944	2023/10/18	2024/10/17
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2023/11/17	2024/11/16
Audix	Test Software	E3	191218 (V9)	N/A	N/A
AH	Preamplifier	PAM-0118P	469	2023/8/19	2024/8/18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-03 1304	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2023/12/11	2024/12/10
AH	Preamplifier	PAM-1840VH	191	2023/9/7	2024/9/6
E-Microwave	Band Rejection Filter	OBSF-2400-2483.5-S	OE01601525	2024/2/21	2025/2/20
Micro-tronics	High Pass Filter	HPM50111	G217	2023/12/1	2024/11/30

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.


After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

1) 9kHz~30MHz

The BLE 1Mbps high channel was tested. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.


2) 30MHz-1GHz

Project No: XMDN240122-04868E-RF
 Test Engineer: Zoo Zou
 Test Date: 2024-4-7
 Polarization: Horizontal
 Test Mode: Transmitting
 Power Source: AC 120V/60Hz
 Note:



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	450.0100	41.88	peak	-5.47	36.41	46.00	9.59
2	549.9200	33.17	peak	-3.43	29.74	46.00	16.26
3	650.8000	32.09	peak	-1.88	30.21	46.00	15.79
4	750.7100	34.58	peak	-0.31	34.27	46.00	11.73
5	850.6200	30.55	peak	0.90	31.45	46.00	14.55
6	950.5300	30.23	peak	2.04	32.27	46.00	13.73

Project No: XMDN240122-04868E-RF
 Test Engineer: Zoo Zou
 Test Date: 2024-4-7
 Polarization: Vertical
 Test Mode: Transmitting
 Power Source: AC 120V/60Hz
 Note:



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	450.0100	40.05	peak	-5.47	34.58	46.00	11.42
2	549.9200	39.86	peak	-3.43	36.43	46.00	9.57
3	649.8300	36.62	peak	-1.88	34.74	46.00	11.26
4	749.7400	34.85	peak	-0.32	34.53	46.00	11.47
5	850.6200	34.84	peak	0.90	35.74	46.00	10.26
6	950.5300	33.15	peak	2.04	35.19	46.00	10.81

3) 1-18GHz:

Test With BLE 2M High channel:


High Channel, Horizontal		High Channel, Vertical																																																																																	
<p>Project No.: XMDN240122-04868E-RF Serial No.: 2622-1 Polarization: Horizontal Tester: Bill Yang Test Mode: Transmitting Note: BLE 2M_high channel 2480MHz</p> <p>Date: 2024-04-12</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Result (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>47.00</td> <td>-2.32</td> <td>44.68</td> <td>74.00</td> <td>29.32</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>4960.00</td> <td>37.36</td> <td>-2.32</td> <td>35.04</td> <td>54.00</td> <td>18.96</td> <td>Average</td> </tr> </tbody> </table>		No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	4960.00	47.00	-2.32	44.68	74.00	29.32	Peak	2	4960.00	37.36	-2.32	35.04	54.00	18.96	Average	<p>Project No.: XMDN240122-04868E-RF Serial No.: 2622-1 Polarization: Vertical Tester: Bill Yang Test Mode: Transmitting Note: BLE 2M_high channel 2480MHz</p> <p>Date: 2024-04-12</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Result (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>47.17</td> <td>-2.32</td> <td>44.85</td> <td>74.00</td> <td>29.15</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>4960.00</td> <td>36.54</td> <td>-2.32</td> <td>34.22</td> <td>54.00</td> <td>19.78</td> <td>Average</td> </tr> </tbody> </table>		No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	4960.00	47.17	-2.32	44.85	74.00	29.15	Peak	2	4960.00	36.54	-2.32	34.22	54.00	19.78	Average																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																																																																												
1	4960.00	47.00	-2.32	44.68	74.00	29.32	Peak																																																																												
2	4960.00	37.36	-2.32	35.04	54.00	18.96	Average																																																																												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																																																																												
1	4960.00	47.17	-2.32	44.85	74.00	29.15	Peak																																																																												
2	4960.00	36.54	-2.32	34.22	54.00	19.78	Average																																																																												
<p>Project No.: XMDN240122-04868E-RF Serial No.: 2622-1 Polarization: Horizontal Tester: Bill Yang Test Mode: Transmitting Note: BLE 2M_high channel 2480MHz</p> <p>Date: 2024-04-12</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Result (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>7440.00</td> <td>46.27</td> <td>2.64</td> <td>48.91</td> <td>74.00</td> <td>25.09</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>36.85</td> <td>2.64</td> <td>39.49</td> <td>54.00</td> <td>14.51</td> <td>Average</td> </tr> <tr> <td>3</td> <td>17493.60</td> <td>44.12</td> <td>15.82</td> <td>59.94</td> <td>74.00</td> <td>14.06</td> <td>Peak</td> </tr> <tr> <td>4</td> <td>17493.60</td> <td>31.56</td> <td>15.82</td> <td>47.38</td> <td>54.00</td> <td>6.62</td> <td>Average</td> </tr> </tbody> </table>		No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	7440.00	46.27	2.64	48.91	74.00	25.09	Peak	2	7440.00	36.85	2.64	39.49	54.00	14.51	Average	3	17493.60	44.12	15.82	59.94	74.00	14.06	Peak	4	17493.60	31.56	15.82	47.38	54.00	6.62	Average	<p>Project No.: XMDN240122-04868E-RF Serial No.: 2622-1 Polarization: Vertical Tester: Bill Yang Test Mode: Transmitting Note: BLE 2M_high channel 2480MHz</p> <p>Date: 2024-04-12</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Result (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>7440.00</td> <td>46.35</td> <td>2.64</td> <td>48.99</td> <td>74.00</td> <td>25.01</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>36.51</td> <td>2.64</td> <td>39.15</td> <td>54.00</td> <td>14.85</td> <td>Average</td> </tr> <tr> <td>3</td> <td>17462.40</td> <td>43.72</td> <td>15.57</td> <td>59.29</td> <td>74.00</td> <td>14.71</td> <td>Peak</td> </tr> <tr> <td>4</td> <td>17462.40</td> <td>31.01</td> <td>15.57</td> <td>46.58</td> <td>54.00</td> <td>7.42</td> <td>Average</td> </tr> </tbody> </table>		No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	7440.00	46.35	2.64	48.99	74.00	25.01	Peak	2	7440.00	36.51	2.64	39.15	54.00	14.85	Average	3	17462.40	43.72	15.57	59.29	74.00	14.71	Peak	4	17462.40	31.01	15.57	46.58	54.00	7.42	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																																																																												
1	7440.00	46.27	2.64	48.91	74.00	25.09	Peak																																																																												
2	7440.00	36.85	2.64	39.49	54.00	14.51	Average																																																																												
3	17493.60	44.12	15.82	59.94	74.00	14.06	Peak																																																																												
4	17493.60	31.56	15.82	47.38	54.00	6.62	Average																																																																												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																																																																												
1	7440.00	46.35	2.64	48.99	74.00	25.01	Peak																																																																												
2	7440.00	36.51	2.64	39.15	54.00	14.85	Average																																																																												
3	17462.40	43.72	15.57	59.29	74.00	14.71	Peak																																																																												
4	17462.40	31.01	15.57	46.58	54.00	7.42	Average																																																																												

High Channel, Bandedge, Horizontal

Project No.: XMDN240122-04868E-RF
 Polarization: Horizontal
 Test Mode: Transmitting
 Note: BLE 2M_high channel 2480MHz

Serial No.: 2622-1
 Tester: Bill Yang

Date: 2024-04-12




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	25.87	28.95	54.82	74.00	19.18	Peak
2	2483.50	15.50	28.95	44.45	54.00	9.55	Average

High Channel, Bandedge, Vertical

Project No.: XMDN240122-04868E-RF
 Polarization: Vertical
 Test Mode: Transmitting
 Note: BLE 2M_high channel 2480MHz

Serial No.: 2622-1
 Tester: Bill Yang

Date: 2024-04-12




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	25.94	28.95	54.89	74.00	19.11	Peak
2	2483.50	15.77	28.95	44.72	54.00	9.28	Average

18-25GHz:

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

BLE 2M



BLE 1M_low channel Frequency **2402** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
2390.00	25.76	PK	H	27.64	0.93	0.00	54.33	74.00	19.67
2390.00	15.54	AV	H	27.64	0.93	0.00	44.11	54.00	9.89
2390.00	27.48	PK	V	27.64	0.93	0.00	56.05	74.00	17.95
2390.00	15.25	AV	V	27.64	0.93	0.00	43.82	54.00	10.18
4804.00	47.81	PK	H	32.84	1.38	37.30	44.73	74.00	29.27
4804.00	36.66	AV	H	32.84	1.38	37.30	33.58	54.00	20.42
4804.00	46.48	PK	V	32.84	1.38	37.30	43.40	74.00	30.60
4804.00	36.56	AV	V	32.84	1.38	37.30	33.48	54.00	20.52
7206.00	45.77	PK	H	35.99	2.39	36.61	47.54	74.00	26.46
7206.00	35.32	AV	H	35.99	2.39	36.61	37.09	54.00	16.91
7206.00	45.21	PK	V	35.99	2.39	36.61	46.98	74.00	27.02
7206.00	35.54	AV	V	35.99	2.39	36.61	37.31	54.00	16.69

BLE 1M_middle channel Frequency **2440** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
4880.00	47.67	PK	H	32.90	1.38	37.01	44.94	74.00	29.06
4880.00	36.56	AV	H	32.90	1.38	37.01	33.83	54.00	20.17
4880.00	46.55	PK	V	32.90	1.38	37.01	43.82	74.00	30.18
4880.00	36.69	AV	V	32.90	1.38	37.01	33.96	54.00	20.04
7320.00	45.78	PK	H	36.27	2.46	36.53	47.98	74.00	26.02
7320.00	35.36	AV	H	36.27	2.46	36.53	37.56	54.00	16.44
7320.00	45.32	PK	V	36.27	2.46	36.53	47.52	74.00	26.48
7320.00	35.61	AV	V	36.27	2.46	36.53	37.81	54.00	16.19

BLE 1M_high channel Frequency **2480** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
2483.50	26.26	PK	H	28.03	0.92	0.00	55.21	74.00	18.79
2483.50	15.36	AV	H	28.03	0.92	0.00	44.31	54.00	9.69
2483.50	25.76	PK	V	28.03	0.92	0.00	54.71	74.00	19.29
2483.50	15.65	AV	V	28.03	0.92	0.00	44.60	54.00	9.40
4960.00	47.37	PK	H	32.97	1.42	36.71	45.05	74.00	28.95
4960.00	36.55	AV	H	32.97	1.42	36.71	34.23	54.00	19.77
4960.00	46.83	PK	V	32.97	1.42	36.71	44.51	74.00	29.49
4960.00	36.63	AV	V	32.97	1.42	36.71	34.31	54.00	19.69
7440.00	47.19	PK	H	36.56	2.53	36.45	49.83	74.00	24.17
7440.00	36.44	AV	H	36.56	2.53	36.45	39.08	54.00	14.92
7440.00	46.45	PK	V	36.56	2.53	36.45	49.09	74.00	24.91
7440.00	35.68	AV	V	36.56	2.53	36.45	38.32	54.00	15.68

BLE 2M_low channel Frequency **2402** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
2390.00	25.36	PK	H	27.64	0.93	0.00	53.93	74.00	20.07
2390.00	15.50	AV	H	27.64	0.93	0.00	44.07	54.00	9.93
2390.00	25.67	PK	V	27.64	0.93	0.00	54.24	74.00	19.76
2390.00	15.61	AV	V	27.64	0.93	0.00	44.18	54.00	9.82
4804.00	47.57	PK	H	32.84	1.38	37.30	44.49	74.00	29.51
4804.00	36.68	AV	H	32.84	1.38	37.30	33.60	54.00	20.40
4804.00	47.97	PK	V	32.84	1.38	37.30	44.89	74.00	29.11
4804.00	36.46	AV	V	32.84	1.38	37.30	33.38	54.00	20.62
7206.00	45.56	PK	H	35.99	2.39	36.61	47.33	74.00	26.67
7206.00	35.69	AV	H	35.99	2.39	36.61	37.46	54.00	16.54
7206.00	45.51	PK	V	35.99	2.39	36.61	47.28	74.00	26.72
7206.00	35.31	AV	V	35.99	2.39	36.61	37.08	54.00	16.92

BLE 2M_middle channel Frequency **2440** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
4880.00	46.83	PK	H	32.90	1.38	37.01	44.10	74.00	29.90
4880.00	36.35	AV	H	32.90	1.38	37.01	33.62	54.00	20.38
4880.00	46.83	PK	V	32.90	1.38	37.01	44.10	74.00	29.90
4880.00	36.00	AV	V	32.90	1.38	37.01	33.27	54.00	20.73
7320.00	45.84	PK	H	36.27	2.46	36.53	48.04	74.00	25.96
7320.00	36.01	AV	H	36.27	2.46	36.53	38.21	54.00	15.79
7320.00	46.00	PK	V	36.27	2.46	36.53	48.20	74.00	25.80
7320.00	35.51	AV	V	36.27	2.46	36.53	37.71	54.00	16.29

BLE 2M_high channel Frequency **2480** MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
			Polar	Factor					
MHz	dBµV	PK/QP/AV	H/V	dB/m	dB	dB	dBµV/m	dBµV/m	dB
2483.50	25.87	PK	H	28.03	0.92	0.00	54.82	74.00	19.18
2483.50	15.50	AV	H	28.03	0.92	0.00	44.45	54.00	9.55
2483.50	25.94	PK	V	28.03	0.92	0.00	54.89	74.00	19.11
2483.50	15.77	AV	V	28.03	0.92	0.00	44.72	54.00	9.28
4960.00	47.00	PK	H	32.97	1.42	36.71	44.68	74.00	29.32
4960.00	37.36	AV	H	32.97	1.42	36.71	35.04	54.00	18.96
4960.00	47.17	PK	V	32.97	1.42	36.71	44.85	74.00	29.15
4960.00	36.54	AV	V	32.97	1.42	36.71	34.22	54.00	19.78
7440.00	46.27	PK	H	36.56	2.53	36.45	48.91	74.00	25.09
7440.00	36.85	AV	H	36.56	2.53	36.45	39.49	54.00	14.51
7440.00	46.35	PK	V	36.56	2.53	36.45	48.99	74.00	25.01
7440.00	36.51	AV	V	36.56	2.53	36.45	39.15	54.00	14.85

5.3 Spot Check With Maximum Conducted Output Power

Serial No.:	2GZ2-3	Test Date:	2024/4/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Alice Tan	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
-----------------------------	----	----------------------------------	----	-------------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY54170006	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/9/10	2024/9/9

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Channel	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1Mbps	2402	6.31	30
	2440	6.25	30
	2480	6.58	30
BLE 2Mbps	2402	6.35	30
	2440	6.28	30
	2480	6.49	30

5.4 Duty Cycle

Serial No.:	2GZ2-3	Test Date:	2024/4/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Alice Tan	Test Result:	/

Environmental Conditions:

Temperature: (°C)	27	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
-----------------------------	----	----------------------------------	----	-------------------------------	-----



Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/9/10	2024/9/9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Mode	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
BLE 1Mbps	0.435	1.246	34.91	2299	3
BLE 2Mbps	0.232	0.626	37.06	4310	5



APPENDIX A - EUT PHOTOGRAPHS

Please refer to the attachment XMDN240122-04868E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and XMDN240122-04868E-RF-INP EUT INTERNAL PHOTOGRAPHS

APPENDIX B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment XMDN240122-04868E-RF-00C-TSP TEST SETUP PHOTOGRAPHS.

APPENDIX C - RF EXPOSURE EVALUATION

Applicable Standard

According to subpart §1.1310,15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Operation Mode	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Bluetooth	2402-2480	1.04	1.27	10	10.00	20.00	0.00253	1.0
2.4G Wifi	2412-2462	1.04	1.27	18	63.10	20.00	0.01596	1.0
5G Wifi	5150-5250	0.35	1.08	18	63.10	20.00	0.01361	1.0
	5250-5350	1.61	1.45	18	63.10	20.00	0.01819	1.0
	5470-5725	2.39	1.73	18	63.10	20.00	0.02177	1.0
	5725-5850	0.3	1.07	18	63.10	20.00	0.01346	1.0

Note:

The Conducted output power including Tune-up Tolerance provided by manufacturer.

The Bluetooth BDR/EDR / BLE /2.4G Wifi / 5G Wifi can't transmit simultaneously.

Result: Compliant. The devices meet FCC MPE at 20 cm distance

******* END OF REPORT *******