

# ELECTRONICS TESTING CENTER, TAIWAN

NO. 8, LANE 29, WEN-MING RD.,  
LO-SHAN TSUN. KUI-SHAN  
HSIANG, TAOYUAN HSIEN  
333, TAIWAN, R. O. C.

Tel:(03)3280026  
Fax:(03)3280034

TUV SUD BABT TCB  
Octagon House,  
Segensworth Road,  
Fareham,  
Hampshire,  
PO15 5RL

Date: 17/10/2017

## **Declaration of KDB680106 Compliance**

**FCC ID: 2AM78-TW-201**

According to KDB680106 D01v02, Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

	Requirements	EUT Conditions	Comply (Y/N)
1	Power transfer frequency is less than 1 MHz	Power transfer frequency is 162 kHz.	Y
2	Output power from each primary coil is less than 5 watts	Output power is less than 5 watts.	Y
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils	The transfer system includes only single primary and secondary coils.	Y
4	Client device is inserted in or placed directly in contact with the transmitter	Client device is placed directly in contact with the transmitter.	Y
5	The maximum coupling surface area of the transmit (charging) device is between 60 cm <sup>2</sup> and 400 cm <sup>2</sup> .	The maximum coupling surface area of the transmit (charging) device is 70 cm <sup>2</sup> .	Y
6	Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.	Aggregate leakage fields at 10 cm surrounding the device is less than 30% of the MPE limit. Refer to MPE evaluations.	Y

Yours sincerely,



Name: S. S. Liou

Title: Section Manager of EMC Testing Department II, Electronics Testing Center, Taiwan