





## No. I19Z61642-SEM03

For

Wiko SAS

**Smart Phone** 

Model name: U307AS

With

Hardware Version: V1.0

Software Version: U307ASV01.11.10

**FCC ID: 2AM86U307AS** 

## Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

## **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT


No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504


Email: <a href="mailto:cttl">cttl</a> terminals@caict.ac.cn, website: <a href="mailto:www.caict.ac.cn">www.caict.ac.cn</a>



Picture 1: Constituents of the sample



**Picture 2: Left Hand Touch Cheek Position** 



Picture 3: Left Hand Tilt 15° Position



Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

## Test positions for body:


The Body SAR is tested at the following 8 test positions all with the distance =10/15mm between the EUT and the phantom bottom:




Picture 6: Front 10mm




Picture 7: Front 15mm




Picture 8: Rear 10mm




Picture 9: Rear 15mm




Picture 10: Left 10mm



Picture 11: Right 10mm



Picture 12: Top 10mm



Picture 13: Bottom 10mm