



# TEST REPORT

**APPLICANT** : WIKO SAS  
**PRODUCT NAME** : Smart phone  
**MODEL NAME** : VHEM-E04  
**BRAND NAME** : WIKO  
**FCC ID** : 2AM86VHEM-E04  
**STANDARD(S)** : 47 CFR Part 15 Subpart E  
**RECEIPT DATE** : 2022-05-17  
**TEST DATE** : 2022-05-17 to 2022-06-09  
**ISSUE DATE** : 2022-06-13

Edited by: Peng Mi  
Peng Mi (Rapporteur)

Approved by: Shen Junsheng  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 3**
- 1.1. Applicant and Manufacturer Information ..... 3**
- 1.2. Equipment Under Test (EUT) Description ..... 3**
- 1.3. Modulation Type and Data Rate of EUT ..... 5**
- 1.4. The Channel Number and Frequency ..... 6**
- 1.5. Test Standards and Results ..... 7**
- 1.6. Environmental Conditions ..... 8**
- 2. 47 CFR Part 15E Requirements ..... 9**
- 2.1. Antenna Requirement ..... 9**
- 2.2. Duty Cycle of the Test Signal ..... 10**
- 2.3. Maximum Conducted Output Power ..... 15**
- 2.4. Emission Bandwidth ..... 20**
- 2.5. Peak Power Spectral Density ..... 59**
- 2.6. Frequency Stability ..... 100**
- 2.7. Conducted Emission ..... 103**
- 2.8. Restricted Frequency Bands ..... 107**
- 2.9. Radiated Emission ..... 125**
- Annex A Test Uncertainty ..... 155**
- Annex B Testing Laboratory Information ..... 156**

Change History		
Version	Date	Reason for change
1.0	2022-06-13	First edition



# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	WIKO SAS
<b>Applicant Address:</b>	132 Boulevard Michelet 13008 Marseille - France
<b>Manufacturer:</b>	WIKO SAS
<b>Manufacturer Address:</b>	132 Boulevard Michelet 13008 Marseille - France

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Smart phone	
<b>Sample No.:</b>	9#	
<b>Hardware Version:</b>	V0.4	
<b>Software Version:</b>	VHEM-V01.04-12.0-STS	
<b>Modulation Technology:</b>	OFDM	
<b>Modulation Mode:</b>	802.11a, 802.11n (HT20), 802.11n (HT40) 802.11ac (VHT20), 802.11ac (VHT40), 802.11ac (VHT80)	
<b>Operating Frequency Range:</b>	5180MHz-5240MHz; 5260MHz-5320MHz; 5500MHz-5720MHz; 5745MHz-5825MHz	
<b>Channel Number:</b>	Refer to 1.3	
<b>Antenna Type:</b>	IFA Antenna	
<b>Antenna Gain:</b>	0.40dBi	
<b>Accessory Information:</b>	Battery	
	<b>Brand Name:</b>	N/A
	<b>Model No.:</b>	HB496590EFW-F
	<b>Serial No.:</b>	N/A
	<b>Capacity:</b>	4900mAh
	<b>Rated Voltage:</b>	3.87V
	<b>Charge Limit:</b>	4.45V
	<b>Manufacturer:</b>	SCUD (Fujian) Electronics Co., Ltd.



<b>Accessory Information:</b>	AC Adapter	
	Brand Name:	WIKO
	Model No.:	SU1A24
	Serial No.:	N/A
	Rated Output:	5.0V=2.0A, 9.0V=2.0A, 10.0V=2.25A
	Rated Input:	100-240V~50/60Hz, 0.75A
	Manufacturer:	Shenzhen Huntkey Electric Co., Ltd.
	USB Cable 1	
	Model No.:	04072179
	Manufacturer:	Guangxi broad Telecommunication Co.,Ltd.
	USB Cable 2	
	Model No.:	04072295
	Manufacturer:	Guangdong Mingji Hi-Tech Electronics Co., Ltd
	USB Cable 3	
	Model No.:	18-93C2CHO-001HF
	Manufacturer:	Freeport Ji an Electronics Co.,Ltd
	USB Cable 4	
	Model No.:	L99UC131-CS-H
	Manufacturer:	LUXSHARE PRECISION INDUSTRY CO., LTD.
	USB Cable 5	
Model No.:	CUDU01B-HC295-EH	
Manufacturer:	FUYU ELECTRONICAL TECHNOLOGY (HUAIAN) CO., LTD.	

**Note 1:** We use the dedicated software to control the EUT continuous transmission.

**Note 2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.3. Modulation Type and Data Rate of EUT

Modulation Technology	Modulation Type	Data Rate (Mbps) <sup>Note1</sup>
OFDM (802.11a)	BPSK	<b>6/9</b>
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n)	BPSK	<b>6.5</b>
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11ac)	BPSK	<b>6.5</b>
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
	256QAM	78

**Note1:** The worst-case mode (black bold) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

## 1.4. The Channel Number and Frequency

<b>(U-NII-1) 5180MHz-5240MHz</b>				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	<b>36</b>	<b>5180</b>	40	5200
	<b>44</b>	<b>5220</b>	<b>48</b>	<b>5240</b>
40MHz	<b>38</b>	<b>5190</b>	<b>46</b>	<b>5230</b>
80MHz	<b>42</b>	<b>5210</b>		
<b>(U-NII-2A) 5260MHz-5320MHz</b>				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	<b>52</b>	<b>5260</b>	56	5280
	<b>60</b>	<b>5300</b>	<b>64</b>	<b>5320</b>
40MHz	<b>54</b>	<b>5270</b>	<b>62</b>	<b>5310</b>
80MHz	<b>58</b>	<b>5290</b>		
<b>(U-NII-2C) 5500MHz-5720MHz</b>				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	<b>100</b>	<b>5500</b>	105	5520
			108	5540
			116	5580
			124	5620
			132	5660
			140	<b>144</b>
40MHz	<b>102</b>	<b>5510</b>	110	5550
			118	5590
			134	<b>142</b>
80MHz	<b>106</b>	<b>5530</b>	<b>122</b>	<b>5610</b>
	<b>138</b>	<b>5690</b>		
<b>(U-NII-3) 5745MHz-5825MHz</b>				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	<b>149</b>	<b>5745</b>	153	5765
	<b>157</b>	<b>5785</b>	161	5805
	<b>165</b>	<b>5825</b>		
40MHz	<b>151</b>	<b>5775</b>	<b>159</b>	<b>5795</b>
80MHz	<b>155</b>	<b>5775</b>		

**Note 1:** The black bold channels were selected for test.



## 1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart E (U-NII band) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15(5-1-14 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	ANSI C63.10	Duty Cycle of the Test Signal	May 18, 2022	Su Xiaoxian	PASS	No deviation
3	15.407(a)	Maximum Conducted Output Power	Jun. 09, 2022	Su Xiaoxian	PASS	No deviation
4	15.407(a) (e)	Emission Bandwidth	May 26, 2022	Su Xiaoxian	PASS	No deviation
5	15.407(a)	Peak Power Spectral Density	May 26, 2022	Su Xiaoxian	PASS	No deviation
6	15.407(g)	Frequency Stability	May 27, 2022	Su Xiaoxian	PASS	No deviation
7	15.207	Conducted Emission	May 19, 2022	Wu Zhaoling	PASS	No deviation
8	15.407(b)	Restricted Frequency Bands	Jun. 05, 2022	Su Zhan	PASS	No deviation
9	15.407(b)	Radiated Emission	Jun. 07, 2022	Su Zhan	PASS	No deviation

**Note 1:** The DFS test report was documented in a separate report (Report No.: SZ22050016W06).

**Note 2:** The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.102013.

**Note 3:** These RF tests were performed according to the method of measurements prescribed in KDB789033 D02 v02r01.



**Note 4:** The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12.0dB contains two parts that cable loss 2.0dB and Attenuator 10dB.

**Note 5:** Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

**Note 6:** When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

## 1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106





## 2.47 CFR Part 15E Requirements

### 2.1. Antenna Requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Test Result: Compliant

Inside of the EUT has a IFA antenna coupled with the metal shrapnel. Please refer to the EUT internal photos.

## 2.2. Duty Cycle of the Test Signal

### 2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be nonconstant.

### 2.2.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

### 2.2.3. Test Procedure

KDB 789033 Section B was used in order to prove compliance.




2.2.4. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*log[1/D])
802.11a	96.88	0.14
802.11n (HT20)	96.65	0.15
802.11n (HT40)	93.53	0.29
802.11ac (VHT20)	96.68	0.15
802.11ac (VHT40)	93.57	0.29
802.11ac (VHT80)	87.67	0.57


B. Test Plot:




(Channel 36, 5180MHz, 802.11a)




(Channel 36, 5180MHz, 802.11n (HT20))




(Channel 38, 5190MHz, 802.11n (HT40))



(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 38, 5190MHz, 802.11ac (VHT40))



(Channel 42, 5210MHz, 802.11ac (VHT80))

## 2.3. Maximum Conducted Output Power

### 2.3.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


(4) According to KDB662911D01 Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.

(5) According to KDB 662911 D01, the directional gain =  $G_{\text{ANT}} + 10\log(N_{\text{ANT}})\text{dBi}$ , where  $G_{\text{ANT}}$  is the antenna gain in dBi,  $N_{\text{ANT}}$  is the number of outputs.

### 2.3.2. Test Description


Section E) 3) of KDB 789033 defines a methodology using a USB Wideband Power Sensor.

#### Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in USB Wideband Power Sensor.

**For ac (VHT80) mode power**



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

**2.3.3. Limits**

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

Mode	Band	Channel (MHz)	26dB BW (MHz)	11+10log(26dB BW)	Limits (dBm)
a	UNII-2a	5260	21.53	24.33	24.33
		5300	19.76	23.96	23.96
		5320	21.76	24.38	24.38
	UNII-2c	5500	23.45	24.70	24.70
		5600	21.04	24.23	24.23
		5720	21.83	24.39	24.39
n20	UNII-2a	5260	23.35	24.68	24.68
		5300	21.38	24.30	24.30
		5320	20.64	24.15	24.15
	UNII-2c	5500	21.56	24.34	24.34
		5600	23.86	24.78	24.78
		5720	22.09	24.44	24.44
ac20	UNII-2a	5260	20.15	24.04	24.04
		5300	20.49	24.12	24.12
		5320	20.14	24.04	24.04
	UNII-2c	5500	20.07	24.03	24.03
		5600	22.55	24.53	24.53
		5720	20.03	24.02	24.02





2.3.4. Test Result

Maximum Average Conducted Output Power

802.11a Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5180	12.43	0.14	12.57	0.018	24	0.25	PASS
5220	12.52		12.66	0.018			
5240	12.39		12.53	0.018			
5260	11.89		12.03	0.016			
5300	11.70		11.84	0.015			
5320	11.82		11.96	0.016			
5500	11.38		11.52	0.014			
5600	11.34		11.48	0.014			
5700	10.72		10.86	0.012			
5745	10.21		10.35	0.011	30	1	
5785	9.66		9.80	0.010			
5825	9.45		9.59	0.009			

802.11n (HT20) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5180	11.23	0.15	11.38	0.014	24	0.25	PASS
5220	11.45		11.60	0.014			
5240	11.10		11.25	0.013			
5260	10.64		10.79	0.012			
5300	10.51		10.66	0.012			
5320	10.63		10.78	0.012			
5500	10.42		10.57	0.011			
5600	9.95		10.10	0.010			
5700	9.41		9.56	0.009			
5745	8.71		8.86	0.008	30	1	
5785	8.40		8.55	0.007			
5825	8.15		8.30	0.007			



**802.11n (HT40) Mode**

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5190	10.87	0.29	11.16	0.013	24	0.25	PASS
5230	10.94		11.23	0.013			
5270	10.28		10.57	0.011			
5310	10.24		10.53	0.011			
5510	10.02		10.31	0.011			
5630	9.64		9.93	0.010			
5670	9.25		9.54	0.009			
5755	8.44		8.73	0.007	30	1	
5795	8.04		8.33	0.007			

**802.11ac (VHT20) Mode**

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5180	11.02	0.15	11.17	0.013	24	0.25	PASS
5220	11.03		11.18	0.013			
5240	11.10		11.25	0.013			
5260	10.57		10.72	0.012			
5300	10.45		10.60	0.011			
5320	10.49		10.64	0.012			
5500	10.05		10.20	0.010			
5600	10.01		10.16	0.010			
5700	9.69		9.84	0.010			
5745	8.79		8.94	0.008	30	1	
5785	8.40		8.55	0.007			
5825	8.09		8.24	0.007			



**802.11ac (VHT40) Mode**

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5190	10.37	0.29	10.66	0.012	24	0.25	PASS
5230	10.42		10.71	0.012			
5270	9.83		10.12	0.010			
5310	9.74		10.03	0.010			
5510	9.88		10.17	0.010			
5630	9.68		9.97	0.010			
5670	8.62		8.91	0.008			
5755	8.28		8.57	0.007	30	1	
5795	7.55		7.84	0.006			

**802.11ac (VHT80) Mode**

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated		dBm	W	
	dBm		dBm	W			
5210	8.08	0.57	8.65	0.007	24	0.25	PASS
5290	7.57		8.14	0.007			
5530	8.10		8.67	0.007			
5610	7.11		7.68	0.006			
5690	6.95		7.52	0.006			
5775	7.72		8.29	0.007	30	1	


## 2.4. Emission Bandwidth

### 2.4.1. Requirement

For purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement. Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

### 2.4.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

### 2.4.3. Test Procedure

1. KDB 789033 Section C) 1) Emission Bandwidth was used in order to prove compliance
  - a) Set RBW = approximately 1% of the emission bandwidth.
  - b) Set VBW > RBW.
  - c) Detector = Peak.
  - d) Trace mode = max hold.
  - e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
2. KDB 789033 Section C) 2) minimum emission bandwidth for the band 5.725-5.85GHz was used in order to prove compliance.  
Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:



- a) Set RBW = 100 kHz.
- b) Set video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 2.4.4. Test Result


##### 802.11a Mode

##### A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	30.00
44	5220	20.49
48	5240	23.03
52	5260	21.53
60	5300	19.76
64	5320	21.76
100	5500	23.45
120	5600	21.04
144	5720	21.83
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	15.10
149	5745	15.68
157	5785	15.41
165	5825	14.71



B. Test Plot:



(Channel 36, 5180MHz, 802.11a)




(Channel 44, 5220 MHz, 802.11a)



(Channel 48, 5240MHz, 802.11a)



(Channel 52, 5260MHz, 802.11a)



(Channel 60, 5300 MHz, 802.11a)



(Channel 64, 5320MHz, 802.11a)





(Channel 100, 5500 MHz, 802.11a)




(Channel 120, 5600 MHz, 802.11a)



(Channel 144, 5720MHz, 802.11a)




(Channel 144, 5720MHz, 802.11a)



(Channel 149, 5745MHz, 802.11a)



(Channel 157, 5785MHz, 802.11a)



(Channel 165, 5825MHz, 802.11a)



802.11n (HT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	20.88
44	5220	22.86
48	5240	23.82
52	5260	23.35
60	5300	21.38
64	5320	20.64
100	5500	21.56
120	5600	23.86
144	5720	22.09
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	15.38
149	5745	14.66
157	5785	15.98
165	5825	15.04

B. Test Plot:




(Channel 36, 5180MHz, 802.11n (HT20))



(Channel 44, 5220MHz, 802.11n (HT20))




(Channel 48, 5240MHz, 802.11n (HT20))



(Channel 52, 5260MHz, 802.11n (HT20))



(Channel 60, 5300MHz, 802.11n (HT20))




(Channel 64, 5320MHz, 802.11n (HT20))



(Channel 100, 5500MHz, 802.11n (HT20))





(Channel 120, 5600MHz, 802.11n (HT20))




(Channel 144, 5720MHz, 802.11n (HT20))



(Channel 144, 5720MHz, 802.11n (HT20))



(Channel 149, 5745MHz, 802.11 n (HT20))



(Channel 157, 5785MHz, 802.11 n (HT20))



(Channel 165, 5825MHz, 802.11 n (HT20))



802.11n (HT40) Test mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	41.76
46	5230	39.96
54	5270	40.32
62	5310	42.07
102	5510	40.44
126	5630	40.41
142	5710	40.80
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	35.06
151	5755	35.08
159	5795	35.01

B. Test Plot:



(Channel 38, 5190MHz, 802.11n (HT40))




(Channel 46, 5230MHz, 802.11n (HT40))




(Channel 54, 5270MHz, 802.11n (HT40))



(Channel 62, 5310MHz, 802.11n (HT40))




(Channel 102, 5510MHz, 802.11n (HT40))




(Channel 126, 5630MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))




(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 151, 5755MHz, 802.11n (HT40))





(Channel 159, 5795MHz, 802.11n (HT40))



802.11ac (VHT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	20.45
44	5220	20.26
48	5240	20.45
52	5260	20.15
60	5300	20.49
64	5320	20.14
100	5500	20.07
120	5600	22.55
144	5720	20.03
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	15.32
149	5745	13.55
157	5785	17.01
165	5825	13.77

B. Test Plot:



(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 44, 5220MHz, 802.11ac (VHT20))



(Channel 48, 5240MHz, 802.11ac (VHT20))



(Channel 52, 5260MHz, 802.11ac (VHT20))




(Channel 60, 5300MHz, 802.11ac (VHT20))



(Channel 64, 5320MHz, 802.11ac (VHT20))



(Channel 100, 5500MHz, 802.11ac (VHT20))




(Channel 120, 5600MHz, 802.11ac (VHT20))




(Channel 144, 5720MHz, 802.11ac (VHT20))



(Channel 144, 5720MHz, 802.11ac (VHT20))



(Channel 149, 5745MHz, 802.11 ac (VHT20))



(Channel 157, 5785MHz, 802.11 ac (VHT20))



(Channel 165, 5825MHz, 802.11 ac (VHT20))





802.11ac (VHT40) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	40.33
46	5230	40.05
54	5270	40.01
62	5310	40.14
102	5510	39.92
126	5630	40.10
142	5710	40.19
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	32.55
151	5755	32.62
159	5795	35.05

B. Test Plot:




(Channel 38, 5190MHz, 802.11ac (VHT40))



(Channel 46, 5230MHz, 802.11ac (VHT40))




(Channel 54, 5270MHz, 802.11ac (VHT40))



(Channel 62, 5310MHz, 802.11ac (VHT40))




(Channel 102, 5510MHz, 802.11ac (VHT40))



(Channel 126, 5630MHz, 802.11ac (VHT40))




(Channel 142, 5710MHz, 802.11ac (VHT40))



(Channel 142, 5710MHz, 802.11ac (VHT40))



(Channel 151, 5755MHz, 802.11ac (VHT40))



(Channel 159, 5795MHz, 802.11ac (VHT40))




802.11ac (VHT80) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
42	5210	81.02
58	5290	80.77
106	5530	79.97
122	5610	80.08
138	5690	80.34
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
138	5690	75.07
155	5775	75.11

B. Test Plot:



(Channel 42, 5210MHz, 802.11ac (VHT80))




(Channel 58, 5290MHz, 802.11ac (VHT80))



(Channel 106, 5530MHz, 802.11ac (VHT80))







(Channel 122, 5610MHz, 802.11ac (VHT80))



(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 155, 5775MHz, 802.11ac (VHT80))

## 2.5. Peak Power Spectral Density

### 2.5.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30dBm in any 500kHz band.


If transmitting antennas of directional gain greater than 6dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(4) According to KDB662911D01 Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.

(5) According to KDB 662911 D01, the directional gain =  $G_{ANT} + 10\log(N_{ANT})$  dBi, where  $G_{ANT}$  is the antenna gain in dBi,  $N_{ANT}$  is the number of outputs.

### 2.5.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



**2.5.3. Test Procedure**

KDB 789033 Section F) Maximum Power Spectral Density (PSD) Method SA-3 was used in order to prove compliance

- 1) Set span to encompass the entire 26-dB emission bandwidth
- 2) Set RBW = 1MHz. Set VBW ≥ 3MHz
- 3) Number of points in sweep ≥ 2 Span / RBW. Sweep time = auto
- 4) Detector = Average
- 5) Trace mode=Max hold
- 6) Record the max value

**2.5.4. Test Result**

**802.11a Mode**

**A. Test Verdict:**

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
36	5180	8.94	0.14	9.08	11	PASS
44	5220	8.89		9.03		
48	5240	8.85		8.99		
52	5260	8.78		8.92		
60	5300	8.22		8.36		
64	5320	8.39		8.53		
100	5500	7.69		7.83		
120	5600	7.16		7.30		
144	5720	7.14		7.28		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
144	5720	4.40	0.14	4.54	30	PASS
149	5745	4.85		4.99		
157	5785	4.51		4.65		
165	5825	3.89		4.03		



B. Test Plot:



(Channel 36, 5180MHz, 802.11a)



(Channel 44, 5220MHz, 802.11a)



(Channel 48, 5240MHz, 802.11a)



(Channel 52, 5260MHz, 802.11a)



(Channel 60, 5300MHz, 802.11a)



(Channel 64, 5320MHz, 802.11a)



(Channel 100, 5500MHz, 802.11a)



(Channel 120, 5600MHz, 802.11a)





(Channel 144, 5720MHz, 802.11a)



(Channel 144, 5720MHz, 802.11a)



(Channel 149, 5745MHz, 802.11a)



(Channel 157, 5785MHz, 802.11a)



(Channel 165, 5825MHz, 802.11a)



**802.11n (HT20) Mode**

**A. Test Verdict:**

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
36	5180	6.96	0.06	7.11	11	PASS
44	5220	6.99		7.14		
48	5240	7.02		7.17		
52	5260	6.93		7.08		
60	5300	7.10		7.25		
64	5320	7.08		7.23		
100	5500	6.37		6.52		
120	5600	5.81		5.96		
144	5720	5.82		5.97		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
144	5720	3.20	0.06	3.35	30	PASS
149	5745	3.55		3.70		
157	5785	3.18		3.33		
165	5825	2.54		2.69		

**B. Test Plot:**



(Channel 36, 5180MHz, 802.11n (HT20))



(Channel 44, 5220MHz, 802.11n (HT20))



(Channel 48, 5240MHz, 802.11n (HT20))




(Channel 52, 5260MHz, 802.11n (HT20))



(Channel 60, 5300MHz, 802.11n (HT20))



(Channel 64, 5320MHz, 802.11n (HT20))



(Channel 100, 5500MHz, 802.11n (HT20))



(Channel 120, 5600MHz, 802.11n (HT20))






(Channel 144, 5720MHz, 802.11n (HT20))



(Channel 144, 5720MHz, 802.11n (HT20))



(Channel 149, 5745MHz, 802.11n (HT20))



(Channel 157, 5785MHz, 802.11n (HT20))



(Channel 165, 5825MHz, 802.11n (HT20))



**802.11n (HT40) Mode**

**A. Test Verdict:**

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
38	5190	4.42	0.29	4.71	11	PASS
46	5230	4.65		4.94		
54	5270	4.29		4.58		
62	5310	4.36		4.65		
102	5510	3.74		4.03		
126	5630	3.18		3.47		
142	5710	3.18		3.47		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
142	5710	0.48	0.29	0.77	30	PASS
151	5755	0.69		0.98		
159	5795	0.33		0.62		

**B. Test Plot:**



(Channel 38, 5190MHz, 802.11n (HT40))



(Channel 46, 5230MHz, 802.11n (HT40))



(Channel 54, 5270MHz, 802.11n (HT40))



(Channel 62, 5310MHz, 802.11n (HT40))



(Channel 102, 5510MHz, 802.11n (HT40))