## RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

FCC ID	2AM87-HY91
Model Name	HY-91, HY-62, HY-63, HY-65, HY-86, HY-90, HY-92, HY-93, HY-95, HY-96, HY-98, T19, C18, C20, C21, C22, C23, C26, C28, C30, C32, C33, C35, C36
Product Description	BLUETOOTH FM TRANSMITTER

# 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

# 3. CALCULATION

According to the follow transmitter output power ( $P_t$ ) formula:  $P_t$ = ( $E \times d$ )  $^2$ / ( $30 \times g_t$ )  $P_t$ =transmitter output power in watts  $g_t$ =numeric gain of the transmitting antenna (unitess) E=electric field strength in V/m d=measurement distance in meters (m)

BT Pt= 2.308dBm=1.701mW

The result for RF exposure evaluation  $SAR=(1.701 \text{mW} /5 \text{mm}) .[\sqrt{2.48}(GHz)] = 0.536 < 3.0 \text{ for } 1-g SAR$ 

FM Pt=0.0000062mW
The result for RF exposure evaluation
SAR=(0.0000062mW /5mm) .[√0.1079(GHz)]= 0.00000041<3.0 for 1-g SAR

Simultaneous transmission between Bluetooth and FM transmitter [(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] • [  $\sqrt{f(GHz)/x}$ ] W/kg, for test separation distances  $\leq$  50 mm; where x = 7.5 for 1-g SAR and x = 18.75 for 10-g SAR.

SAR=(0.527+0.00000041)/7.5=0.070W/kg<1.6W/kg

### 4. CONCLUSION

The SAR evaluation is not required.