

# MPE REPORT

FCC ID: 2AM87-AV83

Date of issue: Mar. 02, 2020


Report number:	MTi19123009-3E3
Sample description:	CAR FM TRANSMITTER
Model(s):	AV839, C89S, C88, BTFM1IS, MNCA102
Applicant:	INTRO UNION ELECTRONICS CO, LIMITED
Address:	6F, F BUILDING, EAST AREA NO.8, SHANGXUE TECH-CITY, BANTIAN, LONGGANG, SHENZHEN, China
Date of test:	Jan. 02, 2020 – Feb. 28, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

<b>TEST RESULT CERTIFICATION</b>	
Applicant's name:	INTRO UNION ELECTRONICS CO, LIMITED
Address:	6F, F BUILDING, EAST AREA NO.8, SHANGXUE TECH-CITY, BANTIAN, LONGGANG, SHENZHEN, China
Manufacture's name:	INTRO UNION ELECTRONICS CO, LIMITED
Address:	6F, F BUILDING, EAST AREA NO.8, SHANGXUE TECH-CITY, BANTIAN, LONGGANG, SHENZHEN, China
Product name:	CAR FM TRANSMITTER
Trademark:	N/A
Model and/or type reference .:	AV839
Serial model.....:	C89S, C88, BTFM1IS, MNCA102
RF exposure procedures.....:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by: 

---

Demi Mu                      Feb. 28, 2020

Reviewed by: 

---

Leo Su                         Mar. 02, 2020

Approved by: 

---

Tom Xue                        Mar. 02, 2020

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

**BT:**

Operation Frequency: BT 2402-2480MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: BT Antenna: PCB Antenna;

WIFI antenna gain: 0dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(0/10)}=1$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-0.12	-1±1	0	1.000	0.00	1.00	0.0002	1
2441		-0.2	-1±1	0	1.000	0.00	1.00	0.0002	1
2480		0.29	-1±1	0	1.000	0.00	1.00	0.0002	1
2402	π/4-DQPSK	-1.21	-1±1	0	1.000	0.00	1.00	0.0002	1
2441		-1.347	-1±1	0	1.000	0.00	1.00	0.0002	1
2480		-1.1	-1±1	0	1.000	0.00	1.00	0.0002	1
2402	8DPSK	-0.72	-1±1	0	1.000	0.00	1.00	0.0002	1
2441		-0.77	-1±1	0	1.000	0.00	1.00	0.0002	1
2480		-0.41	-1±1	0	1.000	0.00	1.00	0.0002	1

### Conclusion:

For the max result: 0.0002 ≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----