

FCC RF Test Report

APPLICANT : Relay, Inc.
EQUIPMENT : Relay
BRAND NAME : Relay
MODEL NAME : RY2268
FCC ID : 2AMBHRY2268
STANDARD : 47 CFR Part 2, Part 27 Subpart Q
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Nov. 29, 2023 ~ Apr. 18, 2024

We, Sporton International Inc. (KunShan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (KunShan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Maximum EIRP Power and Emission Designator	6
1.7 Testing Site	7
1.8 Test Software.....	8
1.9 Applied Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode	9
2.2 Connection Diagram of Test System.....	10
2.3 Support Unit used in test configuration and system	10
2.4 Measurement Results Explanation Example.....	10
2.5 Frequency List of Low/Middle/High Channels	11
3 CONDUCTED TEST ITEMS	12
3.1 Measuring Instruments	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test	12
3.4 Conducted Output Power Measurement	13
3.5 Peak-to-Average Ratio	14
3.6 EIRP	15
3.7 Occupied Bandwidth.....	16
3.8 Conducted Band Edge Measurement	17
3.9 Conducted Spurious Emission Measurement	18
3.10 Frequency Stability Measurement.....	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test	21
4.4 Radiated Spurious Emission Measurement	22
5 LIST OF MEASURING EQUIPMENT	23
6 MEASUREMENT UNCERTAINTY	24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG250507P	Rev. 01	Initial issue of report	May 30, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 16.91 dB at 10356.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Relay, Inc.

4200 Six Forks Rd, Suite 1800, Raleigh, NC 27609, USA

1.2 Manufacturer

Relay, Inc.

4200 Six Forks Rd, Suite 1800, Raleigh, NC 27609, USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Relay
Brand Name	Relay
Model Name	RY2268
FCC ID	2AMBHRY2268
IMEI Code	Conducted : 004400152020000 Radiation : 990007570009388/990007570004066
HW Version	v01
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx/Rx Frequency	5G NR n77: 3450 MHz ~ 3550 MHz 5G NR n78: 3450 MHz ~ 3550 MHz
SCS	30kHz
Bandwidth	n77/n78 SA mode & n78 NSA mode: 10 / 15 / 20 / 25 / 30 / 40 / 50 / 60 / 70 / 80 / 90 / 100MHz n77 NSA mode: 10 / 15 / 20 / 30 / 40 / 50 / 60 / 70 / 80 / 90 / 100MHz
Antenna Gain	<Ant. 1> 5G NR n77: 0.1 dBi 5G NR n78: 0.1 dBi <Ant. 2> 5G NR n77: 0.3 dBi 5G NR n78: 0.3 dBi <Ant. 8> 5G NR n77: -2.00 dBi 5G NR n78: -2.00 dBi <Ant. 9> 5G NR n77: -2.86 dBi 5G NR n78: -2.86 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The device supports n77/n78 SRS resources on Ant.1/2/8/9, only the worst test data of Ant.1 is shown in the report according to the maximum power.
2. The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP of Ant.1 is shown in the report.
3. The device supports HPUE mode for 5G NR n77/n78.
4. 5G NR n77/n78 support SA mode and NSA mode. According to the maximum power, SA covers NSA mode.
5. The EN-DC mode combination could be referred to the product spec.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP and Emission Designator

5G NR n77 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
10	3455.01 ~ 3544.98	0.5152	8M55G7D	0.3972	8M60W7D
15	3457.50 ~ 3542.49	0.5200	13M5G7D	0.4140	13M6W7D
20	3460.02 ~ 3540.00	0.5129	18M2G7D	0.3981	18M2W7D
25	3462.51 ~ 3537.48	0.5689	23M2G7D	0.4266	23M2W7D
30	3465.00 ~ 3534.99	0.5309	27M9G7D	0.4055	27M9W7D
40	3470.01 ~ 3529.98	0.5284	37M8G7D	0.3981	37M9W7D
50	3475.02 ~ 3525.00	0.4831	47M5G7D	0.3733	47M5W7D
60	3480.00 ~ 3519.99	0.4645	57M9G7D	0.3573	57M8W7D
70	3485.01 ~ 3514.98	0.4710	67M3G7D	0.3581	67M6W7D
80	3490.02 ~ 3510.00	0.4677	77M6G7D	0.3556	77M6W7D
90	3495.00 ~ 3504.99	0.4498	87M5G7D	0.3491	87M4W7D
100	3500.01	0.5781	97M4G7D	0.3846	97M6W7D

5G NR n78 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
10	3455.01 ~ 3544.98	0.5370	8M55G7D	0.4130	8M60W7D
15	3457.50 ~ 3542.49	0.5321	13M5G7D	0.4178	13M6W7D
20	3460.02 ~ 3540.00	0.5260	18M2G7D	0.4093	18M2W7D
25	3462.51 ~ 3537.48	0.5662	23M2G7D	0.4467	23M2W7D
30	3465.00 ~ 3534.99	0.5470	27M9G7D	0.4285	27M9W7D
40	3470.01 ~ 3529.98	0.5333	37M8G7D	0.4198	37M9W7D
50	3475.02 ~ 3525.00	0.4875	47M5G7D	0.3811	47M5W7D
60	3480.00 ~ 3519.99	0.4753	57M9G7D	0.3750	57M8W7D
70	3485.01 ~ 3514.98	0.4764	67M3G7D	0.3648	67M6W7D
80	3490.02 ~ 3510.00	0.4742	77M6G7D	0.3664	77M6W7D
90	3495.00 ~ 3504.99	0.4688	87M5G7D	0.3589	87M4W7D
100	3500.01	0.5728	97M4G7D	0.3945	97M6W7D

Note:

- 5G NR Band n77 overlaps the entire frequency range of Band n78, and n77 power > n78 power, therefore the conducted test results of n77 provided in this report cover n78.
- All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH04-KS	AUDIX	E3	210616

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 27 Subpart Q
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission (X plane).

Test Items	5G NR	Bandwidth (MHz)										Modulation					RB #		Test Channel			
		10	15	20	25	30	40	50	60	70~90	100	PI/2 BPSK	QPSK	16 QAM	64 QAM	256 QAM	1	Full	L	M	H	
Max. Output Power	n77	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
	n78	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
Peak-to-Ave rage Ratio	n77			v								v	v				v	v		v		
26dB and 99% Bandwidth	n77	v	v	v	v	v	v	v	v	v	v		v	v	v	v		v		v		
Conducted Band Edge	n77	v							v		v	v	v				v	v	v		v	
Conducted Spurious Emission	n77	v							v		v	v	v				v		v	v	v	
Frequency Stability	n77			v									v					v		v		
E.I.R.P	n77	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
	n78	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
Radiated Spurious Emission	n77	Worst Case																			v	
Note	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. Frequency Stability : Normal Voltage = 3.85V; Low Voltage =3.6V; High Voltage =4.4V.																					

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 3.99 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

=3.99 + 10 = 13.99 (dB)

2.5 Frequency List of Low/Middle/High Channels

5G n77/n78 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	-	633334	-
	Frequency	-	3500.01	-
90	Channel	633000	633334	633666
	Frequency	3495	3500.01	3504.99
80	Channel	632668	633334	634000
	Frequency	3490.02	3500.01	3510
70	Channel	632334	633334	634332
	Frequency	3485.01	3500.01	3514.98
60	Channel	632000	633334	634666
	Frequency	3480	3500.01	3519.99
50	Channel	631668	633334	635000
	Frequency	3475.02	3500.01	3525
40	Channel	631334	633334	635332
	Frequency	3470.01	3500.01	3529.98
30	Channel	631000	633334	635666
	Frequency	3465	3500.01	3534.99
25	Channel	630834	633334	635832
	Frequency	3462.51	3500.01	3537.48
20	Channel	630668	633334	636000
	Frequency	3460.02	3500.01	3540
15	Channel	630500	633334	636166
	Frequency	3457.5	3500.01	3542.49
10	Channel	630334	633334	636332
	Frequency	3455.01	3500.01	3544.98


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP Limit

§ 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. $EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where
 P_T = transmitter output power in dBm
 G_T = gain of the transmitting antenna in dBi
 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

§ 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW ≥ 500 KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 10, 2023	Nov. 29, 2023~Nov. 30, 2023	Oct. 09, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Nov. 29, 2023~Nov. 30, 2023	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Nov. 29, 2023~Nov. 30, 2023	Jul. 05, 2024	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 10, 2023	Apr. 18, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11, 2023	Apr. 18, 2024	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 19, 2023	Apr. 18, 2024	Aug. 18, 2024	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251694	1GHz~18GHz	Jul. 12, 2023	Apr. 18, 2024	Jul. 11, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Apr. 18, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Apr. 18, 2024	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2024	Apr. 18, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 10, 2023	Apr. 18, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 10, 2023	Apr. 18, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 18, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 18, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 18, 2024	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	± 2.26 dB
Occupied Channel Bandwidth	$\pm 0.1\%$
Conducted Power	± 0.46 dB
Peak to Average Ratio	± 0.46 dB
Frequency Stability	± 0.4 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.82 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.56 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.54 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Smile Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

FR1 N77(ANT1)

Transmitter Conducted Output Power And EIRP, ($G_T - L_C$)=0.1dB

NR Band	SCS	Band Width	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP(dBm)	EIRP(W)
77	30	10	630334	3455.01	DFT-s-OFDM PI/2 BPSK	1@1	26.38	26.48	0.4446
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@1	26.42	26.52	0.4487
77	30	10	630334	3455.01	DFT-s-OFDM 16 QAM	1@1	25.2	25.3	0.3388
77	30	10	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.57	26.67	0.4645
77	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.55	26.65	0.4624
77	30	10	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.38	25.48	0.3532
77	30	10	636332	3544.98	DFT-s-OFDM PI/2 BPSK	1@1	26.98	27.08	0.5105
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@1	27.02	27.12	0.5152
77	30	10	636332	3544.98	DFT-s-OFDM 16 QAM	1@1	25.89	25.99	0.3972
77	30	15	630500	3457.5	DFT-s-OFDM PI/2 BPSK	1@1	26.45	26.55	0.4519
77	30	15	630500	3457.5	DFT-s-OFDM QPSK	1@1	26.41	26.51	0.4477
77	30	15	630500	3457.5	DFT-s-OFDM 16 QAM	1@1	25.36	25.46	0.3516
77	30	15	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.61	26.71	0.4688
77	30	15	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.64	26.74	0.4721
77	30	15	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.54	25.64	0.3664
77	30	15	636166	3542.49	DFT-s-OFDM PI/2 BPSK	1@1	27.06	27.16	0.5200
77	30	15	636166	3542.49	DFT-s-OFDM QPSK	1@1	27.05	27.15	0.5188
77	30	15	636166	3542.49	DFT-s-OFDM 16 QAM	1@1	26.07	26.17	0.4140
77	30	20	630668	3460.02	DFT-s-OFDM PI/2 BPSK	1@1	26.35	26.45	0.4416
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@1	26.42	26.52	0.4487
77	30	20	630668	3460.02	DFT-s-OFDM 16 QAM	1@1	25.21	25.31	0.3396
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.57	26.67	0.4645
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.61	26.71	0.4688
77	30	20	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.44	25.54	0.3581
77	30	20	636000	3540	DFT-s-OFDM PI/2 BPSK	1@1	26.97	27.07	0.5093
77	30	20	636000	3540	DFT-s-OFDM QPSK	1@1	27	27.1	0.5129
77	30	20	636000	3540	DFT-s-OFDM 16 QAM	1@1	25.9	26	0.3981
77	30	25	630834	3462.51	DFT-s-OFDM PI/2 BPSK	1@1	26.72	26.82	0.4808
77	30	25	630834	3462.51	DFT-s-OFDM QPSK	1@1	26.73	26.83	0.4819
77	30	25	630834	3462.51	DFT-s-OFDM 16 QAM	1@1	25.61	25.71	0.3724
77	30	25	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.91	27.01	0.5023
77	30	25	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.95	27.05	0.5070
77	30	25	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.79	25.89	0.3882
77	30	25	635832	3537.48	DFT-s-OFDM PI/2 BPSK	1@1	27.45	27.55	0.5689
77	30	25	635832	3537.48	DFT-s-OFDM QPSK	1@1	27.22	27.32	0.5395
77	30	25	635832	3537.48	DFT-s-OFDM 16 QAM	1@1	26.2	26.3	0.4266
77	30	30	631000	3465	DFT-s-OFDM PI/2 BPSK	1@1	26.41	26.51	0.4477
77	30	30	631000	3465	DFT-s-OFDM QPSK	1@1	26.45	26.55	0.4519
77	30	30	631000	3465	DFT-s-OFDM 16 QAM	1@1	25.31	25.41	0.3475
77	30	30	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.67	26.77	0.4753

77	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.74	26.84	0.4831
77	30	30	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.61	25.71	0.3724
77	30	30	635666	3534.99	DFT-s-OFDM PI/2 BPSK	1@1	27.15	27.25	0.5309
77	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@1	27.07	27.17	0.5212
77	30	30	635666	3534.99	DFT-s-OFDM 16 QAM	1@1	25.98	26.08	0.4055
77	30	40	631334	3470.01	DFT-s-OFDM PI/2 BPSK	1@1	26.48	26.58	0.4550
77	30	40	631334	3470.01	DFT-s-OFDM QPSK	1@1	26.56	26.66	0.4634
77	30	40	631334	3470.01	DFT-s-OFDM 16 QAM	1@1	25.34	25.44	0.3499
77	30	40	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.72	26.82	0.4808
77	30	40	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.75	26.85	0.4842
77	30	40	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.61	25.71	0.3724
77	30	40	635332	3529.98	DFT-s-OFDM PI/2 BPSK	1@1	27.1	27.2	0.5248
77	30	40	635332	3529.98	DFT-s-OFDM QPSK	1@1	27.13	27.23	0.5284
77	30	40	635332	3529.98	DFT-s-OFDM 16 QAM	1@1	25.9	26	0.3981
77	30	50	631668	3475.02	DFT-s-OFDM PI/2 BPSK	1@1	26.34	26.44	0.4406
77	30	50	631668	3475.02	DFT-s-OFDM QPSK	1@1	26.36	26.46	0.4426
77	30	50	631668	3475.02	DFT-s-OFDM 16 QAM	1@1	25.25	25.35	0.3428
77	30	50	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.51	26.61	0.4581
77	30	50	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.58	26.68	0.4656
77	30	50	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.45	25.55	0.3589
77	30	50	635000	3525	DFT-s-OFDM PI/2 BPSK	1@1	26.74	26.84	0.4831
77	30	50	635000	3525	DFT-s-OFDM QPSK	1@1	26.71	26.81	0.4797
77	30	50	635000	3525	DFT-s-OFDM 16 QAM	1@1	25.62	25.72	0.3733
77	30	60	632000	3480	DFT-s-OFDM PI/2 BPSK	1@1	26.32	26.42	0.4385
77	30	60	632000	3480	DFT-s-OFDM QPSK	1@1	26.34	26.44	0.4406
77	30	60	632000	3480	DFT-s-OFDM 16 QAM	1@1	25.18	25.28	0.3373
77	30	60	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.48	26.58	0.4550
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.52	26.62	0.4592
77	30	60	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.34	25.44	0.3499
77	30	60	634666	3519.99	DFT-s-OFDM PI/2 BPSK	1@1	26.54	26.64	0.4613
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@1	26.57	26.67	0.4645
77	30	60	634666	3519.99	DFT-s-OFDM 16 QAM	1@1	25.43	25.53	0.3573
77	30	70	632334	3485.01	DFT-s-OFDM PI/2 BPSK	1@1	26.33	26.43	0.4395
77	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@1	26.3	26.4	0.4365
77	30	70	632334	3485.01	DFT-s-OFDM 16 QAM	1@1	25.31	25.41	0.3475
77	30	70	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.56	26.66	0.4634
77	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.59	26.69	0.4667
77	30	70	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.44	25.54	0.3581
77	30	70	634332	3514.98	DFT-s-OFDM PI/2 BPSK	1@1	26.56	26.66	0.4634
77	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@1	26.63	26.73	0.4710
77	30	70	634332	3514.98	DFT-s-OFDM 16 QAM	1@1	25.41	25.51	0.3556
77	30	80	632668	3490.02	DFT-s-OFDM PI/2 BPSK	1@1	26.4	26.5	0.4467
77	30	80	632668	3490.02	DFT-s-OFDM QPSK	1@1	26.42	26.52	0.4487
77	30	80	632668	3490.02	DFT-s-OFDM 16 QAM	1@1	25.26	25.36	0.3436
77	30	80	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.45	26.55	0.4519
77	30	80	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.39	26.49	0.4457
77	30	80	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.41	25.51	0.3556
77	30	80	634000	3510	DFT-s-OFDM PI/2 BPSK	1@1	26.49	26.59	0.4560

77	30	80	634000	3510	DFT-s-OFDM QPSK	1@1	26.6	26.7	0.4677
77	30	80	634000	3510	DFT-s-OFDM 16 QAM	1@1	25.4	25.5	0.3548
77	30	90	633000	3495	DFT-s-OFDM PI/2 BPSK	1@1	26.32	26.42	0.4385
77	30	90	633000	3495	DFT-s-OFDM QPSK	1@1	26.34	26.44	0.4406
77	30	90	633000	3495	DFT-s-OFDM 16 QAM	1@1	25.26	25.36	0.3436
77	30	90	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.34	26.44	0.4406
77	30	90	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.33	26.43	0.4395
77	30	90	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.19	25.29	0.3381
77	30	90	633666	3504.99	DFT-s-OFDM PI/2 BPSK	1@1	26.43	26.53	0.4498
77	30	90	633666	3504.99	DFT-s-OFDM QPSK	1@1	26.43	26.53	0.4498
77	30	90	633666	3504.99	DFT-s-OFDM 16 QAM	1@1	25.33	25.43	0.3491
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	135@67	27.13	27.23	0.5284
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.25	27.35	0.5433
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@271	27.33	27.43	0.5534
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	135@67	27.48	27.58	0.5728
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.36	27.46	0.5572
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@271	27.52	27.62	0.5781
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	135@67	25.54	25.64	0.3664
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.19	25.29	0.3381
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@271	25.75	25.85	0.3846
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	135@67	24.07	24.17	0.2612
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@1	23.52	23.62	0.2301
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@271	24.1	24.2	0.2630
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	135@67	21.98	22.08	0.1614
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@1	21.64	21.74	0.1493
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@271	22.16	22.26	0.1683
77	30	100	633334	3500.01	CP-OFDM QPSK	137@68	25.06	25.16	0.3281
77	30	100	633334	3500.01	CP-OFDM QPSK	1@1	24.66	24.76	0.2992
77	30	100	633334	3500.01	CP-OFDM QPSK	1@271	25.29	25.39	0.3459


Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0025	PASS	NV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0036	PASS	LV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	-0.0045	PASS	HV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0017	PASS	-30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0026	PASS	-20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	-0.0019	PASS	-10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	-0.0013	PASS	0°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0010	PASS	10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0008	PASS	20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0017	PASS	30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0020	PASS	40°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	-0.0029	PASS	50°C

Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	50@0	7.12	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	7.33	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	8.1	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	6.9	13	PASS

N77(20M)_DFT-s-OFDM_PI_2-
BPSK_Outer_Full_Mid_CH




N77(20M)_DFT-s-OFDM_PI_2-
BPSK_Edge_1RB_Left_Mid_CH



N77(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH



N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




Occupied Bandwidth


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
77	30	10	633334	3500.01	CP-OFDM QPSK	24@0	8.5477	9.397
77	30	10	633334	3500.01	CP-OFDM 16 QAM	24@0	8.6018	9.88
77	30	10	633334	3500.01	CP-OFDM 64 QAM	24@0	8.5766	9.763
77	30	10	633334	3500.01	CP-OFDM 256 QAM	24@0	8.5741	9.283
77	30	15	633334	3500.01	CP-OFDM QPSK	38@0	13.534	15.11
77	30	15	633334	3500.01	CP-OFDM 16 QAM	38@0	13.545	15.58
77	30	15	633334	3500.01	CP-OFDM 64 QAM	38@0	13.634	14.77
77	30	15	633334	3500.01	CP-OFDM 256 QAM	38@0	13.568	14.5
77	30	20	633334	3500.01	CP-OFDM QPSK	51@0	18.248	19.82
77	30	20	633334	3500.01	CP-OFDM 16 QAM	51@0	18.208	19.31
77	30	20	633334	3500.01	CP-OFDM 64 QAM	51@0	18.202	19.71
77	30	20	633334	3500.01	CP-OFDM 256 QAM	51@0	18.196	19.29
77	30	25	633334	3500.01	CP-OFDM QPSK	65@0	23.16	24.62
77	30	25	633334	3500.01	CP-OFDM 16 QAM	65@0	23.165	24.11
77	30	25	633334	3500.01	CP-OFDM 64 QAM	65@0	23.182	25.47
77	30	25	633334	3500.01	CP-OFDM 256 QAM	65@0	23.207	24.04
77	30	30	633334	3500.01	CP-OFDM QPSK	78@0	27.892	29.46
77	30	30	633334	3500.01	CP-OFDM 16 QAM	78@0	27.892	29.34
77	30	30	633334	3500.01	CP-OFDM 64 QAM	78@0	27.837	30.0
77	30	30	633334	3500.01	CP-OFDM 256 QAM	78@0	27.821	29.22
77	30	40	633334	3500.01	CP-OFDM QPSK	106@0	37.8	39.36
77	30	40	633334	3500.01	CP-OFDM 16 QAM	106@0	37.91	39.43
77	30	40	633334	3500.01	CP-OFDM 64 QAM	106@0	37.772	39.18
77	30	40	633334	3500.01	CP-OFDM 256 QAM	106@0	37.814	39.29
77	30	50	633334	3500.01	CP-OFDM QPSK	133@0	47.529	49.28
77	30	50	633334	3500.01	CP-OFDM 16 QAM	133@0	47.443	49.28

77	30	50	633334	3500.01	CP-OFDM 64 QAM	133@0	47.526	49.1
77	30	50	633334	3500.01	CP-OFDM 256 QAM	133@0	47.465	50.62
77	30	60	633334	3500.01	CP-OFDM QPSK	162@0	57.92	60.67
77	30	60	633334	3500.01	CP-OFDM 16 QAM	162@0	57.747	59.65
77	30	60	633334	3500.01	CP-OFDM 64 QAM	162@0	57.782	60.75
77	30	60	633334	3500.01	CP-OFDM 256 QAM	162@0	57.818	60.04
77	30	70	633334	3500.01	CP-OFDM QPSK	189@0	67.326	69.57
77	30	70	633334	3500.01	CP-OFDM 16 QAM	189@0	67.354	70.42
77	30	70	633334	3500.01	CP-OFDM 64 QAM	189@0	67.562	70.89
77	30	70	633334	3500.01	CP-OFDM 256 QAM	189@0	67.334	69.61
77	30	80	633334	3500.01	CP-OFDM QPSK	217@0	77.612	80.2
77	30	80	633334	3500.01	CP-OFDM 16 QAM	217@0	77.447	79.91
77	30	80	633334	3500.01	CP-OFDM 64 QAM	217@0	77.609	80.03
77	30	80	633334	3500.01	CP-OFDM 256 QAM	217@0	77.36	79.88
77	30	90	633334	3500.01	CP-OFDM QPSK	245@0	87.529	90.28
77	30	90	633334	3500.01	CP-OFDM 16 QAM	245@0	87.303	90.23
77	30	90	633334	3500.01	CP-OFDM 64 QAM	245@0	87.355	90.22
77	30	90	633334	3500.01	CP-OFDM 256 QAM	245@0	87.401	90.27
77	30	100	633334	3500.01	CP-OFDM QPSK	273@0	97.406	100.7
77	30	100	633334	3500.01	CP-OFDM 16 QAM	273@0	97.552	100.5
77	30	100	633334	3500.01	CP-OFDM 64 QAM	273@0	97.322	100.6
77	30	100	633334	3500.01	CP-OFDM 256 QAM	273@0	97.562	100.6

N77(10M)_CP-OFDM_QPSK_Outer_Full_Mid_CH




N77(10M)_CP-OFDM_16QAM_Outer_Full_Mid_CH




N77(10M)_CP-OFDM_64QAM_Outer_Full_Mid_CH




N77(10M)_CP-OFDM_256QAM_Outer_Full_Mid_CH




N77(15M)_CP-OFDM_QPSK_Outer_Full_Mid_CH




N77(15M)_CP-OFDM_16QAM_Outer_Full_Mid_CH




N77(15M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(15M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N77(20M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(20M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH




N77(20M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(20M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH



N77(25M)_CP- OFDM_QPSK_Outer_Full_Mid_CH




N77(25M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH




N77(25M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH




N77(25M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH




N77(30M)_CP- OFDM_QPSK_Outer_Full_Mid_CH




N77(30M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH



N77(30M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(30M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N77(40M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(40M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH




N77(40M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(40M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N77(50M)_CP-OFDM_QPSK_Outer_Full_Mid_CH




N77(50M)_CP-OFDM_16QAM_Outer_Full_Mid_CH




N77(50M)_CP-OFDM_64QAM_Outer_Full_Mid_CH




N77(50M)_CP-OFDM_256QAM_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_QPSK_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_16QAM_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N77(70M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(70M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH




N77(70M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(70M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH



N77(80M)_CP- OFDM_QPSK_Outer_Full_Mid_CH



N77(80M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH




N77(80M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH




N77(80M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH




N77(90M)_CP- OFDM_QPSK_Outer_Full_Mid_CH




N77(90M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH




N77(90M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(90M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N77(100M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(100M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(100M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N77(100M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




Conducted Spurious Emissions


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	PASS

77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS


N77(10M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(10M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(10M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(10M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(10M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(10M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(60M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH




N77(60M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH




N77(60M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH



N77(60M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH



N77(100M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(100M)_DFT-s- OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(100M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Mid_CH



N77(100M)_DFT-s- OFDM_QPSK_Edge_1RB_Left_Mid_CH



Conducted Band Edge

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	24@0	see graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	24@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@23	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@23	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	24@0	see graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	24@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@161	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@161	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@272	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@272	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	270@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	270@0	see graph	PASS