

RF TEST REPORT



Report No.: 17020065-FCC-R1

Supersede Report No.: N/A

Applicant	SolaX Power Network Technology (Zhe jiang) Co. , Ltd.	
Product Name	Pocket Wifi	
Model No.	Pocket Wifi 2.0	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	May 25 to June 06, 2017	
Issue Date	June 06, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Amos Xia Test Engineer	Deon Dai Engineer Reviewer	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and

Technology Development Park, Nanjing, China

Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17020065-FCC-R1
Page	3 of 52

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH	9
6.3 MAXIMUM OUTPUT POWER	17
6.4 POWER SPECTRAL DENSITY	22
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS	27
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	33
6.7 RADIATED EMISSIONS.....	37
ANNEX A. TEST INSTRUMENT	42
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	43
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	48
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	51
ANNEX E. DECLARATION OF SIMILARITY	52

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17020065-FCC-R1	NONE	Original	June 06, 2017

2. Customer information

Applicant Name	SolaX Power Network Technology (Zhe jiang) Co. , Ltd.
Applicant Add	No.288 Shizhu Road, Tonglu Economic Development Zone, Tonglu City, Zhejiang province, China
Manufacturer	SolaX Power Network Technology (Zhe jiang) Co. , Ltd.
Manufacturer Add	No.288 Shizhu Road, Tonglu Economic Development Zone, Tonglu City, Zhejiang province, China

3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	EZ EMC (Ver.ICP-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Pocket Wifi
Main Model:	Pocket Wifi 2.0
Serial Model:	N/A
Date EUT received:	May 09, 2017
Test Date(s):	May 25 to June 06, 2017
Antenna Gain:	PCB Antenna: 2 dBi IPEX Antenna: 3 dBi
Type of Modulation:	WIFI: 802.11b/g/n(20M): DSSS, OFDM
RF Operating Frequency (ies):	WIFI: 802.11b/g/n(20M): 2412-2472 MHz
Max. Output Power:	20.01 dBm (802.11b)
Number of Channels:	WIFI : 802.11b/g/n(20M): 13CH
Port:	RS232 Port
Input Power:	DC 2.4-3.6V
Trade Name :	SolaX Power
FCC ID:	2AMEH-POCKETWIFI

5. Test Summary

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit. And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

- PCB Antenna for WIFI, the gain is 2 dBi for WIFI.
- IPEX Antenna for WIFI, the gain is 3 dBi for WIFI.

The antenna meets up with the ANTENNA REQUIREMENT.


Result: Compliance.

Operating channel list

Channel	Frequency (MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462
12	2467
13	2472

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	May 25, 2017
Tested By :	Amos Xia

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS Gen(4.6.1)	a)	6dB BW≥500kHz; 20dB BW≥500kHz;	☒
	b)	99% BW: For FCC reference only; required by IC.	☐
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance V04, 8.1 DTS bandwidth <u>6dB bandwidth</u> a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) ≥ 3 × RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <u>20dB bandwidth</u> C63.10 Occupied Bandwidth (OBW=20dB bandwidth) - Set RBW = 1%-5% OBW. - Set the video bandwidth (VBW) ≥ 3 x RBW. - Set the span range between 2 times and 5 times of the OBW. - Sweep time=Auto, Detector=PK, Trace=Max hold. - Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst-case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	1	2412	7.64	14.36	≥0.5
	6	2437	7.66	14.35	≥0.5
	11	2462	7.86	14.27	≥0.5
	12	2467	7.71	14.26	≥0.5
	13	2472	7.69	14.32	≥0.5
802.11g	1	2412	16.53	18.17	≥0.5
	6	2437	16.55	18.30	≥0.5
	11	2462	16.55	18.31	≥0.5
	12	2467	16.54	18.02	≥0.5
	13	2472	16.52	18.13	≥0.5
802.11n (20M)	1	2412	17.76	18.98	≥0.5
	6	2437	17.78	19.08	≥0.5
	11	2462	17.81	19.10	≥0.5
	12	2467	17.79	19.13	≥0.5
	13	2472	17.79	19.11	≥0.5


Test Plots

6dB Bandwidth measurement result







802.11g 6dB Bandwidth - CH 6




802.11g 6dB Bandwidth - CH 11




802.11g 6dB Bandwidth - CH 12




802.11g 6dB Bandwidth - CH 13




802.11n20 6dB Bandwidth - CH 1




802.11n20 6dB Bandwidth - CH 6



802.11n20 6dB Bandwidth - CH 11





802.11n20 6dB Bandwidth - CH 12




802.11n20 6dB Bandwidth - CH 13

20 dB Bandwidth measurement result







802.11g 20dB Bandwidth - CH 6





802.11g 20dB Bandwidth - CH 11




802.11g 20dB Bandwidth - CH 12




802.11g 20dB Bandwidth - CH 13




802.11n20 20dB Bandwidth - CH 1




802.11n20 20dB Bandwidth - CH 6



802.11n20 20dB Bandwidth - CH 11



802.11n20 20dB Bandwidth - CH 12



802.11n20 20dB Bandwidth - CH 13




6.3 Maximum Output Power

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	May 25, 2017
Tested By :	Amos Xia

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b)(3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☒

Test Setup	 Spectrum Analyzer EUT
------------	---

Test Procedure	558074 D01 DTS MEAS Guidance V04, 9.1.2 Integrated band power method Maximum output power measurement procedure - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW $\geq 3 \times$ RBW. - d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run". - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
----------------	---

Remark	
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result


Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	1	2412	19.11	30	Pass
		6	2437	19.31	30	Pass
		11	2462	19.68	30	Pass
		12	2467	19.80	30	Pass
		13	2472	20.01	30	Pass
	802.11g	1	2412	16.12	30	Pass
		6	2437	16.96	30	Pass
		11	2462	17.26	30	Pass
		12	2467	17.43	30	Pass
		13	2472	17.78	30	Pass
	802.11n(20M)	1	2412	14.50	30	Pass
		6	2437	15.10	30	Pass
		11	2462	16.20	30	Pass
		12	2467	15.80	30	Pass
		13	2472	15.93	30	Pass

Test Plots The Average Power







802.11g - AV Output power - CH 6





802.11g - AV Output power - CH 11




802.11g - AV Output power - CH 12




802.11g - AV Output power - CH 13




802.11n20 - AV Output power - CH 1




802.11n20 - AV Output power - CH 6



802.11n20 - AV Output power - CH 11




802.11n20 - AV Output power - CH 12



802.11n20 - AV Output power - CH 13

6.4 Power Spectral Density

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	May 25, 2017
Tested By :	Amos Xia

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance V04, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	802.11b	1	2412	-10.602	8	Pass
		6	2437	-8.924	8	Pass
		11	2462	-9.719	8	Pass
		12	2467	-9.770	8	Pass
		13	2472	-9.144	8	Pass
	802.11g	1	2412	-16.310	8	Pass
		6	2437	-15.822	8	Pass
		11	2462	-15.179	8	Pass
		12	2467	-14.736	8	Pass
		13	2472	-15.088	8	Pass
	802.11n(20M)	1	2412	-17.179	8	Pass
		6	2437	-16.775	8	Pass
		11	2462	-16.719	8	Pass
		12	2467	-16.771	8	Pass
		13	2472	-16.979	8	Pass


Test Plots

Power Spectral Density measurement result







PSD - CH 6 - 802.11g




PSD - CH 11 - 802.11g




PSD - CH 12 - 802.11g




PSD - CH 13 - 802.11g




PSD - CH 1 - 802.11n20




PSD - CH 6 - 802.11n20



PSD - CH 11 - 802.11n20



PSD - CH 12 - 802.11n20



PSD - CH 13 - 802.11n20