

FCC Test Report

Report No.: AGC00737180510FE03

FCC ID : 2AMH2-BH078A

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Bluetooth Headset

BRAND NAME: MPOW

MODEL NAME : BH078A

CLIENT: MPOW TECHNOLOGY CO., LIMITED

DATE OF ISSUE : Jun. 05, 2018

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Subpart C Section 15.249

REPORT VERSION V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spowed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document teannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a training and the sample (s) are retained for 30 days only. The document is issued by AGC, this document teannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a training and the sample (s) are retained for 30 days only. The document is issued by AGC, this document teannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a second and the sample (s) are retained for 30 days only. The document is issued by AGC, this document teacher that the sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only. The document is sample (s) are retained for 30 days only are retained for 30 days on 30

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 60

Report Revise Record

Report Version Revise Time		Issued Date	Valid Version	Notes	
V1.0	June 1 S	Jun. 05, 2018	Valid	Initial release	



TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	6
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM	8 8
6. TEST FACILITY	10
7.TEST METHOD	
8. TEST EQUIPMENT LIST	
9. RADIATED EMISSION	12
9.1TEST LIMIT	12 13
10. BAND EDGE EMISSION	39
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	39 40
11. 20DB BANDWIDTH	44
11.1. MEASUREMENT PROCEDURE	44 44
12. FCC LINE CONDUCTED EMISSION TEST	51
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	51 52 52
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	53
ADDENDIV B. BUOTOGRADUS OF FUT	55



age 4 of 60

1. VERIFICATION OF CONFORMITY

Applicant	MPOW TECHNOLOGY CO., LIMITED
Address	RM 603, 6/F, HANG PONT COMM BLDG 31 TONKIN ST, CHEUNG SHA WAN KL, HK, CHINA
Manufacturer	MPOW TECHNOLOGY CO., LIMITED
Address	RM 603, 6/F, HANG PONT COMM BLDG 31 TONKIN ST, CHEUNG SHA WAN KL, HK, CHINA
Product Designation	Bluetooth Headset
Brand Name	MPOW
Test Model	BH078A
Date of test	May 17, 2018 to May 28, 2018
Deviation	None
Condition of Test Sample	Normal Normal State of the Stat
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By		Jorden Wand	
C "	Jonhen Wang(War	ng Yonghuan)	May 28, 2018
	The state of the s	cust change	
Reviewed By	100	, ,	
	Cool Cheng(Cher	ng Mengguo)	Jun. 05, 2018
		Foresto ce	
Approved By			
	Forrest Lei(Lei ` Authorized	M31	Jun. 05, 2018

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.

Attestation of Global Compliance



Page 5 of 60

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-4.87dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.1
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK
Number of channels	79 for BR/EDR
Hardware Version	V001
Software Version	V002
Antenna Designation	PCB Antenna
Antenna Gain	-6.5dBi
Power Supply	DC 3.7V by battery
Allie	nly used for charging and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCYS

BR/EDR channel List

Frequency Band	Channel Number	Frequency
	0	2402MHz
The total compliants (6)	CO	2403MHz
a Confidence and		
NO NO	38	2440 MHz
2400~2483.5MHz	39	2441 MHz
To Calibrat Compliants (S. Alles auton of S.	40	2442 MHz
S S		
:111	77	2479 MHz
The Secondarios S	78	2480 MHz



Page 6 of 60

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB


4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION				
© # 1.nd cools	Low channel GFSK				
2 2	Middle channel GFSK				
3	High channel GFSK				
· 4 、 6	Low channel π /4-DQPSK				
© 5 to or ciobas	Middle channel π /4-DQPSK				
6	High channel π /4-DQPSK				
7	Low channel 8DPSK				
8 @ M	Middle channel 8DPSK				
90	High channel 8DPSK				
10	BT Link				
The sale was					

Note

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.





The results specified this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.gett.com.

Attestation of Global Compliance



Page 8 of 60

5. SYSTEM TEST CONFIGURATION 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)

	The state of		palos	
EUT		Control box		PC

5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth Headset	MPOW	BH078A	EUT
2	Battery	YJ	551430	Accessory
3	PC	APPLE	A1465	A.E
4	Control box	CSR	USB_SPI_TOOLS	A.E
5	USB Cable	N/A	1m unshielded	A.E.C



Page 9 of 60

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT		
§15.249(a) §15.209	Radiated Emission	Compliant		
§15.249(d)	Band Edges	Compliant		
§15.207	Conduction Emission	N/A		
§15.215	Bandwidth	Compliant		

Note: N/A means it's not applicable to this item.



Page 10 of 60

6. TEST FACILITY

Tite.	
Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012
NVLAP Lab Code	600153-0
Designation Number	CN5028
Test Firm Registration Number	682566
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0



Page 11 of 60

7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

8. TEST EQUIPMENT LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B		Mar. 01, 2018	Feb. 28, 2019
Radiation Cable 1	MXT	RS1	R005	June 6, 2017	June 5, 2018
Radiation Cable 2	MXT	RS1	R006	June 6, 2017	June 5, 2018
Filter (2.4-2.483GHz)	Micro-tronics	087		Jun.20, 2017	Jun.19, 2018



Page 12 of 60

9. RADIATED EMISSION

9.1TEST LIMIT

Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency	Distance	Field Strengths Limit				
(MHz)	Meters	μ V/m	dB(μV)/m			
0.009 ~ 0.490	300	2400/F(kHz)	2			
0.490 ~ 1.705	30	24000/F(kHz)	吃那			
1.705 ~ 30	30	30	E Solution of Global			
30 ~ 88	3	100	40.0			
88 ~ 216	3	150	43.5			
216 ~ 960	3	200	46.0			
960 ~ 1000	3	500	54.0			
Above 1000	3 T. GO	Other:74.0 dB(µV)/m (Average)	(Peak) 54.0 dB(μV)/m			

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 60

9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.

Attestation of Global Compliance



Page 14 of 60


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




9.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz





Page 16 of 60

RADIATED EMISSION TEST SETUP ABOVE 1000MHz



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at although the confirmed at all the confirme



Page 17 of 60

9.4. TEST RESULT

FOR BR/EDR

(Worst modulation: GFSK)

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. gent.com.


Attestation of Global Compliance



Page 18 of 60

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL



A. Suspected List:


	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u∀/m) PK	Limit dB(u∀/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	38.730	H	5.6	17.3	22.9	40.0	17.1	Pass	150.0	108.6
	48.430	Н	5.6	17.1	22.7	40.0	17.3	Pass	100.0	122.7
5	111.965	Н	7.9	14.7	22.6	43.5	20.9	Pass	100.0	266.3
	133.790	Н	6.9	16.5	23.4	43.5	20.1	Pass	200.0	109.6
	787.570	H	5.5	28.4	33.9	46.0	12.1	Pass	150.0	288.6
	960.230	Н	7.1	30.8	37.9	54.0	16.1	Pass	100.0	231.0

RESULT: PASS



Page 19 of 60

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL




A. Suspected List:

Frequer MHz	- 1	Polarization	zation Reading Fact dB(uV) dB (1/m		Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
48.430)	v	6.8	17.1	23.9	40.0	16.1	Pass	200.0	266.7
50.370)	v	6.3	17.0	23.3	40.0	16.7	Pass	150.0	108.6
107.60	0	v	8.9	14.3	23.2	43.5	20.3	Pass	200.0	269.8
111.96	5	v	8.2	14.7	22.9	43.5	20.6	Pass	100.0	324.7
231.76	0	v	10.4	15.8	26.2	46.0	19.8	Pass	200.0	269.8
935.01	0	v	6.4	30.5	36.9	46.0	9.1	Pass	100.0	72.1

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.





RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL



A. Suspected List:


	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u√/m) PK	Limit dB(u∀/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	46.975	H	5.3	17.2	22.5	40.0	17.5	Pass	150.0	288.7
	146.885	Н	5.3	16.6	21.9	43.5	21.6	Pass	100.0	251.7
	159.980	H	5.2	16.6	21.8	43.5	21.7	Pass	200.0	141.8
1	424.305	Н	20.4	21.5	41.9	46.0	4.1	Pass	150.0	181.5
	432.065	Н	19.0	21.7	40.7	46.0	5.3	Pass	200.0	31.9
	936.465	Н	6.7	30.5	37.2	46.0	8.8	Pass	100.0	341.8

RESULT: PASS



Page 21 of 60

RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL



A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
36.305	v	8.0	16.6	24.6	40.0	15.4	Pass	200.0	304.0
62.010	v	8.2	16.0	24.2	40.0	15.8	Pass	150.0	327.1
66.860	v	8.8	15.2	24.0	40.0	16.0	Pass	100.0	105.8
158.525	v	5.9	16.6	22.5	43.5	21.0	Pass	100.0	214.9
444.190	v	9.2	22.0	31.2	46.0	14.8	Pass	200.0	159.8
956.350	v	6.0	30.7	36.7	46.0	9.3	Pass	200.0	267.7

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.


2. The "Factor" value can be calculated automatically by software of measurement system.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a transfer





RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



A. Suspected List:


Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u√/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
47.945	H	5.9	17.2	23.1	40.0	16.9	Pass	150.0	72.2
56.190	Н	4.9	16.6	21.5	40.0	18.5	Pass	200.0	288.4
159.980	Н	5.7	16.6	22.3	43.5	21.2	Pass	100.0	91.7
279.290	Н	5.5	17.7	23.2	46.0	22.8	Pass	150.0	306.1
428.185	Н	19.9	21.6	41.5	46.0	4.5	Pass	100.0	306.1
906.880	Н	5.9	30.2	36.1	46.0	9.9	Pass	200.0	217.6

RESULT: PASS



Page 23 of 60

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
61.525	V	10.1	16.0	26.1	40.0	13.9	Pass	100.0	142.1
66.860	v	9.7	15.2	24.9	40.0	15.1	Pass	100.0	251.2
168.225	V	6.4	16.1	22.5	43.5	21.0	Pass	200.0	163.2
451.950	v	8.0	22.1	30.1	46.0	15.9	Pass	100.0	358.9
610.545	v	6.8	25.1	31.9	46.0	14.1	Pass	150.0	72.1
960.230	v	6.1	30.8	36.9	54.0	17.1	Pass	150.0	72.1

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.




Page 24 of 60

RADIATED EMISSION ABOVE 1GHz FOR BR/EDR

(Worst modulation: GFSK)

For Fundamental

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2402.000	78.36	10.32	88.68	114.00	-25.32	peak			
2	*	2402.000	70.40	10.32	80.72	94.00	-13.28	AVG	100	258	

RESULT: PASS



Page 25 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		2402.000	77.89	10.32	88.21	114.00	-25.79	peak			
2	*	2402.000	69.93	10.32	80.25	94.00	-13.75	AVG	100	314	

RESULT: PASS



Page 26 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
L		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		2441.000	79.00	10.36	89.36	114.00	-24.64	peak			
	2	*	2441.000	71.02	10.36	81.38	94.00	-12.62	AVG	100	236	

RESULT: PASS



Page 27 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



▼	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		2441.000	78.59	10.36	88.95	114.00	-25.05	peak			
	2	*	2441.000	70.51	10.36	80.87	94.00	-13.13	AVG	100	121	

RESULT: PASS


The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.goalt.com.

Attestation of Global Compliance



Page 28 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2480.000	79.92	10.41	90.33	114.00	-23.67	peak			
2	*	2480.000	72.01	10.41	82.42	94.00	-11.58	AVG	100	358	


RESULT: PASS

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type of the confirmed at a type of typ



Page 29 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2480.000	79.46	10.41	89.87	114.00	-24.13	peak			
2	*	2480.000	71.49	10.41	81.90	94.00	-12.10	AVG	100		

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Page 30 of 60

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	78.36	10.32	88.68	114	-25.32	Horizontal	
2402	77.89	10.32	88.21	114	-25.79	Vertical	
2441	79.00	10.36	89.36	114	-24.64	Horizontal	
2441	78.59	10.36	88.95	114	-25.05	Vertical	
2480	79.92	10.41	90.33	114	-23.67	Horizontal	
2480	79.46	10.41	89.87	114	-24.13	Vertical	

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	70.40	10.32	80.72	94	-13.28	Horizontal	
2402	69.93	10.32	80.25	94	-13.75	Vertical	
2441	71.02	10.36	81.38	94	-12.62	Horizontal	
2441	70.51	10.36	80.87	94	-13.13	Vertical	
2480	72.01	10.41	82.42	94	-11.58	Horizontal	
2480	71.49	10.41	81.90	94	-12.10	Vertical	



Page 31 of 60

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	78.00	10.32	88.32	114	-25.68	Horizontal
2402	77.56	10.32	87.88	114	-26.12	Vertical
2441	78.59	10.36	88.95	114	-25.05	Horizontal
2441	78.27	10.36	88.63	114	-25.37	Vertical
2480	79.55	10.41	89.96	114	-24.04	Horizontal
2480	78.99	10.41	89.40	114	-24.60	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	69.94	10.32	80.26	94	-13.74	Horizontal
2402	69.63	10.32	79.95	94	-14.05	Vertical
2441	70.55	10.36	80.91	94	-13.09	Horizontal
2441	70.01	10.36	80.37	94	-13.63	Vertical
2480	71.60	10.41	82.01	94	-11.99	Horizontal
2480	71.05	10.41	81.46	94	-12.54	Vertical



Page 32 of 60

3Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	77.58	10.32	87.90	114	-26.10	Horizontal
2402	77.25	10.32	87.57	114	-26.43	Vertical
2441	78.17	10.36	88.53	114	-25.47	Horizontal
2441	77.78	10.36	88.14	114	-25.86	Vertical
2480	79.24	10.41	89.65	114	-24.35	Horizontal
2480	78.58	10.41	88.99	114	-25.01	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	69.58	10.32	79.90	94	-14.10	Horizontal
2402	69.17	10.32	79.49	94	-14.51	Vertical
2441	70.16	10.36	80.52	94	-13.48	Horizontal
2441	69.56	10.36	79.92	94	-14.08	Vertical
2480	71.29	10.41	81.70	94	-12.30	Horizontal
2480	70.64	10.41	81.05	94	-12.95	Vertical




age 33 of 60

FOR BR/EDR

(Worst modulation: GFSK)

For Harmonics

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		1750.000	37.85	7.25	45.10	74.00	-28.90	peak			
2		3075.000	34.09	11.71	45.80	74.00	-28.20	peak			
3	*	4804.000	42.21	7.69	49.90	74.00	-24.10	peak			

RESULT: PASS



Page 34 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No	D. N	Иk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1			2033.333	34.09	9.92	44.01	74.00	-29.99	peak			
2			3175.000	32.34	11.80	44.14	74.00	-29.86	peak			
3		*	4804.000	41.55	7.69	49.24	74.00	-24.76	peak			

RESIII T. PASS



Page 35 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		1991.667	34.70	9.79	44.49	74.00	-29.51	peak			
2		3266.667	33.19	11.89	45.08	74.00	-28.92	peak			
3	*	4882.000	43.16	7.89	51.05	74.00	-22.95	peak			


RESULT: PASS

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at all the confirmed at



Page 36 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



N	lo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
			MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		1991.667	33.42	9.79	43.21	74.00	-30.79	peak			
	2		3483.333	33.06	12.09	45.15	74.00	-28.85	peak			
Г	3	*	4882.000	42.39	7.89	50.28	74.00	-23.72	peak			

RESULT: PASS


The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



Page 37 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		1708.333	36.83	6.81	43.64	74.00	-30.36	peak			
2		2916.667	32.26	11.44	43.70	74.00	-30.30	peak			
3	*	4960.000	42.10	8.09	50.19	74.00	-23.81	peak			


DECILIT: DACC

The results shows if this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission.



Page 38 of 60

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No	. M	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2225.000	34.29	10.13	44.42	74.00	-29.58	peak			
2		3525.000	33.02	12.26	45.28	74.00	-28.72	peak			
3	*	4960.000	41.91	8.09	50.00	74.00	-24.00	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 39 of 60

10. BAND EDGE EMISSION


10.1. MEASUREMENT PROCEDURE

- 1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

Start frequency(MHz)	Stop frequency(MHz)				
2200	2405				
2478	2500				

10.2 TEST SETUP

RADIATED EMISSION TEST SETUP



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



age 40 of 60

10.3 RADIATED TEST RESULT

FOR BR/EDR

(Worst modulation: GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Table Height Degree		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2373.225	32.17	10.29	42.46	74.00	-31.54	peak			
2		2390.000	32.00	10.31	42.31	74.00	-31.69	peak			
3		2400.000	32.47	10.32	42.79	74.00	-31.21	peak			
4	*	2402.000	78.25	10.32	88.57	74.00	14.57	peak			
5	Х	2402.000	70.28	10.32	80.60	74.00	6.60	AVG	100	247	

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.



Page 41 of 60

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		2375.275	32.10	10.29	42.39	74.00	-31.61	peak			
2		2390.000	31.71	10.31	42.02	74.00	-31.98	peak			
3		2400.000	32.56	10.32	42.88	74.00	-31.12	peak			
4	*	2402.000	77.79	10.32	88.11	74.00	14.11	peak			
5	Х	2402.000	69.81	10.32	80.13	74.00	6.13	AVG	100	157	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 42 of 60

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1	*	2480.000	79.80	10.41	90.21	74.00	16.21	peak			
2	Х	2480.000	71.90	10.41	82.31	74.00	8.31	AVG	100	261	
3		2483.500	33.69	10.41	44.10	74.00	-29.90	peak			
4		2485.223	33.74	10.41	44.15	74.00	-29.85	peak			

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.go.tt.com.



Page 43 of 60

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
ſ	1	*	2480.000	79.34	10.41	89.75	74.00	15.75	peak			
	2	Х	2480.000	71.38	10.41	81.79	74.00	7.79	AVG	100	134	
	3		2483.500	33.26	10.41	43.67	74.00	-30.33	peak			
	4		2485.957	33.98	10.41	44.39	74.00	-29.61	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 44 of 60

11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP



11.3. LIMITS AND MEASUREMENT RESULTS

FOR BR/EDR

BLUETO	BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT								
	Measurement Result								
Applicable Limits		Decult							
		99%OBW (MHz)	-20dB BW(MHz)	Result					
Global Complete	Low Channel	0.926	1.101	PASS					
N/A	Middle Channel	0.919	1.090	PASS					
100	High Channel	0.903	1.084	PASS					


The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.



TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.



Page 46 of 60

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 47 of 60

BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT										
		Measurement Result								
Applicable Limits		Dogult								
		99%OBW (MHz)	-20dB BW(MHz)	Result						
TO THE WOOD OF THE PARTY OF THE	Low Channel	1.210	1.346	PASS						
N/A	Middle Channel	1.207	1.358	PASS						
CC TO	High Channel	1.210	1.369	PASS						


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 49 of 60

BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT									
		Measurement Result							
Applicable Limits		Dogulf.							
		99%OBW (MHz)	-20dB BW(MHz)	Result					
环 控制 T 控制	Low Channel	1.218	1.360	PASS					
N/A	Middle Channel	1.223	1.372	PASS					
	High Channel	1.225	1.365	PASS					


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



age 51 of 60

12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage							
Frequency	Q.P.(dBuV)	Average(dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	8 gg 200 56 gg 100 00 00 00 00 00 00 00 00 00 00 00 00	46 / W						
5MHz~30MHz	60	50						

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 52 of 60

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The BT function of EUT didn't work when charging.


The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.ago.go.tt.com.






APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC RADIATED EMISSION TEST SETUP



The results spowd this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc-gent.com.







The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 1000, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trip://www.agc.gett.com.

Attestation of Global Compliance

AGC 8



FRONT VIEW OF EUT



BACK VIEW OF EUT



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.go.tt.com.

Attestation of Global Compliance



VIEW OF EUT (Port)



OPEN VIEW OF EUT




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type AGC.


Attestation of Global Compliance



VIEW OF BATTERY



INTERNAL VIEW OF EUT-1




The results specified this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gent.com.


Attestation of Global Compliance



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.cett.com.

Attestation of Global Compliance