

TEST REPORT

Reference No. : WTS19S08053265W003
FCC ID..... : 2AMH2-BH387A
Applicant : MPOW TECHNOLOGY CO., LIMITED
Address : RM 603, 6/F, HANG PONT COMM BLDG 31 TONKIN ST CHEUNG
SHA WAN KL, HK, China
Manufacturer : SHENZHEN FENDA TECHNOLOGY CO.,LTD.
Address : Fenda Science Park,Zhoushi Road, Shiyuan Street, Bao'an District,
Shenzhen, China
Brand Name : MPOW/AIR by MPOW
Product : Bluetooth Headphone
Model(s)..... : BH387A
Standards : FCC CFR47 Part 15 Section 15.247:2019
Date of Receipt sample : 2019-08-02
Date of Test..... : 2019-08-03 to 2019-08-12
Date of Issue : 2019-08-12
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Test site/Test location:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Frank Yin

Frank Yin / Test Engineer

Approved by:

 *Philo Zhong*

Philo Zhong / Manager

1 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation, the certification number is 4243.01) of USA, CNAS (China National Accreditation Service for Conformity Assessment, the registration number is L3110) of China. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), ISED (Innovation, Science and Economic Development Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

1.1 Test Facility

A. Accreditations for Conformity Assessment (International)

| Country/Region | Scope Covered By | Scope | Note |
|---|------------------|--------------------|------|
| USA | ISO/IEC 17025 | FCC ID \ DOC \ VOC | 1 |
| Canada | | IC ID \ VOC | 2 |
| Japan | | MIC-T \ MIC-R | - |
| Europe | | EMCD \ RED | - |
| Taiwan | | NCC | - |
| Hong Kong | | OFCA | - |
| Australia | | RCM | - |
| India | | WPC | - |
| Thailand | | NTC | - |
| Singapore | | IDA | - |
| Note: 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. 2. ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A | | | |

B.TCBs and Notify Bodies Recognized Testing Laboratory.

| Recognized Testing Laboratory of ... | Notify body number |
|---|--------------------|
| TUV Rheinland | Optional. |
| Intertek | |
| TUV SUD | |
| SGS | |
| Phoenix Testlab GmbH | 0700 |
| Element Materials Technology Warwick Ltd. | 0891 |
| Timco Engineering, Inc. | 1177 |
| Eurofins Product Service GmbH | 0681 |

2 Contents

| | Page |
|--|-------------|
| COVER PAGE | 1 |
| 1 LABORATORIES INTRODUCTION | 2 |
| 1.1 TEST FACILITY..... | 3 |
| 2 CONTENTS | 4 |
| 3 REVISION HISTORY | 5 |
| 4 GENERAL INFORMATION | 6 |
| 4.1 GENERAL DESCRIPTION OF E.U.T | 6 |
| 4.2 DETAILS OF E.U.T..... | 6 |
| 5 FCC ID: 2AMH2-BH387A RF EXPOSURE REPORT | 7 |
| 5.1 REQUIREMENTS..... | 7 |
| 5.2 THE PROCEDURES / LIMIT..... | 7 |
| 5.3 RESULT: COMPLIANCE..... | 7 |

3 Revision History

| Test report No. | Date of Receipt sample | Date of Test | Date of Issue | Purpose | Comment | Approved |
|--------------------|------------------------|--------------------------------|---------------|----------|---------|----------|
| WTS19S08053265W003 | 2019-08-02 | 2019-08-03 to 2019-08-12 | 2019-08-12 | original | - | Valid |

4 General Information

4.1 General Description of E.U.T

| | |
|-----------------------------|------------------------------|
| Product | : Bluetooth Headphone |
| Model(s) | : BH387A |
| Operation Frequency | : 2402-2480MHz |
| Antenna installation | : PCB Printed Antenna |
| Antenna Gain | : 1.72dBi |
| Type of Modulation | : GFSK, $\pi/4$ DQPSK, 8DPSK |

4.2 Details of E.U.T

| | |
|----------------|---|
| Ratings | DC 3.7V, 58mAh by Li-Polymer Battery DC 5V, 220mA by USB |
|----------------|---|

5 FCC ID: 2AMH2-BH387A RF Exposure Report

Test Requirement: FCC Part 1.1307

Evaluation Method FCC Part2.1093 & KDB 447498 D01 General RF Exposure Guidance v06

5.1 Requirements

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity S

AR where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation
3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

5.2 The procedures / limit

| Conducted Peak power(dBm) | Conducted Peak power(mW) | Source-based time-averaged maximum conducted output power(mW) | Minimum test separation distance required for the exposure conditions (mm) | SAR Test Exclusion Thresholds Calculation Value | SAR Test Exclusion Thresholds Limit | Result |
|---------------------------|--------------------------|---|--|---|-------------------------------------|------------|
| 7.13 | 5.16 | 5.16 | 5 | 1.625 | 3.0 | Compliance |

Remark: Max. duty factor is 100%

Low Chanel: $f=2402\text{MHz}=2.402\text{GHz}$, so $\sqrt{f(\text{GHz})}=1.550$

High Chanel: $f=2480\text{MHz}=2.480\text{GHz}$, so $\sqrt{f(\text{GHz})}=1.575$

5.3 Result: Compliance

No SAR measurement is required.

=====End of Report=====