


FCC PART 15.247  
TEST REPORT

For

**MPOW TECHNOLOGY CO.,LIMITED**

FLAT/RM 605 6/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET  
MONGKOK KL HONG KONG

**FCC ID: 2AMH2-BH525A**

<b>Report Type:</b> Original Report	<b>Product Name:</b> WIRELESS RECEIVER
<b>Report Number:</b>	<u>RDG210322002-00A</u>
<b>Report Date:</b>	<u>2021-04-16</u>
<b>Reviewed By:</b>	Ivan Cao Assistant Manager 
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 <sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
DECLARATIONS.....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
SUPPORT CABLE LIST AND DETAILS .....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS.....</b>	<b>8</b>
Not Applicable: the device was powered by battery.....	8
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
EUT SETUP.....	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	12
TEST PROCEDURE .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	13
TEST DATA .....	13
<b>FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....</b>	<b>19</b>
APPLICABLE STANDARD .....	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST PROCEDURE .....	19
TEST DATA .....	19
<b>FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....</b>	<b>25</b>
APPLICABLE STANDARD .....	25
TEST PROCEDURE .....	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST DATA .....	25
<b>FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST EQUIPMENT LIST AND DETAILS.....	31

TEST DATA .....31

**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....34**

    APPLICABLE STANDARD .....34

    TEST PROCEDURE .....34

    TEST EQUIPMENT LIST AND DETAILS.....34

    TEST DATA .....34

**FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....40**

    APPLICABLE STANDARD .....40

    TEST PROCEDURE .....40

    TEST EQUIPMENT LIST AND DETAILS.....40

    TEST DATA .....40

**FCC §15.247(d) - BAND EDGES TESTING .....42**

    APPLICABLE STANDARD .....42

    TEST PROCEDURE .....42

    TEST EQUIPMENT LIST AND DETAILS.....42

    TEST DATA .....43

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	WIRELESS RECEIVER
<b>EUT Model:</b>	BH525A
<b>Multiple Model:</b>	BH525B, BH525C
<b>Operation Frequency:</b>	2402-2480MHz
<b>Maximum Peak Output Power (Conducted):</b>	1.41 dBm
<b>Antenna Gain <sup>▲</sup>:</b>	0 dBi
<b>Modulation Type:</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Rated Input Voltage:</b>	DC 5V from Car Charger Adapter
<b>Serial Number:</b>	RDG210322002-RF-S1
<b>EUT Received Date:</b>	2021.03.23
<b>EUT Received Status:</b>	Good

*Note: The series product, models BH525A, BH525B, BH525C are electrically identical, the model BH525A was fully tested. The difference between them please refer to the declaration letter for details.*

### Objective

This report is prepared on behalf of **MPOW TECHNOLOGY CO.,LIMITED** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

### Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

## Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

## Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in engineering mode, which was provided by manufacturer.

### EUT Exercise Software

The ' Blue Test3 ' was used during test, which was provided by manufacturer. The maximum power level was configured by the software as below table<sup>▲</sup>:

Test Software Version	Blue Test3		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	50	50	50
$\pi/4$ -DQPSK	60	60	60
8DPSK	60	60	60

### Equipment Modifications

No modification was made to the EUT.


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Xoopar Limited	Speaker	XP81025	XP81025-1
Un-known	load	Un-known	Load1

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.0	Adapter	EUT
AUX Cable	No	No	0.5	Aux Adapter	Speaker
USB Cable	No	No	1.0	Adapter	Load

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
FCC§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
FCC §15.203	Antenna requirement	Compliance
FCC §15.207(a)	AC line conducted emissions	Not Applicable
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(1)	Channel separation	Compliance
FCC §15.247(a)(1)	20 dB bandwidth	Compliance
FCC §15.247(a)(1)(iii)	Quantity of hopping channel test	Compliance
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliance
FCC §15.247(b)(1)	Peak output power measurement	Compliance
FCC §15.247(d)	Band edges	Compliance

Not Applicable: the device was powered by the car charger.



**FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculation formula:**

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

<b>Frequency (MHz)</b>	<b>Antenna Gain</b>		<b>Conducted output power including Tune-up Tolerance</b>		<b>Evaluation Distance (cm)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>MPE Limit (mW/cm<sup>2</sup>)</b>
	<b>(dBi)</b>	<b>(numeric)</b>	<b>(dBm)</b>	<b>(mW)</b>			
2402-2480	0	1.00	2	1.58	20.00	0.0003	1.0

**Result:** The device meet FCC MPE at 20 cm distance

## **FCC §15.203 - ANTENNA REQUIREMENT**

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

<b>Antenna Type</b>	<b>input impedance (Ohm)</b>	<b>Antenna Gain /Frequency Range</b>
PCB	50	0 dBi/2.4~2.5GHz

**Result:** Compliance.


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

#### Below 1GHz:



#### Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber, above 1GHz tests were performed in the 3 meters chamber A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2020-08-25	2023-08-25
R&S	EMI Test Receiver	ESCI	100224	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2020-09-24	2021-09-24
Sonoma	Amplifier	310N	185914	2020-10-13	2021-10-13
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
HUBER+SUHNER	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26E A	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Mini Circuits	High Pass Filter	VHF-6010+	31118	2020-06-16	2021-06-16

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Data

### Environmental Conditions


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
<b>Temperature:</b>	25.3 °C	26.4 °C
<b>Relative Humidity:</b>	49 %	42 %
<b>ATM Pressure:</b>	101.9kPa	101.5kPa
<b>Tester:</b>	Asa Chen	Joker Chen
<b>Test Date:</b>	2021-04-10	2021-04-08

*Test Mode: Transmitting*

1) 30MHz-1GHz (BDR High channel was the worst)

Horizontal:


100.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBμV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
139.6100	46.16	peak	-9.23	36.93	43.50	6.57
156.1000	44.79	peak	-9.38	35.41	43.50	8.09
259.8900	50.12	QP	-9.32	40.80	46.00	5.20
286.0800	46.34	peak	-8.22	38.12	46.00	7.88
337.4900	42.60	peak	-6.82	35.78	46.00	10.22
389.8700	40.18	peak	-5.54	34.64	46.00	11.36

**Vertical:**

100.0 dBµV/m



Frequency (MHz)	Receiver Reading (dBµV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
32.9100	38.59	QP	-5.69	32.90	40.00	7.10
156.1000	46.35	peak	-9.38	36.97	43.50	6.53
259.8900	44.15	peak	-9.32	34.83	46.00	11.17
337.4900	42.42	peak	-6.82	35.60	46.00	10.40
494.6300	40.02	peak	-3.52	36.50	46.00	9.50
546.0400	41.39	peak	-1.97	39.42	46.00	6.58

**2)1GHz-25GHz(BDR Mode was the worst):**




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Remark	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	73.37	PK	H	28.10	2.50	0.00	103.97	N/A	N/A
2402.00	67.94	AV	H	28.10	2.50	0.00	98.54	N/A	N/A
2402.00	66.71	PK	V	28.10	2.50	0.00	97.31	N/A	N/A
2402.00	61.23	AV	V	28.10	2.50	0.00	91.83	N/A	N/A
2390.00	27.91	PK	H	28.08	2.50	0.00	58.49	74.00	15.51
2390.00	16.88	AV	H	28.08	2.50	0.00	47.46	54.00	6.54
4804.00	45.73	PK	H	32.89	3.59	27.36	54.85	74.00	19.15
4804.00	37.83	AV	H	32.89	3.59	27.36	46.95	54.00	7.05
7206.00	36.42	PK	H	35.55	4.68	27.19	49.46	74.00	24.54
7206.00	25.91	AV	H	35.55	4.68	27.19	38.95	54.00	15.05
2298.20	47.89	PK	H	27.90	2.49	28.01	50.27	74.00	23.73
2298.20	40.32	AV	H	27.90	2.49	28.01	42.70	54.00	11.30
Middle Channel: 2441 MHz									
2441.00	74.22	PK	H	28.18	2.51	0.00	104.91	N/A	N/A
2441.00	68.79	AV	H	28.18	2.51	0.00	99.48	N/A	N/A
2441.00	67.61	PK	V	28.18	2.51	0.00	98.30	N/A	N/A
2441.00	62.10	AV	V	28.18	2.51	0.00	92.79	N/A	N/A
4882.00	47.14	PK	H	33.01	3.58	27.56	56.17	74.00	17.83
4882.00	39.42	AV	H	33.01	3.58	27.56	48.45	54.00	5.55
7323.00	38.98	PK	H	35.81	4.64	27.26	52.17	74.00	21.83
7323.00	28.37	AV	H	35.81	4.64	27.26	41.56	54.00	12.44
2337.00	49.50	PK	H	27.97	2.49	27.94	52.02	74.00	21.98
2337.00	43.26	AV	H	27.97	2.49	27.94	45.78	54.00	8.22
High Channel: 2480 MHz									
2480.00	71.76	PK	H	28.26	2.52	0.00	102.54	N/A	N/A
2480.00	66.35	AV	H	28.26	2.52	0.00	97.13	N/A	N/A
2480.00	65.30	PK	V	28.26	2.52	0.00	96.08	N/A	N/A
2480.00	59.94	AV	V	28.26	2.52	0.00	90.72	N/A	N/A
2483.50	29.53	PK	H	28.27	2.53	0.00	60.33	74.00	13.67
2483.50	18.13	AV	H	28.27	2.53	0.00	48.93	54.00	5.07
4960.00	47.55	PK	H	33.14	3.59	27.37	56.91	74.00	17.09
4960.00	39.76	AV	H	33.14	3.59	27.37	49.12	54.00	4.88
7440.00	41.88	PK	H	36.07	4.61	27.22	55.34	74.00	18.66
7440.00	31.43	AV	H	36.07	4.61	27.22	44.89	54.00	9.11
2583.80	48.42	PK	H	28.62	2.63	27.88	51.79	74.00	22.21
2583.80	43.05	AV	H	28.62	2.63	27.88	46.42	54.00	7.58



**Worst plots (GFSK high channel was the worst)**




**Horizontal**

Fundamental  
Test with Band  
Rejection Filter



Vertical

Fundamental Test with Band Rejection Filter



## FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25.9°C
<b>Relative Humidity:</b>	74 %
<b>ATM Pressure:</b>	100.5kPa
<b>Test by:</b>	Tiger Mo
<b>Test Date:</b>	2021-03-30

**Test Result:** Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402	1.000	0.63
	Middle	2441	1.006	0.6
	High	2480	1.000	0.6
EDR ( $\pi/4$ -DQPSK)	Low	2402	1.000	0.82
	Middle	2441	1.000	0.81
	High	2480	1.000	0.82
EDR (8DPSK)	Low	2402	1.000	0.81
	Middle	2441	1.000	0.81
	High	2480	1.000	0.81

Note:  $Limit = (2/3) \times 20dB \text{ bandwidth}$


BDR Mode (GFSK):

Low Channel




Date: 30.MAR.2021 10:30:26

### Middle Channel



Date: 30.MAR.2021 10:32:54


### High Channel



Date: 30.MAR.2021 10:35:17

EDR Mode ( $\pi/4$ -DQPSK):

### Low Channel




Date: 30.MAR.2021 10:38:27

### Middle Channel



Date: 30.MAR.2021 10:40:50

### High Channel



Date: 30.MAR.2021 10:42:12


EDR Mode (8DPSK):

### Low Channel




Date: 30.MAR.2021 10:45:04

### Middle Channel



### High Channel





## FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25.9°C
<b>Relative Humidity:</b>	74 %
<b>ATM Pressure:</b>	100.5kPa
<b>Test by:</b>	Tiger Mo
<b>Test Date:</b>	2021-03-30

**Test Result:** Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.940
	Middle	2441	0.896
	High	2480	0.896
EDR Mode ( $\pi/4$ -DQPSK)	Low	2402	1.224
	Middle	2441	1.220
	High	2480	1.224
EDR Mode (8DPSK)	Low	2402	1.216
	Middle	2441	1.216
	High	2480	1.216

BDR Mode (GFSK):

Low Channel




Date: 30.MAR.2021 10:29:20

### Middle Channel



Date: 30.MAR.2021 10:31:39


### High Channel



Date: 30.MAR.2021 10:34:10

EDR Mode ( $\pi/4$ -DQPSK):

Low Channel



Date: 30.MAR.2021 10:36:16

Middle Channel



Date: 30.MAR.2021 10:39:57


### High Channel



Date: 30.MAR.2021 10:41:11

EDR Mode (8DPSK):

### Low Channel




Date: 30.MAR.2021 10:42:46

### Middle Channel



Date: 30.MAR.2021 10:45:28

### High Channel



Date: 30.MAR.2021 10:46:42

## FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	25.9°C
<b>Relative Humidity:</b>	74 %
<b>ATM Pressure:</b>	100.5kPa
<b>Test by:</b>	Tiger Mo
<b>Test Date:</b>	2021-03-30

**Test Result:** Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Test mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	15
$\pi/4$ -DQPSK	2400-2483.5	79	
8DPSK	2400-2483.5	79	


BDR Mode (GFSK)



Date: 30.MAR.2021 12:16:05




### EDR Mode ( $\pi/4$ -DQPSK)



Date: 30.MAR.2021 10:54:44

### EDR Mode (8DPSK)



Date: 30.MAR.2021 10:53:57

## FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

### Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25.9°C
<b>Relative Humidity:</b>	74 %
<b>ATM Pressure:</b>	100.5kPa
<b>Test by:</b>	Tiger Mo
<b>Test Date:</b>	2021-03-30

**Test Result:** Compliance. Please refer to following tables and plots

*Test Mode: Transmitting*

Mode	Packet type	Channel	Frequency (MHz)	Puse width (ms)	Result (s)	Limit (s)
GFSK	DH1	Middle	2441	0.437	0.14	0.4
	DH3	Middle	2441	1.703	0.272	
	DH5	Middle	2441	2.974	0.317	
$\pi/4$ -DQPSK	2DH1	Middle	2441	0.453	0.145	
	2DH3	Middle	2441	1.709	0.273	
	2DH5	Middle	2441	2.983	0.318	
8DPSK	3DH1	Middle	2441	0.451	0.144	
	3DH3	Middle	2441	1.721	0.275	
	3DH5	Middle	2441	3.001	0.32	

Note:


DH1:Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s

DH3:Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s

DH5:Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s


*BDR Mode (GFSK):*

**DH1: Middle Channel**




Date: 30.MAR.2021 10:02:09

### DH3: Middle Channel



Date: 30.MAR.2021 10:05:22


### DH5: Middle Channel



Date: 30.MAR.2021 10:07:37


EDR Mode ( $\pi/4$ -DQPSK):

**2DH1: Middle Channel**




Date: 30.MAR.2021 10:03:32

**2DH3: Middle Channel**



Date: 30.MAR.2021 10:06:02


**2DH5: Middle Channel**



Date: 30.MAR.2021 10:08:27


*EDR Mode (8DPSK):*

**3DH1: Middle Channel**




Date: 30.MAR.2021 10:04:07

### 3DH3: Middle Channel



Date: 30.MAR.2021 10:06:43

### 3DH5: Middle Channel



Date: 30.MAR.2021 10:09:06

## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.9°C
Relative Humidity:	74 %
ATM Pressure:	100.5kPa
Test by:	Tiger Mo
Test Date:	2021-03-30

**Test Result:** Compliance.



*Test Mode: Transmitting*

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	-0.66	21
	2441	1.12	21
	2480	0.66	21
EDR Mode ( $\pi/4$ -DQPSK)	2402	-0.38	21
	2441	0.96	21
	2480	0.53	21
EDR Mode (8DPSK)	2402	0.03	21
	2441	<b>1.41</b>	21
	2480	0.99	21

Note: The data above was tested in conducted mode.

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data**


**Environmental Conditions**

<b>Temperature:</b>	25.9°C
<b>Relative Humidity:</b>	74 %
<b>ATM Pressure:</b>	100.5kPa
<b>Test by:</b>	Tiger Mo
<b>Test Date:</b>	2021-03-30

**Test Result: Compliance**


Single Channel Mode,  
BDR Mode (GFSK):

**Band Edge, Left Side**




Date: 30.MAR.2021 10:30:07

### Band Edge, Right Side




EDR Mode ( $\pi/4$ -DQPSK):

### Band Edge, Left Side




### Band Edge, Right Side



Date: 30.MAR.2021 10:41:54


EDR Mode (8DPSK):

### Band Edge, Left Side



Date: 30.MAR.2021 10:43:36


**Band Edge, Right Side**



Date: 30.MAR.2021 10:47:29


*Hopping Mode,  
 BDR Mode (GFSK):*

**Band Edge, Left Side**




Date: 30.MAR.2021 12:13:33

### Band Edge, Right Side




EDR Mode ( $\pi/4$ -DQPSK):

### Band Edge, Left Side




### Band Edge, Right Side




EDR Mode (8DPSK):

### Band Edge, Left Side





### Band Edge, Right Side



Date: 30.MAR.2021 10:53:09

\*\*\*\*\* END OF REPORT \*\*\*\*\*