



*Full*

# TEST REPORT

**No. I18D00014-SRD07**

*For*

**Client : IFLYTEK CO.,LTD.**

**Production : TD-LTE Wireless Data Terminal**

**Model Name : easytrans 800**

**FCC ID: 2AMI5-EASYTRANS-800**

**IC ID: 23795-EASYTRANS**

**Hardware Version: V1.0**

**Software Version: V1.0**

**Issued date: 2018-05-04**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

**Test Laboratory:**

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
I18D00014-SRD07	00	2018-04-23	Initial creation of test report
I18D00014-SRD07	01	2018-05-04	Second creation of test report

## CONTENTS

1.	TEST LABORATORY .....	5
1.1.	TESTING LOCATION .....	5
1.2.	TESTING ENVIRONMENT .....	5
1.3.	PROJECT DATA .....	5
1.4.	SIGNATURE .....	5
2.	CLIENT INFORMATION .....	6
2.1.	APPLICANT INFORMATION .....	6
2.2.	MANUFACTURER INFORMATION .....	6
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	7
3.1.	ABOUT EUT .....	7
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	7
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	7
3.4.	STATEMENTS.....	7
4.	REFERENCE DOCUMENTS.....	8
4.1.	REFERENCE DOCUMENTS FOR TESTING .....	8
5.	SUMMARY OF TEST RESULTS.....	9
6.	TEST EQUIPMENT UTILIZED .....	10
7.	TEST ENVIRONMENT .....	12
ANNEX A.	MEASUREMENT RESULTS.....	13
ANNEX A.1.	OUTPUT POWER .....	13
ANNEX A.2.	PEAK-TO-AVERAGE POWER RATIO .....	14
ANNEX A.3.	OCCUPIED BANDWIDTH .....	15
ANNEX A.4.	-26DB EMISSION BANDWIDTH .....	20
ANNEX A.5.	BAND EDGE AT ANTENNA TERMINALS .....	24
ANNEX A.6.	FREQUENCY STABILITY .....	27

<b>ANNEX A.7. CONDUCTED SPURIOUS EMISSION.....</b>	<b>30</b>
<b>ANNEX A.8. RADIATED.....</b>	<b>43</b>
<b>ANNEX B. DEVIATIONS FROM PRESCRIBED TEST METHODS.....</b>	<b>51</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301

### 1.2. Testing Environment

Normal Temperature:	15-35°C
Extreme Temperature:	-10/+55°C
Relative Humidity:	20-75%


### 1.3. Project data

Project Leader:	Ning Kang
Testing Start Date:	2018-04-02
Testing End Date:	2018-04-19


### 1.4. Signature



\_\_\_\_\_  
**Yang Dejun**  
(Prepared this test report)



\_\_\_\_\_  
**Ding Li**  
(Reviewed this test report)



\_\_\_\_\_  
**Zheng Zhongbin**  
Director of the laboratory  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name: IFLYTEK CO.,LTD.  
Address: National Intelligent Speech High-tech Industrialization Base, No. 666,  
Wangjiang Road West, Hefei City, Anhui Province, China  
Postcode: /  
Telephone: 18019939577

### 2.2. Manufacturer Information

Company Name: Shanghai Wind Communication Technologies Co.,Ltd.  
Address: The 12th Floor, East Wing, Guilin Technology Building, No.650, Caobao  
Road, Xuhui District, Shanghai, P. R. China  
Postcode: /  
Chen LuTelephone: 021-64958113

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description	TD-LTE Wireless Data Terminal
Model name	easytrans 800
FCC ID	2AMI5-EASYTRANS-800
IC ID	23795-EASYTRANS
Frequency	GSM850/1900; WCDMA Band II/IV/V CDMA2000 BC0/BC1
Extreme Temperature	-10/+55°C
Nominal Voltage	3.85V
Extreme High Voltage	4.4V
Extreme Low Voltage	3.5V

Note: Photographs of EUT are shown in ANNEX A of this test report.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	Model Name	SN or IMEI	HW Version	SW Version	Date of receipt
N25	easytrans 800	8647720301081 60	V1.0	V1.0	2018-02-01

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	---
AE2	Dummy Battery	---

\*AE ID: is used to identify the test sample in the lab internally.

#### 3.4. Statements

The easytrans 800, supporting GPRS/EDGE/WCDMA/HSDPA/HSUPA/HSPA+/CDMA/LTE/BT/BLE/WLAN, manufactured by Shanghai Wind Communication Technologies Co.,Ltd., which is a new product for testing.

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 2	ANSI/TIA-603-C:2004 ANSI/TIA-98-E:2003	2014
FCC Part 22	PUBLIC MOBILE SERVICES	2014



**5. SUMMARY OF TEST RESULTS**

Item	Test items	Clause in FCC rules	Clause in IC rules	result
1	Output Power	part 2.1046,part 22.913	5.4	Pass
2	Peak-to-Average	part 2.1046,part 22. subpart	5.5	Pass
3	99%Occupied	part 2.1049,part 22. subpart	5.3	Pass
4	-26dB Emission	part 2.1049,part 22. subpart	6.6	Pass
5	Band Edge at antenna terminals	part 2.1051 and part 22.917	6.6	Pass
6	Frequency stability	part 2.1055 and part 22.355	5.5	Pass
7	Conducted Spurious mission	part 2.1055 and part 22.355	6.13/5.5	Pass
8	Emission Limit	part 22.913(a)	5.4	Pass

## 6. Test Equipment Utilized

### Climate chamber

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Climate chamber	SH-641	92012011	ESPEC	2017-12-25	2 Year

### Radiated emission test system

The test equipment and ancillaries used are as follows.

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Universal Radio Communication Tester	CMU200	123123	R&S	2017-05-11	1 Year
2	EMI Test Receiver	ESU40	100307	R&S	2017-05-11	1 Year
3	TRILOG Broadband Antenna	VULB9163	VULB9163-515	Schwarzbeck	2017-02-25	3 Year
4	Double-ridged Waveguide Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
5	2-Line V-Network	ENV216	101380	R&S	2017-05-11	1 Year
6	Substitution Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
7	RF Signal Generator	SMF100A	102314	R&S	2017-05-11	1 Year
8	Substitution Antenna	VUBA9117	9117-266	Schwarzbeck	2017-11-18	3 Year
9	Amplifier	SCU08	10146	R&S	2017-05-11	1 Year

**Conducted test system**

No.	Name	Type	SN	Manufacture	Calibration date	Cal.interval
1	Spectrum Analyzer	FSQ26	101096	R&S	2017-05-11	1 Year
2	Universal Radio Communicat	CMU200	123124	R&S	2017-05-11	1 Year
3	DC Power Supply	ZUP60-1 4	LOC-220Z006 -0007	TDL-Lambda	2017-05-11	1 Year

## 7. Test Environment

**Shielding Room1** (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Ground system resistance	< 0.5 Ω

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber1** (6.9 meters×10.9 meters×5.4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB,30MHz to 1GHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

## ANNEX A. MEASUREMENT RESULTS

### ANNEX A.1. OUTPUT POWER

#### A.1.1. Summary

During the process of testing, the EUT was controlled Rhode & Schwarz Digital Radio. Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### A.1.2. Conducted

##### A.1.2.1. Method of Measurements

Method of measurements please refer to CFR47 (FCC) part 2.1046 and part 22.913. The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSQ(peak). These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

##### A.1.2.2 Test procedures:

1. The transmitter output port was connected to base station.
2. Set the EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### A.1.2.3 Limit:

22.913(a) Mobile stations are limited to 7watts.

24.232(c) Mobile and portable stations are limited to 2 watts.

##### A.1.2.4 Test Procedure:

The transmitter output power was connected to calibrated attenuator, the other end of which was connected to signal analyzer. Transmitter output power was read off the power in dBm. The power outputs at the transmitter antenna port was determined by adding the value of attenuator to the signal analyzer reading.

##### A.1.2.5 CDMA2000 Cellular Test Condition:

RBW	VBW	Sweep time	Span
-----	-----	------------	------

1MHz	1MHz	300ms	10MHz
------	------	-------	-------

### A.1.2.7 Measurement results:

CDMA2000 Cellular BC0		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 777/848.31	23.39	23.32
Low 384/836.52	23.36	23.31
High 1013/824.7	23.42	23.35

CDMA2000 PCS BC1		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 600/1880.0	23.23	23.11
Low 25/1851.25	23.22	23.16
High 1175/1908.75	23.19	23.14

**Conclusion: PASS**

## ANNEX A.2. Peak-to-Average Power Ratio

Method of test measurements please refer to CFR47 (FCC) part 2.1046 and part 22.913.

### A.2.1 PAPR Limit

The peak-to-average power ratio (PAPR) of the transmission may not exceed 13dB

### A.2.2 Test procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2.
  - 1) Select the spectrum analyzer CCDF function.
  - 2) Set RBW  $\geq$  signal's occupied bandwidth.
  - 3) Set the number of counts to a value that stabilizes the measured CCDF curve;
  - 4) Sweep time  $\geq$  1s.
3. Record the maximum PAPR level associated with a probability of 0.1%.

### A.2.3 Test results:

<b>CDMA2000 Cellular BC0</b>
------------------------------

Channel	384	777	1013
Frequency (MHz)	836.52	848.31	824.7
PAPR(dB)	8.43	8.45	8.46

CDMA2000 PCS BC1			
Channel	25	600	1175
Frequency (MHz)	1851.25	1880.0	1908.75
PAPR(dB)	8.37	8.40	8.43

**Conclusion: PASS**

### ANNEX A.3. Occupied Bandwidth

Method of test please refer to CFR 47 (FCC) part 2.1049 and part 22 subpart .

#### A.3.1. Occupied Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of CDMA2000 Cellular, CDMA2000 PCS.

#### A.3.2 Test Procedure:


1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW  $\geq$  3 times RBW,.
3. 99% bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

#### A.3.3 Test result:

CDMA2000 Cellular BC0		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 777	848.31	1.279
Low 384	836.52	1.284
High 1013	824.7	1.279


**Conclusion: PASS**

## CDMA2000 Cellular



Date: 15.APR.2018 11:26:43


### Channel 777-Occupied Bandwidth (99%)



Date: 15.APR.2018 11:25:47

### Channel 384-Occupied Bandwidth (99%)





Date: 15.APR.2018 11:27:19

### Channel 1013-Occupied Bandwidth (99%)


**Conclusion: PASS**

CDMA2000 PCS BC1		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 600	1880.0	1.298
Low 25	1851.25	1.298
High 1175	1908.75	1.293

**Conclusion: PASS**

**CDMA2000 PCS**





Date: 15.APR.2018 12:51:31

## Channel 1175-Occupied Bandwidth

**Conclusion: PASS**

**ANNEX A.4. -26dB Emission Bandwidth**

Method of test please refer to CFR 47 (FCC) part 2.1049 and part 22 subpart.

**A.4.1. -26dB Emission Bandwidth**

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of CDMA2000 Cellular, CDMA2000 PCS.

**A.4.2 Test Procedure:**

1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW  $\geq$  3 times RBW,.
3. 26dB bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

**A.4.3 Measurement methods:**


For CDMA: signal analyzer setting as: RBW=20KHz;VBW=200KHz;Span=3MHz.

**A.4.4 Test results:**

<b>CDMA2000 Cellular BC0</b>		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 777	848.31	1.442
Low 384	836.52	1.433
High 1013	824.7	1.433


**Conclusion: PASS**

**CDMA2000 Cellular**




Date: 15.APR.2018 12:07:17

### Channel 777- Emission Bandwidth (-26dBc BW)



Date: 15.APR.2018 12:06:49

### Channel 384- Emission Bandwidth (-26dBc BW)




Date: 15.APR.2018 12:07:43

### Channel 1013- Emission Bandwidth (-26dBc BW)


CDMA2000 PCS		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 600	1880.0	1.438
Low 25	1851.25	1.495
High 1175	1908.75	1.428

**Conclusion: PASS**  
**CDMA2000 PCS**




Date: 15.APR.2018 12:54:26

### Channel 600- Emission Bandwidth (-26dBc BW)



Date: 15.APR.2018 12:53:33

### Channel 25- Emission Bandwidth (-26dBc BW)



Date: 15.APR.2018 12:55:23

## Channel 1175- Emission Bandwidth (-26dBc BW)

**Conclusion: PASS**

### ANNEX A.5. Band Edge at antenna terminals

Method of test measurements please refer to CFR 47 (FCC) part 2.1051 and part 22.917.

#### A.5.1 Limit:

The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specification in the instruction manual and/or alignment procedure, shall not be less than  $43+10\log(\text{Mean power in watts})$  dBc below the mean power output outside a license's frequency block(-13dBm).

#### A.5.2 Test procedure:


1. The RF output of the transceiver was connected to a signal analyzer through appropriate attenuation.
2. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band
4. The limit line is derived from  $43+10\log(P)$  Db below the transmitter power P(Watts)
 
$$=P(W)-[43+10\log(P)](Db)$$

$$=[30+10\log(P)](dBm)-[43+10\log(P)](Db)$$

$$=-13dBm$$




## CDMA2000 Cellular BC0



Date: 15.APR.2018 11:35:31


## Channel 384- LOW BAND EDGE BLOCK



Date: 15.APR.2018 11:37:14


## Channel 1013- HIGH BAND EDGE BLOCK

## CDMA2000 PCS BC1



Date: 15.APR.2018 12:59:13

## Channel 25- LOW BAND EDGE BLOCK



Date: 15.APR.2018 13:00:39

## Channel 1175- HIGH BAND EDGE BLOCK

**Conclusion: PASS**

## **ANNEX A.6. FREQUENCY STABILITY**

Method of test measurements please refer to CFR47 (FCC) part 2.1055 and part 22.355.

### **A.5.1.Method of Measurement and test procedures**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of GSM850, PCS1900, WCDMA BANDII and WCDMA BANDV, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.5.2. Measurement Limit**

#### **A.5.2.1. For Hand carried battery powered equipment**

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. And the WCDMA is 2.5ppm. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.4VDC, with a nominal voltage of 3.85VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages was varied from 85% to 115%.

### A.5.2.2. For equipment powered by primary supply voltage

According to the JTC standard the CDMA frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

### A.5.3 Test results

#### CDMA2000 Cellular BC0 Mid Channel/fc(MHz) 384/836.52

##### Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.85	-30	3.6	2091
3.85	-20	12.4	2091
3.85	-10	2.9	2091
3.85	0	4.5	2091
3.85	10	11.4	2091
3.85	20	3.0	2091
3.85	30	2.9	2091
3.85	40	7.9	2091
3.85	50	4.3	2091

##### Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.5	25	12.5	2091
3.85	25	9.5	2091
4.4	25	2.6	2091

**CDMA2000 PCS BC1 Mid Channel/fc(MHz) 600/1880****Frequency Error VS Temperature**

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.85	-30	0.9	4700
3.85	-20	1.2	4700
3.85	-10	14.5	4700
3.85	0	2.2	4700
3.85	10	1.3	4700
3.85	20	11.9	4700
3.85	30	2.8	4700
3.85	40	8.5	4700
3.85	50	0.5	4700

**Frequency Error VS Voltage**

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.5	25	3.6	4700
3.85	25	12.6	4700
4.4	25	1.9	4700

**Conclusion: PASS**

**ANNEX A.7. CONDUCTED SPURIOUS EMISSION****A.7.1. GSM Measurement Method and test procedures**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.

2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.

3. The procedure to get the conducted spurious emission is as follows:

The trace mode is set to MaxHold to get the highest signal at each frequency;

Wait 25 seconds;Get the result.

4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

**CDMA2000 Cellular Transmitter**

Channel	Frequency(MHz)
384	836.52
777	848.31
1013	824.7

**CDMA2000 PCS Transmitter**

Channel	Frequency(MHz)
25	1851.25
600	1880.0
1175	1908.75

### A.7.1.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A7.1.2. Measurement result

**Spurious emission limit -13dBm.**


**Note: peak above the limit line is the carrier frequency.**

#### A7.1.2.1. CDMA2000 Cellular BC0




Date: 15.APR.2018 11:42:27

**Channel 384: 9KHz~150KHz**



Date: 15.APR.2018 11:43:48


### Channel 384: 150KHz~30MHz



Date: 15.APR.2018 11:45:06


### Channel 384: 30MHz~1GHz






Date: 15.APR.2018 11:45:58

### Channel 384: 1GHz~12.75GHz




Date: 15.APR.2018 11:48:19

### Channel 777: 9KHz~150KHz




Date: 15.APR.2018 11:48:59

## Channel 777: 150KHz~30MHz




Date: 15.APR.2018 11:49:39

## Channel 777: 30MHz~1GHz




Date: 15.APR.2018 11:50:40

### Channel 777: 1GHz~12.75GHz




Date: 15.APR.2018 11:51:21

### Channel 1013: 9KHz~150KHz




Date: 15.APR.2018 11:51:52

### Channel 1013: 150KHz~30MHz



Date: 15.APR.2018 11:52:34


### Channel 1013: 30MHz~1GHz



Date: 15.APR.2018 11:53:10


## Channel 1013: 1GHz~12.75GHz

### A7.1.2.2. CDMA2000 PCS BC1




Date: 15.APR.2018 13:06:29

## Channel 25: 9KHz~150KHz




Date: 15.APR.2018 13:07:13

## Channel 25: 150KHz~30MHz




Date: 15.APR.2018 13:07:57

## Channel 25: 30MHz~1GHz




Date: 15.APR.2018 13:05:34

## Channel 25: 1GHz~12.75GHz




Date: 15.APR.2018 13:08:39

## Channel 600: 9KHz~150KHz



Date: 15.APR.2018 13:09:13


## Channel 600: 150KHz~30MHz



Date: 15.APR.2018 13:09:44


## Channel 600: 30MHz~1GHz






Date: 15.APR.2018 13:10:22

## Channel 600: 1GHz~12.75GHz




Date: 15.APR.2018 13:11:15

## Channel 1175: 9KHz~150KHz




Date: 15.APR.2018 13:11:46

## Channel 1175: 150KHz~30MHz



Date: 15.APR.2018 13:12:21

## Channel 1175: 30MHz~1GHz



Date: 15.APR.2018 13:12:59

## Channel 1175: 1GHz~12.75GHz

**Conclusion: PASS**

## ANNEX A.8. RADIATED

### A.8.1. ERP

#### A.8.1.1. CDMA ERP

##### A.8.1.1.1. Description


This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power"and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


##### A.8.1.1.2. Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from thereceive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUTfor emission measurements. The height of receiving antenna is 1.5m. The test setup refers tofigure below. Detected emissions were maximized at each frequency by rotating the EUTthrough 360° and adjusting the receiving antenna polarization. The radiated emissionmeasurements of all transmit frequencies in three channels (High, Middle, Low) weremeasured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at thereference point of the chamber. An RF Signal source for the frequency band of interest isisconnected to the substitution antenna with a cable that has been constructed to not interferewith the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of thesubstitution antenna, and adjust the level of the signal generator output until the value of thereceiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. Thetest should be performed by rotating the test item and adjusting the receiving antennapolarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should beconnect between the Amplifier and the Substitute Antenna.

The cable loss ( $P_{cl}$ ), the Substitute Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should berecorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15dBi$ .

**A.8.1.1.3 CDMA2000 Cellular -ERP 22.913(a)**

**A.8.1.1.3.1 Measurement result**

**CDMA2000 Cellular BC0**

Frequency (MHz)	$P_{Mea}$ (dBm)	$P_{cl}$ (dB)	$P_{Ag}$ (dB)	$G_a$ Antenna Gain(dBd)	PeakERP(d Bm)	Polarization

836.52	-16.88	3.1	37	3.11	20.13	H
848.31	-17.34	3.1	37	3.11	19.67	H
824.7	-17.22	3.1	37	3.11	19.79	H

**Frequency: 824.2MHz**

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(-16.88\text{dBm}) - P_{\text{cl}}(3.1\text{dB}) + P_{\text{Ag}}(37\text{dB}) + G_{\text{a}}(3.11\text{dBd})$$

$$= 20.13\text{dBm}$$

**Note: ANALYZER SETTINGS: RBW = VBW = 3MHz**

### A.8.1.1.4 CDMA2000 PCS-EIRP 24.232(c)

#### A.8.1.1.4.2 Measurement result

##### CDMA2000 PCS BC1

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1851.25	-10.98	4.6	36	2.8	23.22	V
1880.0	-9.98	4.6	35.6	2.8	23.82	H
1908.75	-11.4	4.7	36	2.8	22.70	V

**Frequency: 1880MHz**

$$\text{Peak EIRP(dBm)} = P_{\text{Mea}}(-10.98\text{dBm}) - P_{\text{cl}}(4.6\text{dB}) + P_{\text{Ag}}(36\text{dB}) + G_{\text{a}}(2.8\text{dB}) = 23.22\text{dBm}$$

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

### A.8.2 EMISSION LIMIT (§2.1051/§22.917§24.238)


#### A.8.2.1 CDMA Measurement Method

The measurement procedures in TIA-603E-2016 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

#### A.8.2.2 The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10<sup>th</sup> harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_p$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_p$ ) is the summation of the cable loss .

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_p + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$

### A.8.2.3 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least 43

+ 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.8.2.4 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

### A.8.2.5 Measurement Results

**Measurements results:**

Frequency	Channel	Frequency Range	Result
<b>CDMA2000 Cellular BC0</b>	Low	30MHz~10GHz	P
	Middle	30MHz~10GHz	P
	High	30MHz~10GHz	P
<b>CDMA2000 PCS BC1</b>	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

#### CDMA2000 Cellular BC0 Channel 384

**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1841.8	-40.47	4.6	2.9	-42.17	-13	H
2426.8	-37.41	5.3	3.7	-39.01	-13	H
3170.8	-47.65	6.0	4.7	-48.95	-13	V

4016.5	-51.21	6.9	7.7	-50.41	-13	H
4960.4	-50.08	7.7	9.0	-48.78	-13	H
6227.7	-49.71	8.8	10.8	-47.71	-13	V

**Note:**

**BC0, CH384**

**Power(ERP)= Pmea-Pcl+Ga=-49.71-8.8+10.8=-47.71dbm**

**This method Applicable to the following table.**

**BC0 Channel 777**

**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1597.5	-44.86	4.3	3.4	-45.76	-13	V
2559.6	-36.73	5.4	3.7	-38.43	-13	V
3323.1	-48.87	6.2	4.7	-50.37	-13	H
4210.4	-50.51	7.0	7.7	-49.81	-13	V
8235.4	-52.76	10.1	17.3	-45.56	-13	V
8889.2	-51.67	10.4	18.3	-43.77	-13	V

**BC0 Cellular Mode Channel 1013**

**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1856.8	-40.41	4.6	2.9	-42.11	-13	H
2556.4	-36.75	5.4	3.7	-38.45	-13	V
4220.8	-49.5	7.0	7.7	-48.8	-13	H
5125.4	-50.37	7.9	8.7	-49.57	-13	H



6958.5	-50.45	9.3	12.9	-46.85	-13	V
8584.6	-52.95	10.3	18.1	-45.15	-13	V

**CDMA2000 PCS**
**BC1 Mode Channel 25**
**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3687.6	-53.68	6.6	7.7	-52.58	-13	V
5823.6	-53.85	8.4	10.5	-51.75	-13	V
7640.4	-54.47	9.7	15.3	-48.87	-13	H
9448.8	-54.56	10.7	18.6	-46.66	-13	V
11284.8	-49.88	12.1	18.5	-43.48	-13	H
13352.4	-48.3	13.7	21.8	-40.2	-13	H

**BC1 Mode Channel 600**
**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3760.8	-54.37	6.6	7.7	-53.27	-13	H
5641.2	-54.18	8.3	10.5	-51.98	-13	V
7578.0	-53.6	9.7	14.6	-48.7	-13	V
9357.6	-54.41	10.7	18.5	-46.61	-13	H

11253.6	-49.68	12.1	18.5	-43.28	-13	H
14304.0	-48.04	13.6	23.5	-38.14	-13	H

**BC1 Mode Channel 1175**
**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3648.0	-53.72	6.6	7.7	-52.62	-13	V
5553.6	-50.43	8.2	9.5	-49.13	-13	H
7354.8	-53.34	9.6	13.7	-49.24	-13	V
9196.8	-54.57	10.5	18.5	-46.57	-13	V
11670.0	-48.63	12.4	17.6	-43.43	-13	V
14311.2	-48.07	13.6	23.5	-38.17	-13	V

**BC0, CH1175**

**Power(ERP)= Pmea-Pcl+Ga=-48.07-13.6+23.5=-38.17dbm**

**This method Applicable to the following table.**

**Conclusion: PASS**

**Note: the EUT was displayed in several different direction, the worst cases were shown.**

## **ANNEX B. Deviations from Prescribed Test Methods**

No deviation from Prescribed Test Methods.

**\*\*\*\*\*End Of Report\*\*\*\*\***