



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 1 of 29 -

FCC RADIO TEST REPORT

FCC ID: 2AMJYTC-X4DB-A

Product : Smart Video Door Phone

Trade Name : N/A

Model Name : TC-X4DB-A

Serial Model : TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C,
TC-X4DB-D, TC-X4DB-E, TC-X4DB-F

Prepared for

Zhuhai Taichuan Cloud Technology Co., Ltd
Bldg1 Taichuan Technopark No. 611 Huawei Road Qianshan Xiangzhou
519075 Zhuhai Guangdong China

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.
7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,
Shenzhen, China
Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990
Http: www.att-lab.cn



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 2 of 29 -

TEST RESULT CERTIFICATION

Applicant's name : Zhuhai Taichuan Cloud Technology Co., Ltd
Address : Bldg1 Taichuan Technopark No. 611 Huawei Road Qianshan
Xiangzhou 519075 Zhuhai Guangdong China
Manufacture's Name..... : Zhuhai Taichuan Cloud Technology Co., Ltd
Address : Bldg1 Taichuan Technopark No. 611 Huawei Road Qianshan
Xiangzhou 519075 Zhuhai Guangdong China

Product description

Product Name..... : Smart Video Door Phone
Model and/or type reference : TC-X4DB-A
Serial Model : TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C,
TC-X4DB-D, TC-X4DB-E, TC-X4DB-F

Standards : FCC Part15.231:2017

Test procedure..... ANSI C63.10-2013

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

Date of Test.....:

Date (s) of performance of tests : Jun. 05 2017 ~Jun. 14 2017

Date of Issue..... : Jun. 14 2017

Test Result.....: **Pass**

Testing Engineer : Jack Yu
(Jack Yu)
Technical Manager : Jerry You
(Jerry You)
Authorized Signatory : Can Liu
(Can Liu)



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 3 of 29 -

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	12
3.1 STANDARD REQUIREMENT	12
3.2 EUT ANTENNA	12
3.3 CONDUCTED EMISSION MEASUREMENT	13
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.3.2 TEST PROCEDURE	14
3.3.3 DEVIATION FROM TEST STANDARD	14
3.3.4 TEST SETUP	14
3.2.5 TEST RESULT	15
3.4 RADIATED EMISSION MEASUREMENT	17
3.4.1 RADIATED EMISSION LIMITS	17
3.4.2 TEST PROCEDURE	18
3.4.3 DEVIATION FROM TEST STANDARD	18
3.4.4 TEST SETUP	19
3.4.5 TEST RESULTS (BELOW 30MHZ)	21
3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	22
4 . BANDWIDTH TEST	24
4.1 TEST PROCEDURE	24
4.2 DEVIATION FROM STANDARD	24
4.3 TEST SETUP	24
4.4 TEST RESULTS	25
5 . TRANSMITTER TIMEOUT	26



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 4 of 29 -

Table of Contents	Page
5.1 REQUIREMENTS	26
6 . EUT TEST PHOTO	28
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 5 of 29 -

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.231)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	Pass	
15.203	Antenna Requirement	Pass	
15.231	Radiated Spurious Emission	Pass	
15.231	Occupied Bandwidth	Pass	
15.231	Transmitter Timeout	Pass	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 6 of 29 -

1.1 TEST FACILITY

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715; IC Registration No.: 12198A

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 7 of 29 -

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Video Door Phone	
Trade Name	N/A	
Model Name	TC-X4DB-A	
Serial Model	TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C, TC-X4DB-D, TC-X4DB-E, TC-X4DB-F	
Model Difference	All models are identical except model name and colors.	
Product Description	The EUT is a Smart Video Door Phone	
	Product Type	Remote Control
	Operation Frequency:	433.92MHz
	Modulation Type:	FSK
	Number Of Channel	1CH.
	Antenna Designation:	spring Antenna
	Antenna Gain(Peak)	0 dBi
Channel List	N/A	
Adapter	M/N:RS-AB015J00-E	
	Input:100-240V~, 50/60Hz, 0.6A Output:12Vdc, 1.5A	
Battery	DC 12V, 1.5A	
Software version	V1.0	
Hardware Version	V1.1	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	spring Antenna	NA	0	Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission	
Final Test Mode	Description
Mode 1	N/A

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX

Note:

- (1) The EUT used new battery during the measurement.
- (2) After the pre-test All button emission frequency, modulation mode and power. Only recorded the worst case result in this report.
- (3) All test mode perform on continuous transmission mode. Use the test software test_cc1100.exe provide by manufacturer.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1

- Page 9 of 29 -

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

E-1 EUT



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 10 of 29 -

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Smart Video Door Phone	N/A	TC-X4DB-A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 11 of 29 -

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

[illegible]



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 12 of 29 -

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is spring Antenna Welding on the PCB with 0dBi gain. It comply with the standard requirement.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 13 of 29 -

3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP002.
0.50 -5.0			56.00	46.00	LP002.
5.0 -30.0			60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.3.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 15 of 29 -


3.2.5 TEST RESULT

Phase : L Test Voltage : DC 12V from adapter AC 120V/60Hz

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1539	45.86	11.84	57.70	65.78	-8.08	QP	
2	0.1539	28.24	11.84	40.08	55.78	-15.70	AVG	
3	0.7060	30.77	9.98	40.75	56.00	-15.25	QP	
4	0.7060	23.14	9.98	33.12	46.00	-12.88	AVG	
5 *	15.8900	34.00	10.54	44.54	50.00	-5.46	AVG	
6	16.4500	41.62	10.62	52.24	60.00	-7.76	QP	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1


- Page 16 of 29 -

Phase : N Test Voltage : DC 12V from adapter AC 120V/60Hz

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1539	44.60	11.84	56.44	65.78	-9.34	QP	
2	0.1539	32.66	11.84	44.50	55.78	-11.28	AVG	
3	0.7100	36.09	9.98	46.07	56.00	-9.93	QP	
4	0.7180	28.16	9.98	38.14	46.00	-7.86	AVG	
5 *	15.7420	34.49	10.52	45.01	50.00	-4.99	AVG	
6	16.1460	42.68	10.58	53.26	60.00	-6.74	QP	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.231)

Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)
40.66 - 40.70	2250.00	225.00
70 - 130	1250.00	125.00
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3750.00	375.00
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12500.00	1250.00

Notes:

- (1) ** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = 56.81818(F) - 6136.3636; for the band 260-470 MHz, uV/m at 3 meters = 41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in 93 Section 15.209, whichever limit permits a higher field strength.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 18 of 29 -

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8m(1.5m above 1G) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m(1.5m above 1G); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: For radiated emission test above 1GHz:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.


3.4.3 DEVIATION FROM TEST STANDARD

No deviation




3.4.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1

- Page 20 of 29 -

(C) Radiated Emission Test-Up Frequency Above 1GHz





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 21 of 29 -

3.4.5 TEST RESULTS (BELOW 30MHz)

EUT :	Smart Video Door Phone	Model Name. :	TC-X4DB-A
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V by adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 22 of 29 -

3.4.6 TEST RESULTS (BETWEEN 30 – 5000 MHZ)

EUT :	Smart Video Door Phone	Model Name :	TC-X4DB-A
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V by adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	Horizontal

Frequency	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dBuV/m (PK)	dBuV/m	dBuV/m	
433.92	77.34	100.4	80.4	pass
867.84	52.67	80.4	60.4	pass
1301.76	50.75	80.4	60.4	pass
1735.68	45.79	74.00	54.00	pass
2169.60	41.09	74.00	54.00	pass
--	--	74.00	54.00	pass

Note: test perform from 30 – 4000 MHz, no EMI Spurious detected above 2500MHz.

EUT :	Smart Video Door Phone	Model Name :	TC-X4DB-A
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V by adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	Vertical

Frequency	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dBuV/m (PK)	dBuV/m	dBuV/m	
433.92	75.41	100.4	80.4	pass
867.84	55.28	80.4	60.4	pass
1301.76	51.09	80.4	60.4	pass
1735.68	46.67	74.00	54.00	pass
2169.60	43.36	74.00	54.00	pass
--	--	74.00	54.00	pass



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1

- Page 23 of 29 -

Note: test perform from 30 – 4000 MHz, no EMI Spurious detected above 2500MHz.

NoTE:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. *: Denotes restricted band of operation.

Measurements were made using a peak detector and average detector(if peak emi less then average limit,only record the peak emi data). Any emission falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.

3. FCC Limit for Average Measurement = $41.6667(\text{Center frequency}) - 7083.3333$
4. $1/PW = 1/0.55\text{ms} = 1.82 < RBW(120\text{KHz})$, PDCF is not needed



4. BANDWIDTH TEST

4.1 TEST PROCEDURE

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit: center frequency *0.25%

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 25 of 29 -

4.4 TEST RESULTS

EUT :	Smart Video Door Phone	Model Name :	TC-X4DB-A
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 12V by adapter AC 120V/60Hz
Test Mode :	TX		

Test Channel	Frequency (MHz)	20 dBc Bandwidth (kHz)	Limit (kHz)
CH01	433.92	55.125	1085



Date: 12.Jun.2017 17:30:18



5. TRANSMITTER TIMEOUT

5.1 REQUIREMENTS

- 1 A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result: The EUT has a manually activated transmitter, please refer to below detail data

- 2 A transmitter activated automatically shall cease transmission within 5 seconds after activation.

Result: The EUT does not have a automatically activated transmitter

- 3 Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour

Result: The EUT does not employ periodic transmission.

- 4 Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result: The section is not applicable to EUT.


Note: The transmission time of signal will not be affected no matter how lon the button was pressed



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 27 of 29 -

Test data



Date: 12.JUN.2017 09:41:26

CH	THE DURATION OF EACH TRANSMISSION	LIMIT	RESULT
01	0.785	<5s	PASS




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1
- Page 28 of 29 -

6. EUT TEST PHOTO

Radiated Emission (30MHz-1GHz)



Radiated Emission (above 1GHz)





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F1

- Page 29 of 29 -

Conducted Emission (AC Mains)

