



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : RainUs Co., Ltd.

Applicant Address : 3rd Floor, 173-36, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea

Kind of Product : InforTab TAG

Equipment model name : R154

FCC ID : 2AMKA-R154

Antenna type : PCB antenna

Antenna Gain : -2.0 dBi



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

| | |
|----------------|--|
| $EIRP = P + G$ | Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi) |
|----------------|--|

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

Power density at the specific separation:

| | |
|----------------------|---|
| $S = PG / (4R^2\pi)$ | Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE) |
|----------------------|---|

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm² .

The power density at 20cm does not exceed the 1 mW/cm² limit.

2402 – 2480 MHz

| Mode | P (dBm) | P (mW) | G (dBi) | R (cm) | S (mW/cm ²) |
|------|---------|--------|---------|--------|-------------------------|
| DSSS | 6.086 | 4.06 | -2.0 | 20 | 0.0005 |