

# FCC ID: 2AMKM-I50BV2

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

### 11.1 Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm(20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$mW = 10^{(dBm/10)}$

## 11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited:  $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

Antenna gain: 3dBi,

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(3/10)}=2$

BLE:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-1.554	-2±1	-1	0.794	3.00	2.00	0.0003	1
2440		-2.61	-2±1	-1	0.794	3.00	2.00	0.0003	1
2480		-2.078	-2±1	-1	0.794	3.00	2.00	0.0003	1

Operation Frequency: 2412-2462MHz for 802.11b/g/11n(HT20);

2422-2452MHz for 802.11n(HT40);

Power density limited:  $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

Antenna gain: 3dBi,

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(3/10)}=2$

2.4G WIFI

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	13.36	13±1	14	25.119	3.00	2.00	0.0100	1
2437		13.04	13±1	14	25.119	3.00	2.00	0.0100	1
2462		12.9	13±1	14	25.119	3.00	2.00	0.0100	1
2412	802.11g	12.39	12±1	13	19.953	3.00	2.00	0.0079	1
2437		12.21	12±1	13	19.953	3.00	2.00	0.0079	1
2462		11.96	12±1	13	19.953	3.00	2.00	0.0079	1
2412	802.11n H20	12.03	12±1	13	19.953	3.00	2.00	0.0079	1
2437		11.85	12±1	13	19.953	3.00	2.00	0.0079	1
2462		11.74	12±1	13	19.953	3.00	2.00	0.0079	1
2422	802.11n(H T40)	11.2	11±1	12	15.849	3.00	2.00	0.0063	1
2437		11.25	11±1	12	15.849	3.00	2.00	0.0063	1
2452		11.08	11±1	12	15.849	3.00	2.00	0.0063	1

### Conclusion:

For the max result :  $0.01 \leq 1\text{mW}/\text{cm}^2$  for Power density, compliance with RF exposure.

Note: This product does not support WIFI and Bluetooth simultaneous delivery.

*Alex*

Signature:

Date: 2022-01-24

NAME AND TITLE (Please print or type): Alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.