

# FCC RF Exposure

EUT Description: Car Diagnosis tablet PC

Model No.: VPECKER-E4

FCC ID: 2AMKR-TDX

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  

$$[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1 - g SAR and  $\leq 7.5$  for 10 - g extremity SAR,

Where:

Result =  $P \sqrt{F/D}$

F = the RF channel transmit frequency in GHz

P = Maximum turn - up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
802.11b	8.76	8 ± 1	9/7.94	5	2.492	3.0	Pass
802.11g	8.31	8 ± 1	9/7.94	5	2.492	3.0	Pass
802.11n(HT20)	7.76	8 ± 1	9/7.94	5	2.492	3.0	Pass
802.11n(HT40)	6.68	7 ± 1	8/6.31	5	1.976	3.0	Pass
Note: PK Output power = conducted power. Conducted power see the test report UNI170614065-E, antenna gain = 2dBi							

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm