

TEST REPORT

Applicant: Shenzhen Jimi IoT Co., Ltd.
Address: 3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China
Equipment Type: LTE Container GNSS Tracker
Model Name: LL306 (refer section 2.4)
Brand Name: JIMI
FCC ID: 2AMLF-LL306
Test Standard: 47 CFR Part 2.1091
KDB 447498 D04 v01
Sample Arrival Date: Jan. 04, 2023
Test Date: Jan. 05, 2023 - Jan. 19, 2023
Date of Issue: Feb. 22, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Huang Jinsheng

Checked by: Xu Rui

Approved by: Tolan Tu

(Testing Director)

Huang Jinsheng

Xu Rui

Tolan Tu

Revision History		
Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Feb. 22, 2023</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	Factory Information.....	4
2.4	General Description for Equipment under Test (EUT).....	4
2.5	Ancillary Equipment.....	4
2.6	Technical Information	5
3	SUMMARY OF TEST RESULT	6
3.1	Test Standards	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	ASSESSMENT RESULT	9
5.1	Output Power	9
5.2	Tune-up power	10
5.3	RF Exposure Evaluation Result	10
5.4	Conclusion.....	10

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	LTE Container GNSS Tracker
Model Name Under Test	LL306
Series Model Name	LL306LA/LL306L/LL306A/LL306NA/LL306D
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the customer)
Hardware Version	CT10LD_MB_V1.0
Software Version	CT10LD_CT10_WAAE_V2.0_XQNA_230109.1427
Dimensions (Approx.)	43.0*104.0*200.0mm
Weight (Approx.)	370g

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	PL262920
	Serial No.	N/A
	Capacitance	5250 mAh
	Rated Voltage	3.7V
	Limit Charge Voltage	N/A

2.6 Technical Information

Network and Wireless connectivity	2G Network GPRS/EDGE 850/1900 MHz 4G Network LTE FDD Band 2/4/5/7/12/17 2.4G WIFI 802.11b, 802.11g (only RX) GPS
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, LTE		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE Band 12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	LTE Band 17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
Antenna Type	WWAN	PIFA	
Exposure Category	General Population/Uncontrolled Exposure		
EUT Stage	Mobile Device		

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Device:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad \text{(B.2)}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

5 ASSESSMENT RESULT

5.1 Output Power

GSM							
GSM850 Band	Burst Average Power(dBm)			Division Factors	Frame-Averaged power (dBm)		
Channel	128	190	251		128	190	251
GSM (GMSK, 1-Slot)	31.94	32.08	32.19	9.19	22.75	22.89	23.00
GPRS (GMSK, 1-Slot)	31.94	32.08	32.19	9.19	22.75	22.89	23.00
GPRS (GMSK, 2-Slots)	31.76	31.85	31.93	6.13	25.63	25.72	25.80
GPRS (GMSK, 3-Slots)	30.12	30.28	30.37	4.42	25.70	25.86	25.95
GPRS (GMSK, 4-Slots)	28.11	28.23	28.25	3.18	24.93	25.05	25.07
GSM1900 Band	Burst Average Power(dBm)			Division Factors	Frame-Averaged power(dBm)		
Channel	512	661	810		512	661	810
GSM (GMSK, 1-Slot)	29.66	29.57	29.75	9.19	20.47	20.38	20.56
GPRS (GMSK, 1-Slot)	29.66	29.57	29.75	9.19	20.47	20.38	20.56
GPRS (GMSK, 2-Slots)	29.45	29.31	29.55	6.13	23.32	23.18	23.42
GPRS (GMSK, 3-Slots)	27.90	27.72	27.96	4.42	23.48	23.30	23.54
GPRS (GMSK, 4-Slots)	25.70	25.53	25.73	3.18	22.52	22.35	22.55

Note: This table listed the worst case power value, please refer to BL-SZ2310065-501 report for more details.

GSM		
Mode	GSM850	GSM1900
Conducted Power (dBm)	25.95	23.54
Antenna Gain (dBi)	-1.43	3.24
EIRP (dBm)	22.37	26.78

Note: This table listed the worst case power value, please refer to BL-SZ2310065-501 report for more details.

LTE						
Mode	Band 2	Band 4	Band 5	Band 7	Band 12	Band 17
Conducted Power (dBm)	23.13	23.42	23.35	23.01	23.30	22.91
Antenna Gain (dBi)	3.24	5.00	-1.43	6.00	-1.16	-0.50
EIRP (dBm)	26.37	28.42	19.77	29.01	19.99	20.26

Note: This table listed the worst case power value, please refer to BL-SZ2310065-501 report for more details.

5.2 Tune-up power

Mode		Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
GSM	850	[24.00, 26.00]	/	[20.42, 22.42]
	1900	[22.00, 24.00]	[25.24, 27.24]	[23.09, 25.09]
LTE	Band 2	[22.00, 24.00]	[25.24, 27.24]	[23.09, 25.09]
	Band 4	[22.00, 24.00]	[27.00, 29.00]	[24.85, 26.85]
	Band 5	[22.00, 24.00]	/	[18.42, 20.42]
	Band 7	[22.00, 24.00]	[28.00, 30.00]	[25.85, 27.85]
	Band 12	[22.00, 24.00]	/	[18.69, 20.69]
	Band 17	[21.00, 23.00]	/	[18.35, 20.35]

Note1: ERP= EIRP -2.15dB

Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.

5.3 RF Exposure Evaluation Result

Evolution mode	Frequency (Ghz)	Maximum power (dBm)	Maximum power (mw)	Distance (mm)	Threshold Power (mW)	Verdict
GSM850	0.824	26.00	398.11	200	1680.96	Pass
GSM1900	1.850	25.09	322.85	200	3060.00	Pass
LTE B2	1.850	25.09	322.85	200	3060.00	Pass
LTE B4	1.710	26.85	484.17	200	3060.00	Pass
LTE B5	0.824	24.00	251.19	200	1680.96	Pass
LTE B7	2.500	27.85	609.54	200	3060.00	Pass
LTE B12	0.716	24.00	251.19	200	1460.64	Pass
LTE B17	0.716	23.00	199.53	200	1460.64	Pass

5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--