

FCC Part 15C Measurement and Test Report

For

Shenzhen Jimi IOT Co., Ltd

Floor 4th, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road,

District 67, Bao'an, Shenzhen, China

FCC ID: 2AMLF-JM-VL01

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>4G Vehicle GPS Tracker</u>
Tested Model:	<u>JM-VL01</u>
Report No.:	<u>WTX19X09067049W-4</u>
Sample Receipt Date:	<u>2019-09-25</u>
Tested Date:	<u>2019-09-25 to 2019-11-04</u>
Issued Date:	<u>2019-11-04</u>
Tested By:	<u>Jason Su / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Mike Shi

Silin Chen

Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	10
3. RF EXPOSURE	11
3.1 STANDARD APPLICABLE	11
3.2 TEST RESULT	11
4. ANTENNA REQUIREMENT	12
4.1 STANDARD APPLICABLE	12
4.2 EVALUATION INFORMATION	12
5. POWER SPECTRAL DENSITY	13
5.1 STANDARD APPLICABLE	13
5.2 TEST PROCEDURE	13
5.3 SUMMARY OF TEST RESULTS/PLOTS	13
6. DTS BANDWIDTH	17
6.1 STANDARD APPLICABLE	17
6.2 TEST PROCEDURE	17
6.3 SUMMARY OF TEST RESULTS/PLOTS	17
7. RF OUTPUT POWER	21
7.1 STANDARD APPLICABLE	21
7.2 TEST PROCEDURE	21
7.3 SUMMARY OF TEST RESULTS/PLOTS	21
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	26
8.1 STANDARD APPLICABLE	26
8.2 TEST PROCEDURE	26
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	27
8.4 SUMMARY OF TEST RESULTS/PLOTS	27
9. OUT OF BAND EMISSIONS	35
9.1 STANDARD APPLICABLE	35
9.2 TEST PROCEDURE	35
9.3 SUMMARY OF TEST RESULTS/PLOTS	36
10. CONDUCTED EMISSIONS	52
10.1 TEST PROCEDURE	52
10.2 BASIC TEST SETUP BLOCK DIAGRAM	52
10.3 TEST RECEIVER SETUP	52
10.4 SUMMARY OF TEST RESULTS/PLOTS	52

Report version

Version No.	Date of issue	Description
Rev.00	2019-11-04	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Jimi IOT Co., Ltd
Address of applicant: Floor 4th, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, District 67, Bao'an, Shenzhen, China

Manufacturer: Shenzhen Jimi IOT Co., Ltd
Address of manufacturer: Floor 4th, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, District 67, Bao'an, Shenzhen, China

General Description of EUT	
Product Name:	4G Vehicle GPS Tracker
Trade Name:	Jimi
Model No.:	JM-VL01
Adding Model(s):	GV40,VL01
Rated Voltage:	DC3.7V battery/DC9-36V
Battery:	450mAh
Adapter Model:	/
Software Version:	/
Hardware Version:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model JM-VL01, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20
RF Output Power:	14.02dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0.5dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Shenzhen SEM Test Technology Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1093	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an Integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:




- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).




5.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-17.86	8
	2437	-19.75	8
	2462	-20.67	8
802.11g_54Mbps	2412	-21.75	8
	2437	-20.52	8
	2462	-22.75	8
802.11n-HT20_MCS7	2412	-22.84	8
	2437	-21.54	8
	2462	-24.20	8

Please refer to the following test plots:

<p>802.11b-Low</p>	
<p>802.11b-Middle</p>	
<p>802.11b-High</p>	

<p>802.11g-Low</p>	 <p>Agilent 08:00:11 Oct 15, 19 R T</p> <p>Ref 0 dBm Atten 10 dB Mkr1 2.41449 GHz -21.75 dBm</p> <p>#Avg Log 10 dB/Offst 1 dB</p> <p>W1 S2 S3 FC AA</p> <p>Marker 2.414490000 GHz -21.75 dBm</p> <p>Center 2.412 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>802.11g-Middle</p>	 <p>Agilent 08:06:19 Oct 15, 19 R T</p> <p>Ref 0 dBm Atten 10 dB Mkr1 2.44453 GHz -20.52 dBm</p> <p>#Avg Log 10 dB/Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> <p>Marker 2.444530000 GHz -20.52 dBm</p> <p>Center 2.437 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>802.11g-High</p>	 <p>Agilent 08:17:11 Oct 15, 19 R T</p> <p>Ref 0 dBm Atten 10 dB Mkr1 2.45453 GHz -22.75 dBm</p> <p>#Avg Log 10 dB/Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> <p>Marker 2.454530000 GHz -22.75 dBm</p> <p>Center 2.462 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>

<p>802.11n-HT20-Low</p>	
<p>802.11n-HT20-Middle</p>	
<p>802.11n-HT20-High</p>	

6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:




- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




6.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	8.544	≥ 500
	2437	8.612	≥ 500
	2462	9.105	≥ 500
802.11g_54Mbps	2412	15.760	≥ 500
	2437	15.743	≥ 500
	2462	16.415	≥ 500
802.11n-HT20_MCS7	2412	16.324	≥ 500
	2437	16.304	≥ 500
	2462	17.645	≥ 500

Please refer to the following test plots:

<p>802.11b-Low</p>	 <p>Agilent 06:49:11 Oct 15, 19 R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>RBW 30.00000000 kHz</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10 dB/</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 30 kHz #VBW 300 kHz Sweep 33.44 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>11.4993 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -459.765 kHz</p> <p>x dB Bandwidth 8.544 MHz</p>
<p>802.11b-Middle</p>	 <p>Agilent 06:57:20 Oct 15, 19 R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10 dB/</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>11.1233 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 448.160 kHz</p> <p>x dB Bandwidth 8.612 MHz</p>
<p>802.11b-High</p>	 <p>Agilent 07:37:42 Oct 15, 19 R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10 dB/</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>11.8780 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 297.847 Hz</p> <p>x dB Bandwidth 9.105 MHz</p>

<p>802.11g-Low</p>	 <p>Agilent 07:54:26 Oct 15, 19 R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10</p> <p>dB/</p> <p>Offset 1</p> <p>dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>16.5183 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -90.272 kHz</p> <p>x dB Bandwidth 15.760 MHz</p>
<p>802.11g-Middle</p>	 <p>Agilent 08:03:03 Oct 15, 19 R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10</p> <p>dB/</p> <p>Offset 1</p> <p>dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>16.5178 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 71.916 kHz</p> <p>x dB Bandwidth 15.743 MHz</p>
<p>802.11g-High</p>	 <p>Agilent 08:32:34 Oct 15, 19 R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak</p> <p>Log 10</p> <p>dB/</p> <p>Offset 1</p> <p>dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>16.7353 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -24.705 kHz</p> <p>x dB Bandwidth 16.415 MHz</p>

<p>802.11n-HT20-Low</p>	 <p>Agilent 08:45:39 Oct 15, 19</p> <p>Ch Freq 2.412 GHz</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On</p> <p>Scale Type Log</p> <p>Occupied Bandwidth 17.5794 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -54.848 kHz x dB Bandwidth 16.324 MHz</p>
<p>802.11n-HT20-Middle</p>	 <p>Agilent 08:57:57 Oct 15, 19</p> <p>Ch Freq 2.437 GHz</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On</p> <p>Scale Type Log</p> <p>Occupied Bandwidth 17.5854 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 60.005 kHz x dB Bandwidth 16.304 MHz</p>
<p>802.11n-HT20-High</p>	 <p>Agilent 11:04:12 Oct 15, 19</p> <p>Ch Freq 2.462 GHz</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On</p> <p>Scale Type Log</p> <p>Occupied Bandwidth 17.7692 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -15.490 kHz x dB Bandwidth 17.645 MHz</p>

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure




According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth




- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.




7.3 Summary of Test Results/Plots

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	14.02	25.23	1000
	2437	13.58	22.80	1000
	2462	13.00	19.95	1000
802.11g_54Mbps	2412	12.16	16.44	1000
	2437	13.31	21.43	1000
	2462	11.82	15.21	1000
802.11n HT20_MCS7	2412	11.26	13.37	1000
	2437	11.65	14.62	1000
	2462	9.31	8.53	1000

Please refer to the following test plots:

<p>802.11b-Low 11Mbps</p>	 <p>Agilent 06:43:42 Oct 15, 19 R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.412 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density 14.02 dBm / 20.0000 MHz -58.99 dBm/Hz</p>
<p>802.11b-Middle 11Mbps</p>	 <p>Agilent 06:56:52 Oct 15, 19 R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.437 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density 13.58 dBm / 20.0000 MHz -59.43 dBm/Hz</p>
<p>802.11b-High 11Mbps</p>	 <p>Agilent 07:31:32 Oct 15, 19 R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.462 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density 13.00 dBm / 20.0000 MHz -60.02 dBm/Hz</p>

<p>802.11g-Low 54Mbps</p>	 <p>Agilent 07:53:18 Oct 15, 19 R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density</p> <p>12.16 dBm / 20.0000 MHz -60.85 dBm/Hz</p>
<p>802.11g-Middle 54Mbps</p>	 <p>Agilent 08:05:50 Oct 15, 19 R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density</p> <p>13.31 dBm / 20.0000 MHz -59.70 dBm/Hz</p>
<p>802.11g-High 54Mbps</p>	 <p>Agilent 08:34:46 Oct 15, 19 R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <p>Channel Power Power Spectral Density</p> <p>11.82 dBm / 20.0000 MHz -61.19 dBm/Hz</p>

<p>802.11n-HT20-Low MCS7</p>	 <p>Agilent 08:44:44 Oct 15, 19 R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <table border="1"> <thead> <tr> <th>Channel Power</th> <th>Power Spectral Density</th> </tr> </thead> <tbody> <tr> <td>11.26 dBm / 20.0000 MHz</td> <td>-61.76 dBm/Hz</td> </tr> </tbody> </table> <p>Trace/View</p> <p>Trace 1 2 3</p> <p>Clear Write</p> <p>Max Hold</p> <p>Min Hold</p> <p>View</p> <p>Blank</p> <p>More 1 of 2</p>	Channel Power	Power Spectral Density	11.26 dBm / 20.0000 MHz	-61.76 dBm/Hz
Channel Power	Power Spectral Density				
11.26 dBm / 20.0000 MHz	-61.76 dBm/Hz				
<p>802.11n-HT20-Middle MCS7</p>	 <p>Agilent 08:53:33 Oct 15, 19 R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 3 MHz Sweep 8 ms (401 pts)</p> <table border="1"> <thead> <tr> <th>Channel Power</th> <th>Power Spectral Density</th> </tr> </thead> <tbody> <tr> <td>11.65 dBm / 20.0000 MHz</td> <td>-61.36 dBm/Hz</td> </tr> </tbody> </table> <p>Trace/View</p> <p>Trace 1 2 3</p> <p>Clear Write</p> <p>Max Hold</p> <p>Min Hold</p> <p>View</p> <p>Blank</p> <p>More 1 of 2</p>	Channel Power	Power Spectral Density	11.65 dBm / 20.0000 MHz	-61.36 dBm/Hz
Channel Power	Power Spectral Density				
11.65 dBm / 20.0000 MHz	-61.36 dBm/Hz				
<p>802.11n-HT20-High MCS7</p>	 <p>Agilent 11:03:29 Oct 15, 19 R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Channel Power</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Avg Log 10 dB/ Offst 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts)</p> <table border="1"> <thead> <tr> <th>Channel Power</th> <th>Power Spectral Density</th> </tr> </thead> <tbody> <tr> <td>9.31 dBm / 20.0000 MHz</td> <td>-63.70 dBm/Hz</td> </tr> </tbody> </table> <p>Trace/View</p> <p>Trace 1 2 3</p> <p>Clear Write</p> <p>Max Hold</p> <p>Min Hold</p> <p>View</p> <p>Blank</p> <p>More 1 of 2</p>	Channel Power	Power Spectral Density	9.31 dBm / 20.0000 MHz	-63.70 dBm/Hz
Channel Power	Power Spectral Density				
9.31 dBm / 20.0000 MHz	-63.70 dBm/Hz				

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=360KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.


➤ Spurious Emissions Below 1GHz

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.5328	26.75	-11.02	15.73	40.00	-24.27	226	100	peak
2	104.5361	27.77	-13.10	14.67	43.50	-28.83	212	100	peak
3	210.0482	28.43	-12.54	15.89	43.50	-27.61	78	100	peak

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.5016	28.01	-11.09	16.92	40.00	-23.08	96	100	peak
2	110.5687	27.20	-13.08	14.12	43.50	-29.38	104	100	peak
3	502.9395	27.93	-6.18	21.75	46.00	-24.25	123	100	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.0566	27.94	-11.00	16.94	40.00	-23.06	98	100	peak
2	107.8877	28.10	-13.05	15.05	43.50	-28.45	78	100	peak
3	558.7302	29.02	-5.07	23.95	46.00	-22.05	98	100	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.5016	28.01	-11.09	16.92	40.00	-23.08	198	100	peak
2	99.1797	27.60	-13.36	14.24	43.50	-29.26	80	100	peak
3	590.9737	29.12	-4.11	25.01	46.00	-20.99	309	100	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.3318	27.52	-11.11	16.41	40.00	-23.59	97	100	peak
2	106.3850	26.94	-13.08	13.86	43.50	-29.64	103	100	peak
3	530.1014	28.84	-6.02	22.82	46.00	-23.18	102	100	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.2325	27.19	-11.04	16.15	40.00	-23.85	282	100	peak
2	70.0903	29.59	-15.20	14.39	40.00	-25.61	183	100	peak
3	300.3673	27.35	-9.23	18.12	46.00	-27.88	55	100	peak

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	61.93	-3.86	58.07	74	-15.93	H	PK
4824.000	42.44	-3.86	38.58	54	-15.42	H	AV
7236.000	54.65	1.1	55.75	74	-18.25	H	PK
7236.000	38.98	1.1	40.08	54	-13.92	H	AV
4824.000	58.43	-3.86	54.57	74	-19.43	V	PK
4824.000	41.67	-3.86	37.81	54	-16.19	V	AV
7236.000	55.31	1.1	56.41	74	-17.59	V	PK
7236.000	40.76	1.1	41.86	54	-12.14	V	AV
Middle Channel-2437MHz							
4874.000	60.87	-3.74	57.13	74	-16.87	H	PK
4874.000	43.3	-3.74	39.56	54	-14.44	H	AV
7311.000	52.01	1.47	53.48	74	-20.52	H	PK
7311.000	38.53	1.47	40	54	-14	H	AV
4874.000	61.88	-3.74	58.14	74	-15.86	V	PK
4874.000	43.83	-3.74	40.09	54	-13.91	V	AV
7311.000	53.41	1.47	54.88	74	-19.12	V	PK
7311.000	40.71	1.47	42.18	54	-11.82	V	AV
High Channel-2462MHz							
4924.000	59.47	-3.63	55.84	74	-18.16	H	PK
4924.000	43.87	-3.63	40.24	54	-13.76	H	AV
7386.000	54.04	1.62	55.66	74	-18.34	H	PK
7386.000	39.34	1.62	40.96	54	-13.04	H	AV
4924.000	58.76	-3.63	55.13	74	-18.87	V	PK
4924.000	42.84	-3.63	39.21	54	-14.79	V	AV
7386.000	54.12	1.62	55.74	74	-18.26	V	PK
7386.000	38.9	1.62	40.52	54	-13.48	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots


➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.66	-9.66	30.00	54.00	-24.00	Average Detector
	2310.000	53.85	-9.66	44.19	74.00	-29.81	Peak Detector
2	2390.000	55.00	-9.50	45.50	54.00	-8.50	Average Detector
	2390.000	60.68	-9.50	51.18	74.00	-22.82	Peak Detector
3	2400.000	64.49	-9.48	55.01	Delta=37.54 dB		Average Detector
4	2412.239	102.01	-9.46	92.55			Average Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.073	103.49	-9.36	94.13	/	/	Average Detector
	2460.356	108.77	-9.36	99.41	/	/	Peak Detector
2	2483.500	44.18	-9.31	34.87	54.00	-19.13	Average Detector
	2483.500	53.54	-9.31	44.23	74.00	-29.77	Peak Detector
3	2500.000	39.88	-9.28	30.60	54.00	-23.40	Average Detector
	2500.000	50.41	-9.28	41.13	74.00	-32.87	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.81	-9.66	30.15	54.00	-23.85	Average Detector
		52.92	-9.66	43.26	74.00	-30.74	Peak Detector
2	2390.000	53.73	-9.50	44.23	54.00	-9.77	Average Detector
		71.99	-9.50	62.49	74.00	-11.51	Peak Detector
3	2400.000	68.57	-9.48	59.09	Delta=31.47 dB		Average Detector
4	2414.353	100.01	-9.45	90.56			Average Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.834	100.52	-9.36	91.16	/	/	Average Detector
	2460.416	106.86	-9.36	97.50	/	/	Peak Detector
2	2483.500	45.60	-9.31	36.29	54.00	-17.71	Average Detector
	2483.500	62.00	-9.31	52.69	74.00	-21.31	Peak Detector
3	2500.000	40.05	-9.28	30.77	54.00	-23.23	Average Detector
	2500.000	53.34	-9.28	44.06	74.00	-29.94	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.88	-9.66	30.22	54.00	-23.78	Average Detector
		52.62	-9.66	42.96	74.00	-31.04	Peak Detector
2	2390.000	55.89	-9.50	46.39	54.00	-7.61	Average Detector
		78.37	-9.50	68.87	74.00	-5.13	Peak Detector
3	2400.000	68.94	-9.48	59.46	Delta=30.04dB		Average Detector
4	2412.899	98.96	-9.46	89.50			Average Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Vertical(worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.476	98.65	-9.36	89.29	/	/	Average Detector
	2460.595	106.96	-9.36	97.60	/	/	Peak Detector
2	2483.500	47.23	-9.31	37.92	54.00	-16.08	Average Detector
	2483.500	66.31	-9.31	57.00	74.00	-17.00	Peak Detector
3	2500.000	39.20	-9.28	29.92	54.00	-24.08	Average Detector
	2500.000	54.98	-9.28	45.70	74.00	-28.30	Peak Detector

➤ Conducted test



802.11b_11Mbps

Low





802.11b_11Mbps

Middle





802.11b_11Mbps

High





802.11g_54Mbps

Low





802.11g_54Mbps

Middle





802.11g_54Mbps

High





802.11n-HT20_MCS7

Low





802.11n-HT20_MCS7

Middle



802.11n-HT20_MCS7

High




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

- Start Frequency 150 kHz
- Stop Frequency 30 MHz
- Sweep Speed Auto
- IF Bandwidth..... 10 kHz
- Quasi-Peak Adapter Bandwidth 9 kHz
- Quasi-Peak Adapter Mode Normal

10.4 Summary of Test Results/Plots

Not applicable

***** END OF REPORT *****