

Testing Tomorrow's Technology

Application

For

Part 2, Subpart J, Paragraph 2.907 Equipment Authorization of Certification for an Intentional Radiator per Part 15, Subpart C, paragraphs 15.207, 15.209 and 15.249

For the

Sanitag Technologies Corp

Model: AT-004-H

FCC ID: 2AMOW-AT004H

UST Project: 17-0274

Issue Date: September 18, 2017

Total Pages in This Report: 32


**3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com**



I certify that I am authorized to sign for the Test Agency and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

US TECH (Agent Responsible For Test):

By: Alan Ghasiani

Name: 

Title: Compliance Engineer – President

Date September 18, 2017



TESTING
NVLAP LAB CODE 200162-0

This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of US Tech. The results contained in this report are subject to the adequacy and representative character of the sample provided. This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government.

**3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com**

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

MEASUREMENT TECHNICAL REPORT

COMPANYS NAME: Sanitag Technologies Corp

MODEL: AT-004-H

FCC ID: 2AMOW-AT004H

DATE: September 18, 2017

This report concerns (check one): Original grant ☒
Class II change

Equipment type: 2400 – 2483.5 MHz Transmitter Module

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? yes_____ No X

If yes, defer until: N/A
date

agrees to notify the Commission by N/A
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Report prepared by:

US Tech
3505 Francis Circle
Alpharetta, GA 30004
Phone Number: (770) 740-0717
Fax Number: (770) 740-1508

Table of Contents

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
1	General Information.....	7
1.1	Purpose of this Report.....	7
1.2	Characterization of Test Sample	7
1.3	Product Description	7
1.4	Configuration of Tested System	7
1.5	Test Facility	8
1.6	Related Submittals	8
2	Tests and Measurements	10
2.1	Test Equipment	10
2.2	Modifications to EUT Hardware.....	11
2.3	Number of Measurements for Intentional Radiators (15.31(m))	11
2.4	Frequency Range of Radiated Measurements (Part 15.33)	11
2.4.1	Intentional Radiator	11
2.4.2	Unintentional Radiator	12
2.5	Measurement Detector Function and Bandwidth (CFR 15.35)	12
2.5.1	Detector Function and Associated Bandwidth	12
2.5.2	Corresponding Peak and Average Requirements.....	12
2.5.3	Pulsed Transmitter Averaging.....	12
2.6	EUT Antenna Requirements (CFR 15.203)	13
2.7	Restricted Bands of Operation (Part 15.205).....	14
2.8	Transmitter Duty Cycle (CFR 35 (c))	14
2.9	Intentional Radiator, Power Line Conducted Emissions (CFR 15.207)	15
2.10	Intentional Radiator, Radiated Emissions (CFR 15.209, 15.249(a),(c)).....	15
2.11	Band Edge and Restricted Band Measurements – (CFR 15.249 (d)).....	19
2.12	99% Occupied Bandwidth	24
2.13	Unintentional Radiator, Powerline Emissions (CFR 15.107)	28
2.14	Unintentional Radiator, Radiated Emissions (CFR 15.109).....	29
2.15	Measurement Uncertainty	31
2.15.1	Conducted Emissions Measurement Uncertainty	31
2.15.2	Radiated Emissions Measurement Uncertainty	32
3	Test Results.....	32

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

List of Figures

<u>Figures</u>	<u>Title</u>	<u>Page</u>
Figure 1.	Block Diagram of Test Configuration	13
Figure 2.	Measured Duty Cycle	14
Figure 3.	Band Edge Compliance, Low Channel Delta - Peak.....	20
Figure 4.	Radiated Restricted Band 2310 MHz to 2390 MHz, Peak	21
Figure 5.	Band Edge Compliance, High Channel Delta – Peak	22
Figure 6.	Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak	23
Figure 7.	99% Bandwidth - Low Channel	25
Figure 8.	99% Bandwidth – Mid Channel	26
Figure 9.	99% Bandwidth – High Channel	27

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

List of Tables

<u>Table</u>	<u>Title</u>	<u>Page</u>
Table 1.	EUT and Peripherals.....	9
Table 2.	Test Instruments	10
Table 3.	Number of Test Frequencies for Intentional Radiators.....	11
Table 4.	Allowed Antenna(s).....	13
Table 5.	Spurious Radiated Emissions below 30 MHz.....	16
Table 6.	Peak Radiated Fundamental & Harmonic Emissions.....	17
Table 7.	Average Radiated Fundamental & Harmonic Emissions	18
Table 8.	Radiated Restricted Band 2310 MHz to 2390 MHz, Peak	21
Table 9.	Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak.....	23
Table 10.	Radiated Restricted Band 2483.5 MHz to 2500 MHz, Average	24
Table 11.	20 dB Bandwidth and 99% Occupied Bandwidth	24
Table 12.	Transmitter Power Line Conducted Emissions Test Data, Part 15.107 ...	28
Table 13.	Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),	29
Table 14.	Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),	30

List of Attachments

Agency Agreement
Application Forms
Letter of Confidentiality
Equipment Label(s)
Block Diagram(s)
Schematic(s)
Test Configuration Photographs
Internal Photographs
External Photographs
Theory of Operation
User's Manual

1 General Information

1.1 Purpose of this Report

This report is prepared as a means of conveying test results and information concerning the suitability of this exact product for public distribution according to the FCC Rules and Regulations Part 15, Section 249.

1.2 Characterization of Test Sample

The sample used for testing was received by US Tech on July 20, 2017 in good operating condition.

1.3 Product Description

The Equipment under Test (EUT) is the Sanitag Technologies Corp Model AT-004-H. The EUT provides real-time location data on staff members. It has a built in motion sensor, which can detect position and unexpected movements such as fall or immobility over a certain period of time. The EUT operates with a rechargeable battery.

Antenna: Trace etched antenna
Antenna Gain: 2.0 dBi
Protocol: IEEE 802.15.4 WPAN
Output Power: 2.5 dBm (rated)
Data Rate: 250 Kbps (rated)
Operating frequency band: 2400-2483.5 MHz

1.4 Configuration of Tested System

The Test Sample was tested per *ANSI C63.4:2014, Methods of Measurement of Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (2014)*, and *ANSI C63.10.2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices*.

A list of EUT and Peripherals is found in Table 1 below. A block diagram of the tested system is shown in Figure 1. Test configuration photographs are provided in separate Appendices

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

1.5 Test Facility

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA 30004. This site has been fully described and registered with the FCC. Its designation number is 186022. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number 9900A-1.

1.6 Related Submittals

The EUT is subject to the following FCC authorizations:

- a) Certification under section 15.249 as a transmitter.
- b) Verification under 15.101 as a digital device and receiver.

The Verification requirement shares many common report elements with the Certification report. Therefore, though this report is mostly intended to provide data for the Certification process, the Verification authorization report (part 15.107 and 15.109) for the EUT is included herein.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

Table 1. EUT and Peripherals

PERIPHERAL MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID:	CABLES P/D
Staff Tag/ Sanitag Technologies Corp (EUT)	AT-004-H	40000325	2AMOW-AT004H	N/A
Power Supply Adapter/ Mervesan	MS-0505 USB	None	None	1.5 m U P
Readers/ Sanitag Technologies Corp	AC-001-LAN	10000172	2AMOW-AC-001-LAN	P D

U= Unshielded S= Shielded P= Power D= Data

Note: Asset tag tested as the representative sample.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2 Tests and Measurements

2.1 Test Equipment

The table below lists test equipment used to evaluate this product. Model numbers, serial numbers and their calibration status are indicated.

Table 2. Test Instruments

INSTRUMENT	MODEL NUMBER	MANUFACTURER	SERIAL NUMBER	CALIBRATION DUE DATE
SPECTRUM ANALYZER	8593E	HEWLETT-PACKARD	3205A00124	8/23/2017
SPECTRUM ANALYZER	DSA815	RIGOL	DSA8A180300138	12/01//2017
SPECTRUM ANALYZER	E4407B	AGILENT	US41442935	6/22/2018
BICONICAL ANTENNA	3110B	EMCO	9306-1708	5/02/2019 2 yr
BICONICAL ANTENNA	3110B	EMCO	9307-1431	8/25/2017 2 yr
LOG PERIODIC ANTENNA	3146	EMCO	9110-3236	5/01/2019 2 yr
LOG PERIODIC ANTENNA	3146	EMCO	9305-3600	9/21/2018 2 yr
HORN ANTENNA	3115	EMCO	9107-3723	9/22/2018 2 yr
PRE-AMPLIFIER	8449B	HEWLETT-PACKARD	3008A00480	10/26/2017
PRE-AMPLIFIER	8447D	HEWLETT-PACKARD	1937A02980	3/07/2018

Note: The calibration interval of the above test instruments are 12 months unless stated otherwise and all calibrations are traceable to NIST/USA.

2.2 Modifications to EUT Hardware

No physical modifications were made by US Tech in order to bring the EUT into compliance with FCC Part 15, Subpart C Intentional Radiator Limits for the transmitter portion of the EUT or the Subpart B Unintentional Radiator Limits (Receiver and Digital Device) Requirements.

2.3 Number of Measurements for Intentional Radiators (15.31(m))

Measurements of intentional radiators or receivers shall be performed and reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in Table 3 below.

Table 3. Number of Test Frequencies for Intentional Radiators

Frequency Range over which the device operates	Number of Frequencies	Location in the Range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near the top 1 near the bottom
Greater than 10 MHz	3	1 near top 1 near middle 1 near bottom

Because the EUT operates at 2400 MHz to 2483.5 MHz, 3 test frequencies were used.

2.4 Frequency Range of Radiated Measurements (Part 15.33)

2.4.1 Intentional Radiator

The spectrum shall be investigated for the intentional radiator from the lowest RF signal generated in the EUT, without going below 9 kHz to the 10th harmonic of the highest fundamental frequency generated or 40 GHz, whichever is the lowest.

2.4.2 Unintentional Radiator

For the digital device, an unintentional radiator, the frequency range shall be 30 MHz to 1000 MHz, or to 5 times the highest internal clock frequency.

2.5 Measurement Detector Function and Bandwidth (CFR 15.35)

The radiated and conducted emissions limits shown herein are based on the following the parameters outlined following.

2.5.1 Detector Function and Associated Bandwidth

On frequencies below 1000 MHz, the limits herein are based upon measurement equipment employing a CISPR Quasi-peak detector function and related measurement bandwidths (i.e. 9 kHz from 150 kHz to 30 MHz and 120 kHz from 30 MHz to 1000 MHz). Alternatively, measurements may be made with equipment employing a peak detector function as long as the same bandwidths specified for the Quasi-peak device are used.

2.5.2 Corresponding Peak and Average Requirements

Above 1000 MHz, radiated limits are based on measuring instrumentation employing an average detector function. When average radiated emissions are specified there is also a corresponding Peak requirement, as measured using a peak detector, of 20 dB greater than the average limit. For all measurements above 1000 MHz the Resolution Bandwidth shall be at least 1 MHz.

2.5.3 Pulsed Transmitter Averaging

When the radiated emissions limit is expressed as an average value, and the transmitter is pulsed, the measured field strength shall be determined by applying a Duty Cycle Correction Factor based upon dividing the total ON time during the first 100 ms period by 100 ms (or by the period if less than 100 ms). The duty cycle may be expressed logarithmically in dB.

NOTE: If the transmitter was programmed to transmit at >98% duty cycle, then, wherever applicable (where the detection mode was AVG), the duty cycle factor calculated will be applied.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2.6 EUT Antenna Requirements (CFR 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. Only the antenna(s) listed in Table 4 will be used with this module.

Table 4. Allowed Antenna(s)

REPORT REFERENCE	MANUFACTURER	TYPE OF ANTENNA	MODEL	GAIN dB _i	TYPE OF CONNECTOR
1	Sanitag Technolgoies Corp	PCB Antenna	Etched	2.0	PCB trace




Figure 1. Block Diagram of Test Configuration

2.7 Restricted Bands of Operation (Part 15.205)

Only spurious emissions can fall in the frequency bands of CFR 15.205. The field strength of these spurious cannot exceed the limits of 15.209. Radiated harmonics and other Spurious are examined for this requirement see paragraph 2.1

2.8 Transmitter Duty Cycle (CFR 35 (c))




Figure 2. Measured Duty Cycle

Total Pulse Train from Figure 2 = 0.13 or 13% (13mS/100 mS)

$$\text{Duty Cycle} = 20 \text{ Log } (0.13) = \boxed{-17.7 \text{ dB}}$$

NOTE: For test where the transmitter was programmed to transmit at >98% duty cycle, the correction factor calculated above was applied to correct the data.

2.9 Intentional Radiator, Power Line Conducted Emissions (CFR 15.207)

Power line conducted emissions testing was performed to ensure that with the EUT in operation (exercising all transmitter functions), the complete system continues to meet the applicable requirements for CFR 15.207. These measurements were completed and are displayed along with the 15.107 power line test data in the sections below.

2.10 Intentional Radiator, Radiated Emissions (CFR 15.209, 15.249(a),(c))

Radiated Spurious measurements: the EUT was placed into a continuous transmit mode of operation (>98% duty cycle) and tested per FCC KDB Publication 558074 and ANSI C63.10:2013. A preliminary scan was performed on the EUT to find signal frequencies that were caused by the transmitter part of the device. To obtain worse case results the EUT was tested in X, Y and Z axes or in the orientation of normal operation if the device is designed to operation in a fixed position.

Radiated measurements were then conducted between the frequency range of 9 KHz (or lowest frequency used/generated by the device) up to the tenth harmonic of the device (no greater than 40 GHz). In the band below 30 MHz a resolution bandwidth (RBW) of 9 kHz was used; emissions below 1 GHz were tested with a RBW of 120 KHz and emissions above 1 GHz were tested with a RBW of 1 MHz. All video bandwidth settings were at least three times the RBW value.

The EUT was investigated to CFR 15.209, General requirements for unwanted spurious emissions.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H


Table 5. Spurious Radiated Emissions below 30 MHz

9 kHz to 30 MHz, 15.209 limits							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuv)	AF+CA-AMP (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
No emissions found greater than 20 dB below the applicable limit from the lowest clock frequency (9 kHz to 30 MHz).							

Sample Calculation: N/A

Date: August 4, 2017

Evaluated by

Signature:  Name: Robert K. Mills

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H

Table 6. Peak Radiated Fundamental & Harmonic Emissions

Test: FCC Part 15, Para 15.209, 15.249(a)					Client: Sanitag Technologies Corp			
Project: 17-0274					Model: AT-004-H			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Low - Channel								
2405.50	56.44	--	33.39	89.83	114.0	3.0m./VERT	24.1	PK
4802.60	73.48	-9.50*	9.66	73.64	74.0	3.0m./VERT	0.4	PK
Mid - Channel								
2439.50	55.16	--	33.39	88.55	114.0	3.0m./VERT	25.4	PK
4880.00	58.98	--	9.66	68.64	74.0	3.0m./VERT	5.4	PK
High - Channel								
2479.50	53.41	--	33.39	86.80	114.0	3.0m./VERT	27.2	PK
4955.65	49.81	--	10.50	60.31	74.0	3.0m./VERT	13.7	PK

Notes:

1. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic
2. (*) Measurements taken at 1 meter were extrapolated to 3 meters using a factor of (-9.5 dB).
3. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 2405.50 MHz:

Magnitude of Measured Frequency	56.44	dBuV
+Antenna Factor + Cable Loss - Amplifier Gain	33.39	dB/m
Corrected Result	89.83	dBuV/m

Test Date: August 4, 2017

Tested By

Signature:  Name: Robert K. Mills

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H

Table 7. Average Radiated Fundamental & Harmonic Emissions

Test: FCC Part 15, Para 15.209, 15.249(a)					Client: Sanitag Technologies Corp			
Project: 17-0274					Model: AT-004-H			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Low - Channel								
2405.50	19.85	--	33.39	53.24	94.0	3.0m./VERT	40.7	AVG
4802.60	28.98	-9.50*	9.66	29.14	54.0	3.0m./VERT	24.9	AVG
Mid - Channel								
2439.50	20.24	--	33.39	53.63	94.0	3.0m./VERT	40.3	AVG
4880.00	28.57	--	9.66	38.23	54.0	3.0m./VERT	15.8	AVG
High - Channel								
2479.50	19.87	--	33.39	53.26	94.0	3.0m./VERT	40.7	AVG
4955.65	29.38	--	10.50	39.88	54.0	3.0m./VERT	14.1	AVG


Notes:

1. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic
2. (*) Measurements taken at 1 meter were extrapolated to 3 meters using a factor of (-9.5 dB).
3. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 2405.50 MHz:

Magnitude of Measured Frequency	19.85	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain – Duty Cycle	33.39	dB/m
Duty Cycle Correction Factor	Not Applied	dB
Corrected Result	53.24	dBuV/m

Test Date: August 4, 2017

Tested By
 Signature:  Name: Robert K. Mills

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2.11 Band Edge and Restricted Band Measurements – (CFR 15.249 (d))

Band Edge measurements are made following the guidelines in ANSI C63.10-2013 with the EUT initially operating on the Lowest Channel and then operating on the Highest Channel within its band of operation. Radiated measurements are performed to demonstrate compliance with the requirement of 15.249(d) that all emissions outside of the band edges be attenuated by at least 50 dB or 15.209 limits, when compared to its highest in-band value (contained in a 100 kHz band).

Test Date: August 4, 2017

Tested By
Signature:  Name: Robert K. Mills

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H




Figure 3. Band Edge Compliance, Low Channel Delta - Peak

Low Channel Corrected Measured Value from Table 6	89.83	dBuV
Low Channel Band Edge Delta from Figure 4	50.50	dB
Calculated Result	39.33	dBuV/m
Band Edge Limit	54.00	dBuV/m
Calculated Result	39.33	dBuV/m
Band Edge Margin	14.67	dBuV/m

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H




Figure 4. Radiated Restricted Band 2310 MHz to 2390 MHz, Peak

Table 8. Radiated Restricted Band 2310 MHz to 2390 MHz, Peak

2310 MHz to 2390 MHz Restricted Band Peak Measurements							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2310.00	43.03	-0.73	42.30	54.0	3.0m./VERT	11.7	PK
2357.50	43.22	-0.73	42.49	54.0	3.0m./VERT	11.5	PK
2390.00	43.75	-0.73	43.02	54.0	3.0m./VERT	11.0	PK

Note: Peak measurement meets AVG limit.




Figure 5. Band Edge Compliance, High Channel Delta – Peak

High Channel Corrected Measured Value from Table 6	86.80	dBuV
High Channel Band Edge Delta from Figure 6	47.47	dB
Calculated Result	39.33	dBuV/m
Band Edge Limit	54.00	dBuV/m
Calculated Result	39.33	dBuV/m
Band Edge Margin	14.67	dBuV/m

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H




Figure 6. Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak

Table 9. Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak

2483.5 MHz to 2500 MHz Restricted Band Peak Measurements							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	PK Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2483.50	56.85	-0.26	56.59	74.0	3.0m./VERT	17.4	PK
2488.29	51.75	-0.26	51.49	74.0	3.0m./VERT	22.5	PK
2492.45	46.77	-0.26	46.51	74.0	3.0m./VERT	27.5	PK
2500.00	43.76	0.78	44.54	74.0	3.0m./VERT	29.5	PK

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H

Table 10. Radiated Restricted Band 2483.5 MHz to 2500 MHz, Average

2483.5 MHz to 2500 MHz Restricted Band Average Measurements							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP+Duty Cycle (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2483.50	56.85	-17.96	38.89	54.0	3.0m./VERT	15.1	PK
2488.29	51.75	-17.96	33.79	54.0	3.0m./VERT	20.2	PK
2492.45	46.77	-17.96	28.81	54.0	3.0m./VERT	12.5	PK
2500.00	43.76	-16.92	26.84	54.0	3.0m./VERT	27.2	PK

Note: (*) = The Duty Cycle Correction factor was added to the test data Average.

2.12 99% Occupied Bandwidth


These measurements were performed while the EUT was in a constant transmit mode. A method similar to the marker delta method was used to capture the points. The RBW was set to approximately 1/100 of the manufacturers claimed RBW and with the VBW \geq RBW. The results of this test are given in Table 12 and Figures 10-12.

Table 11. 20 dB Bandwidth and 99% Occupied Bandwidth

Frequency (MHz)	99% Occupied Bandwidth (MHz)
2405.00	2.4106
2440.00	2.3049
2480.00	2.2872

Test Date: August 4, 2017

Tested By

Signature: 

Name: Robert K. Mills

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H




Figure 7. 99% Bandwidth - Low Channel

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H




Figure 8. 99% Bandwidth – Mid Channel

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H



Figure 9. 99% Bandwidth – High Channel

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2AMOW-AT004H
 17-0274
 September 18, 2017
 Sanitag Technologies Corp
 AT-004-H

2.13 Unintentional Radiator, Powerline Emissions (CFR 15.107)

The power line conducted voltage emission measurements have been carried out in accordance with CFR 15.107, per ANSI C63.4:2014, Paragraph 7, with a spectrum analyzer connected to a LISN and the EUT placed into a continuous mode of transmission.

NOTE: The test data provided in this section is to support the Verification requirement for the digital apparatus and the radios within.

Table 12. Transmitter Power Line Conducted Emissions Test Data, Part 15.107

150KHz to 30 MHz with Class B Limits						
Test: Power Line Conducted Emissions				Client: Sanitag Technologies Corp		
Project: 17-0274				Model: AT-004-H		
Frequency (MHz)	Test Data (dBuV)	LISN+CL-PA (dB)	Results (dBuV)	AVG Limits (dBuV)	Margin (dB)	Detector PK, QP, or AVG
120 VAC, 60 HZ Phase						
0.4790	43.38	0.06	43.44	46.4	2.9	PK
0.5117	41.20	0.13	41.33	46.0	4.7	PK
1.0733	37.60	0.16	37.76	46.0	8.2	PK
5.5583	32.86	0.31	33.17	50.0	16.8	PK
10.4833	28.49	1.13	29.62	50.0	20.4	PK
26.0500	27.39	0.83	28.22	50.0	21.8	PK
120 VAC, 60 HZ Neutral						
0.4831	36.51	0.20	36.71	46.3	9.6	PK
0.5025	35.82	0.28	36.10	46.0	9.9	PK
1.2600	33.77	0.30	34.07	46.0	11.9	PK
6.3830	31.10	0.46	31.56	50.0	18.4	PK
11.8667	28.74	1.29	30.03	50.0	20.0	PK
24.6667	27.28	0.90	28.18	50.0	21.8	PK

Sample Calculation at 0.4790 MHz:

Magnitude of Measured Frequency	43.38 dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	.06 dB/m
Corrected Result	43.44 dBuV/m

Date: September 18, 2017

Signature: 

Name: John Freeman

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2.14 Unintentional Radiator, Radiated Emissions (CFR 15.109)

Radiated emissions disturbance Measurements were performed with an instrument having both peak and quasi-peak detectors over the frequency range of 30 MHz to 12.5 GHz. Measurements of the radiated emissions were made with the receiver antenna at a distance of 3 m from the boundary of the test unit.

The test antenna was varied from 1 m to 4 m in height while watching the analyzers' display for the maximum magnitude of the signal at the test frequency. The antenna polarization (horizontal or vertical) and test sample azimuth were varied during the measurements to find the maximum field strength readings to record.

The worst-case radiated emissions in the range of 30 MHz to 12.5 GHz are more than 20 dB below the limit.

NOTE: The test data provided in this section is to support the Verification requirement for the digital apparatus and the radios within.

Table 13. Unintentional Radiator, Peak Radiated Emissions (CFR 15.109), 30 MHz to 1000 MHz

30 MHz to 1000 MHz with Class B Limits							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuv)	AF+CA-AMP (dB/m)	Results (dBuV/m)	QP Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or QP
No emissions seen greater than 20 dB below the applicable limit.							

Note: The UWB transmitter was ON and active during this. No contributions were seen from the UWB transmitter circuits.

SAMPLE CALCULATION: N/A

Date: August 1, 2017

Evaluated by
Signature:  Name: Robert K. Mills

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

**Table 14. Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),
1 GHz to 12.5 GHz**

1 GHz to 12.5 GHz with Class B Limits							
Test: Radiated Emissions				Client: Sanitag Technologies Corp			
Project: 17-0274				Model: AT-004-H			
Frequency (MHz)	Test Data (dBuv)	AF+CA-AMP (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
No emissions seen greater than 20 dB below the applicable limit.							

SAMPLE CALCULATION: N/A

Date: August 2, 2017

Evaluated by

Signature: 

Name: John Freeman

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2.15 Measurement Uncertainty

The measurement uncertainties given were calculated using the method detailed in CISPR 16-4-2:2011. A coverage factor of $k=2$ was used to give a level of confidence of approximately 95%.

2.15.1 Conducted Emissions Measurement Uncertainty

Measurement Uncertainty (within a 95% confidence level) for this test is ± 2.85 dB.

This EUT is battery powered; therefore this tested was deemed not applicable.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2AMOW-AT004H
17-0274
September 18, 2017
Sanitag Technologies Corp
AT-004-H

2.15.2 Radiated Emissions Measurement Uncertainty

For a measurement distance of 3 m the measurement uncertainty (with a 95% confidence level) for this test using a Biconical Antenna (30 MHz to 200 MHz) is ± 5.40 dB. This value includes all elements of measurement.

The measurement uncertainty (with a 95% confidence level) for this test using a Log Periodic Antenna (200 MHz to 1000 MHz) is ± 5.19 dB.

The measurement uncertainty (with a 95% confidence level) for this test using a Horn Antenna is ± 5.08 dB.

3 Test Results

The EUT is deemed to have met all the applicable requirements for this evaluation.