

## INTERTEK TESTING SERVICES

---

### RF Exposure

The Equipment under Test (EUT) is a car unit for the TOY RC MONSTER ROCKSLIDE model: DS-2017A operating at 2.4GHz band. It is powered by DC 9.0V (6 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -15.0dBm (tolerance: +/- 3dB).

The normal conducted output power is: -15.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 79.1dB $\mu$ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -16.13dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 77.9dB $\mu$ V/m at 3m in the frequency 2440MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -17.33dBm  
which is within the production variation.

The maximum conducted output power specified is -12.0dBm = 0.06mW

The source- based time-averaging conducted output power  
= 0.06\* Duty cycle mW <0.06 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.475) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 15.0725 ms

Effective period of the cycle = 2.5652ms x 1= 2.5652ms

DC = 2.5652ms / 15.0725 ms = 0.1702 or 17.02 %