

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Toy RC Orbit Tumbler operating at 2.4G Band. The EUT can be powered by DC 9.0V (1 x 9.0V 6F22 battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 96.4dB $\mu$ V/m at 3m in the frequency 2405MHz

The EIRP = [(FS\*D) <sup>2</sup> / 30] mW = 1.17dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 95.2dB $\mu$ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS\*D) <sup>2</sup> / 30] mW = -0.03dBm

which is within the production variation.

The maximum conducted output power specified is 4dBm =2.51mW

The source- based time-averaging conducted output power

=2.51\* Duty cycle mW <2.51 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.475) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 14.8696ms

Effective period of the cycle = 0.1304ms x4=0.5216 ms

DC =0.5216ms / 14.8696ms =0.0351 or 3.51%