

TEST REPORT

Product Name : F10 Pro
Brand Mark : FOCUSPOWER
Model No. : F10 Pro
FCC ID : 2AMQ6-F10PRO
Report Number : BLA-EMC-202001-A4201
Date of Sample Receipt : 2020/1/16
Date of Test : 2020/1/19 to 2020/2/26
Date of Issue : 2020/2/26
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Dongguan Liesheng Electronic Co., Ltd.
13/F, Project Phase 2 of GaoshengTechTower, No.5, Longxi Road,
Nancheng, Dongguan, Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

IOT Test Centre of BlueAsia

**No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,
China**

TEL: +86-755-28682673

FAX: +86-755-28682673

Compiled by:

Jozu .

Review by:

Sweet . Wang

Approved by:

Emen - li

Date:

2020/2/26



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/2/26	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY	6
2 GENERAL INFORMATION	7
3 GENERAL DESCRIPTION OF E.U.T.....	7
4 TEST ENVIRONMENT	8
5 TEST MODE	8
6 MEASUREMENT UNCERTAINTY	8
7 DESCRIPTION OF SUPPORT UNIT.....	9
8 LABORATORY LOCATION.....	9
9 TEST INSTRUMENTS LIST.....	10
ANTENNA REQUIREMENT.....	14
CONCLUSION.....	14
CONDUCTED SPURIOUS EMISSIONS.....	15
LIMITS.....	15
BLOCK DIAGRAM OF TEST SETUP.....	15
TEST DATA.....	16
HOPPING CHANNEL NUMBER.....	17
LIMITS.....	17
BLOCK DIAGRAM OF TEST SETUP.....	17
TEST DATA.....	17
CARRIER FREQUENCIES SEPARATION	18
LIMITS.....	18
BLOCK DIAGRAM OF TEST SETUP.....	18
TEST DATA.....	18
20DB BANDWIDTH	19
BLOCK DIAGRAM OF TEST SETUP.....	19
TEST DATA.....	19
CONDUCTED PEAK OUTPUT POWER	20
LIMITS.....	20
BLOCK DIAGRAM OF TEST SETUP.....	20

TEST DATA	21
CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	22
LIMITS.....	22
BLOCK DIAGRAM OF TEST SETUP.....	22
PROCEDURE	22
TEST DATA.....	24
RADIATED SPURIOUS EMISSIONS	26
LIMITS.....	26
BLOCK DIAGRAM OF TEST SETUP.....	26
PROCEDURE	27
TEST DATA.....	29
RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	35
LIMITS.....	35
BLOCK DIAGRAM OF TEST SETUP.....	36
PROCEDURE	36
TEST DATA.....	37
CONDUCTED BAND EDGES MEASUREMENT	38
LIMITS.....	38
BLOCK DIAGRAM OF TEST SETUP.....	39
TEST DATA.....	39
DWELL TIME.....	40
LIMITS.....	40
BLOCK DIAGRAM OF TEST SETUP.....	40
TEST DATA.....	41
10 APPENDIX.....	42
10.1 APPENDIXA: 20DBEMISSION BANDWIDTH	42
<i>Test Result.....</i>	42
<i>Test Graphs.....</i>	43
10.2 APPENDIXC: MAXIMUM CONDUCTED OUTPUT POWER	48
<i>Test Result.....</i>	48
<i>Test Graphs.....</i>	49
10.3 APPENDIXD: CARRIER FREQUENCY SEPARATION.....	54
<i>Test Result.....</i>	54

<i>Test Graphs</i>	55
10.4 APPENDIX E: TIME OF OCCUPANCY.....	57
<i>Test Result</i>	57
<i>Test Graphs</i>	58
10.5 APPENDIX F: NUMBER OF HOPPING CHANNELS.....	60
<i>Test Result</i>	60
<i>Test Graphs</i>	61
10.6 APPENDIX G: BAND EDGE MEASUREMENTS	63
<i>Test Result</i>	63
<i>Test Graphs</i>	64
10.7 APPENDIX H: CONDUCTED SPURIOUS EMISSION	70
<i>Test Result</i>	70
<i>Test Graphs</i>	71
10.8	84
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	85
APPENDIX B: PHOTOGRAPHS OF EUT	87

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass

2 GENERAL INFORMATION

Applicant	Dongguan Liesheng Electronic Co., Ltd.
Address	13/F,Project Phrase 2 of GaoshengTechTower,No.5,Longxi Road,Nancheng,Dongguan,Guangdong,China
Manufacturer	ShenZhen FuYuan International Supply Chain CO.,LTD
Address	International E-Time B3-803,NO.4,ZhongXing RD.,Ma'An Tang Community,BanTian ST.,LongGang DIST.,ShenZhen,China
Factory	Dongguan Zhengrong Electronics Co., Ltd.
Address	No. 4 Shugang Avenue, Hongmei Town, Dongguan City, Guangdong Province, China

3 GENERAL DESCRIPTION OF E.U.T.

Product Name	F10 Pro
Test Model No.	F10 Pro
Battery	DC3.7V
Hardware Version	V1.0
Software Version	V1.0
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, p/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	0.9dBi

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and no hopping mode all be tested, worse case is no hopping mode and reported)
Remark: Full battery is used during all test except ac conducted emission, DH1, DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned only worse case is reported.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission	±4.34dB
Radiated Emission	±4.24dB
Radiated Emission	±4.68dB
AC Power Line Conducted Emission	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter (UGREEN)	UGREEN	CD112	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
IOT Test Centre of BlueAsia
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Antenna Requirement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
-----------	--------------	-------	-----	----------	---------

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of Carrier Frequencies Separation

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of 20dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2018	6/9/2021
Receiver	R&S	ESPI3	101082	5/7/2019	5/7/2020
LISN	R&S	ENV216	3560.6550.15	7/4/2019	7/3/2020
LISN	安泰信	AT166-2	AKK1806000003	12/18/2019	12/17/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Receiver	R&S	ESR7	101199	5/7/2019	5/6/2020
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2019	7/13/2020
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2019	7/13/2020
Amplifier	SKET	LNPA-0118-45	N/A	7/4/2019	7/3/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2020

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Receiver	R&S	ESR7	101199	5/7/2019	5/6/2020
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2019	7/13/2020
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2019	7/13/2020
Amplifier	SKET	LNPA-0118-45	N/A	7/4/2019	7/3/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2020

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

Test Equipment Of Dwell Time					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/18/2019	12/17/2020
Signal Generator	Agilent	N5182A	MY49060650	12/18/2019	12/17/2020
Signal Generator	Agilent	E8257D	MY44320250	5/7/2019	5/6/2020

ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.9dBi.




CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details
--


CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

BLOCK DIAGRAM OF TEST SETUP




TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

BLOCK DIAGRAM OF TEST SETUP



Remark
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\text{ohm}/50\text{?H} + 5\text{ohm}$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power

cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Resolution bandwidth:

- i) Below 150 kHz: 300 Hz or CISPR 200 Hz (CISPR 200 Hz for QP detector)
- ii) 150 kHz to 30 MHz: 10 kHz or CISPR 9 kHz, (CISPR 9 kHz for QP detector)

Video bandwidth:


- i) VBW for Peak, Quasi-peak, or Average Detector Function: $3 \times RBW$

Detector :

- i) QP AV below 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).

TEST DATA

[TestMode: TX]; [Line: Line]



Site Phase: **L1** Temperature: 26

Limit: FCC Class B Conduction(QP) Power: AC120V/60Hz Humidity: 60 %

EUT:

M/N: f10pro

Mode: BT mode


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2100	21.25	9.89	31.14	63.21	-32.07	QP	
2		0.2100	15.38	9.89	25.27	53.21	-27.94	AVG	
3		0.5100	16.24	9.73	25.97	56.00	-30.03	QP	
4		0.5100	11.50	9.73	21.23	46.00	-24.77	AVG	
5 *		2.1940	23.13	9.82	32.95	56.00	-23.05	QP	
6		2.1940	12.06	9.82	21.88	46.00	-24.12	AVG	
7		7.3860	22.07	9.87	31.94	60.00	-28.06	QP	
8		7.3860	11.29	9.87	21.16	50.00	-28.84	AVG	
9		14.1740	14.65	9.96	24.61	60.00	-35.39	QP	
10		14.1740	7.91	9.96	17.87	50.00	-32.13	AVG	
11		23.9140	4.73	10.06	14.79	60.00	-45.21	QP	
12		23.9140	-1.94	10.06	8.12	50.00	-41.88	AVG	

Test Result: Pass

[TestMode: TX]; [Line: Nutral]

80.0 dBuV



Site: **N** Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC120V/60Hz Humidity: 60 %
EUT:
M/N: f10pro
Mode: BT mode
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2060	21.13	9.88	31.01	63.37	-32.36	QP	
2		0.2060	15.44	9.88	25.32	53.37	-28.05	AVG	
3		0.9540	18.36	9.77	28.13	56.00	-27.87	QP	
4		0.9540	12.52	9.77	22.29	46.00	-23.71	AVG	
5 *		2.1860	26.01	9.86	35.87	56.00	-20.13	QP	
6		2.1860	14.21	9.86	24.07	46.00	-21.93	AVG	
7		7.6220	22.71	9.85	32.56	60.00	-27.44	QP	
8		7.6220	11.92	9.85	21.77	50.00	-28.23	AVG	
9		9.5140	15.10	9.95	25.05	60.00	-34.95	QP	
10		9.5140	6.88	9.95	16.83	50.00	-33.17	AVG	
11		14.6500	15.37	10.01	25.38	60.00	-34.62	QP	
12		14.6500	7.95	10.01	17.96	50.00	-32.04	AVG	

Test Result: Pass

RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX;TX mode (SE) below 1G
Test Mode (Final Test)	TX;TX mode (SE) below 1G
Tester	Jozu
Temperature	25 °C
Humidity	55%


LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP





PROCEDURE

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor "C Preamplifier Factor

3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Resolution bandwidth:

- i) Below 150 kHz: 300 Hz or CISPR 200 Hz (CISPR 200 Hz for QP detector)
- ii) 150 kHz to 30 MHz: 10 kHz or CISPR 9 kHz, (CISPR 9 kHz for QP detector)
- iii) 30 MHz to 1000 MHz: 100 kHz or CISPR 120 kHz, (CISPR 120 kHz for QP detector)
- iv) Above 1 GHz: 1 MHz

Video bandwidth:

- i) VBW for Peak, Quasi-peak, or Average Detector Function: $3 \times$ RBW
- ii) VBW when using peak detector function: 10Hz


Detector :

- i) QP below 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).
- ii) Peak and average above 1 GHz

TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

Power: AC120V/60Hz



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 Class B

Power:

Humidity: %

EUT: F10 Pro

Distance: 3m

M/N: F10 Pro

Mode: BT

Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		54.0711	-2.92	24.04	21.12	40.00	-18.88	QP		
2		97.1148	2.58	20.36	22.94	43.50	-20.56	QP		
3		187.0958	3.86	20.67	24.53	43.50	-18.97	QP		
4		322.1886	2.35	24.51	26.86	46.00	-19.14	QP		
5		590.9737	-0.23	31.02	30.79	46.00	-15.21	QP		
6	*	866.0879	0.66	34.91	35.57	46.00	-10.43	QP		

Test Result: Pass

BlueAsia

[TestMode: TX]; [Polarity: Vertical]

Power: AC120V/60Hz



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 Class B

Power:

Humidity: %

EUT: F10 Pro

Distance: 3m

M/N: F10 Pro

Mode: BT

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm		Table Degree	Comment
								Detector	degree		
1	*	36.5092	4.91	23.52	28.43	40.00	-11.57	QP			
2		84.7019	6.13	19.31	25.44	40.00	-14.56	QP			
3		96.4362	5.44	20.29	25.73	43.50	-17.77	QP			
4		161.4742	-0.63	23.06	22.43	43.50	-21.07	QP			
5		209.3129	3.95	20.73	24.68	43.50	-18.82	QP			
6		576.6443	2.07	30.71	32.78	46.00	-13.22	QP			

Test Result: Pass

[TestMode:8-DPSK mode]

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.

Test channel:lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	41.9	2.38	44.28	74	-29.72	Vertical
7206.00	40.88	2.17	43.05	74	-30.95	Vertical
9608.00	41.67	2.06	43.73	74	-30.27	Vertical
12010.00	*			74		Vertical
14412.00	*			74		Vertical
4804.00	43.54	2.38	45.92	74	-28.08	Horizontal
7206.00	43.36	2.17	45.53	74	-28.47	Horizontal
9608.00	43.07	2.06	45.13	74	-28.87	Horizontal
12010.00	*			74		Horizontal
14412.00	*			74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	31.86	2.38	34.24	54	-19.76	Vertical
7206.00	31.28	2.17	33.45	54	-20.55	Vertical
9608.00	31.11	2.06	33.17	54	-20.83	Vertical
12010.00	*			54		Vertical
14412.00	*			54		Vertical
4804.00	32.97	2.38	35.35	54	-18.65	Horizontal
7206.00	32.59	2.17	34.76	54	-19.24	Horizontal
9608.00	30.16	2.06	32.22	54	-21.78	Horizontal
12010.00	*			54		Horizontal
14412.00	*			54		Horizontal

Test channel:Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	42.51	0.17	42.68	74	-31.32	Vertical

7323.00	40.53	1.43	41.96	74	-32.04	Vertical
9764.00	42.07	1.26	43.33	74	-30.67	Vertical
12205.00	*			74		Vertical
14646.00	*			74		Vertical
4882.00	43.64	0.17	43.81	74	-30.19	Horizontal
7323.00	42.96	1.43	44.39	74	-29.61	Horizontal
9764.00	43.14	1.26	44.40	74	-29.60	Horizontal
12205.00	*			74		Horizontal
14646.00	*			74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	32.29	0.17	32.46	54	-21.54	Vertical
7323.00	33.85	1.43	35.28	54	-18.72	Vertical
9764.00	32.37	1.26	33.63	54	-20.37	Vertical
12205.00	*			54		Vertical
14646.00	*			54		Vertical
4882.00	33.4	0.17	33.57	54	-20.43	Horizontal
7323.00	33.44	1.43	34.87	54	-19.13	Horizontal
9764.00	32.98	1.26	34.24	54	-19.76	Horizontal
12205.00	*			54		Horizontal
14646.00	*			54		Horizontal

Test channel: Highest
Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	41.42	1.04	42.46	74	-31.54	Vertical
7440.00	42.35	2.59	44.94	74	-29.06	Vertical
9920.00	43.56	2.74	46.3	74	-27.7	Vertical
12400.00	*			74		Vertical
14880.00	*			74		Vertical
4960.00	42.06	1.04	43.1	74	-30.9	Horizontal
7440.00	42.38	2.59	44.97	74	-29.03	Horizontal
9920.00	41.76	2.74	44.50	74	-29.50	Horizontal
12400.00	*			74		Horizontal
14880.00	*			74		Horizontal

Average value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	31.24	1.04	32.28	54	-21.72	Vertical
7440.00	30.07	2.59	32.66	54	-21.34	Vertical
9920.00	31.11	2.74	33.85	54	-20.15	Vertical
12400.00	*			54		Vertical
14880.00	*			54		Vertical
4960.00	32.8	1.04	33.84	54	-20.16	Horizontal
7440.00	32.46	2.59	35.05	54	-18.95	Horizontal
9920.00	30.82	2.74	33.56	54	-20.44	Horizontal
12400.00	*			54		Horizontal
14880.00	*			54		Horizontal

Test Result: Pass

RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP



PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

TEST DATA
[TestMode: 8DPSK]

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.

Test channel:lowest
Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	44.99	-4.2	40.79	74	-33.21	Horizontal
2390	49.58	-3.88	45.7	74	-28.3	Horizontal
2310	45.46	-4.49	40.97	74	-33.03	Vertical
2390	49.44	-4.21	45.23	74	-28.77	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	35.19	-4.2	30.99	54	-23.01	Horizontal
2390	39.3	-3.88	35.42	54	-18.58	Horizontal
2310	34.75	-4.49	30.26	54	-23.74	Vertical
2390	39.4	-4.21	35.19	54	-18.81	Vertical

Test channel:Highest
Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	46.37	-3.38	42.99	74	-31.01	Horizontal
2500	45.35	-3.3	42.05	74	-31.95	Horizontal
2483.5	44.53	-3.77	40.76	74	-33.24	Vertical
2500	54.24	-3.7	50.54	74	-23.46	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	36.05	-3.38	32.67	54	-21.33	Horizontal
2500	35.88	-3.3	32.58	54	-21.42	Horizontal
2483.5	34.2	-3.77	30.43	54	-23.57	Vertical

2500	43.92	-3.7	40.22	54	-13.78	Vertical
Test Result: Pass						


CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	55%

LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

10 APPENDIX


Appendix1


10.1 APPENDIX: 20DBEMISSION BANDWIDTH


Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	1.119	2401.457	2402.576	---	PASS
		2441	1.116	2440.460	2441.576	---	PASS
		2480	1.119	2479.457	2480.576	---	PASS
2DH1	Ant1	2402	1.380	2401.328	2402.708	---	PASS
		2441	1.383	2440.325	2441.708	---	PASS
		2480	1.380	2479.328	2480.708	---	PASS
3DH1	Ant1	2402	1.386	2401.322	2402.708	---	PASS
		2441	1.389	2440.322	2441.711	---	PASS
		2480	1.383	2479.322	2480.705	---	PASS


Test Graphs







2DH1_Ant1_2480



3DH1_Ant1_2402





Report No.: BLA-EMC-202001-A4201
Page 47 of 99





10.2 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER


Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	-2.09	<=20.97	PASS
		2441	-2.3	<=20.97	PASS
		2480	-2.33	<=20.97	PASS
2DH1	Ant1	2402	0.33	<=20.97	PASS
		2441	0.09	<=20.97	PASS
		2480	0.06	<=20.97	PASS
3DH1	Ant1	2402	0.91	<=20.97	PASS
		2441	0.58	<=20.97	PASS
		2480	0.65	<=20.97	PASS


Test Graphs









2DH1_Ant1_2480



3DH1_Ant1_2402






10.3 APPENDIX: CARRIER FREQUENCY SEPARATION

Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	0.994	>=0.746	PASS
2DH1	Ant1	Hop	1.006	>=0.922	PASS
3DH1	Ant1	Hop	1	>=0.926	PASS

Test Graphs





10.4 APPENDIX: TIME OF OCCUPANCY

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.40	320	0.128	<=0.4	PASS
DH3	Ant1	Hop	1.67	160	0.267	<=0.4	PASS
DH5	Ant1	Hop	2.89	106.6	0.308	<=0.4	PASS


Note:


DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.

DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.

DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

Test Graphs





10.5 APPENDIX: NUMBER OF HOPPING CHANNELS

Test Result

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	>=15	PASS
2DH1	Ant1	Hop	79	>=15	PASS
3DH1	Ant1	Hop	79	>=15	PASS