

# TEST REPORT

**Product Name** : HAYLOU Watch S8  
**Brand Mark** : Haylou  
**Model No.** : HAYLOU Watch S8  
**FCC ID** : 2AMQ6-S8  
**Report Number** : BLA-EMC-202311-A3504  
**Date of Sample Receipt** : 2023/11/13  
**Date of Test** : 2023/11/14 to 2023/11/20  
**Date of Issue** : 2023/11/22  
**Test Standard** : KDB447498D04 General RF Exposure  
Guidance v01  
**Test Result** : Pass

Prepared for:

**Dongguan Liesheng Electronic Co., Ltd.**  
**Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District,**  
**Dongguan City, Guangdong, China**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,**  
**Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by:

*Lucas*

Review by:

*Sueels*

Approved by:

*Blue Zheng*

Date:

2023/11/22



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2023/11/22	Original

BLUEASIA

**TABLE OF CONTENTS**

<b>1 TEST SUMMARY .....</b>	<b>4</b>
<b>2 GENERAL INFORMATION .....</b>	<b>5</b>
<b>3 GENERAL DESCRIPTION OF E.U.T.....</b>	<b>5</b>
<b>4 LABORATORY LOCATION .....</b>	<b>6</b>
<b>5 RF EXPOSURE COMPLIANCE REQUIREMENT .....</b>	<b>7</b>
5.1 STANDARD REQUIREMENT .....	7
5.2 LIMITS .....	7

BLUEASIA

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

BLUEASIA

## 2 GENERAL INFORMATION

<b>Applicant</b>	Dongguan Liesheng Electronic Co., Ltd.
<b>Address</b>	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China
<b>Manufacturer</b>	Dongguan Liesheng Electronic Co., Ltd.
<b>Address</b>	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China
<b>Factory</b>	Shenzhen Smart Care Technology Limited
<b>Address</b>	The 6 <sup>th</sup> Floor, Block 2, Huixin Science and Technology Industrial Park, Fuhai street, Bao'an District, Shenzhen, China
<b>Product Name</b>	HAYLOU Watch S8
<b>Test Model No.</b>	HAYLOU Watch S8

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	JL14-MB-V12
<b>Software Version</b>	N/A
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	BREDR:GFSK,pi/4DQPSK,8DPSK BLE:GFSK(Data Rate:1Mbps;2Mbps)
<b>Channel Spacing:</b>	BREDR:1MHz BLE:2MHz
<b>Number of Channels:</b>	BREDR:79 BLE:40
<b>Antenna Type:</b>	FPC Antenna
<b>Antenna Gain:</b>	-4.8dBi(Provided by the customer)

#### 4 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.  
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.

BLUEASIA

## 5 RF EXPOSURE COMPLIANCE REQUIREMENT

### 5.1 STANDARD REQUIREMENT

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 5.2 LIMITS

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

Ant gain = -4.8dBi

BREDR:

Max Output power =3.71dBm @EDR@ 2402MHz

ERP = 3.71dBm-4.8dBi-2.15=-3.24dBm

So

worse case :

$10^{-0.324}=0.474\text{mW} < 2.79 \text{ mW}$

Comply with RF exposure exemption limit.

BLE:

Max Output power =7.417dBm @BLE 2M@ 2402MHz

ERP = 7.417dBm-4.8dBi-2.15=0.467dBm

So

worse case :

$10^{0.0467}=1.114\text{mW} < 2.79 \text{ mW}$

Comply with RF exposure exemption limit.

**----END OF REPORT----**

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.